

Non-monotony and Boolean automata networks

Mathilde Noual^{1,3}, Damien Regnault², Sylvain Sené^{2,3}

¹ Université de Lyon, ÉNS-Lyon, LIP, CNRS UMR 5668, 69007 Lyon, France

² Université d'Évry – Val d'Essonne, IBISC, ÉA 4526, 91000 Évry, France

³ Institut rhône-alpin des systèmes complexes, IXXI, 69007 Lyon, France

mathilde.noual@ens-lyon.fr,
{damien.regnault, sylvain.sene}@ibisc.univ-evry.fr

Abstract. This paper aims at setting the keystone of a prospective theoretical study on the role of non-monotone interactions in biological regulation networks. Focusing on discrete models of these networks, namely, Boolean automata networks, we propose to analyse the contribution of non-monotony to the diversity and complexity in their dynamical behaviours. More precisely, in this paper, we start by detailing some motivations, both mathematical and biological, for our interest in non-monotony, and we discuss how it may account for phenomena that cannot be produced by monotony only. Then, to build some understanding in this direction, we propose some preliminary results on the dynamical behaviour of some specific non-monotone Boolean automata networks called XOR circulant networks.

Keywords: Discrete dynamical systems, Boolean automata networks, non-monotony, dynamical behaviours.

1 Introduction

The introduction of Boolean automata networks by McCulloch and Pitts in [1] and Kauffman in [2,3] has initiated many developments in the study of discrete dynamical systems at the frontier of biology, mathematics and theoretical computer science. In the context of modelling biological regulation networks, the pertinence of abstract networks was deeply motivated by Hopfield and Kauffman in the respective contexts of neural and genetic networks. Among other things, Hopfield showed in [4,5] that threshold Boolean automata networks allow to highlight the fundamental neural concepts of associative memory and learning. In [6,7], on the basis of the breakthroughs of Jacob and Monod [8,9], Kauffman put emphasis on the Boolean nature of genes that are simply either actively transcribing or not. These works as well as Thomas' [10,11,12] placed formal approaches at the centre of the understanding of dynamical behaviours and complexity in biology. In particular, both these works claimed that theoretical frameworks would certainly allow biologists to bypass the observational

knowledge which cannot, alone, lead to general conclusions. Since then, numerous theoretical studies have been carried out to acquire a better understanding of these networks, from the computational complexity standpoint [13,14,15,16,17] as well as from the standpoint of the characterisation of their dynamical behaviours [18,19,20,21,22,23,24,25,26].

In the lines of these studies and in order to complete them, we propose in this paper to tackle the question of the role of non-monotony in Boolean automata networks. This question seems to be missing in classical literature dealing with Boolean automata networks as models of biological networks and, in particular, as models of genetic regulation networks. Indeed, on the one hand, the underlying interaction structure of Boolean models of genetic regulation networks are often represented by *signed* digraphs where vertices represent genes and arcs, which are labelled either by a plus or a minus sign, represent directed actions of genes on one another, either activations or inhibitions. This way, a gene that tends to influence the expression of another gene is supposed to be either one of its activators or one of its inhibitors. It cannot be both. That is, it cannot act as an activator under some circumstances and act as an inhibitor under some others. This interpretation of gene regulations leads to define monotone Boolean automata networks as studied in [27,28,29,30,31,32] and [33,34,35,36,37] from theoretical and applied points of view respectively. On the other hand, the class of linear networks has also been studied. This class contains in particular the special non-monotone networks in which *all* local functions are XOR functions. In [38], Cull based his study on [1,39,40] and developed an algebraic description of the dynamical behaviour of linear networks. In [41], Snoussi gave a characterisation of behaviours of very specific XOR networks. But the global dynamical properties of general non-monotone networks have not yet been studied nor has the impact of non-monotone interactions yet been examined *per se*.

Our recent studies on Boolean automata networks have however brought us to believe that non-monotony may be one of the main causes of singular behaviours of Boolean automata networks. Thus, this research axis seems very pertinent in the context of biological regulation networks. The present paper provides the grounds of a *prospective study* on non-monotony in networks. In this context, we develop two lines. First, with some examples, we give some insights that support the importance of non-monotony and the idea that it may be responsible for peculiar network dynamical behaviours. Second, to serve as a tangible starting point and

build intuition, we present some primary results concerning a particular class of non-monotone networks called XOR circulant networks.

In Section 2, we provide general definitions and notations about Boolean automata networks that are crucial for the sequel. Section 3 details why we believe that non-monotony is in some sense at the centre of the existence of specific dynamical behaviours. Section 4 presents preliminary results concerning XOR circulant networks. In particular, it gives properties of their trajectorial behaviours by focusing on convergence speeds and of their asymptotic behaviours by characterising attractors. Eventually, Section 5 proposes perspectives to this first work on non-monotony.

2 Preliminary elements on Boolean automata networks

Informally, a *Boolean automata network* involves interacting elements whose states, which either equal 0 (inactive) or 1 (active), may change over time under the influence of the states of other network elements [18,42]. This section formalises this description by presenting the main definitions and notations which are used in this paper.

2.1 Structure and local transition functions

A *Boolean automata network* N of size n is composed of n elements called automata which are, by convention here, numbered from 0 to $n - 1$. For any automaton i of $V = \{0, \dots, n - 1\}$, the set of possible *states* x_i of i is $\{0, 1\}$. Let us assume that the *time space* \mathcal{T} is discrete, *i.e.*, $\mathcal{T} = \mathbb{N}$. A *configuration* of N corresponds to the allocation of a value of $\{0, 1\}$ to every automaton of N . It can thus be represented by a vector $x = (x_0, \dots, x_{n-1}) \in \{0, 1\}^n$ and $\{0, 1\}^n$ is then the *configuration space* of N . Abusing language, we will denote by $x(t)$ (resp. $x_i(t)$) the configuration of N (resp. the state of automaton i) at time step $t \in \mathcal{T}$. Given an arbitrary configuration $x \in \{0, 1\}^n$, the *density* of x is defined as $d(x) = \frac{1}{n} \cdot |\{x_i \mid (i \in V) \wedge (x_i = 1)\}|$. In our context, we focus particularly on switches of automata states starting in a given network configuration. For this reason, the following notations for network configurations will be useful:

$$\begin{aligned} \forall x = (x_0, \dots, x_{n-1}) \in \{0, 1\}^n, \forall i \in V = \{0, \dots, n - 1\}, \\ \bar{x}^i = (x_0, \dots, x_{i-1}, \neg x_i, x_{i+1}, \dots, x_{n-1}) \\ \text{and, } \forall W \subseteq V, \bar{x}^{W \cup \{i\}} = \overline{\bar{x}^W}^i. \quad (1) \end{aligned}$$




Fig. 1. (left) An interaction graph of a Boolean automata network of size 3 and (right) the local transition functions of its automata.

Thus, in particular, $\bar{0}^i$ where $i \in V$ (resp. $\bar{0}^W$ where $W \subseteq V$) denotes the network configuration in which automaton i has state 1 (resp. all the automata belonging to W have state 1) and all other automata have state 0. The underlying interaction structure of N can be represented by a digraph $G = (V, A)$, called the *interaction graph* of N . In this digraph, V equals the set of automata of N . $A \subseteq V \times V$ is the interaction set. For any automata $i, j \in V$, it satisfies $(j, i) \in A$ if and only if j effectively influences i , that is, in some network configurations (but not necessarily in all of them), the state of j may cause a change of states of i (see Equation 2 below). As an example, Figure 1 (left) pictures the interaction graph of a Boolean automata network of size 3, where $A = \{(0, 0), (0, 1), (0, 2), (1, 0), (2, 0), (2, 1)\}$. Interaction graphs specify what influences apply to each automaton of a network N . The nature of these influences are defined by the *local transition functions* $f_i : \{0, 1\}^n \rightarrow \{0, 1\}$ which are associated to each automaton i of N (as in Figure 1 (right)) such that:

$$\exists x \in \{0, 1\}^n, f_i(x) \neq f_i(\bar{x}^j) \iff (j, i) \in A. \quad (2)$$

Thus, a Boolean automata network is entirely defined by the set of local transition functions of its automata.

2.2 Updating modes and transition graphs

To determine the possible *behaviours* of a network, it remains to be specified how automata states are updated over time. The most general point of view consists in considering all possibilities. That is, assimilating networks with state transition systems, in each configuration, $2^n - 1$ transitions are considered, one for each non-empty set of automata whose states can be updated. More precisely, $\forall W \neq \emptyset \subseteq V$, we define the update function $F_W : \{0, 1\}^n \rightarrow \{0, 1\}^n$ such that:

$$\forall x \in \{0, 1\}^n, \forall i \in V, F_W(x)_i = \begin{cases} f_i(x) & \text{if } i \in W, \\ x_i & \text{otherwise.} \end{cases}$$




Fig. 2. (top) General and (bottom) asynchronous transition graphs of the Boolean automata network of Figure 1.

Then, according to the most *general updating mode*, the global network behaviour is given by the *general transition graph* $\mathcal{G}_g = (\{0, 1\}^n, T_g)$ where $T_g = \{(x, F_W(x)) \mid x \in \{0, 1\}^n, W \neq \emptyset \subseteq V\}$ [43,44,45]. In this graph which usually is a multigraph, arcs can be labelled by the set W of automata that are updated in the corresponding transition $(x, F_W(x))$. For the sake of clarity, in the examples of this paper, arcs with identical extremities are represented by a unique arc with several labels. Figure 2 (top) depicts the general transition graph of the network presented in Figure 1.

Transitions $(x, F_i(x))$ that only involve the update of one automaton $i \in V$ are called *asynchronous transitions*. Transitions $(x, F_W(x)), |W| > 1$ that involve the update of several are called *synchronous transitions*. The subgraph $\mathcal{G}_a = (\{0, 1\}^n, T_a)$ of \mathcal{G}_g whose set of arcs $T_a = \{(x, F_{\{i\}}(x)) \mid x \in \{0, 1\}^n, i \in V\}$ equals the set of *asynchronous transitions* of the network is called the *asynchronous transition graph*. This graph defines the *asynchronous updating mode* according to which, in each configuration, only n transitions are considered, one for each automaton that can be updated alone. This updating mode has been widely used in studies of Thomas and his co-workers in [11,12,29,46,47,23]. An illustration of an asynchronous transition graph is given in Figure 2 (bottom).

Because both the general and the asynchronous transition graphs are very large graphs, in some cases, to draw some intuitions, it may be necessary to restrict our attention to the transitions that are allowed under a specific deterministic updating schedule u . This amounts to considering a transition graph $\mathcal{G}_u = (\{0, 1\}^n, T_u)$ which is the graph of a function $F[u] : \{0, 1\}^n \rightarrow \{0, 1\}^n$ (i.e., $T_u = \{(x, F[u](x)) \mid x \in \{0, 1\}^n\}$). This function has the following form: $F[u] = F_{W_{p-1}} \circ \dots \circ F_{W_1} \circ F_{W_0}$ where $p \in \mathbb{N}$ and $\forall k \leq p, W_k \subseteq V$. It is called the *global transition function* associated to the updating schedule u , that updates simultaneously all automata in W_0 , then updates simultaneously all automata in $W_1 \dots$. This second point of view has been adopted in [48,49,50,51,52,53] following the introduction of *block-sequential updating schedules* by Robert in [18,54] (see Figure 3). Section 4 is set in similar lines. It focuses on the *parallel updating mode* π which consists in deterministically updating all network automata at once in each network configuration. In this case, the global transition function is $F[\pi] = F_V$ such that $\forall i \in V, F[\pi](x)_i = f_i(x)$ and the network behaviour is considered to be described by the graph of $F[\pi]$, that is, the transition graph $\mathcal{G}_\pi = (\{0, 1\}^n, T_\pi)$ where $T_\pi = \{(x, F[\pi](x)) \mid x \in \{0, 1\}^n\}$.

2.3 Dynamical behaviours and non-monotony

Let N be an arbitrary Boolean automata network. Consider any updating mode u among those defined above and let \mathcal{G}_u be the corresponding transition graph. Let $x \in \{0, 1\}^n$ be a configuration of N . We call *trajectory* of x the subgraph of \mathcal{G}_u that is induced by configurations y such that there is a path from x to y in \mathcal{G}_u . Terminal strongly connected components of \mathcal{G}_u are called the *attractors* of N and constitute the asymptotic behaviours of




Fig. 3. Transition graphs of the Boolean automata network of Figure 1 associated to (a) the parallel updating mode, (b) a block-sequential updating schedule u whose global transition function is $F[u] = F_{\{2,3\}} \circ F_{\{1\}}$ and (c) a particular block-sequential updating schedule s , called sequential, whose global transition function is $F[s] = F_{\{2\}} \circ F_{\{3\}} \circ F_{\{1\}}$. Recurrent configurations appear in grey.

N . Their size equals the number of configurations that they contain. Configurations that belong to an attractor are called *recurrent configurations*. Attractors of size 1 (resp. of size strictly greater than 1) are called *stable configurations* (resp. *stable oscillations*). When $\mathcal{G} = \mathcal{G}_u$ is the transition graph associated to a deterministic updating schedule u , stable configurations correspond to fixed points of the global transition function $F[u]$ and stable oscillations of size p , which are rather called *limit cycles* of *period* p in this case, correspond to oriented cycles in \mathcal{G}_u . As an example, Figure 3 shows that the network of Figure 1 admits one unique attractor, a limit cycle of period 2, under any of the three deterministic updating schedules considered. The precise definition of this limit cycle, however, differs in each case. In particular, as proven in [50,55], no configurations besides stable configurations are recurrent under the parallel updating schedule as well as under the sequential updating schedule which updates one automaton at the time been. Furthermore, Figure 2 shows that the same network admits one unique attractor, a stable oscillation of size 8, indifferently when it is subjected to the asynchronous or general updating modes.

By analogy with continuous functions, the local transition function f_i of an automaton $i \in V$ is said to be *locally monotone* in $j \in V$ if, either:

$$\forall x = (x_0, \dots, x_{n-1}) \in \{0, 1\}^n,$$

$$f_i(x_0, \dots, x_{j-1}, 0, x_{j+1}, \dots, x_{n-1}) \leq f_i(x_0, \dots, x_{j-1}, 1, x_{j+1}, \dots, x_{n-1})$$

or:

$$\forall x = (x_0, \dots, x_{n-1}) \in \{0, 1\}^n,$$

$$f_i(x_0, \dots, x_{j-1}, 0, x_{j+1}, \dots, x_{n-1}) \geq f_i(x_0, \dots, x_{j-1}, 1, x_{j+1}, \dots, x_{n-1}).$$

In other terms, f_i is locally monotone in j if, in the conjunctive normal form of $f_i(x)$, either only x_j appears or only $\neg x_j$ does. The function f_i is said to be locally monotone or simply monotone if it is locally monotone in *all* $j \in V$. It is said to be *non (locally) monotone* otherwise. In this latter case, there exists $j \in V$ such that in some configurations, the state of i tends to imitate that of j and in some other configurations, on the contrary, the state of i tends to negate that of j . When all functions f_i , $i \in V$, are monotone, the network is said to be *monotone* itself. Otherwise, if at least one local transition function is non-monotone, the network is said to be *non-monotone*.

3 Motivations

To put forward the importance of studying non-monotony in discrete models of regulation networks, let us first recall the fundamental concept of genetics establishing that a gene is a portion of the DNA which is transcribed into a mRNA (the gene is then said to be expressed) that is itself translated into one or several proteins, called the *products* of that gene. Because proteins can influence the transcription and translation stages, genes have the possibility of interacting with one another through their products. Further, because the effect of a protein may depend on its concentration in the cell, genes may have different effects on one another. If gene g_j influences the expression of gene g_i via one of its protein products p , then it may do so differently according to the concentration of p in the cell. As an illustration, let us consider the infection of a bacterium *Escherichia coli* by a phage λ [56]. The genetic regulations that allow a phage λ to enter its lysogenic and lytic cycles⁴ involve two genes, *Cro* and *cl*. It is well known that *Cro* influences itself and that the nature of this influence is different according to the concentration of its protein product p_{Cro} . If the p_{Cro} concentration in the cell is low (resp. high), *Cro* tends to activate (resp. inhibit) its own expression. This induces an increase (resp. a decrease) of the p_{Cro} concentration. Supposing that automata networks

⁴ The lysogenic cycle of a phage λ is the stage where its genome is inserted in the genome of the bacterium. Its lytic cycle is the stage where it replicates, leading *in fine* to the death of the bacterium.

are reasonable models of genetic networks, such duality in the influence of one gene g_j on the state of the same or another gene g_i corresponds precisely to the formal notion of non-monotony, specifically, that of $f_i(x)$ with respect to x_j .

In the light of some recent developments [43,57], the study of non-monotony in discrete networks also seems pertinent from a different, mathematical standpoint. Indeed, first, let us consider the problem of modularity in gene regulation networks which is essential in the context of biology. Modules are informally defined as independent groups of interacting genes. More precisely, they involve minimal sets of genes (or biobricks) that own independent behaviours specific to real biological functions. Until now, the notion of modularity used in the literature relies on structural parameters [58,59,60]. For instance, modules are often defined simply as strongly connected components. However, although such structural definitions are natural, they can only lead to structural results, necessarily failing to reveal biobricks. In [57], a new notion of modularity is introduced for asynchronous multi-state automata networks considered as discrete models of gene regulation networks. It is supported by dynamical considerations that take into account the asymptotic behaviours of these networks. To detail this, let us consider a network N whose associated interaction graph is $G = (V, A)$. A modular organisation of a network is defined in [57] by an ordered partition⁵ (V_0, \dots, V_{k-1}) of the set of network automata. The subgraph of G induced by V_i is said to be a module of N if the ordered sets V_i , $i < k$, satisfy $\mathcal{E} = \mathcal{E}_0 \circ \dots \circ \mathcal{E}_{k-1}$, where \mathcal{E}_W , $W \subseteq V$ denotes the asymptotic behaviour of the subnetwork of N induced by W and \circ is a composition operator defined in [57]. In this context, the authors of [57] show that any topological ordering⁶ on the set of strongly connected components of the underlying structure of a network N does indeed define a modular organisation of N . However, in the general case, strongly connected components are not minimal modules and thus do not allow to reveal biobricks. In some cases, they can be decomposed into smaller independent sub-modules. What is interesting is that for Boolean automata networks, all encountered examples of non-decomposable strongly connected components involve non-monotony.

⁵ An *ordered partition* (S_0, \dots, S_{k-1}) of an arbitrary set S , is defined by $k \leq |S|$ non-empty ordered subsets $S_i \subset S$ such that $S = \bigsqcup_{i < k} S_i$ (i.e., $\forall i, j < k, i \neq j \Rightarrow S_i \cap S_j = \emptyset$ and $S = \bigcup_{i < k} S_i$).

⁶ If $G = (V, A)$ is a digraph, a *topological ordering* of G is a linear ordering of the vertices in V such that, $\forall (i, j) \in A$, i comes before j in the ordering.





Fig. 4. Top panel: Generic description of the four smallest Boolean automata networks that satisfy the conditions of Proposition 1. Bottom panels: (left) generic (see proof of Proposition 1) asynchronous and (right) general transition graphs of these networks.

In different lines, the importance of non-monotony can also be seen by adapting some results presented in [43]. This produces Proposition 1 below which relates non-monotony to non-trivial changes in the dynamical behaviours of a network when synchronism is added to its asynchronous behaviour. In this proposition, a transition $(x, F_W(x))$ is said to be *sequentialisable* if there exists a series of consecutive asynchronous transitions $(x, F_{\{i\}}(x)), (F_{\{i\}}(x), F_{\{j\}} \circ F_{\{i\}}(x)), \dots$ that start in x and end in $F_W(x)$.

Proposition 1. *The smallest Boolean automata networks that have non-sequentialisable synchronous transitions and significantly different limit behaviours under the asynchronous and general updating modes are non-monotone.*

Proof. Let us find the smallest network N with a non sequentialisable synchronous transition. Obviously, this network needs to have more than one automaton and if it has size 2, then, to have a non-sequentialisable synchronous transition, its general transition graph needs to contain a subgraph of the following form:



where $\bar{x}^{i,j} = \bar{x}^{\{i,j\}} = \bar{x}^i$ (see Equation 1). Moreover, to have significantly

different asymptotic behaviours under the asynchronous and general updating modes, the synchronous transition $(x, \bar{x}^{i,j})$ must go out of a set of configurations that induces a stable oscillation under the asynchronous updating mode. Thus, the general transition graph of N must have the form of the general transition graph pictured in the bottom right panel of Figure 4. Then, only two functions f_0 are possible. If in configuration x above, $x_0 = 1$, then, $f_0(x) : x \mapsto x_0 \oplus x_1$ where \oplus denotes the XOR connector⁷. If in configuration x above, $x_0 = 0$, then $f_0(x) : x \mapsto \neg(x_0 \oplus x_1)$. The function f_1 is defined similarly. In conclusion, there are four smallest networks satisfying the properties of Proposition 1. They have size 2 and their interactions graph equal the graph pictured in the top panel of Figure 4. Their two local interaction functions f_0 and f_1 either equal $x \mapsto x_0 \oplus x_1$ or $x \mapsto \neg(x_0 \oplus x_1)$. \square

The reasons evoked in this section that led us to focus on non-monotony in automata networks emphasise the apparent importance of non-monotone functions. In the next section, to initiate an analysis of the behaviours of general non-monotone networks and develop some intuition in this direction, we focus on a specific class of non-monotone networks, namely XOR circulant networks, and study some of their dynamical properties.

4 XOR circulant networks

Before we present some results on the trajectorial and asymptotic dynamical behaviours of XOR circulant networks, let us first introduce some definitions and preliminary properties in relation to these.

4.1 Definitions and basic properties

A *circulant matrix* \mathcal{C} is a matrix of order n whose i^{th} row vector \mathcal{C}_i ($i < n$) is the right-cyclic permutation with offset i of its first row vector \mathcal{C}_0 so that \mathcal{C} has the following form:

$$\mathcal{C} = \begin{pmatrix} c_0 & c_1 & c_2 & \dots & c_{n-1} \\ c_{n-1} & c_0 & c_1 & \dots & c_{n-2} \\ c_{n-2} & c_{n-1} & c_0 & \dots & c_{n-3} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ c_1 & c_2 & c_3 & \dots & c_0 \end{pmatrix}.$$

⁷ $\forall a, b \in \{0, 1\}$, $a \oplus b = (a \wedge \neg b) \vee (\neg a \wedge b)$.

For any integer $k \geq 2$, a k -XOR *circulant network* of size $n \geq k$ is a Boolean automata network with n automata that can be numbered so that the following four properties are satisfied: (i) the adjacency matrix \mathcal{C} of the network interaction graph $G = (V, A)$ (i.e., the $n \times n$ matrix \mathcal{C} defined by $\forall i, j \in V, \mathcal{C}_{i,j} = 1 \iff (j, i) \in A$), called the *interaction matrix* for short, is a circulant matrix, (ii) each row $\mathcal{C}_i, i \in V$ of this matrix contains exactly k non-null coefficients (i.e., $\forall i \in V, \sum_{j \in V} \mathcal{C}_{i,j} = \deg_G^-(i) = k$), (iii) $\mathcal{C}_{0,n-1} = c_{n-1} = 1$ and (iv) the local transition function f_i of any automaton $i \in V$ is a XOR function:

$$\forall x \in \{0, 1\}^n, f_i(x) = \bigoplus_{j \in V} \mathcal{C}_{i,j} \cdot x_j = \sum_{j \in V} \mathcal{C}_{i,j} \cdot x_j \ [2],$$

where, for any integers a and b , $a[b]$ stands for $a \pmod{b}$. In the sequel, for the sake of simplicity, XOR circulant networks are considered to be subjected to the *parallel updating mode* so that if $x = x(t) \in \{0, 1\}^n$ is the network configuration at time step $t \in \mathcal{T}$, then the network configuration at time step $t+1$ equals $x(t+1) = F(x) = \mathcal{C} \cdot x$ (where operations are supposed to be taken modulo 2). Thus, a XOR circulant network is completely defined by its interaction graph $G = (V, A)$ or by its interaction matrix \mathcal{C} . Figure 5 pictures two examples of 2-XOR circulant networks of size 5. Let us note that one of the four networks satisfying Proposition 1 and defined in Figure 4 is also a 2-XOR circulant network of size 2.

Let us note that by point (iii) in their definitions, k -XOR circulant networks have Hamiltonian circuits underlying their structures. When automata are numbered as suggested in this definition, these circuits are composed of the set of arcs $\{(i, i+1 [n]) \mid i \in V\} \subseteq A$. More generally, it can be shown that each non-null coefficient $c_j = \mathcal{C}_{0,j}$ of a circulant interaction matrix \mathcal{C} induces $\gcd(n, j)$ independent circuits of length $n/\gcd(n, j)$ in the interaction graph G of the corresponding network. Now, it has been shown that to have several stable configurations and/or stable oscillations, Boolean automata networks need to have circuits underlying their interaction graphs [11,47,61]. Thus, the presence of circuits underlying the structures of k -XOR circulant networks guarantees that these networks have interesting, non-trivial dynamical behaviours.

Any k -XOR circulant network N can be seen in terms of *cellular automata*. Indeed, if N has size n and interaction graph $G = (V, A)$, it can be modelled by the finite one-dimensional cellular automaton that has n cells assimilated to the n automata of N and that satisfies what follows. The *neighbourhood* \mathcal{N} of a cell $i \in V$ equals the in-neighbourhood of automaton i in N : $\mathcal{N} = \{j \in V \mid (j, i) \in A\}$. The local rule $\gamma : \{0, 1\}^{|\mathcal{N}|} \rightarrow \{0, 1\}$




Fig. 5. Interaction graphs, local transition functions and interaction matrices of two 2-XOR circulant networks of sizes 5.

of the cellular automaton is defined similarly to the local transition functions of N : $\gamma((x_\ell)_{\ell \in \mathcal{N}}) = \bigoplus_{\ell \in \mathcal{N}} x_\ell$. In the sequel, we use this formalisation to exploit tools drawn from the theory of cellular automata. Thus, if $x = x(0) \in \{0, 1\}^n$ is an initial configuration of N , we consider the corresponding *space-time diagram*, that is, the grid of $\{0, 1\}^n \times \mathcal{T}$ whose line $t \in \mathcal{T}$ represents $x(t)$, *i.e.*, the configuration of N at time step t . The *trace* of cell or automaton $i \in V$ then corresponds to column i of this grid, that is, to the sequence $(x_i(t))_{t \in \mathcal{T}}$. Also, for an arbitrary configuration $x \in \{0, 1\}^n$ and an automaton $i \in V$, $S_i(x)$ denotes the configuration that satisfies $\forall j \in V, S_i(x)_j = x_{2i-j [n]}$. It is called the *symmetric of x with respect to i* . We write \tilde{N} to denote the *symmetric of N* , that is, the k -XOR circulant network whose interaction matrix is ${}^t\mathcal{C}$. In the sequel, by default, $\mathcal{N}^-(i)$ (resp. $\mathcal{N}^+(i)$) denotes the *in-neighbourhood* (resp. the *out-neighbourhood*) of automaton i in N and $\tilde{\mathcal{N}}^-(i)$ (resp. $\tilde{\mathcal{N}}^+(i)$) denotes its in-neighbourhood (resp. its out-neighbourhood) in \tilde{N} . This way, for any two automata $i, j \in V, j \in \mathcal{N}^-(i) \iff j \in \tilde{\mathcal{N}}^+(i)$. The global transition function of \tilde{N} is denoted by \tilde{F} if that of N is denoted by F . One last convention that is used throughout the sequel is the following. By default, unless N is the symmetric of another k -XOR circulant network that was introduced before, its automata are supposed to be numbered as suggested above in the definition of k -XOR circulant networks so that $c_{n-1} = \mathcal{C}_{0, n-1} = 1$. This way, $\{(i, i+1 [n]) \mid i \in V\} \subseteq A$ defines a Hamil-

tonian circuit in the structure of N and $\{(i+1 [n], i) \mid i \in V\} \subseteq A$ defines a Hamiltonian circuit in the structure of its symmetric \tilde{N} .

To end this paragraph, we list some basic properties of XOR circulant networks that follow directly from the definitions of XOR functions and circular matrices.

Proposition 2.

1. The number of k -XOR circulant networks of size n equals $\binom{k-1}{n-1}$.

Any k -XOR circulant network of size n satisfies the following properties:

2. Configuration $(0, \dots, 0)$ is a stable configuration.
3. Configuration $(1, \dots, 1)$ is an antecedent of $(0, \dots, 0)$ if k is even or a stable configuration if k is odd.
4. The trajectory of a configuration x is isomorphic to that of any configuration y which is a circular permutation of x .

4.2 Results

General k -xor circulant networks First, in this paragraph, we concentrate on general k -XOR circulant networks and exploit the cellular automata formalisation presented above to derive some features of the dynamical behaviours of these networks.

Lemma 1. *Let N be a k -XOR circulant network of size n with automata set V and symmetric global transition function \tilde{F} . For any automaton $i \in V$, let $M_i(t)$, $t \in \mathcal{T}$, denote the set of automata which have state 1 in configuration $\tilde{F}^t(\vec{0}^i)$. Then, $\forall x(0) \in \{0, 1\}^n$, $\forall t \in \mathcal{T}$, $x_i(t) = \bigoplus_{j \in M_i(t)} x_j(0)$.*

Proof. We prove Lemma 1 by induction on $t \in \mathcal{T}$.

For $t = 0$, $M_i(0) = \{i\}$ holds by definition of configuration $\vec{0}^i$. Thus, $\forall x(0) \in \{0, 1\}^n$, $x_i(0) = \bigoplus_{j \in M_i(0)} x_j(0)$.

Now, suppose that $\forall x(0) \in \{0, 1\}^n$, $x_i(t) = \bigoplus_{j \in M_i(t)} x_j(0)$ and consider the initial configuration $y(0) \in \{0, 1\}^n$.

Since $y(t+1) = \tilde{F}^{t+1}(y(0)) = \tilde{F}^t(y(1))$, applying the induction hypothesis to configuration $x(0) = y(1)$ yields:

$$y_i(t+1) = \bigoplus_{j \in M_i(t)} y_j(1).$$

By definition, $\forall j \in V$, $y_j(1) = f_j(y(0)) = \bigoplus_{\ell \in \mathcal{N}^-(j)} y_\ell(0) = \bigoplus_{\ell \in \tilde{\mathcal{N}}^+(j)} y_\ell(0)$. Thus, with the commutativity and associativity of the \oplus operator, we can derive that:

$$\begin{aligned} y_i(t+1) &= \bigoplus_{j \in M_i(t)} \left(\bigoplus_{\ell \in \tilde{\mathcal{N}}^+(j)} y_\ell(0) \right) \\ &= \bigoplus_{\{\ell \mid |\tilde{\mathcal{N}}^-(\ell) \cap M_i(t)|=1 \text{ [2]}\}} y_\ell(0) \end{aligned}$$

Now, let us remark that $\forall t \in \mathcal{T}$, $\tilde{F}(\bar{0}^{M_i(t)}) = \bar{0}^{M_i(t+1)}$ by definition. Then, $\forall \ell \in V$, $\bar{0}_\ell^{M_i(t+1)} = 1$ if and only if $|\tilde{\mathcal{N}}^-(\ell) \cap M_i(t)| \equiv 1 \text{ [2]}$. From this follows $y_i(t+1) = \bigoplus_{j \in M_i(t+1)} y_j(0)$ and then $\forall t \in \mathcal{T}$, $x_i(t) = \bigoplus_{j \in M_i(t)} x_j(0)$. \square

Lemma 2. *Let N be a k -XOR circulant network of size n with automata set V and global transition function F . For any automaton $i \in V$, and for any configuration $x \in \{0, 1\}^n$, it holds that $\tilde{F}(S_i(x)) = S_i(F(x))$.*

Proof. For any $j \in V$, the following holds:

$$\begin{aligned} \tilde{F}(S_i(x))_j &= \bigoplus_{\ell \in \tilde{\mathcal{N}}^-(j)} (S_i(x))_\ell = \bigoplus_{\ell \in \tilde{\mathcal{N}}^-(j)} x_{2i-\ell \ [n]} \\ &= \bigoplus_{\{\ell \text{ s.t. } 2i-\ell \ [n] \in \tilde{\mathcal{N}}^-(j)\}} x_\ell \\ &= \bigoplus_{\{\ell \text{ s.t. } j \in \mathcal{N}^-(2i-\ell \ [n])\}} x_\ell. \end{aligned}$$

If $j \in \mathcal{N}^-(2i - \ell \ [n])$, then all automata $l, l' \in V$ of N such that $l - l' = j - (2i - \ell) \ [n]$ are such that $l \in \mathcal{N}^-(l')$. In particular, if automaton $j \in \mathcal{N}^-(2i - \ell \ [n])$, then $\ell \in \mathcal{N}^-(2i - j)$. Hence:

$$\begin{aligned} \bigoplus_{\{\ell \text{ s.t. } j \in \mathcal{N}^-(2i-\ell \ [n])\}} x_\ell &= \bigoplus_{\ell \in \mathcal{N}^-(2i-j \ [n])} x_\ell \\ &= F(x)_{2i-j} \\ &= (S_i(F(x)))_j, \end{aligned}$$

and Lemma 2 follows. \square

Proposition 3. *Let N be a k -XOR circulant network of size n with automata set V and global transition function F . For any automaton $i \in V$ and for the initial configuration $x(0) = \bar{0}^i$, it holds that $\forall t \in \mathcal{T}$, $\tilde{F}^t(x(0)) = S_i(x(t))$.*

Proof. Proposition 3 is proven by induction on $t \in \mathcal{T}$. Let $t = 0$. Property $\tilde{F}^t(x(0)) = S_i(x(t))$ is true because $x(0) = \bar{0}^i$. Suppose that it is true for $t \in \mathcal{T}$. Then, we have $\tilde{F}^{t+1}(x(0)) = \tilde{F}(\tilde{F}^t(x(0))) = \tilde{F}(S_i(x(t)))$. By Lemma 2, $\tilde{F}(S_i(x(t))) = S_i(F(x(t))) = S_i(x(t+1))$, which is the expected result. \square

Remark that this result is due to the fact that F and \tilde{F} are the global transition functions of two symmetric k -XOR circulant networks that are isomorphic by definition (see Figure 6). Proposition 3 implies that, for any automaton $i \in V$, the space-time diagram of $(\bar{0}^i(t))_{t \in \mathcal{T}}$ is the symmetric space-time diagram of $(\bar{0}^{M_i(t)})_{t \in \mathcal{T}}$ with respect to i and is related to the trace of automaton i . Thus, the space-time diagrams of configurations of density $\frac{1}{n}$ carry information on the global behaviours of N . We examine further these properties in the following results.

Proposition 4. *Let N be a k -XOR circulant network of size n with automata set V and global transition function F . The maximum convergence time, i.e., the maximal trajectory length, is reached by configurations of density $\frac{1}{n}$. Moreover, let p_* be the period of the attractors reached by configurations of density $\frac{1}{n}$. Then, for any configuration x of N , the period of its attractor (i.e., of the attractor that is reached by the network when it is initially in configuration x) divides p_* .*

Proof. Since all configurations of density $\frac{1}{n}$ are cyclic permutations of one another, by Proposition 2.4 they all have isomorphic trajectories so that they all hit their limit set at the same time t_* and they all have the same period p_* . Now, consider configuration x and automaton i . By Proposition 3, the space-time diagram of $(\bar{0}^{M_i(t)})_{t \in \mathcal{T}}$ is the symmetric space-time diagram of $(\bar{0}^i(t))_{t \in \mathcal{T}}$ with respect to i . Thus, the space-time diagram of $(\bar{0}^{M_i(t)})_{t \in \mathcal{T}}$ hits its limit set at time t_* and its period is p_* . This means that, $\forall i \in N$, the trace of automaton i has period p_* and hits its limit before t_* . Thus, the trajectory of x reaches its limit set before t_* and its period divides p_* . \square

2-xor circulant networks Let us now concentrate on 2-XOR circulant networks of arbitrary size n and pay particular attention to the space-time diagrams of configurations of density $\frac{1}{n}$. We define the *interaction-step* of such a network N as the smallest integer $s \neq 1 < n$ such that $\forall i \in V, (i, i + s [n]) \in A$. As illustrated in Figure 6 (a) and (b), when $s = 0$ the space-time diagram is the Sierpinski triangle. For other values




Fig. 6. Space-time diagrams (a) of a 2-XOR circulant network of size 14 and interaction-step $s = 0$ (see Section 4.2), (b) of its symmetric network and (c) of another 2-XOR circulant network of size 27 and interaction-step 4.

of s , space-time diagrams seem like deformed Sierpinski triangles. From these observations results the following lemma.

Lemma 3. *Let N be a 2-XOR circulant network of size n with interaction-step $s = 0$. The following holds:*

$$\forall i \in V, \forall q \in \mathbb{N}, x_i(2^q) = x_{(i-2^q) [n]}(0) \oplus x_i(0).$$

Proof. Lemma 3 is proven by induction on q .

Let $i \in V$ be an arbitrary automaton and let q equal 1 initially. Then, obviously, the following is true:

$$\begin{aligned} x_i(2) &= x_{(i-1) [n]}(1) \oplus x_i(1) \\ &= x_{(i-2) [n]}(0) \oplus x_{(i-1) [n]}(0) \oplus x_{(i-1) [n]}(0) \oplus x_i(0) \\ &= x_{(i-2) [n]}(0) \oplus x_i(0), \end{aligned}$$

and the basis of the induction holds.

Now, let us assume as induction hypothesis that $x_i(2^q) = x_{(i-2^q) [n]}(0) \oplus x_i(0)$ is true for $q \in \mathbb{N}$. In the sequel, we pay particular attention to states

$$\begin{aligned} a &= x_i(0), & b &= x_{(i-2^{q-1}) [n]}(0), & c &= x_{(i-2^q) [n]}(0), & d &= x_i(2^{q-1}), \\ e &= x_{(i-2^{q-1}) [n]}(2^{q-1}) & \text{and} & & f &= x_i(2^q), \end{aligned}$$




Fig. 7. Space-time diagram of an arbitrary 2-XOR circulant network of size n and interaction-step $s = 0$.

as illustrated in Figure 7.

Then, for $q + 1$, according to the induction hypothesis, we have:

$$d = a \oplus b, \quad e = b \oplus c \quad \text{and} \quad f = d \oplus e.$$

Then, we derive that:

$$f = d \oplus e = (a \oplus b) \oplus (b \oplus c) = a \oplus c.$$

As a result, we can write:

$$\forall i \in V, \forall q \in \mathcal{N}, \quad x_i(2^q) = x_i(0) \oplus x_{(i-2^q) [n]}(0),$$

which is the expected result. \square

We will use this lemma to analyse 2-XOR circulant networks of size $n = 2^p$, $p \in \mathbb{N}^*$, and interaction step $s = 0$.

2-xor circulant networks of sizes powers of 2 In this paragraph, we focus on 2-XOR circulant networks of sizes $n = 2^p$, where $p \in \mathbb{N}^*$. Let $x = (x_0, \dots, x_{n-1}) \in \{0, 1\}^n$ be a configuration of such a network N . We can see x as the concatenation of two vectors of sizes $\frac{n}{2}$ such that $x = (x', x'')$, where $x' = (x_0, \dots, x_{\frac{n}{2}-1})$ and $x'' = (x_{\frac{n}{2}}, \dots, x_{n-1})$ are called *semi-configurations* of x . The *repetition degree* $\delta_r(x)$ of x is then defined as:

$$\delta_r(x = (x', x'')) = \begin{cases} 0 & \text{if } x' \neq x'', \\ \delta & \text{if } (x' = x'') \wedge (\delta_r(x') = \delta - 1). \end{cases}$$

Notice that if $x = (x', x')$, x is said to be a *repeated configuration* and that, in the worst case (*i.e.*, when the repetition degree $\delta_r(x) = \log_2(n)$ is maximal), the time complexity of the computation of the repetition degree of any configuration x equals n .

Proposition 5 below characterises the dynamical behaviours of repeated configurations $x \in \{0, 1\}^n$ of repetition degree $\delta_r(x) \geq \log_2(n) - 1$ in arbitrary 2-XOR circulant networks of size $n = 2^p$, $p \in \mathbb{N}^*$.

Proposition 5. *Let N be a 2-XOR circulant network of size $n = 2^p$, $p \in \mathbb{N}^*$, and interaction-step s . Configurations $x \in \{0, 1\}^n$ of repetition degree $\delta_r(x) \geq \log_2(n) - 1$ converge towards $(0, \dots, 0)$ in no more than 2 time steps.*

Proof. First, notice that because N is a 2-XOR circulant network of size $n = 2^p$, $p \in \mathbb{N}^*$, there exist only 4 repeated configurations of degree no smaller than $\log_2(n) - 1$, that is, $(0, 1, \dots, 0, 1)$, its dual $(1, 0, \dots, 1, 0)$ and $(1, \dots, 1)$ and its dual $(0, \dots, 0)$. Let us consider the two distinct parities of s independently. Also, let $t \in \mathcal{T}$ and let $x(t)$ be either $(0, 1, \dots, 0, 1)$ or $(1, 0, \dots, 1, 0)$.

1. If s is even, then, by hypothesis on $x(t)$:

$$\forall i \in V, x_{(i+s) [n]}(t+1) = x_i(t) \oplus x_{(i+s-1) [n]}(t) = 1.$$

2. If s is odd, then, by hypothesis on $x(t)$:

$$\forall i \in V, x_{(i+s) [n]}(t+1) = x_i(t) \oplus x_{(i+s-1) [n]}(t) = 0.$$

This, together with Propositions 2.2 and 2.3, yields the expected result. \square

From now on, we restrict the study to 2-XOR circulant networks of sizes $n = 2^p$, $p \in \mathbb{N}^*$, and interaction-steps $s = 0$. We show that such networks necessarily converge towards configuration $(0, \dots, 0)$ in no more than n time steps and that initial configurations with an odd number of 1 converge in exactly n steps.

Theorem 1. *Let N be a 2-XOR circulant network of size $n = 2^p$, $p \in \mathbb{N}^*$, and interaction-step 0. Any configuration x converges to the stable configuration $(0, \dots, 0)$ in no more than n time steps.*

Proof. Since $n = 2^p$, by Lemma 3, we directly draw:

$$\forall i \in V, x_i(n) = x_i(0) \oplus x_{i+n [n]}(0) = x_i(0) \oplus x_i(0) = 0.$$

This allows to conclude that any configuration x converges to the stable configuration $(0, \dots, 0)$ in no more than n time steps. \square

Now, let us consider the configurations for which the convergence speed is maximal.

Lemma 4. *Let N and N' be two 2-XOR circulant networks of respective sizes $n = 2^{p+1}$ and $n' = 2^p$, $p \in \mathbb{N}^*$, and interaction-steps 0. Let x' be a configuration of size 2^p and $x = (x', x')$ be a repeated configuration of size 2^{p+1} . Then, for any $t \in \mathcal{T}$, $x(t) = (x'(t), x'(t))$.*

Proof. Considering an arbitrary repeated configuration x of N , by induction on t , we show that $\forall t \in \mathcal{T}$, $x(t) = (x'(t), x'(t))$. Let us denote by $G' = (V', A')$ the interaction graph of N' .

By hypothesis, the proposition is true for $t = 0$.

Now, consider that $x(t) = (x'(t), x'(t))$ for $t \in \mathcal{T}$ and that

$$\forall i \in V, x_i(t+1) = x_{(i-1) [n]}(t) \oplus x_i(t).$$

Since $x(t)$ is a repeated configuration, we have:

$$\begin{aligned} \forall i \in V, x_i(t+1) &= x_{(i-1) [n]}(t) \oplus x_i(t) \\ &= x_{(i-1+2^p) [n]}(t) \oplus x_{(i+2^p) [n]}(t) \\ &= x_{(i+2^p) [n]}(t+1). \end{aligned}$$

Thus, $x(t+1)$ is also repeated and it satisfies:

$$\begin{aligned} \forall i \in V', x_i(t+1) &= x_{(i-1) [n']}(t) \oplus x_i(t) \\ &= x'_{(i-1) [n']}(t) \oplus x'_i(t) \\ &= x'_i(t+1). \end{aligned}$$

As a result, it holds that $x(t+1) = (x'(t+1), x'(t+1))$. \square

Proposition 6. *Let N be a 2-XOR circulant network of size $n = 2^p$, $p \in \mathbb{N}^*$, and interaction-step 0. Any configuration x such that $n \cdot d(x) \equiv 1 [n]$ (with an odd number of 1s) converges in n time steps exactly.*

Proof. Proposition 6 is proven by induction on p .

If $p = 1$, according to Propositions 2.3 and 5, configurations of repetition degree $\log_2(n) - 1$ are proven to converge in 2 time steps. Thus, Proposition 6 holds for $p = 1$.

Suppose that for $p = q$, any configuration x such that $2^q \cdot d(x) \equiv 1 [n]$ converges in 2^q time steps.

Now, suppose that $p = q + 1$ and consider a 2-XOR circulant network N of size $n = 2^{q+1}$ and interaction-step 0. Let x be a configuration of size 2^{q+1} such that $n \cdot d(x) \equiv 1 [n]$. We show that after 2^q time steps:

1. $x(2^q)$ is a repeated configuration of the form $x(2^q) = (x'(2^q), x'(2^q))$.
By Lemma 3, $\forall i \in \{0, \dots, 2^q - 1\}$, $x_i(2^q) = x_i(0) \oplus x_{(i+2^q) [n]}(0)$.
Hence:

$$\forall i \in \{0, \dots, 2^q - 1\},$$

$$x_i(2^q) = x_{(i+2^{q+1}) [n]}(0) \oplus x_{(i+2^q) [n]}(0) = x_{(i+2^q) [n]}(2^q).$$

2. x' has an odd number of 1s. By Lemma 3 and the property above, since $\forall i \in \{0, \dots, 2^q - 1\}$, $x'_i(2^q) = x_i(2^q) = x_i(0) + x_{(i+2^q) [n]}(0)$, each automaton of $x(0)$ influences exactly one automaton of x' . If $x'_i(2^q) = 0$, then the states of both the automata of $x(0)$ that influence $x'_i(2^q)$ must have the same parity. If $x'_i(2^q) = 1$ then the states of both the automata of $x(0)$ that influence $x'_i(2^q)$ must have different parities. Since there is an odd number of 1s in $x(0)$, there is an odd number of 1s in $x'(2^q)$.

By Lemma 4, $x(2^q)$ behaves exactly like $x'(2^q)$. By the induction hypothesis, x' converges in exactly 2^q time steps. Thus x converges in exactly $n = 2^{q+1}$ time steps. \square

5 Conclusion and perspectives

With this study, we have endeavoured to show that non-monotony is an interesting concept *per se*, despite the lack of specific attention it has received so far. On the one hand, to serve as a stepping-stone and acquire some initial intuitions in this domain, we have considered a special family of non-monotone Boolean automata networks that we named XOR circulant networks. In particular, we have focused on the trajectorial and asymptotic behaviours of these networks, considered their convergence speeds and characterised their attractors. Globally, this preliminary formal analysis revealed that simple non-monotone networks can exhibit non-trivial, engaging properties. On the other hand, more generally and informally, we also have put forward several arguments to support the idea that work needs to be done to build a better understanding of the role of non-monotony in the behaviours of automata networks. In these lines, we have mentioned that studies in this context could find concrete and relevant applications in biology and in particular in the modelling of genetic regulation networks by automata networks. In addition, we have given two theoretical arguments in favour of our insights by which non-monotony could be responsible for singular network behaviours. First, exploiting [57], we have argued that non-monotony may be responsible

for the strongly connected components of networks being non-separable, minimal functional modules. Second, in Proposition 1, with the state transition systems formalism, we have considered “synchronism sensitivity”, that is, the property of Boolean automata networks to display significant behavioural changes when synchronism is added to their automata state updates. And in this context, we have shown that the smallest synchronism sensitive Boolean automata networks are also non-monotone.

The issues presented in this paper open many research directions that could help develop a better understanding of the precise role of non-monotony in formal automata networks and, *a fortiori*, in real biological regulation networks. One of these perspectives consists in identifying the relations that exist between monotone and non-monotone Boolean automata networks. In [43], some preliminary results are derived on synchronism sensitivity. In particular it is shown that this property requires specific circuits underlying the networks structures. Also, monotone examples of synchronism sensitive networks are given. The interesting point is that all of them seem to involve a *monotone coding* of non-monotony. With Proposition 1, this naturally raises the question of whether non-monotony (taken in a more general sense than what we did formally above) can account in a certain way for the synchronism sensitivity in arbitrary monotone and non-monotone networks. Thus, Proposition 1 together with the work presented in [43] call for further researches in this direction. With sufficient knowledge in this context, we then hope to move on to the subject of modularity as developed in [57] and work on establishing the exact non-separability conditions of strongly connected networks. In this context, the first important questions that need to be addressed are: “Does there exist monotone strongly connected networks that are separable into functional modules?” and “How does non-monotony relate to the non-separability of non-monotone networks?”. The relevance of these questions lies in that their answers will help understand modularity in biological regulation networks, which is a central issue in present biological research frameworks such as synthetic biology. Eventually, further analyses also need to be done on the dynamical behaviours of XOR circulant networks. Indeed, we believe that these networks constitute very promising instances of non-monotone networks because of their apparent simplicity and because, since they involve underlying structural circuits, their dynamical behaviours are potentially diverse and complex. Thus, pursuing in this direction, we hope to obtain generalisations of the results that figure above concerning the parallel updating mode by relaxing structural constraints step by step. Also, another interesting per-

spective in this framework is to consider XOR circulant networks as state transition systems, under the asynchronous and general updating modes. This perspective is motivated in particular by the fact that, according to Proposition 1, the smallest synchronism sensitive networks are either XOR circulant networks of size 2 and interaction-step 0, or networks that have the same structures as these and comparable non-monotone interactions.

6 Acknowledgements

We thank Florian Rabin for his relevant comments and are indebted to the *Agence nationale de la recherche* and the *Réseau national des systèmes complexes* that have respectively supported this work through the projects Synbiotic (ANR 2010 BLAN 030701) and Météding (RNSC AI10/11-L03908).

References

1. McCulloch, W.S., Pitts, W.: A logical calculus of the ideas immanent in nervous activity. *Journal of Mathematical Biology* **5** (1943) 115–133
2. Kauffman, S.A.: Metabolic stability and epigenesis in randomly constructed genetic nets. *Journal of Theoretical Biology* **22** (1969) 437–467
3. Kauffman, S.A.: Homeostasis and differentiation in random genetic control networks. *Nature* **224** (1969) 177–178
4. Hopfield, J.J.: Neural networks and physical systems with emergent collective computational abilities. *Proceedings of the National Academy of Sciences of the USA* **79** (1982) 2554–2558
5. Hopfield, J.J.: Neurons with graded response have collective computational properties like those of two-state neurons. *Proceedings of the National Academy of Sciences of the USA* **81** (1984) 3088–3092
6. Kauffman, S.A.: Gene regulation networks: a theory for their global structures and behaviors. In: *Current topics in developmental biology*. Volume 6. Elsevier (1971) 145–181
7. Kauffman, S.A.: *The origins of order*. Oxford University Press (1993)
8. Jacob, F., Monod, J.: Genetic regulatory mechanisms in the synthesis of proteins. *Journal of Molecular Biology* **3** (1961) 318–356
9. Jacob, F., Monod, J.: On the regulation of gene activity. *Cold Spring Harbor Symposia on Quantitative Biology* **26** (1961) 193–211
10. Thomas, R.: Boolean formalisation of genetic control circuits. *Journal of Theoretical Biology* **42** (1973) 563–585
11. Thomas, R.: On the relation between the logical structure of systems and their ability to generate multiple steady states or sustained oscillations. In: *Numerical methods in the study of critical phenomena*. Volume 9 of Springer Series in Synergetics. Springer (1981) 180–193
12. Thomas, R.: Regulatory networks seen as asynchronous automata: a logical description. *Journal of Theoretical Biology* **153** (1991) 1–23

13. Floréen, P., Orponen, P.: On the computational complexity of analyzing Hopfield nets. *Complex Systems* **3** (1989) 577–587
14. Cosnard, M., Koiran, P., Paugam-Moisy, H.: Complexity issues in neural network computations. In: Proceedings of LATIN. Volume 583 of Lecture Notes in Computer Science., Springer (1992) 530–544
15. Koiran, P.: Puissance de calcul des réseaux de neurones artificiels. PhD thesis, École normale supérieure de Lyon (1993)
16. Orponen, P.: Computing with truly asynchronous threshold logic networks. *Theoretical Computer Science* **174** (1997) 123–136
17. Gajardo, A., Moreira, A., Goles, E.: Complexity of Langton’s ant. *Discrete Applied Mathematics* **117** (2002) 41–50
18. Robert, F.: Discrete iterations: a metric study. Volume 6 of Springer Series in Computational Mathematics. Springer (1986)
19. Goles, E., Olivos, J.: Comportement périodique des fonctions à seuil binaires et applications. *Discrete Applied Mathematics* **3** (1981) 93–105
20. Goles, E.: Neural and automata networks: dynamical behaviour and applications. Mathematics and Its applications. Kluwer Academic Publishers (1990)
21. Aracena, J., Demongeot, J., Goles, E.: Fixed points and maximal independent sets in AND–OR networks. *Discrete Applied Mathematics* **138** (2004) 277–288
22. Aracena, J., Demongeot, J., Goles, E.: On limit cycles of monotone functions with symmetric connection graph. *Theoretical Computer Science* **322** (2004) 237–244
23. Remy, E., Ruet, P., Thieffry, D.: Graphic requirements for multistability and attractive cycles in a Boolean dynamical framework. *Advances in Applied Mathematics* **41** (2008) 335–350
24. Demongeot, J., Goles, E., Morvan, M., Noual, M., Sené, S.: Attraction basins as gauges of robustness against boundary conditions in biological complex systems. *PLoS One* **5** (2010) e11793
25. Demongeot, J., Noual, M., Sené, S.: Combinatorics of Boolean automata circuits dynamics. *Discrete Applied Mathematics*, in press.
26. Richard, A.: Local negative circuits and fixed points in non-expansive Boolean networks. *Discrete Applied Mathematics* **159** (2011) 1085–1093
27. Goles-Chacc, E., Fogelman-Soulie, F., Pellegrin, D.: Decreasing energy functions as a tool for studying threshold networks. *Discrete Applied Mathematics* **12** (1985) 261–277
28. Cosnard, M., Goles, E.: Discrete state neural networks and energies. *Neural Networks* **10** (1997) 327–334
29. Remy, E., Mossé, B., Chaouiya, C., Thieffry, D.: A description of dynamical graphs associated to elementary regulatory circuits. *Bioinformatics* **19** (2003) ii172–ii178
30. Chaouiya, C., Remy, E., Ruet, P., Thieffry, D.: Qualitative modelling of genetic networks: from logical regulatory graphs to standard Petri nets. In: Proceedings of Petri Nets. Volume 3099 of Lecture Notes in Computer Science., Springer (2004) 137–156
31. Colón-Reyes, O., Laubenbacher, R., Pareigis, B.: Boolean monomial dynamical systems. *Annals of Combinatorics* **8** (2005) 425–439
32. Jarrah, A.S., Laubenbacher, R., Veliz-Cuba, A.: The dynamics of conjunctive and disjunctive Boolean network models. *Bulletin of Mathematical Biology* **72** (2010) 1425–1447
33. Mendoza, L., Alvarez-Buylla, E.: Dynamics of the genetic regulatory network for *Arabidopsis thaliana* flower morphogenesis. *Journal of Theoretical Biology* **193**(2) (1998) 307–319

34. Mendoza, L., Thieffry, D., Alvarez-Buylla, E.: Genetic control of flower morphogenesis in *Arabidopsis thaliana*: a logical analysis. *Bioinformatics* **15** (1999) 593–606
35. Aracena, J., González, M., Zuñiga, A., Mendez, M.A., Cambiazo, V.: Regulatory network for cell shape changes during drosophila ventral furrow formation. *Journal of Theoretical Biology* **239** (2006) 49–62
36. Georgescu, C., Longabaugh, W.J.R., Scripture-Adams, D.D., David-Fung, E.S., Yui, M.A., Zarnegar, M.A., Bolouri, H., Rothenberg, E.V.: A gene regulatory network armature for T lymphocyte specification. *Proceedings of the National Academy of Sciences of the USA* **105** (2008) 20100–20105
37. Mendoza, L., Pardon, F.: A robust model to describe the differentiation of T-helper cells. *Theory in Biosciences* **129** (2010) 283–293
38. Cull, P.: Linear analysis of switching nets. *Biological Cybernetics* **8** (1971) 31–39
39. Huffman, D.A.: The synthesis of linear sequential coding networks. In: *Information theory*. Academic Press (1956)
40. Elspas, B.: The Theory of Autonomous Linear Sequential Networks. *IRE Transactions on Circuit Theory* **6** (1959) 45–60
41. Snoussi, E.H.: Structure et comportement itératif de certains modèles discrets. PhD thesis, Université Grenoble 1 – Joseph Fourier (1980)
42. Choffrut, C., ed.: Automata networks. Volume 316 of *Lecture Notes in Computer Science*. Springer (1988)
43. Noual, M.: Synchronism vs asynchronism in Boolean networks. Technical report, École normale supérieure de Lyon (2011) arXiv:1104.4039.
44. Noual, M.: General transition graphs and Boolean automata circuits. Submitted
45. Noual, M., Sené, S.: Towards a theory of modelling with Boolean automata networks - I. Theorisation and observations. Technical report, École normale supérieure de Lyon and Université d'Évry – Val d'Essonne (2011) arXiv:1111.2077.
46. Richard, A., Comet, J.P., Bernot, G.: R. Thomas' modeling of biological regulatory networks: introduction of singular states in the qualitative dynamics. *Fundamenta Informaticae* **65** (2004) 373–392
47. Richard, A., Comet, J.P.: Necessary conditions for multistationarity in discrete dynamical systems. *Discrete Applied Mathematics* **155** (2007) 2403–2413
48. Demongeot, J., Elena, A., Sené, S.: Robustness in regulatory networks: a multidisciplinary approach. *Acta Biotheoretica* **56** (2008) 27–49
49. Elena, A., Demongeot, J.: Interaction motifs in regulatory networks and structural robustness. In: *Proceedings of CISIS, IEEE* (2008) 682–686
50. Aracena, J., Goles, E., Moreira, A., Salinas, L.: On the robustness of update schedules in Boolean networks. *Biosystems* **97** (2009) 1–8
51. Aracena, J., Fanchon, É., Montalva, M., Noual, M.: Combinatorics on update digraphs in Boolean networks. *Discrete Applied Mathematics* **159** (2010) 401–409
52. Goles, E., Noual, M.: Block-sequential update schedules and Boolean automata circuits. In: *Proceedings of Automata 2010, DMTCS* (2010) 41–50
53. Goles, E., Noual, M.: Disjunctive networks and update schedules. *Advances in Applied Mathematics*, in press.
54. Robert, F.: Les systèmes dynamiques discrets. Volume 19 of *Mathématiques & Applications*. Springer (1995)
55. Goles, E., Salinas, L.: Comparison between parallel and serial dynamics of Boolean networks. *Theoretical Computer Science* **396** (2008) 247–253
56. Lederberg, E.M.: Lysogenicity in *Escherichia coli* strain K-12. *Microbial Genetics Bulletin* **1** (1950) 5–9

57. Delaplace, F., Klaudel, H., Melliti, T., Sené, S.: Analysis of modular organisation of interaction networks based on asymptotic dynamics. Submitted
58. Milo, R., Shen-Orr, S., Itzkovitz, S., et al.: Network motifs: simple building blocks of complex networks. *Science* **298** (2002) 824–827
59. Rives, A.W., Galitski, T.: Modular organization of cellular networks. *Proceedings of the National Academy of Sciences of the USA* **100** (2003) 1128–1133
60. Gagneur, J., Krause, R., Bouwmeester, T., et al.: Modular decomposition of protein-protein interaction networks. *Genome Biology* **5** (2004) R57
61. Richard, A.: Negative circuits and sustained oscillations in asynchronous automata networks. *Advances in Applied Mathematics* **44** (2010) 378–392