

RECEIVED: March 18, 2023

REVISED: June 14, 2023

ACCEPTED: June 22, 2023

PUBLISHED: July 10, 2023

SNOWMASS'2021 ACCELERATOR FRONTIER

# PetaVolts per meter Plasmonics: introducing extreme nanoscience as a route towards scientific frontiers

## nano<sup>2</sup>WA collaboration

Aakash A. Sahai,<sup>a,\*</sup> Mark Golkowski,<sup>a</sup> Stephen Gedney,<sup>a</sup> Thomas Katsouleas,<sup>b</sup> Gerard Andonian,<sup>c</sup> Glen White,<sup>d</sup> Joachim Stohr,<sup>d</sup> Patric Muggli,<sup>e</sup> Daniele Filippetto,<sup>f</sup> Frank Zimmermann,<sup>g</sup> Toshiki Tajima,<sup>h</sup> Gerard Mourou<sup>i</sup> and Javier Resta-Lopez<sup>j</sup>

<sup>a</sup>University of Colorado Denver, Denver, CO 80204, U.S.A.

<sup>b</sup>University of Connecticut, Storrs, CT, U.S.A.

<sup>c</sup>University of California, Los Angeles, CA, U.S.A.

<sup>d</sup>Stanford Linear Accelerator Center, Menlo Park, CA, U.S.A.

<sup>e</sup>Max-Planck-Institut fur Physik, Munich, Germany

<sup>f</sup>Lawrence Berkeley National Laboratory, Berkeley, CA, U.S.A.

<sup>g</sup>European Center for Nuclear Research (CERN), Geneva, Switzerland

<sup>h</sup>University of California Irvine, Irvine, CA, U.S.A.

<sup>i</sup>Ecole Polytechnique, Paris, France

<sup>j</sup>Institute of Materials Science, University of Valencia, Paterna, Valencia, Spain

E-mail: [aakash.sahai@ucdenver.edu](mailto:aakash.sahai@ucdenver.edu)

**ABSTRACT:** A new class of plasmons has opened access to unprecedented PetaVolts per meter electromagnetic fields which can transform the paradigm of scientific and technological advances. This includes non-collider searches in fundamental physics in addition to making next generation colliders feasible. PetaVolts per meter plasmonics relies on this new class of plasmons uncovered by our work in the large amplitude limit of collective oscillations of quantum electron gas. This Fermi gas constituted by “free” conduction band electrons is inherent in conductive media endowed with a suitable combination of constituent atoms and ionic lattice structure. As this quantum gas of electrons can be as dense as  $10^{24} \text{ cm}^{-3}$ , the coherence limit of plasmonic electromagnetic fields is extended in our model from the classical to the quantum domain,  $0.1\sqrt{n_0}(10^{24} \text{ cm}^{-3}) \text{ PVm}^{-1}$ . Appropriately engineered, structured materials that allow highly tunable material properties also make it possible to overcome disruptive instabilities that dominate the interactions in bulk media. The ultra-high density of conduction electrons and the existence of electronic energy bands engendered by the ionic lattice is only possible due to quantum mechanical effects. Based on this framework,

\*Corresponding author.

it is critical to address various challenges that underlie PetaVolts per meter plasmonics including stable excitation of plasmons while accounting for their effects on the ionic lattice and the electronic energy band structure over femtosecond timescales. We summarize the challenges and ongoing efforts that set the strategy for the future. Extreme plasmonic fields can shape the future by not only opening the possibility of tens of TeV to multi-PeV center-of-mass-energies but also enabling novel pathways in non-collider HEP. In view of this promise, our efforts are dedicated to realization of the immense potential of PV/m plasmonics and its applications.

**KEYWORDS:** Charge transport and multiplication in solid media; Accelerator modelling and simulations (multi-particle dynamics, single-particle dynamics); Waveguides; Interaction of radiation with matter

---

## Contents

<b>1</b>	<b>Introduction: grand challenge of extreme electromagnetic fields</b>	<b>2</b>
<b>2</b>	<b>Scope and organization of the work</b>	<b>4</b>
<b>3</b>	<b>Fundamental framework of PetaVolts per meter Plasmonics</b>	<b>6</b>
<b>4</b>	<b>Non-collider searches through direct access of HEP frontiers: physics case</b>	<b>10</b>
4.1	Examination of nonlinear Quantum Electro-dynamics (QED): opening the vacuum with extreme plasmonic fields	10
4.2	Examining quantum gravity model: ultra-energetic photons from nano-wiggler	11
<b>5</b>	<b>Past ultrafast experiments with conductive materials</b>	<b>11</b>
<b>6</b>	<b>Large-amplitude plasmons: strongly electrostatic and relativistic mode</b>	<b>13</b>
<b>7</b>	<b>Extreme bunch compression, focusing and diagnostics for plasmonics</b>	<b>15</b>
7.1	Longitudinal compression of particle beams to greater than 100kA peak bunch current	15
7.2	Permanent magnet quadrupoles for high-field focusing	19
7.3	Electro-optic sampling (EOS) bunch-length diagnostics for intense beams	19
7.4	Advanced ionization beam-profile diagnostics for intense beams	20
<b>8</b>	<b>X-ray laser driven Carbon Nano-Tubes (CNT)</b>	<b>21</b>
<b>9</b>	<b>PV/m plasmonic: challenges, risks, possibilities, and ongoing efforts</b>	<b>21</b>
9.1	Challenges, risks and possibilities	21
9.1.1	Challenges: direct access to non-collider frontier HEP using PV/m plasmonics	22
9.1.2	Challenges: plasmonic accelerator module for a future collider	22
9.1.3	Challenges: theoretical and computational modeling of plasmonic processes	22
9.1.4	Challenges: plasmonic materials research	23
9.1.5	Risks: PV/m plasmonics initiative	23
9.1.6	Possibilities: unforeseen applications of PV/m plasmonics	24
9.2	Ongoing and future efforts	24
<b>10</b>	<b>Summary and discussion</b>	<b>24</b>

---

## 1 Introduction: grand challenge of extreme electromagnetic fields

Expanding the frontier of accessible electromagnetic field strength naturally opens avenues for advances in the scientific and technological landscape. Particularly, our understanding of the fundamental physical phenomena is heavily dependent upon the technologies available for scaling the maximum accessible strength of electromagnetic fields. Electromagnetics is the only fundamental force field which is amenable to a great degree control.

PetaVolts per meter (PV/m) plasmonics [1–5] elucidated in this work opens access to unprecedented electromagnetic field strengths using a new class of plasmons. Plasmons are widely used quasi-particles constituted by perturbative oscillations of quantum electron gas [6] which are pivotal for nanosciences. Our work innovates a large-amplitude, non-perturbative plasmon [1, 2] for extreme intensification of electromagnetic energy by making possible its confinement over a few nanometers. This unlocks pathways to access unknown fundamental physics.

There is reinforced commitment by the worldwide high-energy physics (HEP) community which studies the fundamental nature of our universe to continue to support the development of new techniques that are capable of breaching the energy and intensity frontier. A crucial part of basic research and development (R&D) on high electromagnetic fields is to open new possibilities to probe frontier physics. Furthermore, high EM fields are also capable of shrinking charged particle accelerators and light-sources in recognition of their critical need for future fundamental discoveries, in general.

This work follows from the contribution of the *nano<sup>2</sup>WA collaboration* to the proceedings of the US Community Study on the Future of Particle Physics or the Snowmass 2021 process. This contribution aims at providing an overview of the PV/m plasmonics initiative and the scientific possibilities it opens.

A new class of plasmons [1–5] introduced by our work opens access to PetaVolts per meter electromagnetic fields. This work is aimed at bringing to the attention of the worldwide HEP community and the accelerator community to new possibilities using PV/m plasmonics. Our PV/m plasmonics model [1–5] extends the coherence limit of collective oscillations from the classical to the quantum domain.

Conventional plasmonic is based upon excitation of perturbative surface plasmons which are purely electromagnetic in nature and commonly based upon the transverse magnetic (TM) mode. Our work [7–11] has introduced a large-amplitude surface plasmon in the strongly electrostatic, crunch-in regime which has significant advantage over perturbative plasmons. Surface plasmons are generally preferred because they avoid direct interaction between the excitation and the plasmonic material. This is discussed below in further details.

We also highlight the strong alignment of the PV/m plasmonics initiative with technological trends in nanoscience, material science and beam physics etc. For instance, the trend in beam physics is towards micron and sub-micron scale charged particle beam compression and diagnostic techniques [1–5]. These technological trends enable the general principles underlying PV/m plasmonics initiative to continue to further develop based upon technological progress. This alignment augurs well for the opening of new possibilities in science as well as technology.

First ideas on using condensed matter systems to drastically shrink the size of collider using possible TeraVolts per meter fields were put forth more than half a century ago by one of the

original pioneers of high-energy physics. Being an early pioneer and experimental nuclear physicist, Robert Hofstadter (awarded the Nobel prize in physics in 1961) first envisioned and advocated technological innovations to dramatically reduce the size of accelerators and extend the reach of HEP. It is to be noted that the experiments led by Hofstadter had extensively utilized the two-mile long Stanford linac for pioneering electron scattering studies to determine the nucleonic structure. In a proposal presented in 1968 [12], Hofstadter envisioned shrinking the several mile long tunnel of his experiments to a room-sized lab using an “atomic accelerator”. We quote [12]:

“To anyone who has carried out experiments in physics with a large modern accelerator there always comes a moment. . . wishes that a powerful compression. . . could take place.”

and,

“Unless there is a new idea which can radically change this picture there would seem to be some kind of limitation on the types of leviathans that the world physics can build in the future.”

As radiofrequency (RF) acceleration technology has been a reliable workhorse of HEP since 1950s, it has undergone continual improvements and redesigns to optimize its size and economic viability. But, it has become apparent over the past several decades that this legacy technology has inherent limits on attainable energy in a practical layout for future colliders. The lack of its scalability is because the highest electromagnetic fields that RF cavities can support are limited to around 100 MV/m. This limit on attainable electromagnetic fields and the acceleration gradient dictates that the only way forward in particle physics is to increase the infrastructure size and as a consequence the cost. Moreover, this limit on gradients for both acceleration and focusing severely limit the possibilities for exploration across the energy, intensity and cosmic frontiers.

Consequently, past and ongoing strategic planning processes around the world have recognized the critical need for advanced accelerator R&D as summarized below (extracts from a few prominent reports are cited):

1. **2014 Particle Physics Prioritization Planning Panel (P5) report [13]**: “Recommendation 26: Pursue accelerator R&D . . . with an appropriate balance among general R&D, directed R&D, and accelerator test facilities and among short-, medium-, and long-term efforts. Focus on outcomes and capabilities that will dramatically improve cost effectiveness for mid-term and far-term accelerators”,
2. **2020 Update for European strategy for particle physics [14]**: “3. High-priority future initiatives: A. the particle physics community should ramp up its R&D effort focused on advanced accelerator technologies. . .”,
3. **2015 HEP Advisory Panel (HEPAP) sub-panel on accelerator R&D [15]**: “Long-term: perform the exploratory research aimed at developing new concepts that will make possible the complementary accelerator facilities of possible science interest after the Next Step” and “R&D that provides higher performance at lower cost should be more heavily emphasized in the definition of the R&D programs.”

**Excessive cost of radio-frequency EM field technology based next collider.** Increasing the accelerating gradient is especially critical for HEP applications that are reliant on beams with TeV energy and beyond. With gradients of the state-of-the-art RF technology being limited to  $< 100 \text{ MeV/m}$ , TeV machines would be tens of kilometers long. The cost of the tunnel of length “L” hosting the accelerators has been estimated in a global study to be  $\sim 2 \text{ Billion USD (2014)} \times (L/10 \text{ km})^{1/2}$  [16].

Even with reduction in length by a factor of only a few, savings in Billions of USD are expected. A very large reduction can be expected from the ultra-high gradients of accelerator module based upon PV/m plasmonics described here. Moreover, longer the accelerators more complex are the associated practical constraints. For instance, stretches of land with geological characteristics suitable for the construction, operation and stability of a collider are difficult to find. Access for maintenance and repair over such distances becomes a major logistic challenge. Therefore, reducing the accelerator and collider length by increasing the accelerating gradient will not only reduce the cost of such a machine, but also simply make it possible to build one.

## 2 Scope and organization of the work

The scope of this work is limited to introducing a new class of plasmons for explorations in fundamental science. Plasmons are quasi-particles excited in condensed matter systems where atomic electrons populate the conduction band at equilibrium. Condensed matter systems have *ultra-high electron densities uniquely afforded by quantum effects* which are inaccessible to a classical ensemble of electrons.

The PetaVolts per meter plasmonics effort uncovers an unprecedented mechanism to access extreme EM fields of plasmons by using the unique properties of condensed matter materials with periodic ionic lattice such as certain crystals and nanomaterials. Access to unprecedented EM fields opens up ultra-high particle acceleration and focusing gradients beyond the reach of existing “advanced” techniques that have matured over many decades in the recent past.

Particularly, of importance are those condensed matter properties that stem from the structure of the *ionic lattice* which inevitably gives rise to *electronic energy bands*. In conductive materials, dictated by principles of quantum mechanics a large density of electrons occupy conduction band energy levels. The conduction electrons are free to move and oscillate in response to external excitation. The collective oscillations of this free electron (Fermion) gas which follows Fermi-Dirac statistics constitute plasmons [6]. The quantum nature of the free electron Fermi gas enables its density to be as high as  $10^{24} \text{ cm}^{-3}$  which in the large-amplitude plasmon model makes it possible to access PetaVolts per meter EM fields [17]. PetaVolts per meter plasmonics mitigates direct collision with the ionic lattice by utilizing a “crunch-in” surface wave which has been uncovered by our work over the past decade [7–11].

Our scope is limited to mechanisms where there exists a strongly correlated ionic lattice and corresponding electronic energy bands during these collective oscillations. Under these conditions, quantum mechanical effects dominate. Specifically, our effort focusses on acceleration and focusing gradients as high as PetaVolts per meter that can be sustained by plasmons that are collective oscillations of the free electron Fermi gas.

The scope of our work *DOES NOT* include:

1. **Solid-state plasmas:** in solid-state plasmas, individual ions are uncorrelated as there is no ionic lattice. Solid-state plasmas are obtained by ablation of solids such as by interacting the solid with a high-intensity optical (near-infrared) laser. These plasmas have been experimentally studied in the past for laser-plasma ion acceleration in addition to being proposed for schemes such as channeling acceleration to guide and accelerate positively charged particles [18] or solid-state plasma acceleration. For further clarification we quote [18]:

“To use such. . . oscillations to accelerate charged particles. . . is problematic since the radiation length for electrons and positrons is of order 1 cm in solids,. . . These problems can be substantially mitigated for heavy positively charged particles by utilizing the channeling phenomenon in crystals.”

and

“The basic concept of crystal channel acceleration combines plasma wave acceleration with the well known channeling phenomenon. . .”!

Channeling requires that particles are injected along crystallographic direction of a crystal in order to undergo a series of glancing collisions with the ionic lattice. If these collisions with individual ions are capable of trapping the charged particles within the inter-planar space, this phenomena is referred to as crystal channeling. Because the basis of energy exchange process is individual collisions of charged particles with positively charged ionic sites it favors positively charged particles.

2. **Dielectric or insulating solids:** dielectric or insulating materials have near zero electron density in the conduction band. The excitation of dielectrics relies on polarization of electron cloud bound to ionic sites which effectively generates high frequency electromagnetic radiation through the Cherenkov mechanism. It has been experimentally demonstrated that when electrons are driven by high electromagnetic fields to transition into the conduction band of a dielectric material, the Cherenkov electromagnetic wave is rapidly shielded which puts an end to dielectric acceleration [19].
3. **Optical plasmons:** in conventional plasmonics, a low-intensity optical femtosecond laser is used to excite weakly-driven plasmons. Such weakly-driven or perturbative optical plasmons have also been proposed as a novel pathway for particle acceleration [20]. On the other hand, the longer timescale radiation energy that is unavoidably present in the pre-pulse of a high-intensity optical laser ablates the interacting material into solid-state plasma which is out of the scope of our work.

While the existing parallel efforts on R&D of plasma and dielectric accelerators have been duly recognized and well supported by funding agencies, our effort being at an early stage calls out for special attention and investment by the HEP community.

In order to bring out the promise of this effort, while also identifying its challenges and mapping out strategies for the future, the following sections are structured as follows.

- Section 3 introduces the fundamentals of PetaVolts per meter plasmonics and the ultrafast dynamics of free electron Fermi gas.

- Section 4 charts out a physics case for the possibility of using the PetaVolts per meter fields of plasmons over the next decade to open up exploration at the frontiers of high-energy physics.
- Section 5 summarizes certain fascinating findings of a past experiment that specifically studied the interaction of an ultrafast electron beam with conducting materials.
- Section 6 provides brief description of large-amplitude plasmons that enable acceleration and focusing of particle beams. The role of a strongly electrostatic surface plasmon to mitigate well known disruptive effects of collision between particle beams and bulk materials is also briefly discussed.
- Section 7 discusses novel techniques for extreme bunch compression, focusing and diagnostic for ultra-dense particle beams. This includes longitudinal compression towards  $< 100$  nm bunch lengths and multi-MegaAmpere peak currents as well as focusing of the beam waists to the order of 100 nm.
- Section 8 outlines hypothesized x-ray laser driven nanostructures which use the proposed high intensity keV-photon laser to drive carbon nanotubes.
- Section 9 describes the challenges, possibilities and efforts (ongoing and future) to prototype PV/m plasmonics.


### 3 Fundamental framework of PetaVolts per meter Plasmonics

PV/m plasmonics [1–3] relies on the electronic energy band structure inherent in conducting materials due to an appropriate combination of suitable constituent atoms and ionic lattice structure. The electron energy band structure of conducting materials supports free electrons (electron not tied to any specific atoms) in the conduction band. In particular, electrons that occupy energies in the conduction band constitute a *free electron Fermi gas*. This electron gas is a quantum mechanical entity and follows the Fermi-Dirac statistics unlike a classical electron gas.

The Fermi electron gas freely moves about the entire lattice. It is interesting to note that the free electron Fermi gas in conducting solids is the highest density collection of electrons that is accessible at a terrestrial lab. Upon external excitation, this electron gas undergoes collective oscillations [6] and in the process excites collective fields which form the basis of the general field of plasmonics and plasmonic accelerators, in particular.

PetaVolts per meter plasmonics is based upon a new class of plasmons in the large-amplitude limit which has not been explored before. The strongly electrostatic surface plasmon underlying PV/m plasmonics is sustained by relativistically oscillating Fermi electron gas, as depicted in figure 1, reproduced from [1]. This figure is a snapshot in time of the evolving interaction between an electron beam (with its envelope at a given density in orange) and the free electron Fermi gas (darker colors representing a higher density) modeled using simulations that use the particle tracking approach to treat collisionless behavior of the conduction band free electron gas. Our past work [7–11] has introduced and modeled a nonlinear surface wave in the “crunch-in” regime which further motivates the exploration of a crunch-in surface plasmon.





**Figure 1.** Density profile of free electron Fermi gas of surface crunch-in plasmon, reproduced from [1], in a tube with equilibrium conduction band density,  $n_e$  in the tube walls of  $n_t = 2 \times 10^{22} \text{ cm}^{-3}$ . The snapshot is at  $20 \mu\text{m}$  ( $\sim 73 \text{ fs}$ ) of interaction of a  $\sigma_z = 400 \text{ nm}$ ,  $\sigma_r = 250 \text{ nm}$  beam with tube. The tube has a vacuum-like core of radius,  $r_t = 100 \text{ nm}$  (nearly flat-top beam limit,  $\sigma_r = 2.5 \times r_t$ ). The beam envelope (in orange) although initially larger than the tube has undergone self-focusing approaching ultra-solid densities. Reproduced with permission from [1]. CC BY-NC-ND 4.0.

The free electron Fermi gas is a quantum mechanical entity. The near-continuum energy levels that make up the conduction band and give rise to free electrons are entirely a consequence of two distinct quantum mechanical phenomena related to the electron wave-function in an ionic lattice:

1. inter-atomic bonding due to orbital overlap of neighboring atoms, and
2. periodic potential exerted by the background lattice on electron wave-functions.

Due to their quantum mechanical origins and having a fixed energy (and dispersion relation), quanta of collective oscillations of free electron Fermi gas are treated as quasi-particles and labelled as plasmons.

Plasmonic accelerators rely on excitation of the free electron Fermi gas by ultrafast sources with temporal duration that may perturb or distort the ionic lattice but cannot disrupt it. Modeling the transient modification of the ionic lattice and as consequence the electron energy band structure has been identified as a key challenge which is summarized in section 9.

Over those timescales of interaction between a charged particle beam and the free electron Fermi gas, where the periodic ionic lattice structure and its corresponding quantum mechanical derivative of electronic energy band structure are still present, plasmonic processes are dominant and control the interaction. Especially because the free electron Fermi gas has the highest density and therefore (in accordance with eq. (3.1)) the shortest response times to external excitations. Therefore, plasmonic processes are the fastest when considering electron dynamics.

**Properties of plasmons.** As a consequence of the fact that the equilibrium density of free electron Fermi gas in conducting solids defines the limit of accessible electron density, its dynamics presents a unique set of properties.

The characteristic energy of plasmonic quasi-particles depends only on the free electron density  $n_e$  in the conduction band of an ionic lattice,  $\hbar\omega_{\text{plasmon}} (= 3.7 \text{ eV}\sqrt{n_e [10^{22} \text{ cm}^{-3}]})$ . For comparison, the photon energy of a near-IR optical ( $\lambda_0 = 800 \text{ nm}$ ) laser is around 1.2 eV.

The characteristic oscillation time of the free electron Fermi gas is,

$$2\pi\omega_{\text{plasmon}}^{-1} [\text{fs}] = 1.1 [n_e (10^{22} \text{ cm}^{-3})]^{-1/2} \quad (3.1)$$

The characteristic spatial dimension or size of plasmons is dictated by their wavelength which depends upon the properties of the conducting condensed matter material that sustain them. The wavelength of plasmons is a function of the density ( $n_e$ ) of the free electron Fermi gas in the conduction band,

$$\lambda_{\text{plasmon}} [\text{nm}] = 330 [n_e (10^{22} \text{ cm}^{-3})]^{-1/2} \quad (3.2)$$

In a typical metallic nanostructure with conduction band electron density of  $10^{22-24} \text{ cm}^{-3}$ , the characteristic size of a plasmon (planar surface plasmon is longer) ranges from few hundred nanometers to a few nanometers.

If the free electron Fermi gas is undergoing relativistic oscillations with electron momentum of  $\mathbf{p}_{\text{plasmon}}$  (and velocity,  $v_{\text{plasmon}}$ ) approaching  $m_e c$  as is the case in our work, then the time and spatial scales of plasmonic oscillations need to be modified (and elongated) by the average relativistic factor of electrons,  $\gamma_{\text{plasmon}} = \sqrt{1 + \frac{\mathbf{p}^2}{m_e^2 c^2}} = (1 - \beta^2)^{-1/2}$ , where  $\beta = v_{\text{plasmon}}/c$ , as follows:

$$\begin{aligned} 2\pi\omega_{\text{plasmon}}(\gamma_{\text{plasmon}})^{-1} [\text{fs}] &= 1.1\sqrt{\gamma_{\text{plasmon}}} [n_e (10^{22} \text{ cm}^{-3})]^{-1/2} \\ \lambda_{\text{plasmon}}(\gamma_{\text{plasmon}}) [\text{nm}] &= 330\sqrt{\gamma_{\text{plasmon}}} [n_e (10^{22} \text{ cm}^{-3})]^{-1/2} \end{aligned} \quad (3.3)$$

Highly non-linear electron oscillations of the electron gas approach the coherence limit of orderly collective electron oscillations or the wave-breaking limit [17] which is defined in terms of the electric field amplitude that is sustained during oscillations. The one-dimensional coherence limit of the electric field is,

$$E_{\text{plasmon}} [\text{PV/m}] = 0.1\sqrt{n_e (10^{24} \text{ cm}^{-3})}. \quad (3.4)$$

While electric fields many times the one-dimensional coherence limit are practically achievable, oscillations become less orderly and coherent upon exceeding the limit in eq. (3.4).

**Scaling law.** The strength of accessible plasmonic field scales with equilibrium density of the quantum electron gas in accordance with eq. (3.4). In conductive condensed matter systems, this corresponds to the density of the conduction band electrons. For instance, large-amplitude plasmons excited in Aluminum with  $n_e \simeq 2 \times 10^{23} \text{ cm}^{-3}$ , can access about 100 TV/m fields in the coherence limit. The density of this quantum electron gas can be widely varied in engineered materials, making it possible to program the desired EM field strength.

This scaling law may be better understood in the context of utilizing these plasmonic fields for ultra-compact particle acceleration. The energy of an ultrarelativistic, GeV-scale beam (for instance, a 10GeV electron beam) capable of exciting large-amplitude plasmons can be doubled in a few hundred microns ( $100 \text{ TV/m} \times 100 \mu\text{m}$ ) using coherence limited metallic plasmons. This opens the potential for a multi-stage accelerator to access 1 TeV beam energy in less than a meter long array of plasmonic modules. Therefore, the scaling law for utilizing plasmonic fields further emphasize the immense promise of PV/m plasmonics technology.

**Key enablers behind the emergence of plasmonic accelerators.** There are two fundamental realizations that have enabled the emergence of ultra-high gradient plasmonic accelerator modules for a future collider:

1. past experimental observation of the **absence of damage in conducting materials** for electron bunch lengths,  $\sigma_{\parallel} \leq 10 \mu\text{m}$  as summarized in section 5, and
2. **sub-micron bunch compression techniques** (discussed in section 7) that can match the spatial, eq. (3.2) and temporal, eq. (3.1) scales of plasmonic oscillations: (i) which can longitudinally compress the bunch through manipulation of the bunch phase-space correlations using magnetic lattices, (ii) bunch waist compression using permanent magnet quadrupole triplet systems.

In contrast with conducting media which have free electrons occupying the conduction band, insulators or dielectrics have near zero electron density in the conduction band. So, plasmons can not be sustained in insulating (dielectric) materials.

**Distinction from dielectric or insulating solids.** Although there appear to be phenomenological similarities between the plasmons in conducting media and the dielectric modes in an insulating dielectric because both are excited in a hollow solid tube, the physics of each is fundamentally distinct.


Whereas plasmons are supported by collective oscillations of free electron Fermi gas, dielectric modes are supported by polarization currents generated by the distortion of the electron cloud of ions in the lattice. Plasmonic oscillations are out of phase with the drive electric field while dielectric polarization currents are not. In dielectrics, polarization currents excite large amplitude Cherenkov radiation which supports the acceleration mechanism. In plasmonics, electrostatic plasmons supported by large-scale charge separation between the free electron Fermi gas and ionic lattice sustain ultra-high gradients.

As a result the dispersion relation of each type of wave is quite different:

- $\omega = \omega_{\text{plasmon}}/\sqrt{2}$  for a plasmonic surface wave and
- $\omega = kc/n_{\text{dielec}}$  for a dielectric wave, where  $n_{\text{dielec}}$  is the index of refraction of the dielectric.

The resulting mode structure can be predicted from the intersection of the dispersion relations and the driver disturbance at  $\omega = kv_b$  (where,  $v_b$  is the beam velocity) as in figure 2(a). From this we see that the surface plasmon has but one wavenumber and frequency and gives rise to planar wave fronts and sinusoidal oscillations as seen in the cartoon of figure 2(b). On the other hand, the dielectric dispersion intersects the beam disturbance at the Cerenkov angle ( $\cos(\theta_c) = 1/n_{\text{dielec}}$ ) at every  $\omega$  and  $k$ . This supports the familiar Cerenkov cone type wavefront structure familiar in the wake of supersonic jets and illustrated in the cartoon in figure 2(c).

This shock-like cone propagates out to the outer conducting wall boundary of the dielectric whereupon it is reflected back toward the axis, giving rise to an accelerating spike on the axis as in figure 2(c). It is clear from this picture that these two modes differ considerably. In the first, the accelerating field is nominally sinusoidal (in the linear regime) and the location of the accelerating peak is controlled by the free electron Fermi gas density in the tube. In the second, the accelerating field is a single spike and its location is determined by the outer radius of the dielectric and the dielectric constant of the tube.



**Figure 2.** Dispersion relation for surface plasmon and dielectric modes in (a) and their overlap with the drive particle bunch which determines the spatial and temporal profile, (b) of the surface plasmon mode, (c) of the dielectric mode. Reproduced with permission from [2]. CC BY-NC-ND 4.0.

**Distinction from plasmas.** It is quite critical to note that our initiative does NOT deal with solid-state plasmas or gaseous plasmas. In solid-state plasmas, produced by ablation of solids the ionic lattice is completely disrupted with the constituent ions entirely losing their mutual correlations. By definition, solid-state plasmas therefore, do not have an energy band structure. Solid-state plasmas have been utilized for laser-plasma ion acceleration, but, due to their contingency on the turbulent ablation process they may not be controllable for consistent properties desired from acceleration modules underlying a collider.

Due to highly randomized nature of ions in gaseous plasmas, the properties of plasma oscillations significantly diverge from that of plasmons especially at solid densities. Using one simplified example, the characteristics of electron-electron collisions which increase with the density of a gaseous plasmas are ineffectual for a **quantum mechanical electron gas** due to strict requirements set by the **Pauli exclusion principle**.

#### 4 Non-collider searches through direct access of HEP frontiers: physics case

In this section we chart out short-term physics case for PetaVolts per meter plasmonics initiative. This is based upon non-collider examination of the predictions of theoretical models in HEP that lie at the energy, intensity and cosmic frontier. With conventional and other advanced mechanisms of producing energetic particles, these non-collider searches remain out of the reach. However, the availability of PV/m plasmonic fields will for the first time make it possible to pursue these predictions.

These are the **decadal goals of the PetaVolts per meter plasmonics** effort in parallel with understanding various elements of an integrated collider design using plasmonic accelerator modules.

##### 4.1 Examination of nonlinear Quantum Electro-dynamics (QED): opening the vacuum with extreme plasmonic fields

It is predicted that extremely strong electromagnetic fields produce positron-electron pairs directly off of the vacuum when their energy density is high enough. Specifically, the QED theory that when the electromagnetic fields approach the Schwinger field limit of  $E_s = 1.3 \times 10^{18}$  V/m [21], the

probability of observing positron-electron pairs directly produced from the vacuum increases with the electric field,  $E_{\text{lab}}$  as  $\exp\left(-\frac{\pi m_e^2 c^3}{e E_{\text{lab}} h}\right)$ , as is the case with tunneling effects.

PetaVolts per meter plasmonics can “open the vacuum” based upon plasmonic nano-focusing of particle beams [5]. While there are existing lab-based routes to experimentally examine this fundamental HEP theory of spontaneous pair-production, such as colliding two high-intensity laser pulses or the collision of an ultra-relativistic particle beam with a laser pulse, PV/m plasmonics offers certain distinct experimental capabilities.

As the plasmons have a near-zero group velocity and are localized in space, the plasmonic fields *do not*:

- travel with the particle or laser beams, or
- are experienced in a Lorentz-boosted frame, or
- exist only momentarily at the collision

unlike the underlying construct in other experimental techniques. Moreover, it is easier to tune the interaction parameters of the plasmonic experiments.

#### 4.2 Examining quantum gravity model: ultra-energetic photons from nano-wiggler

Theories that attempt to describe gravity using a quantum mechanical framework as well as theory of everything models are considered to be examinable only using astrophysical observation data. One of predictions of the string theoretical model is that the vacuum exhibits a non-trivial permittivity to ultra-energetic photons [22]. With the nature of the interaction between short wavelength photons and the vacuum, the most appropriate probes for this model are sources that produce short bursts of ultra-energetic photons.

However, with the existing state of technology the only bursty sources of TeV or PeV photons are astrophysical bodies. Therefore, detection of these quantum gravity effects is solely dependent on observational data.

Production of TeV photons using the nano-wiggler mechanism [1] based upon PV/m plasmonics promises to open novel possibilities for searches in HEP. The nano-wiggler utilizes the ultra-high focusing fields of plasmons to wiggle the ultrarelativistic electrons of the beam that have a relativistic factor,  $\gamma_b \simeq 10^{4-6}$  with nanometric wiggling oscillations wavelengths,  $\lambda_{\text{osc}}$ . The energy of the photons so produced is  $2\gamma_b^2 hc / \lambda_{\text{osc}}$ .


### 5 Past ultrafast experiments with conductive materials

A set of past experiments [23, 25] that studied the interaction of conducting materials (Iron/ Cobalt alloys) with ultrafast electron beam of Final Focus Test Beam [26] at the Stanford linear accelerator center (SLAC) sets the precedent to answer several questions about plasmonic accelerator in addition to beam-driven plasmonics, in general.

These experiments are briefly discussed here to note two critical points. Firstly, the processes related to motion of a quantum gas are distinct from understanding developed based upon a classical gas. Secondly, these experiments provide an early signature of interaction of short timescale electromagnetic fields with conductive materials.

The findings of these experiments are directly relevant and provide a strong experimental basis for the initiative on plasmonic accelerators. This is because these past experiments on ultrafast magnetic switching are also based upon femtosecond excitation [24] of metallic alloys that possess free electron Fermi gas.

Experiments conducted on ultrafast magnetic switching using the FFTB electron bunch at the SLAC laboratory observe fascinating phenomenon in a metal, namely **the lack of heating**, when the field strengths are increased well into the GV/m regime while the field pulses are shortened to less than 100 fs. These experiments studied the response of the same  $\text{Co}_{70}\text{Fe}_{30}$  thin film samples of dimensions and geometry described in [25].



**Figure 3.** A comparison of the sample images obtained with Scanning Electron Microscope (SEM) with spin polarization (SEMPE), on the left, and conventional SEM pictures of the structure, on the right, zooming in on the region where the beam hit. It is evident from this comparison that for the shorter electron pulses,  $\sigma_{\parallel} \leq 100$  fs no topological deformation is seen. Reproduced with permission from [2]. CC BY-NC-ND 4.0.

Figure 3 presents a comparison of material damage for the two field pulses of different lengths and strengths illustrated using spin sensitive transmission electron microscopy in figure 3(a) and conventional transmission electron microscopy in figure 3(b).

By examination of the magnetic patterns written into the ferromagnetic film by the fields of the electron bunch it is found that only the longer electric fields of 2.3 ps and magnitude  $\leq 0.6$  GV/m heat the sample above its Curie temperature of  $T_C \leq 1200$  K, while no such heating is observed for the shorter 70 fs pulse with fields up to 20 GV/m.

As in previous work the experiments were carried out using the Stanford Linear Accelerator and by use of a special electron bunch compressor the Gaussian shaped bunch length could be shortened from several picoseconds to below 100 femtoseconds. These bunches had longitudinal Gaussian rms widths,  $\sigma_t$  of 2.3 ps and 70 fs, as indicated in figure 3. As a result of relativistic field contraction, the fields are entirely parallel to the surface of the sample oriented perpendicular to the



direction of bunch propagation. The 10 nm thick polycrystalline  $\text{Co}_{70}\text{Fe}_{30}$  thin film sample with uniaxial in-plane magnetic anisotropy was deposited onto a 0.5 mm thick [110]-MgO substrate with intervening buffer layers consisting mainly of 30 nm  $\text{Cr}_{80}\text{Mg}_{20}$  and capped with a 1.5 nm thick layer of Pt to prevent corrosion.

The magnetic pattern written by the 2.3 ps pulse exhibits the formation of stripe domains along the horizontal easy axis which are characteristic for a sample that has been heated to a temperature above the Curie temperature  $T_C = 1200$  K and then cooled in the absence of a magnetic field. In addition, conventional SEM images revealed non-magnetic changes of the sample surface near the beam impact area, as shown on the right in figure 3. In contrast, the magnetic pattern written by the 70 fs pulse, shown underneath, has sharp domain walls and is clearly written by the magnetic beam field as discussed in the earlier results with 2.3 ps pulse [25]. Also, **no non-magnetic SEM contrast indicative of beam “damage” was observable.**

The pulsed E-field leads to current flow and Joule heating. Since the peak E-field of the beam scales as  $N_e/\sigma_t$  and the pulse energy scales with  $N_e^2/\sigma_t$  (where,  $N_e$  is number of bunch particles and  $\sigma_t$  is the bunch length), the shorter pulse is expected to produce more heat. This is at odds with our experimental observation.

It is surmised that these puzzling observations can be explained by the non-linear response of the electrons in a metal when the fields become extremely large. The relativistic and nonlinear response of the free electron Fermi gas is driven by GV/m electric fields of the beam results in processes that do not follow the conventional Ohm’s law.

## 6 Large-amplitude plasmons: strongly electrostatic and relativistic mode

**Surface plasmon.** For preservation of the essential properties of a particle beam, it is critical to mitigate its direct collision with the ionic lattice. Random collisions between particles and the ionic lattice not only result in loss of energy of the individual particles of the beams but can also disrupt the beam, as a collective entity, through a wide-range of instabilities. These instabilities include filamentation, hosing and several others which can rapidly grow and completely disrupt the beam. Our effort on plasmonic accelerators, therefore, utilizes a surface plasmon where the beam propagates through vacuum surrounded by conducting walls.

**Conventional surface modes.** It is well known that the Transverse Magnetic (TM) mode which is a purely electromagnetic mode sustains zero focusing forces on a beam inside a metallic cavity or tube. In fact contrary to focusing forces, charged particle beams propagating inside hollow cavities are well known to excite strong deflecting forces if not perfectly aligned to the axis of the cavity.

Whereas the conventional metallic cavities that form the basis of modern particle accelerators and light sources utilize electron currents in the metallic walls that oscillate only at the radiofrequency (rf), plasmonic accelerators utilize collective oscillations at spatial and temporal frequencies, eq. (3.1) and (3.2), dictated by the density of the free electron Fermi gas itself.

**Purely electromagnetic surface wave mode.** Besides metallic cavities, existing works on excitation of the TM mode by a charged particle beam in a hollow tube of gaseous plasma have also analytically demonstrated that there are zero focusing forces [27], we quote:


“The focusing force is zero inside the channel for a very relativistic particle.”

**Experiments on purely electromagnetic surface wave mode.** Experiments on excitation of TM mode by a charged particle beam in a vaguely hollow tube of gaseous plasma have confirmed the above theoretical result [28], we quote:

“We find that when the positron beam propagates on-axis through the channel, there are no significant changes in the spatial profile, indicating the absence of the transverse focusing forces within the channel, thus demonstrating the merit of using hollow channel plasmas for PWFA.”

The crunch-in regime [7, 9] is known to violate the conditions imposed by the purely electromagnetic TM mode.

**Strongly electrostatic surface crunch-in mode.** The strongly electrostatic surface crunch-in plasmon, in contrast with the TM mode, sustains strong focusing forces. As the free electron Fermi gas is driven by beam fields larger than tens of MV/m, the free electron gas gains relativistic momentum. With relativistic momentum, the kinetic energy of plasmonic oscillations increases beyond the surface potential. The oscillating electron gas can thus breach the surface potential. Further details of relativistic plasmonic oscillations and the surface crunch-in process are in [1–3, 7, 9, 11].



**Figure 4.** Longitudinal (top,  $E_z$ ) and Focusing (bottom,  $E_y - cB_x$ ) fields of the surface crunch-in plasmon from 3D PIC simulations in cartesian geometry. The tube and beam parameters are exactly the same as in figure 1. Reproduced with permission from [1]. CC BY-NC-ND 4.0.

The density structure of the free electron Fermi gas oscillating to sustain the surface crunch-in mode is demonstrated in figure 1 and the corresponding field structure is shown in figure 4. Due to the highly nonlinear and relativistic nature of plasmonic oscillations in our work, crunch-in plasmon is demonstrated using particle-in-cell simulations of metallic free electron Fermi gas density of  $n_t = 2 \times 10^{22} \text{ cm}^{-3}$ . The beam density is  $n_b = 5 \times 10^{21} \text{ cm}^{-3}$ . These simulations demonstrate that the surface crunch-in plasmon supports strong focusing fields ( $E_r$ ) in addition to longitudinal field ( $E_z$ ).



As these plasmonic oscillations are sustained at the coherence limits which are dictated by the density of the free electron Fermi gas,  $n_e$ , they support electromagnetic fields at the coherence limit in eq. (3.4). This is modeled to be possible by exciting novel high amplitude modes of plasmonic oscillation with dense particle beams. In the crunch-in mode, just like the beam which excites the plasmon, the accelerated bunch does not interact with the background ionic lattice. Due to this negatively charged as well as positively charged particles can be accelerated with equivalent efficacy. Apart from the injection of an electron within the plasmon, it is also possible to inject ultrashort positron bunch as well as positive and negative muons. Ultrashort bunches of exotic particles, such as positrons [29] and muons [30], may be obtained from a plasma-based accelerator.

**Surface crunch-in plasmon breaks the scaling of purely EM surface modes.** It follows from the Panofsky-Wenzel theorem at a given frequency that when the longitudinal field of a charge in a structure increases with miniaturization as  $1/a^2$ , where  $a$  is the transverse structure dimension, the transverse field amplitude increases as  $1/a^3$ . These transverse fields lead to head-tail instabilities that severely limit the amount of charge that can be accelerated in miniaturized devices. Moreover, transverse misalignment between the beam axis and the axis of symmetry of the structure excites higher-order mode that further deflect the beam off-axis.

On the other hand, this scaling can be overcome when the transverse aperture is dynamic as in a plasmonic crunch-in surface mode. In that case the head of an electron beam strongly drives out the free electron Fermi gas which as part of their oscillation trajectory go across the surface and re-converge on the axis behind the driver. The aperture behind the beams can be vanishingly small and result in large accelerating fields, while the aperture seen by the beam and associated with the transverse fields is much larger. These dynamic structures can overcome the scaling limitation described above that otherwise limits fixed structures.

The study of the above regime of plasmon in micro to nano-scale tubes will reveal the new physics of plasmonic surface modes. Large-amplitude plasmons offer extreme gradients and an alternate and potentially more direct path to achieving milestones such as staging, positron acceleration and control of emittance growth.

## 7 Extreme bunch compression, focusing and diagnostics for plasmonics

### 7.1 Longitudinal compression of particle beams to greater than 100kA peak bunch current

Recent advances in bunch compression have opened up the possibility of producing sub-micron bunch lengths with MegaAmpere (MA) peak currents. For example, ongoing upgrades at the FACET facility of the Stanford Linear Accelerator Center (SLAC) are expected to provide the possibility for  $> 200$  kA pulses with  $< 1$   $\mu\text{m}$  rms bunch length in the near future. Precedented to the attainment of sub-micron electron bunches was set by routine generation of 20–30  $\mu\text{m}$  rms bunch length, with 30kA peak current at the same facility during the last decade.

Taking the next logical step and compressing electron bunches into the  $< 0.1$   $\mu\text{m}$ ,  $> 1$  MA regime would support the development of revolutionary new applications across a range of fields including PetaVolts per meter plasmonics and plasmonic accelerators for addressing challenges across the energy, intensity and cosmic frontiers.

To reach the regime of multi-MA peak current compression, in addition to a next-generation high-brightness source or injector (not discussed here), various non-linearities present in the bunch compression process need to be considered in order to preserve both longitudinal and transverse emittance.

One of the most limiting physical processes is that of coherent synchrotron radiation (CSR) which causes transverse emittance growth of many orders of magnitude, in addition to strongly limiting the final achievable peak current in the regime considered. To compensate for the CSR emittance degradation, chicane designs more complex than the standard 4-bend chicane need to be considered, e.g. multi-bend chicanes, quadrupole and sextupole loaded chicanes or arcs or wigglers.

### Design Parameters, Constraints and General Considerations

- We consider a bunch compressor design capable of compressing an electron bunch to peak currents  $\gg 100$  kA with  $\ll 1$  mm-mrad transverse emittance growth.
- A next-generation photo-injector with transverse emittance  $< 0.1$  mm-mrad,  $0.1$ – $2$  nC charge and few  $100$  A initial peak current is considered. Typical injector energies are  $\sim 100$  MeV.
- The injector should be capable of  $> 2$  nC initial charge to allow for collimation of tails as part of the compression scheme.
- Although precise amount of charge is dependent on the scientific case, most demanding is a collider which requires  $> nC$  bunch charge and the smallest transverse emittances,  $< 0.05$  mm-mrad
- Multi-stage compression will be required to achieve compression ratios  $> 1000\times$ 
  - E.g., FACET-II uses 3 compression stages at  $0.3, 4.5, 10$  GeV
  - Removes need for excessive energy spread
- Final compression stage should operate at the final energy
  - Helps with CSR, where emittance growth scales as  $\Delta\epsilon_n/\epsilon_n \sim 1/\sqrt{\gamma}$
  - Adverse surface effects are expected at high compression ( $I^2R$  pulse heating)
  - This allows the use of the energy chirp induced by wakefields in the final accelerating section:
    - \* Demands final compression stage should have +ve R56 (requires quadrupole loaded optics) to make use of wakefield chirp
    - \* This also helps with non-linearities from compression system, T566 due to partial self-cancellation from rf curvature
- As a good compromise between CSR mitigation, whilst maintaining a reasonable system length (which scales strongly with energy due to Incoherent Synchrotron Radiation growth in bends) here a final energy of  $30$  GeV is considered with beam parameters tabulated in figure 5.

**NB:** Convention used here is **negative R56** requires **higher energy at tail** of bunch, **positive R56** requires **higher energy at head** of bunch.

Initial compression stages reduce the initial bunch length to  $20\mu\text{m}$  rms, where the peak current is a 12 kA, similar to the largest values used at FEL facilities, where at low charge emittance preservation has been experimentally demonstrated ( $< 200\text{ pC}$  charges). The final compression stage required to compress the electron bunch to  $< 1\mu\text{m}$  in length requires careful design to mitigate emittance growth effects and is the subject of this section.


<b>Energy</b>	E	30 GeV
<b>Bunch Charge</b>	Q	2 nC
<b>Initial RMS Bunch Length</b>	$\sigma_{z,i}$	20 $\mu\text{m}$
<b>Initial bunch peak current</b>	$I_{pk,i}$	12 kA
<b>Initial normalized transverse emittance</b>	$\gamma\epsilon_{x,y}$	0.5 mm-mrad
<b>Initial energy chirp</b>	$\delta_E$	0.1%
<b>Chicane compression</b>	R <sub>56</sub>	17 mm

**Figure 5.** Initial electron bunch parameters considered for final bunch compression stage.

**Four types of bunch compression optics.** We now consider 4 styles of compression optics for use in the final compression stage: a simple 4-bend chicane; a minimal extension to provide CSR canceling- a 5-bend chicane; a double chicane with quadrupole optics between; and finally, a quadrupole (and sextupole) loaded arc or wiggler system.


1. **4-bend chicane:** a classic 4-bend chicane is used for compression in (at least the later stages) many existing FEL facilities. It is simple to install and operate and has some nice features, such as automatic achromaticity correction to second-order, transversely. It is included here mainly for comparison purposes. This chicane system needs to be quite long at our 30 GeV design energy. The R56 of a chicane is also -ve, requiring it to “fight” the chirp induced in the rf structures of the final acceleration stage. There is no mechanism for canceling the CSR emittance growth (predominantly generated in the final 2 bend magnets).
2. **5-bend chicane:** adding an additional bend to the chicane provides the minimum required additional free parameters to partially self-cancel emittance dilution due to CSR (e.g., see [31]). For our case, this design suffers from the problems outlined in the 4-bend chicane case (wrong sign R56, long footprint). Additionally, realistic simulations (such as [31]) show expected performance of CSR cancelation at about the  $\sim 10\%$  level which for the most demanding cases (particle collider) would not be sufficient.
3. **Dogleg or zig-zag chicane:** in order of increasing complexity, the next design to consider would be a double-chicane configuration (e.g., as considered in [32]). This directly cancels the CSR degradation in the first chicane by introducing a second chicane and carefully tuning the optics to arrange for the CSR cancellation, including a quadrupole-based lattice between chicane pairs. Although, from simulation studies, more effective in CSR cancelation than the 5-bend chicane design: for our high-energy requirement, this design suffers again from having the wrong R56 sign and more so from system length.

4. **Arc or Wiggler compression lattice:** to achieve the desired +ve R56 compression in our final compressor design, we need a quadrupole-loaded lattice such as an arc or wiggler (depending on whether net-bending is a desired feature or not).



**Figure 6.** Simulation of Twiss parameters of 30 GeV arc compression lattice.

To demonstrate the idea, we constructed a model of a wiggler system designed to perform the tasks of our final compressor using the tracking code Lucretia shown in figure 6. The design is a triplet-based arc (9 cells) with a total bend angle of 67 mrad @ 30 GeV. The arc provides +17mm of R56 in a length of  $\sim 150$  m whilst keeping emittance growth to  $< 5\%$  due to incoherent SR in the bends. Sextupoles are included in the optics, as depicted in figure 6. Without CSR and with sextupoles deactivated, these optics are achromatic to second order.




**Figure 7.** Results from particle tracking through the arc compressor, and 4-bend chicane for comparison. Slice emittance is shown as a function of peak current. The compression is controlled by the initial chirp of the beam and the optimization parameters.

Figure 7 shows the results of tracking simulations through these optics, with an initial optimization of sextupole strengths. The blue and red curves show the performance with/without sextupole optimization, respectively. The red curve represents the Pareto front output of the optimizer. The control variables used in the optimizer are the 18 sextupole strengths, in addition to 9 quadrupole strength knobs and fine control of the incoming energy chirp. The corresponding

performance of a simple 4-bend chicane is shown for comparison. As seen, the arc compressor is a significant improvement over the chicane design, and optimization of sextupoles provide further improvements. The maximum compression for this design is limited at 375 kA, with 5 mm-mrad of slice emittance growth ( $\sim 15$  mm-mrad full emittance growth including beam tails). Work is ongoing to further improve the emittance growth at higher peak currents.

## 7.2 Permanent magnet quadrupoles for high-field focusing

Excitation of the strongly electrostatic plasmonic fields in the crunch-in modes requires very dense drive beams within the core of the conducting nano-structures. Beam densities on the order of  $10^{17}$  cm $^{-3}$  to  $10^{21}$  cm $^{-3}$  are required to explore the different regimes of nano-plasmonic acceleration, which corresponds to transverse spot sizes on the sub-micron scale for intense beams. In order to produce conditions optimal for crunch-in mode formation, an appropriate focusing scheme must be implemented. Furthermore, in realistic experimental scenarios where regions are constrained by spatial limitations, the focusing system should be compact and robust.



**Figure 8.** Examples of different permanent magnet quadrupoles in the Halbach geometry, produced for ultrafast electron microscopy at the Brookhaven National Laboratory. Photographs courtesy of J. Penney. Reproduced with permission from Gerard Andonian, 2023.

Permanent magnet quadrupoles are ideal candidates for such applications as they are able to provide very high gradients (in excess of 700 T/m [36]) in a compact form factor, without the need for external cooling that electromagnetic counterparts require. However, quadrupoles only offer focusing in one dimension, while defocusing the beam in the other. Hence, the simplest configuration of permanent magnet quadrupoles for overall focusing requires a triplet configuration. The triplet system is tunable by the relative reconfiguration of quadrupole locations, and higher order moments can be tuned out by magnetic shimming as needed.

Current applications of permanent magnet quadrupoles are varied across the accelerator physics landscape, including final focus systems for inverse Compton scattering [36], beam-break up mitigation for extended energy exchange in wakefield interactions, and high quality imaging in ultrafast electron microscopy [37]. Advances in material development and higher levels of sophistication in fabrication techniques also allow for control of higher order modes, such as in the Halbach configuration [38]. Technological advances in permanent magnet quadrupole integration into existing beamlines, applied in-vacuum or out-of-vacuum with hybrid split-designs [39], offer further flexibility for use within the strict constraints in nano-plasmonic acceleration.


## 7.3 Electro-optic sampling (EOS) bunch-length diagnostics for intense beams

An advanced diagnostic technique of estimation of the relative position of a charged particle beam with the capability to resolve at the sub-micron scale uses electro-optic sampling (EOS). By

measuring the change in the birefringence of a crystal subjected to collective fields of the beam makes it possible to estimate the bunch length and its distance from the crystal in addition to the possibility of estimating a few other beam properties. The change in birefringence depends upon the magnitude of the beam fields. This change in birefringence is measured by detecting the changes in the polarization of a laser propagating through a birefringent crystal. By autocorrelating the rotation of the polarization of the laser, it becomes possible to estimate the position of the beam. The resolution of EOS technique as a result depends upon the resolution of the polarization auto-correlator. EOS is a well-known technique that is currently being implemented in a novel configuration at the FACET facility at SLAC [40]. These configurations can utilize multiple arms to not only estimate the position of the beam but also its bunch length and possibly also its longitudinal bunch profile.

#### 7.4 Advanced ionization beam-profile diagnostics for intense beams

The generation of the crunch-in modes in nano-plasmonic acceleration requires the delivery and transport of high intensity beams through small apertures. Traditional diagnostics for transverse beam profile and centroid for alignment would not be sufficient due to damage from the intense beams. Alternative methods, preferably non-destructive are required to parameterize drive and witness beams through nano-plasmonic structures.



**Figure 9.** Gas film ionization beam profile monitor for dense beams.

An exciting new diagnostic tool for high intensity beams operating in a minimally intercepting topology is the gas sheet ionization monitor. The concept is based on the generation of a thin neutral gas sheet, or curtain, that is propagated perpendicular to the drive beam. As the beam passes the neutral gas sheet, the particles are ionized, leaving a footprint of the initial beam distribution. The ionization distribution is then imaged using a series of electrostatic lenses and a micro-channel plate. The ion distribution is then back-convolved using a reconstruction algorithm to determine the initial beam profile at the point of ionization. Such methods have been used at low energy [41] and also proposed



for high intensity beams at SLAC FACET [42]. The technique is ripe for modern machine learning methods to extrapolate beam profile information where conventional techniques are not viable.

## 8 X-ray laser driven Carbon Nano-Tubes (CNT)

The recent invention of the Thin Film Compression (TFC) model opens the way to introduce the availability of the single-cycled laser pulse and thus the Relativistic Compressed X-ray laser pulse [43]. This innovation allows relativistically high-intensity X-ray laser pulses to be prototyped. This high-intensity X-ray laser pulse fits the need for X-ray laser driven nanostructured wakefield acceleration (xWFA) possibility [45]. This technology and arrangements allow the level of accelerating gradient on the order of 100 TeV/m.

Although the energy level and time duration of x-ray or optical energy in the pre-pulse of the yet to be prototyped x-ray laser remains uncharacterized, it is critical to note that **plasmonic processes are only relevant if this radiation energy ahead of the main x-ray pulse does not completely ablate the target and dismantle the ionic lattice**. Furthermore, it is critical that the energy of the x-ray photon does not fully ionize the non-valence electrons, significantly modifying the interaction parameters.

Another important path is nanostructures such as carbon nanotubes. The use of concavity of nanostructures such as CNT allows to eliminate collisions of the accelerated particles with the “background medium particles” and to serve to conduct electrons with self-focusing force. This leads to the potential of on the order of TeV/cm accelerating gradient possibility. Nanostructures help also the “confinement” of the driving pulse of X-rays or charged particle beams. Furthermore, the introduction of such ultrahigh accelerating gradient opens up a path of non-luminosity paradigm of doing extreme high-energy physics, by stacking 1000 nano-fibers would lead to PeV over 10m.

Acceleration of muons (instead of electrons or hadrons) channeling between the planes in crystals or inside carbon nanotube (CNT) with high charge carrier density holds the promise of the maximum theoretical accelerating gradients of 1–10 TeV/m allowing envisioning of a compact 1 PeV linear crystal muon collider [46]. The choice of muons is beneficial because of small scattering on solid media electrons, absence of beamstrahlung effects at the IP, and continuous focusing while channeling in crystals, i.e., acceleration to final energy can be done in a single stage. Muon decay becomes practically irrelevant in such very fast acceleration gradients as muon lifetime quickly grows with energy. Initial luminosity analysis of such machines assumes a small number of muons per bunch  $O(1000)$ , a small number of bunches  $O(100)$ , high repetition rate  $O(1\text{ MHz})$  and ultimately small sizes and overlap of the colliding beams  $O(1\text{ Angstrom})$ .

## 9 PV/m plasmonic: challenges, risks, possibilities, and ongoing efforts

### 9.1 Challenges, risks and possibilities

The challenges of the **PV/m plasmonics** initiative are defined by its **two distinct focal points**:

1. in the near-term: direct access to frontier HEP using extreme plasmonic fields, or
2. in the longer-term: ultra-high gradient accelerator modules for a future collider.

### 9.1.1 Challenges: direct access to non-collider frontier HEP using PV/m plasmonics

The physics case are already summarized above in section 4. The challenges that underlie have been identified as follows:

- computational modeling and material design
- detailed modeling of physical processes behind plasmonic nanofocusing
- in-depth understanding of nano-wiggler mechanisms and its limits for coherent gamma-ray laser
- specialized and unconventional diagnostics for ultra-solid beams of photons and particles
- development of new diagnostic techniques to measure and experimentally characterize the modeled physics
- design of short-term test cases of frontier HEP
- developing a stepwise plan for attaining the limits of EM fields.

### 9.1.2 Challenges: plasmonic accelerator module for a future collider

The challenges and areas in need of further study for the design of a plasmonic accelerator module are summarized below:

- scaling of net power requirement for a collider-level machine with acceleration gradient
- preliminary integrated design study using plasmonic accelerator modules
- beam dynamics and beam quality using plasmonic modules - addressing instabilities such as beam break-up instability, etc.
- technological questions such as alignment of the injected beam, staging, and inter-stage alignment
- nano-wiggler for coherent-gamma-ray laser for gamma-gamma collider
- path to highest energy colliders
- high energy accelerators for dark sector searches.

### 9.1.3 Challenges: theoretical and computational modeling of plasmonic processes

A comprehensive approach to modeling of relativistic and highly nonlinear plasmons in conductive materials is required to appropriately incorporate the multi-scale and multi-physics nature of the underlying processes. These nonlinear plasmons being strongly electrostatic significantly differ from the conventional optical plasmons and do not lend themselves to being modeled using purely electromagnetic codes. Optical plasmons are typically modeled using Finite-Difference-Time-Domain (FDTD) method where the perturbative electron oscillations are simply approximated using constitutive parameters. The FDTD approach with constitutive parameters cannot be used when the



trajectories of collective electron oscillations attain amplitudes which are a significant fraction of the plasmonic wavelength and as a result requires a non-perturbative approach.

Our work has adopted the kinetic approach along with Particle-In-Cell (PIC) computational modeling of collective oscillations of the free electrons Fermi gas to account for the nonlinear characteristics of strongly electrostatic plasmons. It is noted that PIC methodology already utilizes the FDTD solver for calculation of electromagnetic fields but utilizes charge and current densities based upon particle tracking. This approach utilizes the collisionless nature of relativistic oscillations of the Fermi gas. This approach does not assume any constitutive parameters as part of the initial conditions. However, the initialization and self-consistent evolution of the electron density implicitly accounts for most of the constitutive parameters.

Moreover, as relativistic oscillations of the free electron Fermi gas have been experimentally observed to go beyond the Ohm's law, the long-term evolution of these oscillations still remains not fully accounted for by collisionless modeling approach. Specifically, conductivity which is a critical constitutive parameter based upon electron-ion collisions is not properly understood in the relativistic plasmonic regime. Therefore, longer-term processes resulting from the excitation of relativistic plasmons are not fully incorporated in the kinetic modeling approach.

In consideration of this immense promise of PV/m plasmonics using nanomaterials, we call for support of the modeling community to engage with our effort and understand several new challenges that are not part of conventional modeling tools.

Below we outline a few of the key challenges identified through our ongoing efforts and bring out the unique requirements our modeling effort:

- Modeling the effect of relativistic energy gain of free electrons in a particle-in-a-box model
- Understanding the effects of the energy density of plasmons on the energy-band structure
- Incorporating effects from atomistic modeling within the kinetic approach
- Devising an approach to handle collisions to determine the longer term effects of electrostatic plasmonic fields and account effects related to conductivity.

#### **9.1.4 Challenges: plasmonic materials research**

Material engineering is an essential ingredient of plasmonic accelerators. In such aspect, this research direction takes great benefit from the recent advances in nanofabrication techniques, which enable three-dimensional surface structuring of a plasmonic metal with single-digit nanometer precision. Also, the interface surface quality is of crucial importance in plasmonic accelerators, as any asperity can create local enhancement, field distortion, and be a source of energy depletion through radiative effects. The progress in electron beam lithography techniques, allows control of the material surface roughness at the Angstrom level [44].

#### **9.1.5 Risks: PV/m plasmonics initiative**

There are a few risks associated with the PV/m plasmonics initiative because it enters a domain that has only been accessed in a few experiments such as in [23, 25] and it extends the well known models of weakly perturbed quantum electron gas into the non-perturbative regime. Below we enlist a few of these:

- unknown processes that may begin to dominate the interactions at extreme field strengths which have never been previously attained in the lab leading to potential breakdown of the theoretical models of perturbative modes in condensed matter systems,
- development of appropriate diagnostics to probe unprecedentedly large fields and reliance on indirect measures such as acceleration gradient as probes,
- generation of energetic photons and particles with uncontrolled characteristics that adversely affect the plasmonic material but also the shielding and diagnostic equipment.

These risks will be significantly mitigated by the experimental effort being undertaken by the PV/m plasmonics collaboration.

### 9.1.6 Possibilities: unforeseen applications of PV/m plasmonics

Extreme fields of plasmons help envision unforeseen possibilities. A few of these possibilities are listed below:

- plasmonic accelerator can help realize the long sought-after crystalline beams
- medical applications of ultra-compact accelerators for nano-surgery, or diagnostics inside the human body
- beam-based inertial fusion and possibility to address world's energy problems using nanosciences.

## 9.2 Ongoing and future efforts

Experimental effort to prototype PetaVolts per meter Plasmonics was proposed by the nano2WA collaboration at the SLAC FACET-II facility in 2020 [47, 48]. The PV/m Plasmonics effort presented a short-term experimental plan in 2022 [49].

Besides the FACET-II effort there are currently several ongoing collaborative efforts to realize the potential of PV/m plasmonics by synergistically working with the plasma acceleration community. The quality and ultrashort nature of plasma accelerated beams can help further study plasmonic accelerators.

In view of the promise of PV/m plasmonics, in the future it may be a possible to request a dedicated facility to study non-collider physics to test HEP frontiers.

## 10 Summary and discussion

PetaVolts per meter electromagnetic fields accessible using the new class of large-amplitude plasmons can transform the paradigm of scientific and technological advances. In the near-term, *PetaVolts per meter plasmonics* will make it possible to directly access unprecedented fundamental tests of non-collider HEP such as “opening the vacuum” and “examining quantum gravity models”. This non-collider paradigm effort which sets the decadal goals of the PV/m plasmonic initiative will be pursued in parallel with the rather long-term goal of an integrated collider design using plasmonic accelerator modules.

PetaVolts per meter plasmonics relies on the unmatched density of the free electron Fermi gas inherent in conductive media, made possible by non-interacting quantum electron energy levels. Because the free electron Fermi gas is a quantum mechanical entity inherent in the conduction band of conductive materials, several different *quantum mechanical effects* work together in unison to make it the highest accessible equilibrium leptonic density, of the order of  $10^{24} \text{ cm}^{-3}$ . Moreover, this dense Fermi electron gas is free to move in response to external excitations without the need for any special preparation of the conductive sample even at ambient pressure and temperature. The electromagnetic fields of collective oscillations scale as the square root of the electron density of the media. Therefore, extending into the quantum regime, electromagnetic fields of the order of  $0.1\sqrt{n_0}(10^{24} \text{ cm}^{-3}) \text{ PVm}^{-1}$  can be sustained by plasmons which redefine the limits of extreme electromagnetics.

The innovation of large-amplitude plasmons characterized by highly nonlinear and relativistic oscillations of the free electron Fermi gas has been theoretically modeled in three dimensions using collisionless particle-tracking methods. Whereas, the purely electromagnetic Transverse Magnetic (TM) surface mode neither focusses the beam nor does it access fields at the coherence limit, these restrictions do not apply to the strongly electrostatic, large-amplitude plasmons. Electrostatic plasmons are capable of focusing a charged particle beam as well as accelerating them at the field coherence or wavebreaking limit.

In addition to these vital understructures of PetaVolts per meter plasmonics, several other theoretical, computational and experimental considerations that are crucial for its realization are identified and briefly discussed. Synergistically, ongoing efforts to experimentally address various immediate challenges as well as to realize the short-term goals have been outlined. A strategy is mapped out to focus on challenges to learn and incorporate principles derived from the current efforts. In addition, the longer-term challenges associated with realization of PV/m plasmonic modules for a future plasmonic collider using PetaVolts per meter gradients are outlined.

## Acknowledgments

This work was supported by the department of Electrical Engineering at University of Colorado Denver. The NSF RMACC Summit and Alpine supercomputers utilized for computational modeling were supported by the NSF awards ACI-1548562, ACI-1532235 and ACI-1532236, the University of Colorado Boulder, and Colorado State University [50, 51].

## References

- [1] A.A. Sahai, *Nanomaterials based nanoplasmonic accelerators and light-sources driven by particle-beams*, *IEEE Access* **9** (2021) 54831.
- [2] A.A. Sahai, M. Golkowski, T. Katsouleas, G. Andonian, G. White, C. Joshi et al., *Approaching Petavolts per meter plasmonics using structured semiconductors*, *IEEE Access* **11** (2023) 476 [arXiv:2208.00966](https://arxiv.org/abs/2208.00966).
- [3] A. Sahai, *Emergence of TeraVolts per meter plasmonics using relativistic surface plasmonic modes*, *Proc. SPIE* **11797** (2021) 117972A.

- [4] A.A. Sahai, *Nanostructure nanoplasmonic accelerator, high-energy photon source, and related methods*, <https://patentimages.storage.googleapis.com/55/0a/6c/7b757efb9e9547/WO2021216424A1.pdf>.
- [5] A.A. Sahai, *Plasmonic nano-focusing of particle beams by surface crunch-in plasmons excited in tapered tubes*, *Proc. SPIE* **11999** (2022) 1199903.
- [6] D. Bohm and D. Pines, *A Collective Description of Electron Interactions: 3. Coulomb Interactions in a Degenerate Electron Gas*, *Phys. Rev.* **92** (1953) 609.
- [7] A.A. Sahai, *Excitation of a nonlinear plasma ion wake by intense energy sources with applications to the crunch-in regime*, *Phys. Rev. Accel. Beams* **20** (2017) 081004 [[arXiv:1612.03520](https://arxiv.org/abs/1612.03520)].
- [8] A.A. Sahai, *Chapter 8. Positron Acceleration using Positron-Beam Excited Wakefields in an Ion-wake Channel*, in *On Certain Non-linear and Relativistic Effects in Plasma-based Particle Acceleration*, Ph.D. thesis, Duke University (2015), pp. 299–312.
- [9] A.A. Sahai and T.C. Katsouleas, *Optimal positron-beam excited plasma wakefields in Hollow and Ion-Wake channels*, in proceedings of the *6th International Particle Accelerator Conference*, Richmond, VA, U.S.A., 3–8 May 2015, pp. 2674–2677 [[arXiv:1512.08013](https://arxiv.org/abs/1512.08013)].
- [10] A.A. Sahai, T.C. Katsouleas, F.S. Tsung and W.B. Mori, *Long Term Evolution of Plasma Wakefields*, in proceedings of the *North American Particle Accelerator Conference*, Pasadena, CA, U.S.A., 29 September–4 October 2013, pp. 90–92 [[arXiv:1405.4302](https://arxiv.org/abs/1405.4302)].
- [11] A.A. Sahai, T. Tajima, P. Taborek and V.D. Shiltsev, *Solid-state tube wakefield accelerator using surface waves in crystals*, *Int. J. Mod. Phys. A* **34** (2020) 1943009 [[arXiv:2101.11774](https://arxiv.org/abs/2101.11774)].
- [12] R. Hofstadter, *The Atomic accelerator*, Tech. Rep. HEPL-560 (1968).
- [13] HEPAP SUBCOMMITTEE collaboration, *Building for Discovery: Strategic Plan for U.S. Particle Physics in the Global Context*, Report of the Particle Physics Project Prioritization Panel (P5), May 2014, [https://www.usparticlephysics.org/wp-content/uploads/2018/03/FINAL\\_P5\\_Report\\_053014.pdf](https://www.usparticlephysics.org/wp-content/uploads/2018/03/FINAL_P5_Report_053014.pdf).
- [14] European Strategy Group, *2020 update of the european strategy for particle physics (brochure)*, 2020, <https://doi.org/10.17181/CERN.JSC6.W89E>.
- [15] *Accelerating Discovery, A Strategic Plan for Accelerator R&D in the U.S.*, Report of the HEPAP Accelerator R&D Subpanel, April 2015, [https://science.osti.gov/-/media/hep/hepap/pdf/Reports/Accelerator\\_RD\\_Subpanel\\_Report.pdf](https://science.osti.gov/-/media/hep/hepap/pdf/Reports/Accelerator_RD_Subpanel_Report.pdf).
- [16] V. Shiltsev, *A Phenomenological Cost Model for High Energy Particle Accelerators*, 2014 *JINST* **9** T07002 [[arXiv:1404.4097](https://arxiv.org/abs/1404.4097)].
- [17] J.M. Dawson, *Nonlinear Electron Oscillations in a Cold Plasma*, *Phys. Rev.* **113** (1959) 383.
- [18] P. Chen and R.J. Noble, *A solid state accelerator*, *AIP Conf. Proc.* **156** (1987) 222.
- [19] B.D. O’Shea, G. Andonian, S.K. Barber, C.I. Clarke, P.D. Hoang, M.J. Hogan et al., *Conductivity Induced by High-Field Terahertz Waves in Dielectric Material*, *Phys. Rev. Lett.* **123** (2019) 134801.
- [20] D. Bar-Lev and J. Scheuer, *Plasmonic Meta-Surface for Efficient Ultra-Short Pulse Laser-Driven Particle Acceleration*, *Phys. Rev. ST Accel. Beams* **17** (2014) 121302 [[arXiv:1409.6501](https://arxiv.org/abs/1409.6501)].
- [21] J.S. Schwinger, *On gauge invariance and vacuum polarization*, *Phys. Rev.* **82** (1951) 664.
- [22] G. Amelino-Camelia, J.R. Ellis, N.E. Mavromatos and D.V. Nanopoulos, *Distance measurement and wave dispersion in a Liouville string approach to quantum gravity*, *Int. J. Mod. Phys. A* **12** (1997) 607 [[hep-th/9605211](https://arxiv.org/abs/hep-th/9605211)].

- [23] S.J. Gamble, M.H. Burkhardt, A. Kashuba, R. Allenspach, S.S.P. Parkin, H.C. Siegmann et al., *Electric field induced magnetic anisotropy in a ferromagnet*, *Phys. Rev. Lett.* **102** (2009) .
- [24] J. Stohr and H.C. Siegmann, *Magnetism: From Fundamentals to Nanoscale Dynamics*, Vol. 152 of Springer Series in Solid-State Sciences, Springer (2006), [10.1007/978-3-540-30283-4](https://doi.org/10.1007/978-3-540-30283-4).
- [25] I. Tudosa, C. Stamm, A.B. Kashuba, F. King, H.C. Siegmann, J. Stohr et al., *The Ultimate speed of magnetic switching in granular recording media*, *Nature* **428** (2004) 831.
- [26] P. Emma, R. Iverson, P. Krejcik, P. Raimondi and J. Safranek, *Femtosecond electron bunch lengths in the SLAC FFTB beamline*, *Conf. Proc. C* **0106181** (2001) 4038.
- [27] T.C. Chiou and T.C. Katsouleas, *High Beam Quality and Efficiency in Plasma-Based Accelerators*, *Phys. Rev. Lett.* **81** (1998) 3411.
- [28] S. Gessner et al., *Demonstration of a positron beam-driven hollow channel plasma wakefield accelerator*, *Nat. Commun.* **7** (2016) 11785.
- [29] A.A. Sahai, *Quasimonoelectric laser plasma positron accelerator using particle-shower plasma-wave interactions*, *Phys. Rev. Accel. Beams* **21** (2018) 081301 [[arXiv:1801.06385](https://arxiv.org/abs/1801.06385)].
- [30] A.A. Sahai, T. Tajima and V. Shiltsev, *Schemes of Laser Muon Acceleration: Ultra-Short, Micron-Scale Beams*, *Int. J. Mod. Phys. A* **34** (2019) 1943008.
- [31] D.Z. Khan and T.O. Raubenheimer, *LCLS-II bunch compressor study: 5-bend chicane*, in proceedings of *FEL2014*, Basel, Switzerland, 25–29 August 2014, pp. 755–762
- [32] Y. Jing, Y. Hao and V.N. Litvinenko, *Compensating effect of the coherent synchrotron radiation in bunch compressors*, *Phys. Rev. ST Accel. Beams* **16** (2013) 060704.
- [33] P. Emma and R. Brinkmann, *Emittance dilution through coherent energy spread generation in bending systems*, *Conf. Proc. C* **970512** (1997) 1679.
- [34] *Lucretia*, Matlab particle tracking code, <https://www.slac.stanford.edu/accel/ilc/codes/Lucretia/>.
- [35] C. Mayes, *Computational approaches to coherent synchrotron radiation in two and three dimensions*, *2021 JINST* **16** P10010.
- [36] J.K. Lim, P. Frigola, G.A. Travish, J.B. Rosenzweig, S.G. Anderson, W.J. Brown et al., *Adjustable, short focal length permanent-magnet quadrupole based electron beam final focus system*, *Phys. Rev. ST Accel. Beams* **8** (2005) 072401.
- [37] P. Denham and P. Musumeci, *Space Charge Aberrations in Single Shot Time-Resolved Transmission Electron Microscopy*, *Phys. Rev. Appl.* **15** (2021) 024050 [[arXiv:2010.04152](https://arxiv.org/abs/2010.04152)].
- [38] K. Halbach, *Design of Permanent Multipole Magnets with Oriented Rare Earth Cobalt Material*, *Nucl. Instrum. Meth.* **169** (1980) 1.
- [39] G. Andonian, T. Campese, M. Fedurin, I. Gadjev, C. Hall, K. Kusche et al., *High Resolution Imaging Design Using Permanent Magnet Quadrupoles at BNL UEM*, in proceedings of the *12th International Particle Accelerator Conference*, Campinas, SP, Brazil, 24–28 May 2021, pp. 485–488.
- [40] K. Hunt-Stone, R. Ariniello, C. Doss, V. Lee and M. Litos, *Electro-optic sampling beam position monitor for relativistic electron beams*, *Nucl. Instrum. Meth. A* **999** (2021) 165210.
- [41] V. Tzoganis, H.D. Zhang, A. Jeff and P. Welsch, Carsten *Design and first operation of a supersonic gas jet based beam profile monitor*, *Phys. Rev. Accel. Beams* **20** (2017) 062801.

- [42] N. Norvell, G. Andonian, T. Campese, N. Cook, A.-L. Lamure, J. Penney et al., *Gas Sheet Ionization Diagnostic for High Intensity Electron Beams*, in proceedings of the *12th International Particle Accelerator Conference*, Campinas, SP, Brazil, 24–28 May 2021, pp. 489–491.
- [43] G. Mourou, S. Mironov, E. Khazanov and A. Sergeev, *Single cycle thin film compressor opening the door to Zeptosecond-Exawatt physics*, *Eur. Phys. J. ST* **223** (2014) 1181 [[arXiv:1402.5676](https://arxiv.org/abs/1402.5676)].
- [44] D.B. Durham, F. Riminucci, F. Ciabattini, A. Mostacci, A.M. Minor, S. Cabrini et al., *Plasmonic lenses for tunable ultrafast electron emitters at the nanoscale*, *Phys. Rev. Appl.* **12** (2019) 054057.
- [45] T. Tajima and M. Cavenago, *Crystal x-ray accelerator*, *Phys. Rev. Lett.* **59** (1987) 1440.
- [46] X. Zhang, T. Tajima, D. Farinella, Y. Shin, G. Mourou, J. Wheeler et al., *Particle-in-cell simulation of x-ray wakefield acceleration and betatron radiation in nanotubes*, *Phys. Rev. Accel. Beams* **19** (2016) 101004 [[arXiv:1805.03725](https://arxiv.org/abs/1805.03725)].
- [47] A.A. Sahai, *Ultra-solid beams using nanostructure nanoplasmonic wiggler and accelerator*, responses of nano<sup>2</sup>WA collaboration to the SLAC FACET-II PAC committee, October 2020, [https://facet.slac.stanford.edu/sites/facet.slac.stanford.edu/files/FACET-II\\_PAC\\_committee\\_answers\\_nano2WA\\_proposal\\_Sahai.pdf](https://facet.slac.stanford.edu/sites/facet.slac.stanford.edu/files/FACET-II_PAC_committee_answers_nano2WA_proposal_Sahai.pdf).
- [48] FACET PAC committee, *SLAC FACET-II PAC 2020 Closeout Session*, Closeout session video recording, October 29, 2020, [https://www-lcls.slac.stanford.edu/web/FACET-II\\_PAC2020Meeting/PAC%202020%20Closeout%20Session%2010.29.2020.mp4](https://www-lcls.slac.stanford.edu/web/FACET-II_PAC2020Meeting/PAC%202020%20Closeout%20Session%2010.29.2020.mp4)
- [49] A.A. Sahai, *PetaVolts per meter plasmonics using engineered materials*, experimental proposal of the nano<sup>2</sup>WA collaboration to the SLAC FACET-II facility, [https://facet-ii.slac.stanford.edu/sites/default/files/SAHAI\\_Plasmonics\\_FACET-II\\_2022\\_Nano2WA\\_proposal\\_0.pdf](https://facet-ii.slac.stanford.edu/sites/default/files/SAHAI_Plasmonics_FACET-II_2022_Nano2WA_proposal_0.pdf).
- [50] J. Towns et al., *XSEDE: Accelerating Scientific Discovery*, *Comput. Sci. Eng.* **16** (2014) 62.
- [51] J. Anderson, P.J. Burns, D. Milroy, P. Ruprecht, T. Hauser and H.J. Siegel, *Deploying RMACC summit*, in proceedings of the *Practice and Experience in Advanced Research Computing 2017 on Sustainability, Success and Impact*, New Orleans, LA, U.S.A., 9–13 July 2017, article no. 8.