

# FIRST COAXIAL HOM COUPLER PROTOTYPES AND RF MEASUREMENTS ON A COPPER CAVITY FOR THE PERLE PROJECT

C. Barbagallo\*<sup>1</sup>, P. Duchesne, W. Kaabi, G. Olivier, G. Olry, S. Roset, F. Zomer<sup>1</sup>  
Laboratoire de Physique des 2 Infinis Irène Joliot-Curie (IJCLab), Orsay, France

J. Henry, S. A. Overstreet, G.-T. Park, R. A. Rimmer, H. Wang  
Jefferson Lab, Newport News, USA

S. Barrière, S. Clement, R. Gérard, F. Gerigk, P. Maurin, CERN, Geneva, Switzerland

<sup>1</sup>also at The Paris-Saclay University, Gif-sur-Yvette, France

## Abstract

The PERLE (Powerful Energy Recovery Linac for Experiments) project relies on superconducting RF (SRF) cavities to reach its goals. The installation of coaxial couplers on the cutoff tubes of SRF cavities is foreseen for damping cavity's Higher Order Modes (HOMs). The prototyping and fabrication of 3D-printed HOM couplers for the PERLE cavity have recently started in collaboration with JLab and CERN. This paper provides an overview of the design of the fabricated HOM couplers and the first RF measurements of the cavity's HOMs performed at warm on an 801.58 MHz 2-cell copper cavity to validate coupler design performances. Measured cavity data is also compared to eigenmode simulations to confirm simulated results and see to what extent any reduction in damping can be predicted.

## INTRODUCTION

The PERLE accelerator [1] comprises two 82 MeV superconducting linacs, each consisting of four 5-cell elliptical Nb cavities ( $\beta = 1$ ), capable of operating at 801.58 MHz in continuous-wave (CW) mode [2]. The installation of coaxial-type HOM couplers is being considered to mitigate the beam-induced HOMs effect. After optimizing the RF transmission of the Probe, Hook, and DQW HOM couplers based on the HOM spectrum of the 5-cell PERLE cavity (as presented in [3]), we demonstrated in our previous work (ref. [4]) that these coupler designs fulfill regenerative beam breakup (BBU) and fundamental mode (FM) RF-heating requirements. Consequently, prototypes of each coupler were fabricated, as illustrated in Fig. 1, to validate their performance on an 801.58 MHz two-cell PERLE-type OFHC (Oxygen-free High Thermal Conductivity) copper cavity since the 5-cell copper cavity was still under fabrication at Jefferson Lab during the measurement campaign. This decision was based on the assumption that the frequency spectrum of a 5-cell cavity is sufficiently similar to that of a 2-cell cavity.

In the following, we will discuss the fabrication technique employed for the HOM coupler prototypes. Then, we will present external quality factor ( $Q_{ext}$ ) measurements for FM and trapped high  $R/Q$  HOMs, which are the most critical, to evaluate whether our measurement setup is appropriate for verifying the simulated eigenmode CST [5] results.

\* carmelo.barbagallo@ijclab.in2p3.fr




Figure 1: Mechanical design (a) and 3D-printed plastic and copper-coated prototypes (b) of the Probe, Hook, and DQW HOM couplers (from left to right).

## HOM COUPLER PROTOTYPING

To evaluate in a design phase HOM coupler transmission behavior via low-power RF measurements at room temperature, expensive Nb coupler fabrication can be avoided. A potential cost-saving and time-efficient technique currently under development at CERN involves 3D-printing HOM couplers using epoxy and copper-coating the surface via electroplating to impart necessary electrical characteristics.

### 3D Printing for HOM Coupler Fabrication

The CERN Polymerlab team employed the Viper si2 SLA<sup>®</sup> (Stereolithography) rapid prototyping machine to 3D print HOM couplers using both Accura<sup>®</sup> 25 [6] and Accura<sup>®</sup>



antenna into the cutoff tube was used for all three couplers. The designed couplers were equipped with a rotating flange enabling the investigation of damping performance for different orientations of the coupling antenna. The procedure to measure  $Q_{\text{ext}}$  for FM and HOMs involves the following steps [10, 11]: (i) Measuring the loaded quality factor  $Q_1$  by  $S_{21}$  transmission. (ii) Measuring the coupling factor  $\beta_1$  and  $\beta_2$  for the antennas from the measured  $S_{11}$  and  $S_{22}$ . The coupling factor  $\beta$  is calculated from the measured  $S_{11}$  using the formula  $\beta = \frac{1 \pm |S_{11}|}{1 \mp |S_{11}|}$ , where the upper sign corresponds to over-coupling and the lower sign to under-coupling. (iii) Evaluating the intrinsic quality factor  $Q_0 = Q_1(1 + \beta_1 + \beta_2)$ . (iv) Determining  $Q_{\text{ext}} = Q_0/\beta$ . Figure 5 shows the results for suitable coupler orientations for efficient HOM damping. The study found that simulated eigenmode CST results agree with measurements for the studied configurations.




Figure 5: Measured and simulated  $Q_{\text{ext}}$  for FM and trapped high  $R/Q$  HOMs, using one Hook (a), Probe (b) or DQW (c) coupler on a 2-cell 801.58 MHz Cu cavity.

However, significant deviations were observed for certain modes, particularly for one of the two polarizations of dipole modes. This could be due to various reasons: (i) The orientation of the coupler plays a crucial role, as a slight tilt  $\delta\theta$  (for example  $0.5^\circ$ ) can result in a significant impact on either the magnetic or electric coupling to the antenna, leading to a considerable change in  $Q_{\text{ext}}$  for certain coupler directions. (ii) Measurements of  $S_{11}$ , or  $S_{22}$ , for modes with weak coupling to the antennas can lead to measurement inaccuracy. Only in a few cases, we succeeded in measuring the two polarizations of dipole modes separately. (iii) Cavity imperfections and weak RF contact in the clamped assembly can also be sources of error. In addition, in this configuration with a single coupler, only one polarization is effectively attenuated. To damp the other polarization, an additional coupler could be installed on the opposite side of the cavity.

The built couplers demonstrated satisfactory performance in rejecting the FM and damping HOMs within BBU requirements. Specifically, it has been observed that the second version of the fabricated Hook coupler (ref. HookV02) exhibits superior performance compared to its predecessor (ref. HookV01). This improvement may be attributed to the more precise alignment of the antenna to the coupler shell and a reduction in both shrinkage and excess material on the coupler surface. Our investigation suggests that the Probe coupler can efficiently damp monopole modes, while the Hook coupler shows promising results in damping dipole modes. On the other hand, the DQW coupler is the most effective solution for attenuating both monopole and dipole HOMs.

## CONCLUSION

In this paper, we conducted RF measurements of coaxial HOM coupler prototypes installed on an 801.58 MHz 2-cell OFHC Cu cavity designed for R&D bench measurements for the PERLE project. Our study has successfully demonstrated the potential of using 3D-printed epoxy copper-coated coaxial HOM couplers to facilitate the design process and verify transmission behavior. Simulated eigenmode results obtained from CST agree with the measurements for the analyzed configurations. The DQW coupler was found to be particularly effective in damping both dipole and monopole modes. Future tests on the 5-cell copper cavity with various coupler schemes (for instance, 4 DQW couplers) are planned to confirm if their measured damping performance meets the BBU requirements. Further RF heating studies are needed to determine if active cooling is required for the Nb version of the couplers that are intended to be installed on the Nb 5-cell PERLE cavity.

## ACKNOWLEDGEMENTS

The author thanks the IJCLab and JLab machine shops and the CERN Polymer lab for their support. Special thanks to Olivier Choisnet (CERN) for manufacturing 3D-printed prototypes and to Jean-Philippe Rigaud (CERN) for conducting metrology measurements on the HOM couplers.

## REFERENCES

- [1] D. Angal-Kalinin *et al.*, "PERLE. Powerful energy recovery linac for experiments. Conceptual design report", *Journal of Physics G: Nuclear and Particle Physics*, vol. 45, no. 6, p. 065003, 2018. doi : 10.1088/1361-6471/aaa171.
- [2] W. Kaabi *et al.*, "PERLE: A High Power Energy Recovery Facility", in *Proc. IPAC'19*, Melbourne, Australia, May 2019, pp. 1396–1399. doi : 10.18429/JACoW-IPAC2019-TUPGW008.
- [3] C. Barbagallo *et al.*, "Higher Order Modes Investigation in the PERLE Superconducting RF Cavity", in *Proc. 31st Linear Accelerator Conference (LINAC'22)*, Liverpool, UK, Aug.-Sep. 2022, pp. 731–734. doi : 10.18429/JACoW-LINAC2022-THPOJ021.
- [4] C. Barbagallo *et al.*, "HOM-damping Studies in a Multi-cell Elliptical Superconducting RF cavity for the Multi-turn Energy Recovery Linac PERLE", in *Proc. 66th ICFA Advanced Beam Dynamics Workshop on Energy Recovery Linacs (ERL'22)*, Ithaca, New York, USA, October 2022, unpublished.
- [5] CST Studio Suite 2023, <https://www.cst.com/>.
- [6] 3D Systems, Accura 25 Datasheet, 2020, Available online: [www.3dsystems.com/sites/default/files/2020-11/3d-systems-accura-25-datasheet-us-a4-2020-09-23-a-print.pdf](http://www.3dsystems.com/sites/default/files/2020-11/3d-systems-accura-25-datasheet-us-a4-2020-09-23-a-print.pdf).
- [7] 3D Systems, Accura 48 Datasheet, 2020, Available online: <https://www.3dsystems.com/sites/default/files/2020-11/3d-systems-accura-48-htr-datasheet-a4-us-2020-09-11-a-print.pdf>.
- [8] P. Maurin, "Copper-coating for PERLE project", CERN, Geneva, Switzerland, Unpublished internal document, 2023.
- [9] J.-P. Rigaud, "Inspection report on HOM Hook Coupler", CERN, Geneva, Switzerland, Rep. EDMS 2787740, Dec. 2022.
- [10] H. Wang and J. Guo, "Bead-pulling measurement principle and technique used for the SRF cavities at JLab", USPAS Education in Beam Physics and Accelerator Technology, SRF Practices and Hands-on Measurements, Thomas Jefferson Lab, USA (2015).
- [11] K. Papke *et al.*, "Comparison of coaxial higher order mode couplers for the CERN Superconducting Proton Linac study", *Physical Review Accelerators and Beams*, vol. 20, no. 6, p. 060401, 2017. doi : 10.1103/PhysRevAccelBeams.20.060401.