Algorithms: Solutions 7

```
                               X
                               X
                               X
                               X
                               X
                               X
                               X
                               X
                               X
number of                      X
homeworks                X     X
                         X     X
                         X  X  X
                X        X  X  X
                X        X  X  X
                X     X  X  X  X
             X  X  X  X  X  X  X
             X  X  X  X  X  X  X
          X  X  X  X  X  X  X  X
          -----------------------
          3  4  5  6  7  8  9  10
                  grades
```

Problem 1
Write algorithms for converting (a) an adjacency-list representation of a graph into an adjacency matrix and (b) an adjacency matrix into adjacency lists.

We denote the adjacency list of a vertex u by *Adj-List*$[u]$, and the adjacency-matrix element for vertices u and v by *Adj-Matrix*$[u, v]$. The time complexity of both algorithms is $\Theta(V^2)$.

(a) Converting adjacency lists into a matrix.

LISTS-TO-MATRIX(G) $\triangleright$ G is represented by adjacency lists
for each $u \in V[G]$
  do for each $v \in V[G]$
    do *Adj-Matrix*$[u, v] \leftarrow 0$
for each $u \in V[G]$
  do for each $v \in$ *Adj-List*$[u]$
    do *Adj-Matrix*$[u, v] \leftarrow 1$

(b) Converting an adjacency matrix into lists.

MATRIX-TO-LISTS(G) $\triangleright$ G is represented by an adjacency matrix
for each $u \in V[G]$
  do initialize an empty list *Adj-List*$[u]$
for each $u \in V[G]$
  do for each $v \in V[G]$
    do if *Adj-Matrix*$[u, v] = 1$
      then add v to *Adj-List*$[u]$

Problem 2

Consider a directed graph with n vertices, represented by a matrix $M[1..n, 1..n]$. A vertex is called a *sink* if it has $(n-1)$ incoming edges and no outgoing edges. Give an algorithm that finds the sink vertex; if the graph has no sink, it should return 0.

The following algorithm consists of two parts: the first loop finds a vertex i that *may* be a sink, and ensures that no other vertex is a sink; the second loop tests whether i is indeed a sink. The running time is $\Theta(n)$.

```
FIND-SINK(M, n)
i ← 1
j ← 1
while i < n and j ≤ n        ▷ find a sink candidate i
    do if M[i, j] = 0
            then j ← j + 1
            else i ← i + 1
for k ← 1 to n        ▷ check whether i is a sink
    do if M[i, k] = 1
            then return 0
        if k ≠ i and M[k, i] = 0
            then return 0
return i
```

Problem 3

Give a formula for C_n, defined by the following recurrence:

$$
\begin{aligned}
C_0 &= 0 \\
C_n &= 3 \cdot C_{n-1} + \frac{3^n}{n \cdot (n+1)} \qquad \text{(where } n \geq 1\text{)}
\end{aligned}
$$

We unwind this recurrence as follows:

$$
\begin{aligned}
C_n &= 3 \cdot C_{n-1} + \frac{3^n}{n \cdot (n+1)} \\
&= 3 \cdot \left(3 \cdot C_{n-2} + \frac{3^{n-1}}{(n-1) \cdot n}\right) + \frac{3^n}{n \cdot (n+1)} \\
&= 3^2 \cdot C_{n-2} + \frac{3^n}{(n-1) \cdot n} + \frac{3^n}{n \cdot (n+1)} \\
&\ \ \vdots \\
&= \frac{3^n}{1 \cdot 2} + \frac{3^n}{2 \cdot 3} + \ldots + \frac{3^n}{(n-1) \cdot n} + \frac{3^n}{n \cdot (n+1)} \\
&= 3^n \cdot \left(\frac{1}{1 \cdot 2} + \frac{1}{2 \cdot 3} + \ldots + \frac{1}{(n-1) \cdot n} + \frac{1}{n \cdot (n+1)}\right) \\
&= 3^n \cdot \left(\left(\frac{1}{1} - \frac{1}{2}\right) + \left(\frac{1}{2} - \frac{1}{3}\right) + \ldots + \left(\frac{1}{n-1} - \frac{1}{n}\right) + \left(\frac{1}{n} - \frac{1}{n+1}\right)\right) \\
&= 3^n \cdot \left(1 - \frac{1}{n+1}\right) \\
&= \frac{3^n \cdot n}{n+1}
\end{aligned}
$$