

The Complexity of Data-Driven Norm Synthesis and Revision

Davide Dell’Anna , Natasha Alechina , Brian Logan , Maarten Löffler ,
Fabiano Dalpiaz , Mehdi Dastani

Utrecht University

{d.dellanna, n.a.alechina, b.s.logan, m.loffler, f.dalpiaz, m.m.dastani}@uu.nl

Abstract

Norms have been widely proposed as a way of coordinating and controlling the activities of agents in a multi-agent system (MAS). A norm specifies the behaviour an agent should follow in order to achieve the objective of the MAS. However, designing norms to achieve a particular system objective can be difficult, particularly when there is no direct link between the language in which the system objective is stated and the language in which the norms can be expressed. In this paper, we consider the problem of synthesising a norm from traces of agent behaviour, where each trace is labelled with whether the behaviour satisfies the system objective. We show that the norm synthesis problem is NP-complete.

1 Introduction

There has been a considerable amount of work on using norms to coordinate the activities of agents in a multi-agent system (MAS) (Chopra et al. 2018). Norms can be viewed as standards of behaviour which specify that certain states or sequences of actions in a MAS should occur (obligations) or should not occur (prohibitions) in order for the objective of the MAS to be realized (Boella and van der Torre 2004). We focus on conditional norms with deadlines which express behavioral properties (Tinnemeier et al. 2009). Conditional norms are triggered (detached) in certain states of the MAS and have a temporal dimension specified by a deadline. The satisfaction or violation of a detached norm depends on whether the behaviour of the agent brings about a specified state before a state in which the deadline condition is true. Conditional norms are implemented in a MAS through enforcement. That is, violation of a norm results in the violating agent incurring a sanction, e.g., a fine; see, e.g., (Alechina, Dastani, and Logan 2013; Dell’Anna, Dastani, and Dalpiaz 2020) for how to determine an appropriate level of sanction.

For many applications it is assumed that the MAS developer will design an appropriate norm to realise the system objective. However, this can be difficult, particularly when the internals of the agents are unknown, e.g., in the case of open MAS (Artikis and Pitt 2001), and when there is no direct connection between the language in which the system objective is stated and the language in which norms can be expressed. For example, one objective of a traffic system may be to avoid traffic collisions, but ‘not colliding’ is not a

property under direct agent control, and prohibition of collisions cannot be stated as a norm. A poorly designed norm may fail to achieve the system objective, or have undesirable side effects, e.g., the objective is achieved, but the autonomy of the agents is restricted unnecessarily.

The increasing availability of large amounts of system behaviour data introduces the possibility of a new approach to the design of norms, namely the synthesis of norms directly from data collected during the execution of the system. For example, data may show that collisions always happen when an agent’s speed is very high, allowing us to state a norm prohibiting agents from speeding too much. In this paper, we consider the problem of synthesising norms from traces of agent behaviour, where each trace is labelled with whether the behaviour satisfies the system objective. We show that synthesising a norm (i.e., an obligation or a prohibition) that correctly classifies the traces (i.e., the norm is violated on traces where the behaviour does not satisfy the system objective, and is not violated on other traces) is an NP-complete problem. We also consider the problem of synthesizing a norm that is “close” to a target norm. This problem is relevant where there is an existing norm that does not achieve the system objective, but which is accepted, e.g., by human users of a system, and we wish a minimal modification that does achieve the objective. We show that the minimal norm revision problem is also NP-complete.

There has been a considerable amount of work on the automated synthesis of norms. For example, (Shoham and Tennenholtz 1995) consider the problem of synthesising a *social law* that constrains the behaviour of the agents in a MAS so as to ensure that agents in a *focal* state are always able to reach another focal state no matter what the other agents in the system do. They show that synthesising a useful social law is NP-complete. In (van der Hoek, Roberts, and Wooldridge 2007), the problem of synthesising a social law is recast as an ATL model checking problem. They show that the problem of whether there exists a social law satisfying an objective expressed as an arbitrary ATL formula (feasibility) is NP-complete, while for objectives expressed as propositional formulae, feasibility (and synthesis) is decidable in polynomial time. In contrast to the approach we present here, these and related approaches (e.g., (Fitoussi and Tennenholtz 2000; Wooldridge and van der Hoek 2005; Ågotnes et al. 2007))

are used to synthesise norms at design time, and assume a complete model the agents' behaviour is available, e.g., in the form of a transition system or a Kripke structure. Another strand of work focusses on the 'online' synthesis of norms, where norms emerge from the interactions of agents in a decentralised way, e.g., (Airiau, Sen, and Villatoro 2014; Savarimuthu and Cranefield 2011). Unlike our approach, such approaches typically assume that the agents are cooperative, and/or that some minimal standards of behaviour can be assumed. Closer to our work are approaches that use agents' behaviour to guide (centralised) norm synthesis. For example, (Morales et al. 2015) present algorithms for the online synthesis of compact *action-based* norms when the behaviour of agents leads to undesired system states. In contrast, we consider norms that regulate patterns of behaviour. (Corapi et al. 2011) and (Athakravi et al. 2012) apply Inductive Logic Programming to norm synthesis and revision. They represent the system objective in terms of desired outcomes of event traces. In contrast to our approach, traces encode use cases provided by a human developer, and the system objectives are expressed in the same language as norms.

2 Preliminaries

In this section we give formal definitions of the behaviour of agents in the MAS and of conditional norms.

We assume a finite propositional language L that contains propositions corresponding to properties of states of the MAS. A *state* of the MAS is a propositional assignment. A conjunction of all literals (propositions or their negations) in a state s will be referred to as a *state description* of s . A propositional formula is a boolean combination of propositional variables. The definition of a propositional formula ϕ being true in a state s is standard.

A *trace* is a finite sequence of states. We use the notation (s_1, \dots, s_k) for a trace consisting of states s_1, \dots, s_k . We denote the i -th state in a trace ρ by $\rho[i]$. We assume that the behaviour exhibited by the agents in the MAS is represented by a set of finite traces Γ . For example, a trace could be generated by the actions of all vehicles involved in a traffic accident. We denote by $S(\Gamma)$ or simply by S the set of states occurring in traces in Γ . Each subset X of $S(\Gamma)$ is definable by a propositional formula ϕ_X (a disjunction of state descriptions of states in X). Note that the size of ϕ_X is linear in the size of X (the sum of sizes of state descriptions of states in X). Γ is partitioned into two sets Γ_T (positive traces) and Γ_F (negative traces). The partition is performed with respect to the system objective, which typically does not correspond directly to the properties expressible in L .

The problem we wish to solve is how to generate a conditional norm which is expressed using propositions from L that is obeyed on traces in Γ_T and violated on traces in Γ_F .

Definition 1 (Conditional Norm). A conditional norm (over L) is a tuple $(\phi_C, Z(\phi_Z), \phi_D)$, where ϕ_C , ϕ_Z and ϕ_D are propositional formulas over L , and $Z \in \{P, O\}$ indicates whether the norm is a prohibition (P) or an obligation (O).

We refer to ϕ_C as the (detachment) condition of the norm,

and ϕ_D as the deadline. ϕ_Z characterizes a state that is prohibited (resp. obligated) to occur after a state where the condition of the norm ϕ_C holds, and before a state where the deadline of the norm ϕ_D holds. We define the conditions for violation of norms formally below.

Definition 2 (Violation of Prohibition). A conditional prohibition $(\phi_C, P(\phi_P), \phi_D)$ is violated on a trace (s_1, s_2, \dots, s_m) if there are i, j with $1 \leq i \leq j \leq m$ such that ϕ_C is true at s_i , ϕ_P is true at s_j , and there is no k with $i < k < j$ such that ϕ_D is true at s_k .

Definition 3 (Violation of Obligation). A conditional obligation $(\phi_C, O(\phi_O), \phi_D)$ is violated on a trace (s_1, s_2, \dots, s_m) if there are i, j with $1 \leq i \leq j \leq m$ such that ϕ_C is true at s_i , ϕ_D is true at s_m , and there is no k with $i \leq k \leq j$ such that ϕ_O is true at s_k .

A conditional norm is obeyed on a trace if it is not violated on that trace. Violation conditions of conditional norms can be expressed in Linear Time Temporal Logic (LTL) and evaluated on finite traces in linear time (Alechina, Dastani, and Logan 2014).

3 Complexity of Norm Synthesis

Given a set of agent behaviour traces Γ partitioned into Γ_T and Γ_F , we wish to synthesize a norm that correctly classifies each trace (that is, the norm is violated on all traces in Γ_F , and is not violated on any trace in Γ_T). Clearly, this is not always possible; two sets of traces may not be distinguishable by a single conditional norm (or even by a set of conditional norms). For example:

$$\Gamma_T = \{(s_1, s_2, s_3)\}, \Gamma_F = \{(s_1, s_1, s_2, s_3)\}$$

cannot be distinguished by a conditional norm.

3.1 Prohibition Synthesis

Next we define formally the decision problem we call *prohibition synthesis*.

Definition 4. The prohibition synthesis problem is the following decision problem:

Instance A finite set of propositions L ; a finite set of finite traces Γ partitioned into Γ_T and Γ_F , each trace given as a sequence of state descriptions over L .

Question Are there three propositional formulas ϕ_C , ϕ_P , and ϕ_D over L such that

Neg every trace in Γ_F violates $(\phi_C, P(\phi_P), \phi_D)$

Pos no trace in Γ_T violates $(\phi_C, P(\phi_P), \phi_D)$

The correspondence between sets of states and formulas over L allows us to restate the prohibition synthesis problem as follows: given a set of positive traces Γ_T and negative traces Γ_F , find three sets of states X_C , X_P , X_D such that:

Neg For every trace $\rho \in \Gamma_F$, exist i and j with $i \leq j$ such that $\rho[i] \in X_C$, $\rho[j] \in X_P$, and there is no k with $i < k < j$ such that $\rho[k] \in X_D$.

Pos For every trace $\rho \in \Gamma_T$, if for some i and j , $i \leq j$, $\rho[i] \in X_C$, $\rho[j] \in X_P$, then there exists k such that $i < k < j$ and $\rho[k] \in X_D$.

Theorem 1. *The prohibition synthesis problem is NP-complete.*

Proof. The prohibition synthesis problem is clearly in NP (a non-deterministic Turing machine can guess the sets and check in polynomial time that they satisfy the conditions). To prove that it is NP-hard, we reduce 3SAT (satisfiability of a set of clauses with 3 literals) to prohibition synthesis.

Suppose an instance of 3SAT (a set of clauses C_1, \dots, C_n over variables x_1, \dots, x_m) is given. We generate an instance of the prohibition synthesis problem such that it has a solution iff C_1, \dots, C_n are satisfiable (each clause contains at least one true literal). The set of states in the prohibition synthesis problem consists of two states s and t which are a technical device (intuitively they serve as the detachment condition and the violation of the prohibition), and for each variable x_i , two states u_i and v_i , intuitively meaning that x_i is true (u_i) or false (v_i). Below is the rest of the construction. Comments in square brackets explain the intuition behind it.

The set of negative traces Γ_F contains:

- a two state trace (s, t) [together with $s, t \notin X_C \cap X_P$ below, this forces $s \in X_C$ and $t \in X_P$];
- for every variable x_i in the input, a trace (s, v_i, t, s, u_i, t) [this ensures that either v_i or u_i are not in X_D].

The set of positive traces Γ_T contains:

- a single state trace (s) [so s cannot be in $X_C \cap X_P$];
- (t) [so t cannot be in $X_C \cap X_P$];
- for every variable x_i in the input: (s, v_i, u_i, t) [this means that either v_i or u_i are in X_D]; (v_i) ; (u_i) ; (v_i, t) ; (u_i, t) ; (s, v_i) ; (s, u_i) ;
- for every pair of variables x_i, x_j in the input: (v_i, u_j) ; (u_j, v_i) [this together with preceding traces ensures that v_i and u_i are not in X_C or X_P];
- for each clause C in the input over variables x_j, x_k, x_l : (s, z_j, z_k, z_l, t) where z_i is u_i if x_i occurs in C positively, and v_i if it occurs negatively.

The reduction is polynomial in the number of variables (quadratic) and clauses (linear).

We claim that there exists an assignment f of 0, 1 to x_1, \dots, x_m satisfying C_1, \dots, C_n if, and only if, there is a solution to the prohibition synthesis problem above where $X_C = \{s\}$, $X_P = \{t\}$, and for every i , $u_i \in X_D$ iff $f(x_i) = 1$ and $v_i \in X_D$ iff $f(x_i) = 0$.

Assume an assignment f satisfying C_1, \dots, C_n exists. Let $X_C = \{s\}$ and $X_P = \{t\}$. For every i , place u_i in X_D if $f(x_i) = 1$ and $v_i \in X_D$ iff $f(x_i) = 0$. This produces a solution because: s, t satisfies **Neg**; for every i , either u_i or v_i are not in X_D , so s, v_i, t, s, u_i, t satisfies **Neg**. Positive traces satisfy **Pos**: either s followed by t does not occur on a trace, or u_i, v_i occur between s and t and one of them is in X_D , or (from the clause encoding) one of the literals in the clause is true, so for positive x_i it means that u_i is in X_D and **Pos** is satisfied, or for negative $\neg x_i$ it means that v_i is in X_D and again **Pos** is satisfied.

Assume there is a solution to the prohibition synthesis problem. It is clear (see the comments in square brackets

above) that it has to be of the form $X_C = \{s\}$, $X_P = \{t\}$ and X_D containing some u_i s and v_i s. In particular, since (s, v_i, u_i, t) is a positive trace, for every i either u_i or v_i has to be not in X_D . Set $f(x_i)$ to be 1 if u_i in X_D and 0 otherwise. Then each clause $C = \{\sim x_j, \sim x_k, \sim x_l\}$ (where $\sim x_j$ denotes x_j if it occurs positively or $\neg x_j$ if it occurs negatively) is satisfied by f since for every clause there will be one literal which is true. This is because (s, z_j, z_k, z_l, t) is a positive trace, and either for some positive literal x_i, u_i is in X_D , or for some negative literal $\neg x_i, v_i$ is in X_D , so u_i is not in X_D , so $f(\neg x_i) = 1$. \square

3.2 Obligation Synthesis

We now consider the *obligation synthesis problem*.

Definition 5. *The obligation synthesis problem is the following decision problem:*

Instance *A finite set of propositions L , a finite set Γ of finite traces partitioned into Γ_T and Γ_F , where each trace is given as a sequence of state descriptions.*

Question *Are there three propositional formulas ϕ_C, ϕ_O , and ϕ_D over L such that*

Neg *every trace in Γ_F violates $(\phi_C, O(\phi_O), \phi_D)$*

Pos *no trace in Γ_T violates $(\phi_C, O(\phi_O), \phi_D)$*

Analogously to the prohibition synthesis problem, the obligation synthesis problem can be equivalently restated in terms of states: are there three sets of states X_C, X_O and X_D such that:

Neg For every trace $\rho \in \Gamma_F$, there exist i and j with $i \leq j$ such that $\rho[i] \in X_C, \rho[j] \in X_D$, and there is no k with $i \leq k \leq j$ such that $\rho[k] \in X_O$

Pos For every trace $\rho \in \Gamma_T$, if for some i and $j, i \leq j$, $\rho[i] \in X_C, \rho[j] \in X_D$, then there exists k such that $i \leq k \leq j$ and $\rho[k] \in X_O$.

Theorem 2. *The obligation synthesis problem is NP-complete.*

Proof. The obligation synthesis problem is clearly in NP. To prove that it is NP-hard, we again use a reduction from the 3SAT problem.

As before, consider a set of clauses C_1, \dots, C_n over variables x_1, \dots, x_m , which is an instance of 3SAT. We generate an instance of the obligation synthesis problem such that it has a solution iff C_1, \dots, C_n are satisfiable. The idea of the reduction is similar to that for prohibitions. We use two auxiliary states s and t , intuitively to serve as the detachment condition and the deadline, and make sure that neither of them is also the obligation, but now instead of inserting a deadline between s and t in positive traces, we insert an obligation. We want to make some subset of $\{v_i : i \in [1, \dots, m]\} \cup \{u_i : i \in [1, \dots, m]\}$ to be the obligation (X_O), so that exactly one of v_i, u_i for each i is in X_O . Then $u_i \in X_O$ can encode that x_i is true, and $v_i \in X_O$ that x_i is false, and we can make the encoding work by creating a positive trace corresponding to each clause so that at least one of the literals in the clause should be true.

The set of negative traces contains:

- a 2 state trace (s, t) [this forces either $s \in X_C \cap \overline{X_D} \cap \overline{X_O}$, $t \in X_D \cap \overline{X_C} \cap \overline{X_O}$, or $s \in X_C \cap X_D \cap \overline{X_O}$, or $t \in X_C \cap X_D \cap \overline{X_O}$.

To rule out the latter two possibilities, we require below that s and t on their own are positive traces.]

- for every variable x_i in the input, a trace (s, v_i, t, s, u_i, t) [this ensures that either v_i or u_i are not in X_O , because there is one (s, \dots, t) sub-trace that does not contain a state from X_O].

The set of positive traces contains:

- a one state trace (s) [so s cannot be in $X_C \cap X_D \cap \overline{X_O}$]
- a one state trace (t) [so t cannot be in $X_C \cap X_D \cap \overline{X_O}$]
- for every variable x_i in the input, a trace (s, v_i, u_i, t) [this ensures that either v_i or u_i are in X_O]
- for each clause C in the input over variables x_j, x_k, x_l , a trace (s, z_j, z_k, z_l, t) where z_i is u_i if x_i occurs in C positively, and v_i if it occurs negatively.

The reduction is linear in the number of variables and clauses.

We claim that there exists an assignment f of 0, 1 to x_1, \dots, x_m satisfying C_1, \dots, C_n if, and only if, there is a solution to the obligation synthesis problem above where $s \in X_C$, $t \in X_D$, and for every i , $u_i \in X_O$ iff $f(x_i) = 1$ and $v_i \in X_O$ iff $f(x_i) = 0$. The proof of this claim is analogous to that of Theorem 1.

Assume an assignment f satisfying C_1, \dots, C_n exists. Let $X_C = \{s\}$ and $X_D = \{t\}$. For every i , place u_i in X_O iff $f(x_i) = 1$ and $v_i \in X_O$ iff $f(x_i) = 0$. It is easy to check that this is a solution to the obligation synthesis problem.

Assume there is a solution to the obligation synthesis problem. It is clear (see the comments in brackets above) that any solution should satisfy $s \in X_C \cap \overline{X_D} \cap \overline{X_O}$ and $t \in X_D \cap \overline{X_C} \cap \overline{X_O}$. Since (s, v_i, t, s, u_i, t) is a negative trace for every i , this means that it contains an unsatisfied conditional obligation. This means that for every i , either v_i or u_i is not in X_O . Since (s, v_i, u_i, t) is a positive trace, then in any solution, for every i , either u_i or v_i has to be in X_O . Hence we can use the membership in X_O to produce a boolean valuation of variables x_i (1 if $u_i \in X_O$, and 0 if $v_i \in X_O$). Since for every clause $C = \{\sim x_j, \sim x_k, \sim x_l\}$, the trace (s, z_j, z_k, z_l, t) (where z_i is v_i if $\sim x_i = \neg x_i$, and u_i if $\sim x_i = x_i$) is a positive trace, at least one of z_i is in X_O . This means that the valuation based on the membership in X_O satisfies all the clauses (since at least one literal in each clause will evaluate to 1). \square

From Theorems 1 and 2, it follows immediately that the problem of generating a set of norms of size at most m that correctly classifies a set of traces Γ (that is, no norm N_i is violated on any trace in Γ_T , and all traces in Γ_F violates at least one norm N_j) is also NP-complete.

4 Complexity of Minimal Revision

In this section, we consider the problem of (minimally) revising conditional prohibitions (we omit the treatment of obligations, which is analogous). This problem is often relevant when there is an existing norm that does not achieve the system objective, and we wish a minimal modification of the existing norm that does achieve the objective.

Assume we are given a set of traces and a conditional prohibition $(\phi_C, P(\phi_P), \phi_D)$, and need to change it in a minimal way so that it classifies the traces correctly. The editing distance between conditional prohibitions can be defined in various ways, e.g., for formulas ϕ_C, ϕ_P, ϕ_D in disjunctive normal form, this could be the sum of the numbers of added and removed disjuncts for all three formulas. Note that the set of non-equivalent propositional formulas built from the set L is finite, and so is the number of possible different conditional prohibitions (or obligations). Regardless of how the distance between different conditional norms is defined, for a fixed set of propositional variables L there is a maximal editing distance $max(L)$ between any two norms using formulas over L .

Given some distance measure $dist$ defined for any two conditional prohibitions α_1 and α_2 over L , the decision problem for minimal revision can be stated as:

Definition 6. *The (decision form) of the minimal prohibition revision problem is as follows:*

Instance A number m ; a finite set of propositions L ; a finite set Γ of finite traces partitioned into Γ_T and Γ_F ; a conditional prohibition $(\phi_C, P(\phi_P), \phi_D)$ over L .

Question Are there three propositional formulas ϕ'_C , ϕ'_P , and ϕ'_D over L such that

Dist $dist((\phi_C, P(\phi_P), \phi_D), (\phi'_C, P(\phi'_P), \phi'_D)) \leq m$

Neg every trace in Γ_F violates $(\phi'_C, P(\phi'_P), \phi'_D)$

Pos no trace in Γ_T violates $(\phi'_C, P(\phi'_P), \phi'_D)$

Theorem 3. *Let $dist(\alpha_1, \alpha_2)$ be computable in time polynomial in the size of α_1 and α_2 , and the range of $dist$ over norms built over propositions from L be bounded by $max(L)$. Then the minimal prohibition revision problem is NP-complete.*

Proof. The membership in NP follows from the fact that a solution can be guessed and checked in polynomial time.

NP-hardness is by reduction from the prohibition synthesis problem. Note that if a solution to the prohibition synthesis problem exists, it will be at most at distance $max(L)$ from the input norm. So to solve the prohibition synthesis problem, we can ask for a solution to the minimal prohibition revision problem with $m = max(L)$. \square

5 Conclusions

We considered the problem of synthesising and minimally revising norms to achieve a system objective from labelled traces of agent behaviour. We showed that the problems of norm synthesis and revision are NP-complete. In future work, we plan to investigate the synthesis of approximate norms (i.e., norms that do not classify all traces perfectly), and more tractable heuristic approaches to norm synthesis and revision.

References

- Ågotnes, T.; van der Hoek, W.; Rodríguez-Aguilar, J. A.; Sierra, C.; and Wooldridge, M. J. 2007. On the logic of normative systems. In Veloso, M. M., ed., *Proceedings of the 20th International Joint Conference on Artificial Intelligence (IJCAI 2007)*, 1175–1180.
- Airiau, S.; Sen, S.; and Villatoro, D. 2014. Emergence of conventions through social learning. *Autonomous Agents and Multi-Agent Systems* 28(5):779–804.
- Alechina, N.; Dastani, M.; and Logan, B. 2013. Reasoning about normative update. In Rossi, F., ed., *Proceedings of the Twenty Third International Joint Conference on Artificial Intelligence (IJCAI 2013)*, 20–26. Beijing, China: IJCAI.
- Alechina, N.; Dastani, M.; and Logan, B. 2014. Norm approximation for imperfect monitors. In *International conference on Autonomous Agents and Multi-Agent Systems, AAMAS '14, Paris, France, May 5-9, 2014*, 117–124.
- Artikis, A., and Pitt, J. 2001. A formal model of open agent societies. In *Proceedings of the Fifth International Conference on Autonomous Agents, AGENTS 2001, Montreal, Canada, May 28 - June 1, 2001*, 192–193.
- Athakravi, D.; Corapi, D.; Russo, A.; Vos, M. D.; Padget, J. A.; and Satoh, K. 2012. Handling change in normative specifications. In *International Conference on Autonomous Agents and Multiagent Systems, AAMAS 2012, Valencia, Spain, June 4-8, 2012 (3 Volumes)*, 1369–1370.
- Boella, G., and van der Torre, L. W. N. 2004. Regulative and constitutive norms in normative multiagent systems. In *Principles of Knowledge Representation and Reasoning: Proceedings of the Ninth International Conference (KR2004), Whistler, Canada, June 2-5, 2004*, 255–266.
- Chopra, A.; van der Torre, L.; Verhagen, H.; and Villata, S., eds. 2018. *Handbook of Multiagent Systems*. London: College Publications.
- Corapi, D.; Russo, A.; Vos, M. D.; Padget, J. A.; and Satoh, K. 2011. Normative design using inductive learning. *Theory Pract. Log. Program.* 11(4-5):783–799.
- Dell’Anna, D.; Dastani, M.; and Dalpiaz, F. 2020. Runtime revision of sanctions in normative multi-agent systems. *Autonomous Agents and Multi-Agent Systems* 34(2):1–54.
- Fitoussi, D., and Tennenholtz, M. 2000. Choosing social laws for multi-agent systems: Minimality and simplicity. *Artificial Intelligence* 119(1):61–101.
- Morales, J.; Lopez-Sanchez, M.; Rodríguez-Aguilar, J. A.; Vasconcelos, W.; and Wooldridge, M. 2015. Online automated synthesis of compact normative systems. *ACM Transactions on Autonomous and Adaptive Systems (TAAS)* 10(1):1–33.
- Savarimuthu, B. T. R., and Cranefield, S. 2011. Norm creation, spreading and emergence: A survey of simulation models of norms in multi-agent systems. *Multiagent and Grid Systems* 7(1):21–54.
- Shoham, Y., and Tennenholtz, M. 1995. On social laws for artificial agent societies: Off-line design. *Artificial intelligence* 73(1-2):231–252.
- Tinnemeier, N.; Dastani, M.; Meyer, J.-J.; and van der Torre, L. 2009. Programming normative artifacts with declarative obligations and prohibitions. In *Proceedings of the IEEE/WIC/ACM International Conference on Intelligent Agent Technology (IAT’09)*, 69–78.
- van der Hoek, W.; Roberts, M.; and Wooldridge, M. J. 2007. Social laws in alternating time: effectiveness, feasibility, and synthesis. *Synthese* 156(1):1–19.
- Wooldridge, M., and van der Hoek, W. 2005. On obligations and normative ability: Towards a logical analysis of the social contract. *Journal of Applied Logic* 3(3):396–420.