

# UNITE: A Unified Benchmark for Text-to-SQL Evaluation

Wuwei Lan, Zhiguo Wang, Anuj Chauhan, Henghui Zhu, Alexander Li, Jiang Guo, Sheng Zhang, Chung-Wei Hang, Joseph Lilien, Yiqun Hu, Lin Pan, Mingwen Dong, Jun Wang, Jiarong Jiang, Stephen Ash, Vittorio Castelli, Patrick Ng and Bing Xiang

AWS AI Labs

{lanwuwei, zhiguow, patricng}@amazon.com

## Abstract

A practical text-to-SQL system should generalize well on a wide variety of natural language questions, unseen database schemas, and novel SQL query structures. To comprehensively evaluate text-to-SQL systems, we introduce a **UN**ified benchmark for **T**ext-to-SQL **E**valuation (UNITE). It is composed of publicly available text-to-SQL datasets, containing natural language questions from more than 12 domains, SQL queries from more than 3.9K patterns, and 29K databases. Compared to the widely used Spider benchmark (Yu et al., 2018), we introduce  $\sim$ 120K additional examples and a threefold increase in SQL patterns, such as comparative and boolean questions. We conduct a systematic study of six state-of-the-art (SOTA) text-to-SQL parsers on our new benchmark and show that: 1) Codex performs surprisingly well on out-of-domain datasets; 2) specially designed decoding methods (e.g. constrained beam search) can improve performance for both in-domain and out-of-domain settings; 3) explicitly modeling the relationship between questions and schemas further improves the Seq2Seq models. More importantly, our benchmark presents key challenges towards compositional generalization and robustness issues — which these SOTA models cannot address well.<sup>1</sup>

## 1 Introduction

Text-to-SQL semantic parsing aims to transform natural language questions (NLQ) into SQL queries over underlying relational databases. It provides an interface for non-technical users to query their database. The current state-of-the-art text-to-SQL systems achieve more than 90% accuracy on WikiSQL dataset (Zhong et al., 2017) and 85% accuracy on Spider dataset (Yu et al., 2018). However, these scores do not reflect real-world system performances. In real scenario, the text-to-SQL systems

will encounter large database tables, out-of-domain entities, new compositional SQL structures, and diversified NLQ expressions. The existing single dataset is biased towards specific aspect and cannot evaluate text-to-SQL system comprehensively. For example, WikiSQL has only one table for each database, and the SQL statements have no JOIN clauses. Spider is known to have explicit column mention (Suhr et al., 2020) and simplified table names and column names (Lee et al., 2021). The text-to-SQL datasets studied in (Finegan-Dollak et al., 2018) only have one database for each topic, which is inappropriate for cross-database evaluation. Spider-Syn (Gan et al., 2021a) is for robustness evaluation against synonym replacement, while Spider-DK (Gan et al., 2021b) is designed for domain knowledge. Therefore, these datasets are proposed for a specific aspect of text-to-SQL task, the reported results in one or few selected datasets don't represent real-world performance.

In this work, we propose a **UN**ified benchmark for **T**ext-to-SQL **E**valuation (UNITE), which consists of 18 publicly available text-to-SQL datasets covering different domains, including Wikipedia, healthcare, education, geography, transportation, software engineering, and finance. UNITE provides several benefits as a comprehensive text-to-SQL benchmark: 1) its dataset size is the largest to date, consisting of 97K training and 27K test examples; 2) it introduces a threefold increase of SQL patterns compared to the Spider benchmark, and contains examples from over 12 domains and 29K databases; and 3) its unified format aims to facilitate apples-to-apples text-to-SQL benchmarking on generalizability and robustness.

To better understand the challenges of UNITE benchmark, we evaluate six state-of-the-art text-to-SQL parsers. The best performance is below 50%, showing the limited generalization ability of these text-to-SQL models in a realistic setting. Among these SOTA models, Codex (Chen et al., 2021) in-

<sup>1</sup>Our code and data processing scripts <https://github.com/aws-labs/unified-text2sql-benchmark>

context learning (Rajkumar et al., 2022) has the best out-of-domain performance, thus demonstrating the great potential of large-scale language models. We also observed that customized decoding, such as constrained beam search from PICARD (Scholak et al., 2021), and relation-aware self-attention can further improve the Seq2Seq models.

In summary, our main contributions are: (1) We introduce a new benchmark with a wide variety of databases, SQL, and NLQ patterns to evaluate text-to-SQL comprehensively. (2) We perform in-depth statistics and analysis of our UNITE benchmark. (3) We unify the format of 18 publicly available text-to-SQL datasets and remove the obstacles of data access and usage. We will release this unified collection and its evaluation framework to facilitate realistic text-to-SQL evaluation. (4) We systematically study 6 SOTA text-to-SQL models (including Codex in-context learning) on our benchmark.

## 2 UNITE Benchmark

### 2.1 Selection Criteria

Our guideline of dataset selection is based on diversity, which means a dataset will be included in our benchmark if it can introduce new domains, new question types, new SQL patterns and new aspects for addressing specific issues.

**WikiSQL** Zhong et al. (2017) synthesized SQLs with pre-defined rules on top of Wikipedia tables, then generated crude NLQs from templates, which are rewritten and paraphrased by human annotators. **Spider** Yu et al. (2018) did not use any templates and directly instructed students from computer science major to write complex NLQ and SQL pairs over 200 databases.

**SQUALL** To explore the necessity of fine-grained supervision for text-to-SQL semantic parsing, Shi et al. (2020) introduce detailed alignment between NLQ spans and SQL fragments (e.g., *the highest* ↔ *ORDER BY ... LIMIT 1*) on top of WikiTable-Questions (Pasupat and Liang, 2015).

**Spider-Syn** Gan et al. (2021a) replace the schema-related words with the manually selected paraphrases, then eliminate the explicit mention between NLQ and schema to study model robustness against synonym substitution.

**Criteria2SQL** In medical domain, Yu et al. (2020) introduce a text-to-SQL dataset that can translate eligibility criteria to executable SQL queries. All SQLs follow the same structure: `SELECT patient_id FROM table_id WHERE condition.`

**SparC** Instead of mapping a single complex question into a SQL query, Yu et al. (2019b) decomposes the long question in Spider into a sequence of simpler questions that are conditioned together to study the text-to-SQL task in context.

**CoSQL** Yu et al. (2019a) collect 3k dialogues through Wizard-or-Oz, where a DB user and a SQL expert interact with each other to finish the query process. The SQL expert needs to compose SQLs, retrieve answers, clarify questions and inform unanswerable questions.

**Spider-DK** Gan et al. (2021b) study the text-to-SQL robustness against rarely observed domain knowledge, where they define five types of domain knowledge and manually incorporate them into Spider development set.

**ParaphraseBench** Utama et al. (2018) study model robustness against different linguistic variations in NLQ, including naive, syntactic, morphological, lexical, semantic and missing information. **XSP** Suhr et al. (2020) repurpose eight text-to-SQL datasets cross database semantic parsing by filtering out redundant or non-trivial examples. We select four of them that have a relatively large size and use the original **Restaurants** dataset (Tang and Mooney, 2000) instead, since it contains more novel SQL patterns.

**KaggleDBQA** Lee et al. (2021) introduce a text-to-SQL dataset with realistic databases from the Kaggle website, these databases have abbreviated and obscure column names.

**ACL-SQL** On top of ACL anthology dataset (Singh et al., 2018), Kaoshik et al. (2021) create ACL-SQL dataset that contain complex queries depending on up to five tables.

**SEOSS-Queries** Tomova et al. (2022) collect NLQs and SQLs from software engineering domain, then paraphrase with more variations.

**FIBEN** Sen et al. (2020) introduce a text-to-SQL benchmark from financial domain, the NLQs are typical analytical queries generated by BI experts. Compared to other text-to-SQL datasets, the number of tables per database schema is at least an order of magnitude larger.

### 2.2 Formatting

Although these 18 text-to-SQL datasets are publicly available, it's non-trivial to convert them into the same format. For example, one of the SQUALL example has SQL label like this: 'SELECT c1 FROM w ORDER BY c3\_number LIMIT 1', to make sure

Dataset	Domain	Size			Schema			NLQ			SQL		
		Train	Dev	Test	# DB	# Tables / DB	# Cols / Table	Unique NLQs	% of COL	% of VAL	Unique SQLs	Unique Patterns	Overlap w/ Spider
Spider	Misc.	7000	-	1034*	166	5.3	5.3	7990	49.1	95.8	4525	1009	100
WikiSQL	Wikipedia	56355	8421	15878	26531	1	7.3	80311	76	100	80175	556	4.3
SQUALL	Wikipedia	9069	-	2207*	1617	1.9	9.5	11218	26	78.4	9814	687	16.2
Spider-Syn	Misc.	7000	-	1034	166	5.3	5.3	7995	35	95.4	4514	1009	98.4
Criteria2SQL	Healthcare	1400	300	303	371	1	11.7	1902	32.2	66.3	1515	366	5.2
SparC	Misc.	9025	-	1203*	166	5.3	5.3	9161	50.4	96.2	8978	1385	67.6
CoSQL	Misc.	7343	-	1007*	178	5.4	5.4	8187	54.6	94.2	8004	1316	46.5
Spider-DK	Misc.	-	-	535	20	5.3	5.3	535	39.3	80.0	283	155	85.8
ParaphraseBench	Medical	-	-	342	1	1	8	57	75.9	92.2	56	42	47.6
Restaurants	Restaurant	-	-	309	1	3	4.3	125	0.5	81.6	23	16	0.0
XSP-Advising	Education	-	-	378	1	15	7.5	309	7.9	89.4	271	23	8.7
XSP-ATIS	Transportation	-	-	289	1	25	5.3	287	0.0	98.4	258	82	2.4
XSP-GeoQuery	Geography	-	-	532	1	7	4.3	532	23.3	98.1	363	75	22.7
XSP-IMDB	Entertainment	-	-	107	1	17	4	107	4.8	100	103	41	7.3
KaggleDBQA	Kaggle	-	-	272	8	2.1	11	272	29.0	80.2	249	120	50
ACL-SQL	ACL	-	-	491	1	13	2.2	465	37.0	97.5	445	56	21.4
SEOSS-Queries	Software	-	-	1162	1	13	6.2	1157	61.6	85.6	168	94	46.8
FIBEN	Finance	-	-	275	1	152	2.5	296	0.1	8.5	230	180	0.0

Table 1: Analysis of UNITE. # DB, # Tables / DB and # COLs / Table represent the number of databases, number of tables per database, and number of columns per table, respectively. For NLQ analysis, we measure the number of unique NLQs, the percentage of COLUMN mentions (% of COL), and CELL VALUE mentions (% of VAL) of the targeting SQLs. We also analyze SQL redundancy (unique SQLs and patterns) and novelty (extra new patterns introduced by measuring the overlap with Spider dataset). \* means original dev sets are used for test sets.

SQL target is aligned with natural language question, we recover SQL and database schema with the original column name and git rid of column variables (e.g. c1 and c3) for general purpose. Finally, We convert all databases into SQLite format and NLQ/SQL pairs into JSONL format to simplify the training and evaluation process. For each example, there are three fields: database identifier, question and SQL query. For database schema, we keep both original names and clean names for tables and columns, we also keep column type, primary keys and foreign keys, all of them are saved in JSON object.

### 2.3 Statistics and Analysis

Table 1 shows train/dev/test split of each dataset in our UNITE benchmark. To construct a cross-database setup, datasets with single database are used for test sets only. For the multi-database datasets, we follow the same split as the original work for fair comparison. Some datasets have no publicly available test sets, we use dev sets instead. The final benchmark has no database overlap between training and test set to satisfy the cross-database evaluation setup.

We give detailed statistics from three aspects to demonstrate the diversity and comprehensiveness of our UNITE benchmark:

**Schema** Spider related datasets (e.g. Spider-Syn, SparC, Spider-DK) have similar database structure, for example, each database has  $\sim 5$  tables and each

table has  $\sim 5$  columns on average. However, other databases are quite different, the table size ranges from 1 to 152, and the column size ranges from 2.5 to 11.7. These diversified schema will post new challenges for text-to-SQL systems.

**NLQ** Our benchmark contains various question types, such as *When*, *Who*, *What*, *How* and *Which*, and also statement questions, comparative questions, and Boolean questions. Additionally, ParaphraseBench introduce different paraphrase types. The explicit column mentions and cell value mentions in NLQs imply the easiness of producing the final SQL queries, since model can directly copy from NLQ to finish the column or cell value linking. These two measurements are distinct across different datasets, and some of them are even lower than Spider, showing the potential challenges of our UNITE benchmark.

**SQL** Compositional generalization is critical to text-to-SQL semantic parsing. To measure this aspect, our UNITE benchmark contains various SQL patterns. Traditionally, Spider dataset is widely used for model training and evaluation, however, the distinct pattern overlap ratio in the last column of Table 1 demonstrates the necessity of evaluating over a broader datasets. We also show SQL complexity measures in Appendix Table 3, our benchmark consists of SQLs from different levels, ranging from single-table single-column to multi-table multi-column.

Dataset	Codex		UL-20B	RASAT		SmBoP	T5-3B		PICARD		Prev.
	zero-shot	few-shot	Spider	Spider	UNITE	Spider	Spider	UNITE	Spider	UNITE	
Spider	73.4	72.7	77.4	76.5	75.9	78	74.4	74.9	<b>79.4</b>	78.4	80.5
WikiSQL	44.9	46.3	38.4	20.2	<b>84.8</b>	32.7	24.1	84.1	40.3	84.2	92.7
SQUALL	50.0	51.6	28.2	15.6	<b>71.4</b>	25.2	13	71.1	19.7	64.6	42.2
Spider-Syn	61.7	43.8	72.7	62.2	70.1	65.4	63.1	70.0	70.9	<b>74.0</b>	-
Criteria2SQL	0	0	5.8	0	<b>77.9</b>	0	0	68.0	0	62.3	20.7
SparC	41.9	40	41.9	39.7	45.4	<b>48.3</b>	40.2	45.1	41.4	47.1	73.3
CoSQL	21.7	56.2	21.0	52.4	<b>57.3</b>	25.8	20.7	21.5	21.8	22.7	67.0
<i>Out-of-domain</i>											
Spider-DK	<b>65.1</b>	63.0	62.8	55.5	60.2	59.1	57.4	58.9	62.6	62.1	-
ParaphraseBench	<b>88.3</b>	88.0	78.4	75.1	81.6	80.7	82.5	82.8	81.6	83.0	74.6
Restaurants	39.4	<b>51.1</b>	41.3	36.5	34.9	18.3	23.8	30.2	46.0	47.6	-
XSP-Advising	7.1	6.8	7.4	<b>11.7</b>	10.4	1.9	6.8	9.1	6.8	9.7	6.9
XSP-ATIS	1.4	<b>3.1</b>	1.4	0.7	0.7	0	0.7	0.7	2.1	1.7	5.5
XSP-GeoQuery	56.4	65.0	63.2	44.9	57.5	37.4	45.1	66.4	48.1	<b>68.2</b>	59.5
XSP-IMDB	37.4	<b>41.1</b>	24.3	24.3	26.2	18.7	21.5	6.5	28.0	7.5	37.1
KaggleDBQA	23.9	<b>40.4</b>	34.9	27.6	26.8	27.2	26.8	33.8	29.8	36.8	26.8
ACL-SQL	<b>69.7</b>	50.1	44.0	43.4	33.6	40.1	38.1	31.8	44.2	40.9	-
SEOSS-Queries	<b>64.5</b>	63.2	44.1	41.1	50.0	26.9	43.4	42.9	49.3	44.9	-
FIBEN	0	0	<b>28.4</b>	0.3	4.4	5.1	0	2.0	11.5	26.7	-
Average (overall)	41.5	43.5	39.7	34.9	<b>48.3</b>	32.8	32.3	44.4	38.0	47.9	-
Average (out-domain)	41.2	<b>42.9</b>	38.9	32.8	35.1	28.7	31.5	33.2	37.3	39.0	-

Table 2: Comparison of different state-of-the-art models on UNITE. The last column "Prev." reports execution accuracy from previous works (Qi et al., 2022; Xu et al., 2022; Shi et al., 2020; Yu et al., 2020; Deng et al., 2021). Columns *Spider* and *UNITE* represent models trained with Spider or UNITE, respectively. The *overall* average refers to all test sets in our benchmark, while the *out-domain* average considers datasets with test sets only.

## 2.4 Evaluation Metric

Our UNITE benchmark contains SQLs from different standards, ground truth SQLs may have different realizations. Following previous work (Yu et al., 2018; Suhr et al., 2020), we use execution accuracy to measure the correctness, which execute both predictions and ground truths over the underlying database and compare the execution results. We also filtered out some examples that have empty execution results and keep a relatively low ratio (e.g. < 5%), to accurately reflect denotation accuracy.

## 3 Experiments

We compare six state-of-the-art models in our experiments: **Codex** Chen et al. (2021), a 175B GPT model further fine-tuned on public code; **UL-20B** (Tay et al., 2022), a 20B Seq2Seq model pre-trained with mixture of denoisers; **T5-3B**, Shaw et al. (2021) showed competitive performance of T5-3B for text-to-SQL task; **RASAT**, Qi et al. (2022) further improved the T5-3B model by explicitly modeling the relationship between NLQs and schemas; **SmBoP** (Rubin and Berant, 2021), a semi-autoregressive bottom-up parser that generates SQL tree reversely from leaf nodes to root node; **PICARD** (Scholak et al., 2021), a constrained beam search decoding method that generates SQL sequentially and discards illegal gener-

ations with incremental parsing.

**Settings.** We report zero-shot and 3-shot performance for Codex, by following prompt design in Rajkumar et al. (2022). For other fine-tuning based models, we report performance with the original public checkpoints trained on Spider dataset<sup>2</sup>. We also re-train T5-3B and RASAT with our UNITE training set, which is a combination of the seven training sets in Table 1. We use codebase from previous works and keep hyperparameters unchanged.

### 3.1 Results and Analysis

Our main results are shown in Table 2. Firstly, these SOTA models have performance level 70%~80% for Spider, but below 50% on our UNITE benchmark on average. Thus the Spider benchmark is a poor proxy for evaluating real-world applications. Secondly, if we switch the training data from *Spider* to *UNITE*, we see consistent performance improvement from RASAT, T5-3B, and PICARD. This implies the necessity of more training instances for fine-tuning models. Thirdly, Codex — even without fine-tuning on any training data — achieves the best out-of-domain performance. This is remarkable because very large language models pretrained on text and code can achieve similar or even better performance than models fine-tuned on rich human

<sup>2</sup>UL-20B has no public checkpoint for text-to-SQL, we fine-tuned it with 7k training examples from Spider.

annotations. Other observations include:

**Codex is more robust to NLQ variations.** ParaphraseBench and SEOSS-Queries contain rich paraphrase variations, Codex performs better than fine-tuned models, we hypothesize that the improvements are attributed to (1) model size, i.e. Codex has 175B parameters, but others have at most 20B; and (2) learning paradigm, i.e. in-context learning ingests data in a more natural way and does not update model parameters.

**Codex zero-shot sometimes outperforms the few-shot setting.** Codex<sup>3</sup> zero-shot has a lower average score, but it outperforms few-shot on 8 out of 18 datasets. We hypothesize that prompt engineering or picking the correct exemplars is important to in-context model performance on out-of-domain data.

**Customized decoding is important for text-to-SQL generalization.** The PICARD model improves T5-3B model on 15 out of 22 datasets and increases both in-domain and out-domain performance. The SmBoP model, even with a smaller Grappa encoder than T5-3B, also shows advantage on some datasets, such as Spider, WikiSQL, SQUALL and SparC.

**Relation-aware self-attention further improves the Seq2Seq model.** Comparing T5-3B and RASAT, we can see the benefit of explicitly modeling the relational structures for schema linking and schema encoding, which is realized through self-attention mechanism in the pre-trained T5 model.

## 4 Conclusion

We proposed a UNITE benchmark to evaluate text-to-SQL in a realistic setting, which consists of 18 datasets that cover a broad range of databases, SQLs and NLQs, we compared six SOTA models systematically and analyzed their performance with regarding to model architecture and decoding strategies. We will make our benchmark publicly available to benefit the whole community.

## Limitations

UNITE is a not a multi-lingual text-to-SQL benchmark, we only consider English and may lose opportunities to other languages. In our experiments, we did not retrain UL-20B with UNITE training set because of limited compute resources, therefore we miss the best performance of fine-tuning based

<sup>3</sup>Note that Codex may have seen some of the evaluation sets via webscraping or GitHub during pretraining.

models. Since some models (e.g. Codex, UL-20B and SmBoP) are not designed for conversational text-to-SQL, to fairly compare all the SOTA models, we didn't consider conversation history in our experiments, therefore we see lower performance on SparC and CoSQL compared to previous works. Considering model size and limited compute, we don't run experiments with multiple seeds.

## Ethics Statement

Our benchmark experiments take extremely high amount of compute resources, which may not be environment-friendly. For example, UL-20B fine-tuning experiment needs 64 NVIDIA A100-SXM4-40GB GPUs for a total of 10 days training time. Our UNITE training set is 13 times larger than Spider, which can increase the training time and cause more CO2 emission, for example, T5-3B needs two more days to get converged in a single A100-SXM4-40GB GPU card.

## References

- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebggen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. 2021. [Evaluating large language models trained on code](#).
- Xiang Deng, Ahmed Hassan Awadallah, Christopher Meek, Oleksandr Polozov, Huan Sun, and Matthew Richardson. 2021. [Structure-grounded pretraining for text-to-SQL](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1337–1350, Online. Association for Computational Linguistics.
- Catherine Finegan-Dollak, Jonathan K. Kummerfeld, Li Zhang, Karthik Ramanathan, Sesh Sadasivam, Rui Zhang, and Dragomir Radev. 2018. [Improving text-to-SQL evaluation methodology](#). In *Proceedings of the 56th Annual Meeting of the Association for*

- Computational Linguistics (Volume 1: Long Papers)*, pages 351–360, Melbourne, Australia. Association for Computational Linguistics.
- Yujian Gan, Xinyun Chen, Qiuping Huang, Matthew Purver, John R. Woodward, Jinxia Xie, and Pengsheng Huang. 2021a. [Towards robustness of text-to-SQL models against synonym substitution](#). In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 2505–2515, Online. Association for Computational Linguistics.
- Yujian Gan, Xinyun Chen, and Matthew Purver. 2021b. [Exploring underexplored limitations of cross-domain text-to-SQL generalization](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 8926–8931, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Ronak Kaoshik, Rohit Patil, Prakash R, Shaurya Agarawal, Naman Jain, and Mayank Singh. 2021. [Acl-sql: Generating sql queries from natural language](#). In *8th ACM IKDD CODS and 26th COMAD, CODS COMAD 2021*, page 423, New York, NY, USA. Association for Computing Machinery.
- Chia-Hsuan Lee, Oleksandr Polozov, and Matthew Richardson. 2021. [KaggleDBQA: Realistic evaluation of text-to-SQL parsers](#). In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 2261–2273, Online. Association for Computational Linguistics.
- Panupong Pasupat and Percy Liang. 2015. [Compositional semantic parsing on semi-structured tables](#). In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1470–1480, Beijing, China. Association for Computational Linguistics.
- Jiexing Qi, Jingyao Tang, Ziwei He, Xiangpeng Wan, Yu Cheng, Chenghu Zhou, Xinbing Wang, Quanshi Zhang, and Zhouhan Lin. 2022. [Rasat: Integrating relational structures into pretrained seq2seq model for text-to-sql](#). *ArXiv*, abs/2205.06983.
- Nitarshan Rajkumar, Raymond Li, and Dzmitry Bahdanau. 2022. [Evaluating the text-to-sql capabilities of large language models](#).
- Ohad Rubin and Jonathan Berant. 2021. [SmBoP: Semi-autoregressive bottom-up semantic parsing](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 311–324, Online. Association for Computational Linguistics.
- Torsten Scholak, Nathan Schucher, and Dzmitry Bahdanau. 2021. [PICARD: Parsing incrementally for constrained auto-regressive decoding from language models](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 9895–9901, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Jaydeep Sen, Chuan Lei, Abdul Quamar, Fatma Özcan, Vasilis Efthymiou, Ayushi Dalmia, Greg Stager, Ashish Mittal, Diptikalyan Saha, and Karthik Sankaranarayanan. 2020. [Athena++: Natural language querying for complex nested sql queries](#). *Proc. VLDB Endow.*, 13(12):2747–2759.
- Peter Shaw, Ming-Wei Chang, Panupong Pasupat, and Kristina Toutanova. 2021. [Compositional generalization and natural language variation: Can a semantic parsing approach handle both?](#) In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 922–938, Online. Association for Computational Linguistics.
- Tianze Shi, Chen Zhao, Jordan Boyd-Graber, Hal Daumé III, and Lillian Lee. 2020. [On the potential of lexico-logical alignments for semantic parsing to SQL queries](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 1849–1864, Online. Association for Computational Linguistics.
- Mayank Singh, Pradeep Dogga, Sohan Patro, Dhiraj Barnwal, Ritam Dutt, Rajarshi Haldar, Pawan Goyal, and Animesh Mukherjee. 2018. [CL scholar: The ACL Anthology knowledge graph miner](#). In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Demonstrations*, pages 16–20, New Orleans, Louisiana. Association for Computational Linguistics.
- Alane Suhr, Ming-Wei Chang, Peter Shaw, and Kenton Lee. 2020. [Exploring unexplored generalization challenges for cross-database semantic parsing](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8372–8388, Online. Association for Computational Linguistics.
- Lappoon R. Tang and Raymond J. Mooney. 2000. [Automated construction of database interfaces: Integrating statistical and relational learning for semantic parsing](#). In *2000 Joint SIGDAT Conference on Empirical Methods in Natural Language Processing and Very Large Corpora*, pages 133–141, Hong Kong, China. Association for Computational Linguistics.
- Yi Tay, Mostafa Dehghani, Vinh Q. Tran, Xavier Garcia, Jason Wei, Xuezhi Wang, Hyung Won Chung, Dara Bahri, Tal Schuster, Huaixiu Steven Zheng, Denny Zhou, Neil Houlsby, and Donald Metzler. 2022. [U12: Unifying language learning paradigms](#).

- Mihaela Todorova Tomova, Martin Hofmann, and Patrick Mäder. 2022. [Seoss-queries - a software engineering dataset for text-to-sql and question answering tasks](#). *Data in Brief*, 42:108211.
- Prasetya Utama, Nathaniel Weir, Fuat Basik, Carsten Binnig, Ugur Cetintemel, Benjamin Hättasch, Amir Ilkhechi, Shekar Ramaswamy, and Arif Usta. 2018. [An end-to-end neural natural language interface for databases](#).
- Kuan Xu, Yongbo Wang, Yongliang Wang, Zihao Wang, Zujie Wen, and Yang Dong. 2022. [SeaD: End-to-end text-to-SQL generation with schema-aware denoising](#). In *Findings of the Association for Computational Linguistics: NAACL 2022*, pages 1845–1853, Seattle, United States. Association for Computational Linguistics.
- Tao Yu, Rui Zhang, Heyang Er, Suyi Li, Eric Xue, Bo Pang, Xi Victoria Lin, Yi Chern Tan, Tianze Shi, Zihan Li, Youxuan Jiang, Michihiro Yasunaga, Sungrok Shim, Tao Chen, Alexander Fabbri, Zifan Li, Luyao Chen, Yuwen Zhang, Shreya Dixit, Vincent Zhang, Caiming Xiong, Richard Socher, Walter Lasecki, and Dragomir Radev. 2019a. [CoSQL: A conversational text-to-SQL challenge towards cross-domain natural language interfaces to databases](#). In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 1962–1979, Hong Kong, China. Association for Computational Linguistics.
- Tao Yu, Rui Zhang, Kai Yang, Michihiro Yasunaga, Dongxu Wang, Zifan Li, James Ma, Irene Li, Qingning Yao, Shanelle Roman, Zilin Zhang, and Dragomir Radev. 2018. [Spider: A large-scale human-labeled dataset for complex and cross-domain semantic parsing and text-to-SQL task](#). In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3911–3921, Brussels, Belgium. Association for Computational Linguistics.
- Tao Yu, Rui Zhang, Michihiro Yasunaga, Yi Chern Tan, Xi Victoria Lin, Suyi Li, Heyang Er, Irene Li, Bo Pang, Tao Chen, Emily Ji, Shreya Dixit, David Proctor, Sungrok Shim, Jonathan Kraft, Vincent Zhang, Caiming Xiong, Richard Socher, and Dragomir Radev. 2019b. [SPaC: Cross-domain semantic parsing in context](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4511–4523, Florence, Italy. Association for Computational Linguistics.
- Xiaojing Yu, Tianlong Chen, Zhengjie Yu, Huiyu Li, Yang Yang, Xiaoqian Jiang, and Anxiao Jiang. 2020. [Dataset and enhanced model for eligibility criteria-to-SQL semantic parsing](#). In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 5829–5837, Marseille, France. European Language Resources Association.
- Victor Zhong, Caiming Xiong, and Richard Socher. 2017. [Seq2sql: Generating structured queries from natural language using reinforcement learning](#). *CoRR*, abs/1709.00103.

## A Appendix

Dataset	SQL			
	# JOINS / Query	Nesting Depth	Unique Patterns	# SQLs / Pattern
Spider	0.5	1.1	1009	8
WikiSQL	0	1	556	145.1
SQUALL	0.1	1.2	687	16.4
Spider-Syn	0.5	1.1	1009	8
Criteria2SQL	0	1	366	5.5
SparC	0.5	1.1	1385	7.4
CoSQL	0.4	1.1	1316	6.3
Spider-DK	0.6	1.1	155	3.5
ParaphraseBench	0	1	42	1.4
Restaurants	0	1.3	16	23.6
XSP-Advising	0.4	1.1	23	13.4
XSP-ATIS	0	1.1	82	3.5
XSP-GeoQuery	0.01	1.6	75	7.1
XSP-IMDB	0	1	41	2.6
KaggleDBQA	0.2	1.1	120	2.3
ACL-SQL	1.1	1	56	8.8
SEOSS-Queries	0.3	1.1	94	12.4
FIBEN	4.0	1.5	180	1.6

Table 3: SQL complexity (# JOINS per query and nesting depth) and redundancy (# SQLs per pattern) analysis on UNITE benchmark.

As shown in Table 3, our UNITE benchmark contains datasets that have more complex SQLs than Spider data, for example, FIBEN has four JOINS per SQL query, XSP-GeoQuery has 1.6 nesting depth<sup>4</sup>. We also have simple SQLs with only one table involved, such as WikiSQL, Criteria2SQL, ParaphraseBench, etc.

<sup>4</sup>The nesting depth is defined as Count of SELECT - (Count of INTERSECT + Count of EXCEPT).