

Bug-fixing

```
private void METHOD_1 ( int VAR_1 , int offset ) { switch ( VAR_1 ) { case 0 : this . VAR_2 = offset ; case 1 : this . VAR_3 = offset ; case INT_1 : this . VAR_4 = offset ; case INT_2 : this . VAR_5 = offset ; } }

private void METHOD_1 ( int VAR_1 , int offset ) { switch ( VAR_1 ) { case 0 : this . VAR_2 = offset ; break ; case 1 : this . VAR_3 = offset ; break ; case INT_1 : this . VAR_4 = offset ; break ; case INT_2 : this . VAR_5 = offset ; break ; } }

public void METHOD_1 ( final long [ ] data , boolean length ) { int VAR_1 = ( data . length ) * ( VAR_2 ) ; if ( length ) METHOD_2 ( VAR_1 ) ; METHOD_3 ( ( ( position ) + VAR_1 ) ) ; VAR_3 . METHOD_4 ( data , VAR_4 , null , ( ( VAR_5 ) + ( position ) ) , VAR_1 ) ; position += VAR_1 ; end = ( ( position ) > ( end ) ) ? position : end ; }

public void METHOD_1 ( final long [ ] data , boolean length ) { int VAR_1 = data . length ; if ( length ) METHOD_2 ( VAR_1 ) ; VAR_1 *= VAR_2 ; METHOD_3 ( ( ( position ) + VAR_1 ) ) ; VAR_3 . METHOD_4 ( data , VAR_4 , null , ( ( VAR_5 ) + ( position ) ) , VAR_1 ) ; position += VAR_1 ; end = ( ( position ) > ( end ) ) ? position : end ; }
```

Mutants generation

```
public int METHOD_1 ( int a ) { int index = VAR_1 [ ( a + 1 ) ] ; return VAR_2 . METHOD_2 ( index ) ; }

public int METHOD_1 ( int a ) { int index = VAR_1 [ a ] ; return VAR_2 . METHOD_2 ( index ) ; }

public java.lang.String METHOD_1 ( final java.lang.String VAR_1 ) { return STRING_1 . METHOD_2 ( VAR_2 . METHOD_3 ( ) . METHOD_4 ( ) ) ; }

public java.lang.String METHOD_1 ( final java.lang.String VAR_1 ) { return VAR_2 . METHOD_3 ( ) . METHOD_4 ( ) ; }
```

Generation of assert statements

```
// Test method
shouldNeverValidateNullUserIV ( ) { final uk . gov . gchq . gaffer . federatedstore . FederatedAccess access = new uk . gov . gchq . gaffer . federatedstore . FederatedAccess . Builder ( ) . addingUserId ( null ) . build ( ) ; "<AssertPlaceholder>" ; }

// Focal method
isValidToExecute ( uk . gov . gchq . gaffer . user . User ) { return ( isPublic ) || ( ( null != user ) && ( ( isAddingUser ( user ) ) || ( ( ! ( isAuthsNullOrEmpty ( ) ) ) && ( isUserHasASharedAuth ( user ) ) ) ) ) ; }

org . junit . Assert . assertFalse ( access . isValidToExecute ( null ) )

// Test method
testClone ( ) { org . apache . flink . api . common . accumulators . DoubleMinimum min = new org . apache . flink . api . common . accumulators . DoubleMinimum ( ) ; double value = 3.14159265359 ; min . add ( value ) ; org . apache . flink . api . common . accumulators . DoubleMinimum clone = min . clone ( ) ; "<AssertPlaceholder>" ; }

// Focal method
getLocalValue ( ) { return null ; }

org . junit . Assert . assertEquals ( value , clone . getLocalValue ( ) , 0.0 )
```

Code summarization

```
public void update() { check Widget ( ) ; Utils . paintComponentImmediately ( handle ) ; update ( false ) ; }

forces all outstanding paint requests for the widget

public void setWordWrap(int row, int column, boolean wrap) { prepareCell ( row , column ) ; String wrapValue = wrap ? "" : "nowrap" ; DOM . setStyleAttribute ( getElement ( row, column ) , "whiteSpace" , wrapValue ) ; }

sets whether the specified cell will allow word wrapping of its contents
```

Wrong but meaningful predictions for the code summarization task

```
testCase getTestCase ( String implementationNumber ) int index = Integer . valueOf ( implementationNumber ) ; int value = return getTestCase ( index ) ;
return the specific test case
returns the test case with the given implementation number

protected void doConfigure(HierarchicalConfiguration config) throws ConfigurationException {}

override to handle config
subclasses can override this method to perform custom configuration
```