

INPUT1

```
public static boolean METHOD_1<MASK_1>.io.File file<MASK_2>
    throws TYPE_1 {
    try<MASK_3>
    java.util.Scanner VAR_1 = new java.util.Scanner(file);
    while ( VAR_1 . METHOD_2 ( ) ) {
        java.lang.String VAR_2 = VAR_1.METHOD_3().trim<MASK_4>);
        <MASK_5> ( ( VAR_2<MASK_6>() ) ) > 1 )
        {
            return<MASK_7>.startsWith<MASK_8>STRING_1);
            <MASK_9>
        }
    }
    ...
}
```

TARGET

<MASK_1> = ‘(java’<MASK_2> = ‘)’<MASK_3> = ‘{’

<MASK_4> = ‘(’<MASK_5> = ‘if’<MASK_6> = ‘.length’

<MASK_7> = ‘VAR_2’<MASK_8> = ‘(’<MASK_9> = ‘}’

INPUT2

```
public void setVariables (java.util.Map<MASK_1>.lang.Integer,
    java.lang<MASK_2> Object> data)
{
    for (<MASK_3>.util.<MASK_4>.Entry <MASK_5>.
        lang.<MASK_6>, java.<MASK_7>Object> entry:
            data<MASK_8> entrySet())
        {

            <MASK_9>.setVariable(entry.getKey(), entry<MASK_10>());
        }
    binding.executePendingBindings();
}
```

TARGET

<MASK_1> = ‘java’<MASK_2> = ‘.’<MASK_3> = ‘java’

<MASK_4> = ‘Map’<MASK_5> = ‘java’<MASK_6> = ‘Integer’

<MASK_7> = ‘lang.’<MASK_8> = ‘.’<MASK_9> = ‘binding’

INPUT3

Creates new default rows for table for clearing <MASK_1> existing <MASK_2> first

TARGET

<MASK_1> = ‘any’<MASK_2> = ‘rows’