

EUROPEAN ORGANIZATION FOR NUCLEAR RESEARCH
ORGANISATION EUROPEENNE POUR LA RECHERCHE NUCLEAIRE

CERN - PS DIVISION

PS/ PA/ Note 96-06 (PPC)

PROCEEDINGS OF THE PS PERFORMANCE DAY (PPD '96)

Edited by D. Manglunki

Abstract

The PS Performance Day, organised by the PS Performance Committee, was held in Chavannes-de-Bogis, Vaud, Switzerland on 16 February 1996. The first two sessions covered the beam performance of all the machines of the PS complex in 1995, their expected performance and their required machine study periods in 1996. The third session was devoted to the new developments and projects under way in the PS division, in view of the short- (generalisation of the ABS, new antiproton deceleration dedicated facility), medium- (LHC beams, laser ion source), and long- (CLIC) term future. The last session consisted of short summaries underlining, for each group of machines, the current issues facing the specialists in charge.

PS Performance Day (PPD '96) held in Chavannes-de-Bogis (Vaud, Switzerland), on February 16th 1996

Geneva, Switzerland
15 March 1996

Index

Topic	Speaker	Page
PS complex performance in 1995	J.Boillot	7
LPI evolution and MDs	J.P.Potier	21
Ion source and Linac 3 evolution and MDs	Ch.Hill	31
Ion MDs in PS	Dj.Manglunki	37
PSB evolution and MDs	K.Schindl	47
Status of ABS in the PS Complex	B.Autin	55
PS dynamic aperture for LHC beam	R.Cappi	69
CT 5 turn improvements	M.Martini	79
Fast ejection of e+ in SS61	J.P.Riunaud	87
LEAR MD with ions	G.Tranquille	93
Antiproton deceleration tests in AC	F.Pedersen	107
East Hall New Look	J.Y.Hémery	115
Laser ion source developments	H.Kugler	123
CTF95 and CTF2	H.Braun	139
Linac 2 & 3 summaries	M.Vretenar	153
PSB summary	K.Schindl	159
LPI summary	J.P.Potier	163
AAC summary	C.Metzger	169
LEAR summary	M.Chanel	173
PS summary	R.Cappi	181
Closing address	D.J.Simon	187

PS Performance Day 1996

PS Complex performance in 1995

Jean BOILLOT

Abstract

In 1995, the running time of the PS Complex exceeded 6680 hours with an overall beam availability better than during the previous years: about 92% for the different beams delivered to SPS and LEP, 94% for the ISOLDE beam and 87% for the antiproton beams serving the LEAR experiments.

The lepton beams ran well with a good regularity. The 2 lepton cycles were advanced to the 9th and 10th slots of the PS supercycle. This interesting improvement allowed better flexibility for machine developments and operations.

After various optimisations carried out on the Linac2, Booster and PS, good results were obtained with the intensity delivered to SPS fixed target physics reaching 2.3 to 2.5 10^{13} protons per PS cycle, intensity which was maintained during the 2 physics runs.


The proton intensity for ISOLDE very often reached 2.9 to 3 10^{13} protons per pulse. ISOLDE also worked at low intensity for several experiments and used for the first time the staggered extraction of 3 Booster rings.

The East Hall test experiments ran during 25 weeks with the classical PS slow extraction of protons at 24 GeV/c. (about 1.1 10^6 spills shared between 40 physics groups)


After a careful commissioning with Pb ions of Linac3, PSB and PS the operational run was very successful for these beams serving SPS fixed target physics for the second year. An average of 1.7 10^{10} charges of Pb⁸²⁺ per cycle was currently provided for SPS.

AAC worked well over this year with an average stacking efficiency of 79% and a good availability for physics (97.5%).

LEAR ran for 11 different experiments with a record of 4196 spills delivered for physics and a total intensity of 2.2 10^{13} antiprotons injected in the machine. Unfortunately, the average transfer efficiency from AAC to LEAR went down to 61% due to numerous problems affecting AAC, PS and LEAR. Nevertheless a very effective improvement was carried out in order to compensate the non-understood instabilities at 200 MeV/c. Another good performance was achieved in LEAR with a spill duration of 14 hours at 310 MeV/c.




PS Complex fault rates
 Hadrons (ions & protons) for SPS & Leptons for SPS/LEP




Antiproton beam for South hall Experiments - Fault rates

(statistics calculated for the main user)



**PS Complex total particle intensity extracted
from PSB for SPS fixed target physics**


E18 protons
E15 Pb53+ ions




1995-PS Complex - Proton beam for SPS


Average intensity per PSB + PS cycle

E12 protons






1995 - Proton Beam for ISOLDE -
Average intensity per PSB cycle and per 24 hrs




1995 - PS Complex - Pbar production beam for AAC
 Average intensity per PS cycle and per 24 hrs


E12 protons



Pbar transfer and stacking efficiencies




1986 -1995 - LEAR running statistics



LEAR Operation efficiency

Number of spills used by physics / number of LEAR fillings



PS Performance Day 1996

LPI evolution and MDs

Jean-Pierre POTIER

Abstract

The LEP Injector Linac (LIL) produced its first beam 10 years ago. Since then it has had a large evolution aimed at reducing its complexity and improving its reliability. The LIL beam is also used as an LHC beam simulator, as it has the same characteristics as the latter, for what concerns synchrotron radiation.

LPI PPDAY96

J.Clendenin, J.P.Potter

Summary of the contribution, complementary information to the attached transparencies.

The LPI 10 years after its first beam

LIL (LEP Injector Linacs) part of the LPI (LEP Pre Injector, i.e. the lepton source for LEP) produced its first beam 10 years ago (November 22, 1985). Since that time, it has had a large evolution aimed at reducing, its complexity and improving its reliability. In figure 1, these changes as well as the design, achieved and operational performances are summarised.

LPI fault rate over the last five years

Since 1991 the LPI fault rate has dropped monotonically from 7.9 % to 3.3 % , if we exclude 1994 where the klystron modulator 13 gave a lot of stops, during the LEP production runs (see figure 2 top graph). In parallel, the overall number of stops dropped from 800 per year to 470 (figure 2 middle graph). If we remove the stops < 10 min (fixed without specialist intervention) the MTBF rises to an annual average of 22h (figure 2 bottom) and as high as 72h during the last run thanks to the efforts of the different systems responsible.

Simplifications of LIL RF powering

MDK03 withdraw

In figure 3 top, where the LIL RF network is shown, it can be seen that KLY-03 which powers the bunching system, is run at a very low level, 3.0 MW for a 35 MW klystron, and could be replaced by a power derivation from KLY-13.

As the buncher is a resonant cavity, its behavior, when it is powered by a LIPS (power pulse compressor), which produces an RF wave with a

sharp peak, was not known. An experiment (figure 3 bottom left) was setup. It was found that its behavior was satisfactory and a power coupler was installed during December 95 for tests (figure 3 bottom right) to connect the buncher to klystron 13. The results which are satisfactory, are summarised in table 1, top. In 96, LIL will be run in these conditions.

Towards MDK35 withdraw ?

Pushing further the considerations above, it can be seen that increasing the power of klystrons 25, 27 and 31 (from 15.4 MW to 21.8 MW) allows one to stop klystron 35. This situation was tested during December 95, showed a lower positron production rate. Then some tuning work will have to be done on the positron production in order to recover to the usual production rates.

LHC Irradiations

(LHC vacuum team, information provided by V.Baglin)

In LHC the pressure inside the beam pipe will be essentially dominated by photo-desorption since thermal desorption of all gases except He will be very small at the beam screen temperature (between 5 to 20 dg K). At 308 MeV with leptons, the critical energy of the synchrotron light emitted in EPA is the same as in LHC with protons at flat top energy. In order to test the behavior of the future beam screen of LHC, at 2K, a cryostat, with a test sample, has been installed in the EPA tunnel at the output of HR.BHZ91, on a light port. At this momentum, the LPI can be run with $45E10$ electrons in 8 bunches circulating.

The phenomena to be evaluated are mainly:

Primary photo-desorption: photo-desorption due to tightly bounded gas molecules which are desorbed by the photons from the near oxide surface. It constitutes a source of gas

Recycling photo-desorption: photo-desorption of weakly bound gas molecules phisorbed (cryopumped) on the cold surface. This coefficient could be much larger than the primary one.

Apparatus

It is shown in figure 4.

1995 experiments

- Calibrations
- Long irradiations run at 4.2 K (figure 5 top): The rapid increase is followed by a slow increase due to the recycling effect and partially by a vapor pressure change. The increase of the base pressure when the irradiation is off may be due to the increase of the H₂ surface coverage and hence vapor pressure on the cold non-irradiated areas of the sample.
- Primary photo-desorption yields (see figure 5 bottom) versus temperature.

This work is the subject of a thesis (V.Baglin)






Figure 1

Evolution of the LPI fault rate since 91

Evolution of LPI fault rate in %



Evolution of the number of stops in the LPI > 10 mn or < 10 mn (in 1991 classification of stops length not available)



Yearly values of the evolution of the mean time between stops and of the mean time between interventions (>10 mn) on the LPI in hours







Figure 2

LIL with the buncher powered from LIPS13

/J.Clendenin, J.P.Potier, G.Rossat



End 94 and early 95 tests Buncher fed by LIPS13 through an amplifier and MDK03

December 95 setup and planned 96 startup: Buncher fed by LIPS13

LIL with the buncher powered from LIPS13

J.J.Clendenin, J.P.Potier, G.Rossat

Beam momentum at buncher exit

No absolute measurements done (no spectrometer available). Relative measurements have been done using a vertical dipole in the front end showing an energy gain in the LIPS13 configuration equivalent to 3 MW applied from MDK03 => OK.

Transmission and conversion efficiencies

Buncher powered by MDK03 or from LIPS13

	Operational values in 95	24 MW end 95 tests	18 MW end 95 tests
Bunching %	50 to 60	55 to 57	52
LIL transmission in %	75 to 85	70 to 78	75
Number of e- on the converter target	1.75 E11	1.75 E11	1.46 E11
LILV momentum MeV	205	200	171
Conversion e+/e- in %	0.45 to 0.52	0.47 to 0.51	0.41
Normalised yield e+/(e-*GeV) in %	2.2 to 2.5	2.3 to 2.5	2.4

Conclusion:

Powering of the bunching system from LIPS13 gives results similar to the usual MDK03 powering, future tests will be done with EPA accumulation

Towards MDK 35 stop ?

1996 planned setting

PB and Buncher fed from LIPS13 with 180 dg phase inversion, No LIPS 25

9.3 MV/m e+ trapping field in ACS 25 (same as 95 runs)

High power in MDK27, e+ production reduced by 5%

Planned 96 operation	Unit	MDK13	MDK25	MDK27	MDK31	MDK35	Sum
MDK in production/ dummy				Yes			
Calibration	Mev/ MW ^{0.5}	42.75	21.24	45.00	45.00	21.24	
Energy gain	MeV	209.43	83.35	209.43	154.36	72.86	520.00
Klystron power	MW	24.00	15.40	21.66	11.77	11.77	

Possible setting with MDK35 OFF

PB +B fed from LIPS13 with 180 dg phase inversion No LIPS 25

Av gain and e+ trapping in ACS 25 = 11.3 MV/m (in 95 9.3 MV/m)


Stop of MDK35 ?	Unit	MDK13	MDK25	MDK27	MDK31	Sum
MDK in production/ dummy				Yes		
Calibration	Mev /MW ^{0.5}	41.85	21.24	45.00	45.00	
Energy gain	MeV	210.36	99.29	210.36	210.36	520.00
Klystron power	MW	25.26	21.85	21.85	21.85	

First tests without MDK35 (and MDK03) performed end December 95:

Low production of e+ which needs to be optimised (perturbations by the field imperfections of the solenoid following the converter target).

Studies planned in 96 on positron production and beam optics consequences of the faster acceleration

Table 1



Thermal screen at 77 K
 only when liquid He is in the cryostat

Control volume with injection line

Figure 4





Figure 5

PS Performance Day 1996

Ion source and Linac 3 evolution and MDs

Charles HILL

Abstract

Following the 1994 lead ion run, time was available during the first part of 1995 to consolidate the new heavy ion linac. Apart from hardware improvements, studies were carried out not only on the ion source but also on the machine itself. The results of these tests are presented together with an initial idea of the tests that would be of interest in the near future. Some of the results presented were beneficial to the machine performance during the 1995 ion run and others indicated where limits to the present performance exist.

Naturally, certain experiments were focused on the future when the heavy ion injector will be coupled to the LEAR machine for LHC.

SOURCE


Extraction Gap

Following the 1994 period, the source was reoptimised on Pb 27+ to see what were the limits for analysed current at the Faraday cup. A special optic with extra secondary electron suppression is needed in the LEBT which is not compatible with operation.

Tests were performed with some optimisation on a small number of extraction gaps to see the influence on the beam. Computer simulations of the extraction will be needed to continue these tests a) to see the effect on the emittance, b) to reduce the number of vacuum breaks, and c) to set limits for a variable extraction.

There were indications that for a short (LEAR) beam more could be gained than for a long (PSB) beam but stability needs checking.

**Evolution of Extracted Current
with Extraction Gap at 2.5 keV/u
for Pb27+**



Other Ions

Ion	Extraction kV	keV/u	I μ A	Notes
40 A 8+	13.8	2.76	210	optimised for 8+
40 A 9+	12.3	2.76	120	optimised for 8+
40 A 9+	12.3	2.76	150	optimised for 9+
40 A 8+	13.8	2.76	175	optimised for 9+
40 A 9+	20	4.5	220	not optimised
84 Kr 18+	12.5	2.68	20 (equ 40)	Source failure *
16 O 4+	20	5	520	
16 O 6+	20	7.5	530	
16 O 8+	20	10	15	
4 He 2+	20	10	1300	100 μ s flat top
4 He 1+	20	5	1000 - 1200	Quasi CW

* Test failed before full optimisation due to HT failure - Metalisation of extraction insulator.

Lower Limit for extraction HT 13 kV unless extraction mechanically optimised for new species. This requires a vacuum break. Source has space charge limited diode characteristics (at least in operating range), i.e. extracted current increases with voltage. (Maximum HT 25 kV)

Gas Mixing


Follow up ideas of Shirkov that the addition of Neon to discharge should increase yield of Lead 27+.

a) Tests for Pb 27+

A test in 1994 indicated that the replacement of oxygen by neon led to a steady reduction of the extracted lead current as the oxygen was eliminated from the source. In 1995, this test was repeated with an oxygen/neon mixture.

As compared to 120 μ A in normal operation, with neon the current fell to 70 μ A. Increasing the percentage of oxygen increased the Pb current until full current was attained without neon.

b) Test for Charge State



Charge state distributions during the afterglow for:-a) Normal oxygen operation and b) Oxygen and neon as plasma gas

In this test the source was tuned for maximum charge state with neon. Spectra were obtained for peak charge states up to Pb 32+ seeming to confirm theory. However, it proved possible to obtain similar performance without neon!

Future Tests

The following tests are envisaged to increase the yield of the source:-

- Biased electrode in plasma chamber (RF co-axial feed).
- Higher magnetic fields for axial confinement.
- Plasma chamber coatings or liners.
- Other extraction gaps derived from computer simulations (variable extraction ?)
- Other ions (feedback from physics needed)
- Optimisation of short (LEAR) beams

LINAC 3

Linac Structure Tests


Installation and setting up of definitive 101 MHz amplifier for Tank 1 with full measurement of beam characteristics at 1.86 MeV/u using the Bunch Length and Velocity Detector. This, and the repetition of BLVD measurements on the output of the two remaining tanks, resulted in the establishment of a new RF working point for Tank 3 which allowed a reduction of RF power by 10% (and less X-rays).

At the request of GSI, a test was performed to examine the acceleration field limits of Tank 2. Up to 550 kW (limited by amplifier) was injected into the tank which would correspond to an average accelerating gradient of 7.7 MV/m (6.1 MV/m nominal at 346 kW).

Energy Variations

MD1. Investigation of the working point in Tank 3 showed that it was possible to vary the output energy by 140 keV/u (3%) by the correct choice of RF levels and tuner positions. This should be of help in adapting the linac energy for stripper foil thickness variations (and also for optimising Pb 54+).

MD2. In anticipation of LEAR demands for a ramped energy of ± 25 keV/u over 50 μ s the effects of debuncher amplitude and phase on beam energy and energy spread were studied. These indicated that, in the present static case, varying the debuncher phase by $\pm 60^\circ$ with respect to the nominal setting would provide the requested change.



Beams

Development continued on the Pb 53+ beam for PSB in collaboration with colleagues from PSB. This was mainly limited to fine tuning of Linac and transfer parameters for operation.

With colleagues from LEAR, set up and provided beams of Pb 52+, 53+, 54+, 55+ for their cooling experiments.

Future Plans

- a) Continue power tests for GSI in Tank 2 up to 1 MW.
- b) Repeat fine tuning tests on the RFQ with its final 101 MHz amplifier.
- c) Is it possible to modify the optic around the stripper to gain in horizontal emittance at the expense of vertical? Does this help the stripper?
- d) Recommence the testing of the Phase Probes.
- e) Accelerate Pb 25+ in the machine (design particle).
- f) Accelerate O 2+ in the machine to simulate beam loading.
- g) Emittance studies.
- h) Continue studies on energy ramping.

PS Performance Day 1996

Ion MDs in the PS

Django MANGLUNKI

Abstract

Many hours of MD were devoted in 1995 to the preparation of the autumn ion run, in collaboration with the SPS teams. Several "test beams" of protons and ions - fully or partially stripped - at various energies, emittances and intensities were set up to perform measurements, cross-checks and instrumentation calibrations in both rings and in the transfer lines. A special session was devoted to the measurement of energy straggling, stripping efficiency and emittance blow-up in the stripper foil, in order to determine the optimum stripper thickness.

Lead Ion MDs in the PS

D.Manglunki, 16/2/96

- GL.Arduini/SL, H.Burkhardt/SL, R.Cappi/PS, M.Martini/PS ...
- PS machine modifications
- Test beams
- Bunch rotation
- Scraping
- Stripping
- Performances in 1995
- Prospects for 1996

PS Machine modifications

- Recabling of beam control
 - Transparent to OP (not to RF)
- Control system
 - 24 users
 - NAOS
 - Too few access points made parasitic MDs very difficult
- Bdot regulation of Main Power Supply
 - Better energy reproducibility
 - No PFWs for ions
- Temperature tests

$$\frac{\Delta p}{p} = \frac{1}{\alpha} \frac{\Delta R}{R}$$

Test beams

- P+ 20 GeV/c for PS (simulate Pb⁵³⁺)
- P+ 13 GeV/c for SPS (simulate Pb⁸²⁺)
 - Good agreement in PS/TT2/TT10/SPS for ϵ_H and ϵ_V
 - PS-TRA379 97% ; TRA379-SPS 94% ; PS-SPS 91%
- Unstripped Pb⁵³⁺
 - No Blow-up PS-SPS
 - PS-SPS transmission 93%
- Small longitudinal emittance at low intensity
 - longitudinal acceptance reduction

Bunch rotation

- Longer bunches for smaller $\Delta p/p$
- Voltage reduction (200 kV \rightarrow 20 kV)
- Bunch length = 6 ns \rightarrow 18 ns
- $\Delta p/p = 0.8 \text{ E-3} \rightarrow 0.3 \text{ E-3}$
- Kept in operation

Scraping

- Use of “measurement targets” before extraction
- Reduce emittances
 - for PS/SPS transmission tests
 - Down to $\epsilon_H = 0.8 \pi \text{ mm.mrad}$; $\epsilon_V = 0.9 \pi \text{ mm.mrad}$
- Not used for operation

Stripping




- Energy loss
 - 0.35% / mm
- Emittance blow-up
 - $0.75 \pi \text{ mm mrad} / \text{mm}$ in Horizontal plane
 - $0.6 \pi \text{ mm mrad} / \text{mm}$ in Vertical plane
- Stripping “efficiency” (ratio of Pb^{82+})
 - 95% for 0.8mm
 - 100% for 1mm
- 0.8 mm
 - “Best compromise”
 - will be kept for operation in 1996 (or shall we keep 1mm?)

Performances in 1995

- $N > 1.5 \times 10^{10}$ charges of Pb^{82+}/PS pulse
- $\epsilon_H = 1.8 \pi$ mm.mrad
- $\epsilon_V = 1.5 \pi$ mm.mrad
- $\tau_B = 18$ ns
- $\Delta p/p = 0.3 \times 10^{-3}$

Prospects for 1996

- Instrumentation upgrade in 1996
 - MRP
- SMH42 in ppm in 1996
 - will allow better injection -> smaller H emittances
- Control system
 - Extraction will be part of control system
 - SPS ion request
 - NAOS
 - Varilog fully in operation



HARDSETTING

COUNTER: DC
 SLEW: 0.158
 PA: 012
 100000
 100000
 100000
 PA: PAS
 S: 1000
 TRIGGER: 2.00 V
 S: 1000
 SIGNAL OFFSET: 93.750 mV

MAIN PANEL FOR SCREEN B

In ~~IR~~ In
 Gb ~~IR~~ Gb
 Gb ~~IR~~ Gb
 Tools: ~~IR~~ ~~IR~~ ~~IR~~ ~~IR~~
 Vantage: ~~IR~~ ~~IR~~ ~~IR~~
 SYSTEM: ~~IR~~ ~~IR~~ ~~IR~~

MAIN PANEL FOR SCREEN C

In ~~IR~~ In
 Gb ~~IR~~ Gb
 Gb ~~IR~~ Gb
 Tools: ~~IR~~ ~~IR~~ ~~IR~~ ~~IR~~
 Vantage: ~~IR~~ ~~IR~~ ~~IR~~
 SYSTEM: ~~IR~~ ~~IR~~ ~~IR~~

CH1: PA-C10VDETSU-H20
 Tr1: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV
 CH2: PA-C10VDETSU-H20
 Tr2: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV
 CH3: PA-C10VDETSU-H20
 Tr3: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV
 CH4: PA-C10VDETSU-H20
 Tr4: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV

CH5: PA-C10VDETSU-H20
 Tr5: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV
 CH6: PA-C10VDETSU-H20
 Tr6: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV
 CH7: PA-C10VDETSU-H20
 Tr7: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV
 CH8: PA-C10VDETSU-H20
 Tr8: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV

CH9: PA-C10VDETSU-H20
 Tr9: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV
 CH10: PA-C10VDETSU-H20
 Tr10: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV
 CH11: PA-C10VDETSU-H20
 Tr11: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV
 CH12: PA-C10VDETSU-H20
 Tr12: PX-042 Left +
 100 ms/div -46.000 ms
 500 mV/div -93.750 mV




Message Area.

Message Area.

Message Area.

Pls: MDION PX.ASG02 1 - PR.DCBEFEJE 1.1E10 Dec 12 10:23:11 1995

c(20) 1.037100M 1.030E-3




Rest Position | Single Shot | Unfreeze | Run Math

Programme in pause !!!


Trigger : Train C
Train C : 730
Acq Train C: 730
Train RF/H : 572
Acq RF: 572

DELAY : 80 ns
Vertical Scale
10 mVolts/div



One SHOT Multi SHOT Stop SHOT
Message Area

ZOOM IN ZOOM OUT Bunch length Undo Zoom



3034.0
Date: Mon Dec 11 15:45:13 1995 Time base: 2.0ns/DIV Vert. Scale: 0.010V/DIV

Trigger : Train C
Train C : 715
Acq Train C: 715
Train RF/H : 2
Acq RF: 2

DELAY : 80 ns


Vertical Scale
10 mVolts/div

One SHOT Multi SHOT Stop SHOT Length bunch : 6.4 ns

Message Area

19.2 sec. duration -

PS SUPERCYCLE



particle	pbar											
PS Energy (GeV/c)	20	20	20	20	26	3.5	13	26	24	3.5	3.5	13
user	SPS	SPS	SPS	SPS	AAC	LEAR	Pb simul	AAC	EAST HALL	SPS LEP	SPS LEP	Pb simul ZERO
intensity	1.1E+10	1.1E+10	1.1E+10	1.1E+10	1.6E+13	2.1E+09	1E+12	1.6E+13	3.5E+11	2.5E+11	2.5E+11	1E+12
PSB user & intensity					ISOLDE 2.9E+13	ISOLDE 2.9E+13		ISOLDE 2.9E+13	ISOLDE 2.9E+13	ISOLDE 2.9E+13	ISOLDE 2.9E+13	ISOLDE 2.9E+13

PS Performance Day 1996

PSB evolution and MDs

Karlheinz SCHINDL

Abstract

The most demanding PSB beam is the one for ISOLDE who are regularly requesting proton intensities of up to $3 \cdot 10^{13}$ p/pulse. While these levels have been often attained, the concomitant beam losses at high energy remain a major issue, as they are causing increased machine irradiation and personnel doses. These losses are mainly due to longitudinal coupled-bunch modes and possibly microwave instabilities (ring 4) which are being investigated.

The Pb beam intensity produced by the PSB ($1.5 - 2 \cdot 10^{10}$ charges per cycle) exceeds the design figure ($1.2 \cdot 10^{10}$ charges). Nevertheless, MD's to analyse performance limitations, as well as close monitoring of the very critical vacuum system, were performed. It was found that loss rates for Pb^{53+} and Pb^{54+} do not differ, whereas the beam is lost much faster in ring 3 than in the others.

The ISOLDE line transports $\sim 10^{13}$ p/sec, but beam diagnostics is far from adapted to this level. A crash programme for adding monitors (PU, current transformers, SEMs, also in view of using ABS) and more work on the optics is required. The staggered beam extraction, seemingly the only way to enable liquid targets to stand the shock wave generated by $>10^{13}$ p/pulse, was further studied and should be rendered operational as soon as possible.

PSB High Intensity Proton Beams 1995 (ISOLDE, SFT, AA)

Problem	MD results and/or actions	Comments
Beam loss - low energy (multiturn, capture, stopbands)	Frequent readjustments of injection, frequent readjustment of beam control h=5,10	not very relevant for machine irradiation, but limits performance
Beam loss - high energy (coherent instabilities, extraction losses)	Repeated readjustments of long. coupled-bunch mode damping system, Frequent readjustment of voltage/phase of h=5 and h=10 cavities, Increase of ejection kicker by 10% to 36 kV Main contributor to loss (on BLM's): ring 4. <ul style="list-style-type: none"> • instability 1 (at 320 ms): long. μ-wave, spill-out of bucket • instability 2 (at 360 ms): almost disappears with $\xi_v \sim 0$ (vertical high-frequency?) 	Main reason for machine irradiation irradiation around ejection septum down by factor 3 lost vertically because of ξ_v -1.8
Annual collective doses 1995	Still increasing	frequent ring interventions
"Sabotage" of PS (and PSB) RF, beam control	Production beam with 2 rings until 8/95, four rings with funnelling (RF dipole) afterwards	marked increase of intensity with 4 rings

nevertheless, PSB intensity regularly between 2.7 and 3 10^{13} p/p (ISOLDE)

PPD 16.2.96, K.Schindl

PSB - General Issues 1995 (and '96)

Problem	Actions, MD results	Comments
Linac LBS spectrometer: measurement of mean momentum <p>	spectrometer magnet equipped with NMR => to monitor changes in <p>	marked improvement
$\Delta p/p$ measurement of injected beam by long. BTFM	compares rather well to $\Delta p/p$ measured in LBS	soon operational?
PS stray field deflects beams from both linacs	improve shielding	<i>PS subvention '96</i>
B-train: jitter several G, resolution 1 G, insufficient for digital beam control (ions, future $h=1$, $h=2$)	2 NMR installed in ref. magnet, new B-train envisaged (1 G jitter, 0.1 G resolution)	<i>PS subvention '96</i>
Shaver dipoles: pulsed power supplies unreliable (used for PHY, MD, TST, maybe LHC)	new supplies to be built	<i>PS subvention '96</i>
Deviation control/acquisition of Q-tuning supplies	supplies improved during 1995	new supplies (LHC)

PSB for LHC 1995

Problem	Action and/or MD	Comments
Beam profile measurement device (for LHC beam)	spare wire scanner being installed in ring 1	lowest energy?
Increase of PSB energy 1 to 1.4 GeV (Bdl +26%)	longer 20° magnet BTM.BHZ10 being installed (beam to measuring line and ISOLDE)	modified optics for ML, ISOLDE
Q-measurement by kicking the beam	hopefully available soon (not only for LHC!)	
PSB-PS recombination + transfer beam steering	ABS helps pinning down inconsistencies	analysis of geometry

PPD 16.2.96 K.Schindl


PSB - Pb Ions 1995

Problem	MD results and/or actions	Comments
Intensity per PSB cycle	Max. 2 10^{10} charges Pb^{53+} achieved, although linac3 22...25 μA	not really better than 94
Injection line steering (with scintill. screens) (alignment different under vacuum?)	attempts to invert experimental steering matrices with limited success	SEM upstream Pb distrib. required
Setting-up of RF trapping tedious	control code to be written	
Pb ion - rest gas interaction	<ul style="list-style-type: none"> • continuous battle for better vacuum • lifetime (at injection energy 4.2 MeV/u) 2x worse in ring 3 than in the others • lifetime (at injection) of Pb^{53+} same as Pb^{54+} 	many interventions vacuum leak ring 3? chamber 15RB2 ring 3 changed
Synchronisation (of the four rings before transfer to PS) failures	fewer than 1994 - hardware improved? less jitter on PSB flat top?	NMR marker for new B-train generator useful
Pb^{53+} emittance measurement at 95.4 MeV/u in ML	3 SEM's give good signals, but optics to be improved	

PSB - ISOLDE 1995


Problem	MD results and/or actions	Comments
10^{13} p/second, with diagnostics for 10^{10} p/second	Crash programme to install basic instruments: <ul style="list-style-type: none"> • beam transformers near GPS and HRS targets • two electrostatic PU (~10 needed) • a SEM near each target 	Do we lose beam?? Only route to ABS to understand optics
Significant discrepancies between computed and real optics	not clearly understood; more analysis; more dedicated MD's in ISOLDE line	Render HRS operational (almost no diagnostics)
Vertical setting of ISOLDE building (~10 mm)	special trajectory worked out	doesn't ease steering
Beam spot on target - steering and shaping	Low- β doublet moved upstream	stronger dipoles needed; automated optics setting?
Staggered extraction - only way to use liquid targets with $> 10^{13}$ p/burst and to match isotope yield at SC	Test runs with ring-to-ring distance 10 μ s: liquid targets work up to $2 \cdot 10^{13}$! But beam transformers cannot digitize the extended beam length unless 100 kfr invested	Further test 1996 foreseen Routine operation (1997?): beam current measurement indispensable for watchdog

DOSE COLLECTIVE ANNUELLE BOOSTER




Graph. 2



Fig. 6: SOS signals of the BLM's 7L2, 8L2, 9L2 sup. together with the beam current of Ring 4. 6a without and 6b with excitation of the zero-harmonic sextupoles such as to compensate vertical chromaticity.




6b




6a



LOSS OF Pb^{81+} IONS



$-Cumsum(Re(btf)), dp/p = +-1.7e-3, +-1.5e-3$



$\frac{\Delta p}{p}$ MEASUREMENT OF THE BEAM COASTING AT 50 MeV
IN THE BOOSTER BY BEAM TRANSFER FUNCTION MEASUREMENT

Pb

K. V. L.
Calame.



Dec 12 13:56:28 1995

Beam profile and emittance measurements with SEM-grids


file Controls Options View Pls Option

Pls: MEIGN BX.ASCBR 300 MS BTM.TRA -2.6E10

c(2o): 32.26 π μ m $\Delta p/p$: 1.00 E-3



NORMAL EXTRACTION
(SOLID TARGETS)



STAGGERED
EXTRACTION
(LIQUID TARGETS)

NORMAL AND "STAGGERED" EXTRACTION FOR ISOLDE

Pb⁵³⁺ IONS IN THE 1 GeV MEASUREMENT
LINE (ML)

PS Performance Day 1996

Status of ABS in the PS Complex

Bruno AUTIN

Abstract

Automatic beam steering has been introduced in the PS complex in 1994 for the correction of the proton coherent oscillations in the PS and the transfer of particles between booster and PS. The two tests were successful and, beyond the obvious simplification of the operation, improved the reliability of the machine by imposing a better quality of the instrumentation and revealing hidden hardware bugs. In 1995, the automation has been consolidated in the PSB-PS line and the correction of injection errors in the PS has been extended to leptons. The adjustment of the Linac-PSB line has been simulated and shows an anomalous sensitivity in the horizontal plane especially, a concern reported by the operation crew in the past years. A revision of this line is thus under study and dedicated experimental tests will be performed this year.

Motivation

Operation

- Simplicity and reliability for fast setting-up and corrections

Performances

- Lower beam losses due to a precise beam steering

Long term

- Emittance preservation for LHC and eventually CLIC.

Cast

M. Arruat, B. Autin, F. Di Maio, V. Ducas,

G.H. Hemelsoet, A. Kazymov, O. Jensen, M. Lindroos,

A. Lombardi, M. Martini, H. Schonauer, O. Tungesvik,

V. Vicente, E. Wildner.

Fields of activity

System Architecture

PS Booster-PS line


Linac-Booster line

System architecture

- Access to data base (*ACCIS*)
- Data base
- Selector
- Programs
 - BeamOptics
 - CorrectionMatrix
 - Micado
- User interface


Automatic Beam Control

Data base



Automatic Beam Control

Selector



Automatic Beam Control

Example

```
In[1]:= Install["/mcr/math/Packages/SAP/BO_Loader"]
```

```
Out[1]= LinkObject[/mcr/math/Packages/SAP/BO_Loader, 1, 1]
```

```
In[2]:= <<SAP`BeamOptics
```

```
In[3]:=
```

```
db = Selector["BOOSTER", "BTY", "BeamOptics"];
```

```
In[4]:= Short[db]
```

```
Out[4]//Short=
```

```
{{BTY.QFO304, Q, 0.564, 0, 0.9493, 0, 0, 0, 0, 0},
```

```
<<80>>}
```

```
In[5]:= ch=ToChannel[db];
```

```
In[6]:= Short[ch]
```

```
Out[6]//Short=
```

```
Channel[ Q[0.564, 0.9493],
```

```
SS[0.5],
```

```
<<78>>,
```

```
Q[0.564, 0.5209]]
```


Automatic Beam Control

Programs

- **BeamOptics**

General paraxial optics program with symbolic, numeric and graphics facilities.

- **CorrectionMatrix**

Builds the correction matrix A of a machine m for a given correction type and stores the result in an operation file $file$.

Example:

```
m=Selector["Booster","BR1","Steering"];
```

```
a=CorrectionMatrix[m,Steering,file]
```

It returns the correction matrix, the list of monitors, the list of correctors

- **Micado**

Solves the correction system

$$A x + b = r$$

by finding the corrections x which minimize the norm of the residual vector r for initial measurements b . Note the **generality of the process**: b may denote the positions of a trajectory or of a closed orbit, the tunes at different momenta, etc. The correction is iterative up to an order n . It needs the monitors mv and correctors cv validated by the operator.

Example:


```
Micado[file,b,n,mv,cv]
```

returns: the r.m.s. values of r_1, r_2, \dots, r_n , the corrections $\{\{c_1, x_1\}, \dots, \{c_n, x_n\}\}$, the residual vector r_n .

Automatic Beam Control

User interface

- The Correction window is generic.
- The Instrument window depends on the instrument.




Automatic Beam Control

PS


- Preparation of lepton injection.
- Test of positron injection.
- Preparation of optics model for the PS magnet stray field at ejection.

Functional field map



Automatic Beam Control

Trajectory



Particle coordinates near the central orbit:

In	Out	
-2550	2730	mm z
-18.46	-23.8324	mm x
31.41	-31.0825	mrad phi

Horizontal transfer matrix:


$$\begin{pmatrix} 1.26475 & 5.26483 \\ -0.0116791 & .74206 \end{pmatrix}$$

Booster

- **Booster to PS transfer**
 - Available in operation for four rings.
 - New system for simultaneous acquisition of the four beams.
 - Need for PPM in BTP line.
- **Linac to Booster transfer**
 - Very sensitive beam steering (see β -functions, dispersion and matrix coefficients).
 - Revised optics to concile beam envelope and centroid motion.

Automatic Beam Control

The problem of the Linac line



Explosion of horizontal β -function resulting from reverse tracking in the linac-booster line.

-0.17	0	0	0	0	0	0	0	0	0	0	0	0
-0.71	-1.5	0	0	0	0	0	0	0	0	0	0	0
-0.36	-2.6	-0.17	0	0	0	0	0	0	0	0	0	0
2.	-5.5	-6.8	-0.35	0	0	0	0	0	0	0	0	0
-0.9	2.6	3.1	0.066	-0.42	0	0	0	0	0	0	0	0
1.2	-6.4	-5.4	4.	-2.8	-1.4	0	0	0	0	0	0	0
-0.75	5.6	4.	-4.9	3.7	1.1	-1.9	0	0	0	0	0	0
-2.8	17.	13.	-13.	9.8	3.6	-3.8	-2.2	-0.15	0	0	0	0
-2.	12.	9.3	-8.2	5.9	2.5	-1.7	-2.4	-2.8	-0.15	0	0	0
-1.8	9.1	7.8	-5.7	4.	2.1	-0.52	-3.	-5.3	-2.1	0	0	0
2.5	-16.	-12.	12.	-9.1	-3.3	3.7	1.7	-0.82	-2.8	-4.3	0	0
3.1	-19.	-15.	15.	-11.	-4.	4.2	2.4	0.13	-2.7	-4.8	-0.64	0
6.5	-39.	-31.	29.	-21.	-8.3	7.5	6.3	4.1	-3.	-8.3	-4.4	-2.1

Horizontal matrix coefficients in mm/A: the adjustment of beam position within 1 mm at the end of the line requires a precision in current setting of .01 Ampère!

Conclusions

- **α -version of ABC**

Data base, selector, algorithms and user interface exist.

To be done: data entry, running-in of the full system, polishing.

- **PS and PSB**

Improved operation already clear for steering.

The number of automatic tasks will be increased.

Experimental study of the linac-booster line with a probable re-design of the focusing.

- **Think of an automatic correction of orbit dispersion and emittance blow-up.**

PS Performance Day 1996

PS dynamic aperture for the LHC beam

Roberto CAPPI

Abstract

The LHC beam at PS 26 GeV/c extraction has a large momentum spread. Foreseen at the beginning as $dp/p = \pm 2 \times 10^{-3}$ it was then "raised" to $\pm 4 \times 10^{-3}$ to eventually gain stability in the SPS.

Studies were made in the first part of 95 to check if it was possible to extract and transfer to the SPS such a beam without destroying its transv. emittances. Some preliminary results concerning measurements done in 1995 are presented. They show that we can expect a PS to SPS transmission of ~100% for beams with $dp/p < \pm 4 \times 10^{-3}$. Possible transverse mismatch has not been yet investigated.

Instrumentation calibrations and TT2 optics verifications done for these measurements have also improved the performance of operational beams (e.g. ions).

PS (DYNAMIC) APERTURE FOR LHC BEAM

Instrumentation: C. Dutriat, U. Raich, J. Olsfors, M. Arruat

Operation: G. Azzoni, B. Vandorpe

Beam Studies: R. Cappi, D. Manglunki, M. Martini, J-P. Riunaud

The problem:

The LHC beam at PS 26 GeV/c extraction has a large momentum spread. Foreseen at the beginning as $dp/p = \pm 2 \cdot 10^{-3}$ it was then "raised" to $\pm 4 \cdot 10^{-3}$ to eventually gain stability in the SPS.

Studies were made in the first part of 95 to check if it was possible to extract and transfer to the SPS such a beam without destroying its transv. emittances.

1st PART:

DA measurements of the circulating beam at 26 GeV/c

Transv. emittance measurements (H & V) were done with WS's before and after extraction bumps ($\Delta t \sim 30$ ms), keeping the extraction kicker OFF and changing the beam momentum with a radial perturbation

$$I_p \sim 10^{12} \text{ ppp}, \quad k_b = 20, \quad \varepsilon_l = 0.5 \text{ eVs}, \quad dp/p = \pm 0.3 \cdot 10^{-3},$$

$$\varepsilon_x^* \sim \varepsilon_y^* \sim 4 \mu\text{m} (1\sigma)$$

RESULTS:

a) no significant $\epsilon_{x,y}$ blow-up (< few %) for
 $-5 \cdot 10^{-3} < dp/p < 5 \cdot 10^{-3}$

b) at these positions only few % of beam losses were measured (SS16).

2nd PART:

Extracted beam

Transv. emittances measured on TT2 SEMgrids and SEMfils.
 Transmission measured with transformers up to SPS injection.


RESULTS:

a) $\epsilon_{x,y}$ values consistent (+-20%) with those measured in the machine with WS's.

b) Transmission close to 100% for

$$-4 \cdot 10^{-3} < dp/p < 4 \cdot 10^{-3}$$

including SPS injection




REMARKS:

☞ Mismatch factors of 20 - 100 % were measured...but uncertainties exist on the consistency of these data...*A SUIVRE...VERY IMPORTANT !*

☞ A lot of time was devoted to check and calibrate the instrumentation (WS's, SEM's, etc.)...and many problems were detected and cured. *Some improvements are still missing in the signal and data processing and WS measurements.*

☞ Many efforts were also dedicated in carefully tuning the machine working point (e.g. chromaticity) taking advantage of the new GFA's, Q-meas., the PC "passerelle" etc. *We don't need HE octupoles any more!*


☞ The horizontal orbit was found to deteriorate at high energy. Why? *This will have to be investigated in the future.*





☞ TT2 optics was also examined (for ex. by measuring the dispersion SEM positions). The measured values were in agreement with the theoretical ones...but not exactly (+- 20%).


☞ We profited of the many special beams we had to prepare, in parallel, for the μ W SPS instability studies.

These beams, of various long. dimensions and densities, were obtained by combining RF scraping and bunch rotation gymnastics.




VKT Restriction





③



④

THE GOOD NEWS (T. Linnecar, E. Shaposhnikova)

Preliminary results indicate that bunches of $N_b = 10^{11}$ p/b
 $\epsilon_1 \sim 0.35$ eVs, $\tau_b \sim 3.5$ ns, $dp/p \sim \pm 2.5 \cdot 10^{-3}$ will be stable
 in the SPS.

CONCLUSIONS

- ☺ The PS_{extr} - TT2 - TT10 - SPS_{inj} transmission is $\sim 100\%$ if
 $-4 \cdot 10^{-3} < dp/p < 4 \cdot 10^{-3}$
- ☹ Transverse matching is for the time being unexplored
- ☺ All these studies have definitely profited to the performance
 of the normal operational beams (e.g. ions)

1996 PROGRAM (concerning the LHC beam)

We will concentrate on

transverse matching
collective effects during the acceleration and
debunching (*1st prototype of 40MHz cavity in the*
PS at the end of the year!).

a last remark

With the SPS //MD cycle we are entering in a new phase of operation:

one more user
many more and “difficult” beams

this demands good

coordination,
communication,
flexibility,
collaboration

PS Performance Day 1996

CT 5 turn improvement

Michel MARTINI

Abstract

Two split foils in TT10 have been equipped with a wide band readout electronics to measure the proton intensity and beam centroid position profiles during the continuous transfer from CPS to SPS. Vertical excursions have been observed during the spill with a maximum peak-to-peak amplitude of about 20 mm. No relevant horizontal displacement has been observed. An almost complete cancellation of the vertical beam position excursion along the spill has been achieved in two steps:

- Adjustment of the timing and strength of the kick provided by the *Emittance Reduction Dipole* (ERD1) in TT2 acting on the last (5th) PS turn.
- Addition of a second kick provided by a spare *Emittance Reduction Dipole* (ERD2) to adjust independently the 4th and 5th PS turns.

A reduction of the mean vertical emittance of the injected beam up to 21% and an improvement of the injection efficiency in the SPS up to 3% have been achieved.

Continuous Transfer (CT) Improvements

**GOAL: Provide high intensity proton beams for
SPS Fixed Target Physics (SFT)**

Outline

- SFT Beam Process
- CT System
- CT Improvements

SFT Beam Process

SFT beam characteristics

p [GeV/c]	I_p [p/batch]	n	σ_x [μm]	σ_y [μm]	σ_z [eVs]	$\Delta p/p$	τ_b [ns]
14	$2.5 \cdot 10^{13}$	420	11	7	0.1	10^{-3}	5

PROCESS

- 20 bunches PS injection at 1 GeV
- Acceleration on h=20 beam (9.5 MHz) up to 14 GeV/c
- Debunching and rebunching on h=420 (200 MHz)
- Continuous transfer to SPS (5 turn shaving ejection):
 - 420 bunches/turn: 1 SPS batch of 2100 bunches (5/11 of SPS)
 - 4200 SPS bunches in 2-batch ejection (4620 SPS buckets)

CT System (1)

ELEMENTS FOR CT


- 1 PS electrostatic septum (SES): 5 turn beam shaving
- 1 PS electromagnetic septum (SMH): beam slice ejection (the shaved slices are kicked out of the PS)
- 2 PS slow bumpers (BSW): place the beam near SES and SMH
- 2 PS fast bumpers (BFA): shift the beam progressively into SES
- 2 PS quadrupoles (QKE): kick enhancement, SES high β -function, zero dispersion function (avoid losses and momentum drift)
- PS pole face windings, figure-in-eight-loop: $Q_x=6.25$ ($E_{x,y}>0$)
- 1 TT2 electromagnetic kicker (ERD - Emittance Reduction Dipole): 5th slice angle correction (reduce integrated 5 turns ϵ_x)

Michel Martini

CT 5 turn improvements

3

CT System (2)




Michel Martini

CT 5 turn improvements

4

CT System (3)

Phase plane beam peeling:
Q=6.25



Michel Martini

CT 5 turn Improvements

5



CT System (4)

5 turn shaving ejection :

Horizontal phase plane
at SES

Q=6.25

Horizontal phase plane at
SMH



Michel Martini

CT 5 turn Improvements

6

CT Improvements (1)

PROBLEM

- Adequate TT2 horizontal alignment of the 5 beam slice centroids cannot be achieved with a single *ERD*
 - Variable beam slice ejection trajectories due to a *BFA* (5th turn - 4th? - angle at *SMH* different from the other)
 - Vertical emittance blow-up at SPS injection (TT10 emittance exchange to cope with SPS vertical acceptance limitation)


SOLUTION

- Installation of 2 *SPLIT FOILS* in TT10:
 - Measure beam centroid position profiles and Intensity
- Additional *ERD* in TT2:
 - 2nd kick to better align the ejected turns:

Michel Martini • 1st *ERD* (5th turn), 2nd *ERD* (4th turn) CT 5 turn Improvements

7

CT Improvements (2)





Michel Martini CT 5 turn Improvements

8

CT Improvements (3)

TT10 beam before ERD tuning

- Vertical beam centroid position
 - BFA's rise/fall times yield peaks at spill beginning/end
 - 20 mm peak-to-peak oscillation between the 4th-5th turns
 - No horizontal oscillation observed between turns
- Spill intensity profile
 - Adjusted with the BFAs



Michel Martini



CT 5 turn improvements

9

CT Improvements (4)

TT10 beam after ERD tuning

- Vertical beam centroid position
 - 1st ERD: timing and kick strength adjustments (5th turns)
 - 2nd ERD: timing and kick strength adjustments (4th and 5th turns)
 - 4 mm peak-to-peak displacement between 4th and 5th turns
- Spill intensity profile



Michel Martini

CT 5 turn improvements

10

CT Improvements (5)

New performance

Mean beam parameters

TT10 horizontal emittance reduction $\Delta\epsilon_x^*/\epsilon_{x0}^*$	0 %
TT10 vertical emittance reduction $\Delta\epsilon_y^*/\epsilon_{y0}^*$	21 %
SPS injection efficiency increase	3 %
SPS 440 GeV transmission efficiency increase	3 %

PS Performance Day 1996

Fast ejection of positrons in straight section 61

Jean-Pierre RIUNAUD

Abstract

A short MD session was devoted to the Fast Extraction of e^+ beams to the East Area (FE61). The purpose of the experiment was to take advantage of the fast extraction to the East Area of p^+ beam at low energy (<3.5 GeV/c), already achieved in 1994 for the Energy Amplifier Test, to send e^+ to this area via the same process. The final aim being to check whether the PS can provide a pure and high flux (10^9) e^+ beam to East Area users, who presently get these leptons as secondaries at low fluxes ($<10^5$) and mixed with other secondaries.

Fast extraction of e^+ (or p^+) to the East Area makes use of the PS general purpose full aperture kicker KFA71-79 and elements of the slow extraction, namely 4 dipoles for the orbit bump and 2 magnetic septa. For positron extraction, the Pole Face Windings at low current, normally powered during the lepton acceleration cycle, were used to tune machine parameters such as chromaticities, transverse tunes and (partially) damping.

An e^+ beam was successfully extracted and observed on the first TV scintillator screen of the area.

Fast Extraction of e^+ to the East Area

Aim:

- Make use of the low energy p^+ Fast Extraction (FE61) achieved for the Energy Amplifier Test
- Add the possibility of providing “pure” and “high flux” e^+ beams to the users of the East Area

MD session : 19/10/95

R. Cappi, L. Durieu, J.-Y. Hémerly, M. Martini, G. Métral, B. Vadorpe, J.-P. Riunaud

Jean-Pierre Riunaud

Fast Extraction of e^+ to the East Area

Proportion of e^+ in Secondary Beams

(2. 10^{11} p^+ hitting the target at 24 GeV/c)

© PS/PA/Note 93-21
L. Durieu, D.J. Simon




Fig. 14 Relative distribution of protons, pions and positrons in the t7-beam, as measured by PS188 (Ref. 6,7)




Fig. 26 Observed particle fractions in the t11 be (particle identification by 2 Cerenkov counters + 1 pre-shower detector) UA2-test (1987)

Jean-Pierre Riunaud

Fast Extraction of e^+ to the East Area

Fast Extraction FE61


(p^+ or e^+)

- Elements

- Fast kicker KFA71/79
- Some dipolar elements of Slow Extraction 61

- Adjustments

- $Q_x = 6.10$ for proper phase advance & Horiz. Dispersion



Jean-Pierre Riinaud

Fast Extraction of e^+ to the East Area

3

Fast Extraction of e^+ compared to p^+

- Smaller beam size of e^+
 - Radiation damping
 - Vertical emittance only due to coupling
- Use of Pole Face Windings to control
 - Chromaticity
 - Damping (partially)
 - Focusing
- Tool to control $\xi_x, \xi_y, J_x, Q_x, Q_y$ with 3 PFW and a Wiggler

Jean-Pierre Riinaud

Fast Extraction of e^+ to the East Area

4

Tuning ξ_h, ξ_v, Q_h with PFW currents I_F, I_D, I_B

- PS natural chromaticities: $\xi_{x,v} = -1$
- Use of PFW_{F,D} to change chromaticities
 - Requirements: $\Delta \xi_{x,v} > 1$ to get $\xi_{x,v} > 0$ for e⁺ stability
 - Produced by PFW_{F,D}: $I_F > 0$ & $I_D < 0$
 - Consequence: $\Delta Q_x > 0$ & $\Delta Q_v < 0$
- Use of PFW_B to reduce Q_x to 6.1
 - $\Delta Q_v > 0$ and no effects on $\xi_{x,v}$
 - Produces a favourable Damping change ($\Delta J_x = .6$)
- Final results: $\xi_x = .80$; $\xi_v = .35$; $Q_x = 6.11$; $Q_v = 6.39$

Results and Next Steps

Achieved

- Operational changes:
 - Slow Extraction / Fast Extraction / Lepton cycle
- Beam on first TV screen at entrance of East Area (TV2)

Next step

- Transport e⁺ down to secondary line

Possible Positron Beams in the East Area

	Slow Extraction Primary $p^+ \gg e^+$	Fast Extraction Primary e^+
User (s)	Beam sharing	Single user
Beam composition	e^+, p^+, π^+, \dots	e^+
Energy	0 - 5 GeV	3.5 GeV or lower, fixed
Flux [e^+ / pulse]	$10^3 - 10^5$	$10^7 - 10^9$
Burst duration	350 ms	5 ns bunches, within $2 \mu s$
PS cycle	2.4 s, High energy	1.2 s, Low energy

PS Performance Day 1996

LEAR MDs with ions

Gérard TRANQUILLE

Abstract

In the framework of the LHC project, LEAR is expected to be used as a lead ion accumulator where electron cooling plays an important role in the stacking process.

Development time has been devoted to improving the transport of the ions from the Linac 3 to LEAR, the understanding of the mechanisms that limit the beam lifetime under electron cooling, and also the reduction in the cooling time constant through the variation of various cooling and machine parameters.

LEAR MD with ions

- Motivation for the studies
 LEAR to be used as a Pb ion accumulator for LHC
 Stack 1×10^9 ions in 2 secs.
 Cooling times < 100 ms for multiturn injection

Studies made

- Transfer line : beam transport
 injection matching
- Beam lifetime measurements
- Cooling time measurements

Machine parameters

Ion energy	4.2	MeV/u
Proton eq. momentum	341	MeV/c
Velocity	0.094c	ms^{-1}
Ring circumference	78.54	m
Cooling length	1.50.02	m
Electron beam radius	0.025	m
Electron beam current	0.02-0.5	A
Electron density	2.2×10^{11}	cm^{-3}
Longitudinal B field	628	G
Machine I		
D	3.6	m
β_{\parallel}	1.7	m
β_{\perp}	6.5	m
Machine IV		
D (SS1 & SS3)	0	m
β_{\parallel} (SS1 & SS3)	11	m
β_{\perp} (SS1 & SS3)	7	m

Allocated MD time

- December 1994 - Pb⁵³⁺, injection & lifetime
- June 1995 - Pb^{52+,53+,54+}, lifetime
- December 1995 - Pb^{53+,54+,55+}, lifetime & cooling time

Transfer Line

- Problem taking the beam around the E0 loop
- Poor instrumentation - 1 SEM grid & 5 TV screens
- Injection matching still difficult
- $1..2 \times 10^8$ charges/injection
- All charge states transported and injected

Lifetime measurements

- Power density of Schottky signal is directly proportional to the intensity
- Lifetime τ (1/e) obtained from an exponential fit of the Schottky power density evolution recorded on a spectrum analyzer
- The decay rate $1/\tau = \sum_r 1/\tau_r$ where r = machine vacuum
electron recombination
other losses (I.B. stripping)
- Plotting $1/\tau$ vs. I_e the slope of the curve gives us information on recombination processes


$$\alpha = (1/\tau)/(2.25 \times 10^6 I_e)$$

Cooling time measurements

- Measured the total cooling time, i.e. the time to reach a certain equilibrium !!!! (approximately 2-3 times the cooling time constant)
- Schottky signals
100 kHz bw forsec, all 3 planes simultaneously
- Ionisation profile monitors (BIPM)
spatial resolution of 1mm, maximum beam dimension 32mm
temporal resolution of about 100ms
- Measurements at injection or by kicking part of the beam
- Cooling time constant $\tau_{cool} \propto \theta^3 / (I_e \eta_{cool})$, $\eta_{cool} = L_{cool} / L_{machine}$, $\theta = (\epsilon / \beta)^{1/2}$
therefore to reduce the cooling time can :
 - increase I_e and/or η_{cool}
 - reduce θ i.e. increase the β function in the cooler


Conclusions & things to do

- Use Pb54+
- Improve instrumentation in the transfer lines
- Vacuum quality influences the lifetime => need to improve the vacuum by a significant factor
- Need stable high intensity electron beam. Up to now 200 mA obtained, above the beam is unstable
- Investigate the effect of electron beam neutralisation
- Increase of the β function did not give any appreciable gain in the cooling time. Why ??
- Test multiturn injection with energy ramping
- Study doubling the cooler length



GPIB instruments :
spectrum analyzers
network analyzers
oscilloscopes
DVM etc....


PCMCIA-IEEE interface



RS232



Toshiba T4850CT




500MB
removable
hard disk

BIPM

DeskStation IV

DAS1802HC





DAS16F



analogue signals
Schottky etc....


Variation of the Schottky power density at 36.097MHz as a function of time






Charge state	α theory
52+	2.25
53+	2.29
54+	2.32
55+	2.36

graphs



Pb 53+



Pb 54+

For 1e-12 Torr/atom	
H	1210
He	603
C	205
N	178
O	157
Ar	79
Xe	37.8

Following Franske's formulae and D. Moehl's excel progs.


decembre 1995												
	RGA	103	202	303	402	rel <P>	1/life	1/life	1/life	1/life	#DIV/0!	
For 1e-12 pp*	length[m]	27 <P>***	16 <P>	15 <P>	12 <P>	12 <P>	19.7 <P>	12 <P>	12 <P>	12 <P>	0	
H2	605.00	18	6.19	12	2.44	15	3.06	12	3.01	0.706	0.024295	41.161
He	603.00	0.4	0.13	0.16	0.03	1.7	0.35	0.16	0.04	0.026	0.000906	1103.902
CH4	122.19	6	2.06	2.6	0.53	0.7	0.14	2.6	0.65	0.163	0.027719	36.076
H2O	124.65	0.9	0.31	1.4	0.29	0	0.00	1.4	0.35	0.046	0.007615	131.324
N2	89.00	0	0.00	0	0.00	0	0.00	0	0.00	0.000	0	#DIV/0!
CO	88.91	1.1	0.38	0.1	0.02	0	0.00	0.1	0.03	0.020	0.004764	209.886
Ar	79.00	1.6	0.55	0	0.00	0.11	0.02	0	0.00	0.028	0.007246	138.004
CO2	56.76	0.4	0.14	0.2	0.04	0	0.00	0.2	0.05	0.011	0.004024	248.507
Xe	37.80	0	0.00	0	0.00	0	0.00	0	0.00	0.000	0	#DIV/0!


Meas. Taulife = 10..11 s calc. Taulife[s] 13.06

* pp=Partial physical pressure in pTorr
 *** <P>= contribution of this section to the average pressure of the ring

JUN 1995												
	RGA	103	204**	303	304	rel <P>	1/life	1/life	1/life	1/life	1/life	
For 1e-12 pp*	length[m]	50 <P>***	50 <P>	16 <P>	4 <P>	4 <P>	16 <P>	16 <P>	16 <P>	16 <P>	16 <P>	
H2	605.00	18	5.50	5.1	1.04	16	3.26	6.1	1.53	0.647	0.018725	53.403
He	603.00	0.6	0.21	1.3	0.26	3.1	0.63	9.4	2.36	0.198	0.005739	174.257
CH4	122.19	0.4	0.14	1.6	0.33	1.1	0.22	1.1	0.28	0.055	0.007885	126.827
H2O	124.65	0.7	0.25	1.4	0.29	0	0.00	1.1	0.28	0.046	0.006487	154.152
N2	89.00	0	0.00	0	0.00	0	0.00	2	0.50	0.029	0.005637	177.413
CO	88.91	0.2	0.07	0.28	0.06	0.85	0.17	0	0.00	0.017	0.003362	297.398
Ar	79.00	0	0.00	0.21	0.04	0	0.00	0.17	0.04	0.005	0.001081	924.826
CO2	56.76	0	0.00	0.16	0.03	0	0.00	0.13	0.03	0.004	0.001149	870.576
												17.51

Meas. Taulife = 16..20 s calc. Taulife[s] 19.974






horizontal



vertical




longitudinal


$I_e = 100 \text{ mA}$
 machine 1
 injection

3DPROF.XLS


Electron cooling of Pb54+ ions in LEAR observed on the ionisation profile monitor (BIPM)
Ie=120mA



at injection



t=300ms




t=600ms

13/02/96

16:20

17:14

13/02/96



PS Performance Day 1996

Antiproton deceleration tests in AC

Flemming PEDERSEN

Abstract

To enable continued low energy antiproton trap experiments, the AD project has been proposed. It consists of replacing the presently used four rings (AC, AA, PS, and LEAR) with a single ring (AC->AD). It requires slow deceleration of low intensity antiprotons and medium intensity protons (for diagnostics) in the AC ring. The addition of ramping software for synchronous ramping of RF and magnets, as well of the addition of a new digital beam control system for MD's is described. Results and problems identified during MD's in 1995 and outlook for MD's in 1996 are presented.

Deceleration Tests in AC

PPD 96 - February 16

F. Pedersen

Outline

The AD proposal

Why decelerate protons and antiprotons in AC?

How did we do it?

AC Low Level RF System

What has been achieved in 95? Problems?

What should be done in 96?



The AD proposal

There is a physics community who has a strong interest in antihydrogen spectroscopy

The present antiproton complex (AC, AA, PS, LEAR) is very costly to operate and will stop end 96

A single ring 'antiproton trap filler' based on pulsed operation of a single ring (AC -> AD) has been proposed: single shot - no accumulation (almost)

Decision expected some time late spring / summer 96



Why decelerate protons and antiprotons in AC?

The AC was not designed for ramping, magnets only measured at fixed field, ring optics < 3.5 GeV/c?
Power supply ripple at low momentum?

The proposal requires deceleration of very low intensities: $5 \cdot 10^7$ pbars to 100 MeV/c. Beam phase loop OK?

Single coulomb scattering lifetime and multiple coulomb emittance heating rates scales as $1/\beta p^2$ (factor 10^4 ; do we need a bakeable vacuum system?)



How did we do it?

NODAL Program written for synchronous ramping of magnets and rf frequency program, tune correction tables (Tommy Eriksson). Orbit & tune diagnostics.

New digital beam control added to existing analog beam control; harmonic number change; fixed filter -> superheterodyne (10.7 MHz IF) (René Barthelemy)


Cavity (1.6 MHz) tuning range extended to 1 - 2 MHz, 3 kV_p

Beam phase PU sensitivity (Z_L incr.), lower noise (pbars)


Band I intermediate cooling at 2 GeV/c required for pbars (RF acceptance). (Fritz Caspers)



AC Low Level RF System



AC Low Level RF System, modified



What has been achieved in 95?

In parasite with operation for LEAR:

Test protons decelerated to 1.61 MeV/c, 46% of nominal momentum of 3.5 GeV/c (via loop and AA)

Mixers and IF electronics installed but not yet tested with beam (needed below 1.4 MHz)

Deceleration of a few 10^7 pbars (from target area direct) to 2 GeV/c (Longit. cooling needed at 2 GeV/c), 10^5 pbars seems possible

No problems with eddy currents so far (very slow ramp, 9 min., limited by soft B-train)



Deceleration Tests in AC

Slide 7

Problems?

Main problem: Intermittent but frequent trips of main power supplies during ramping. Identified to be 'bug' in power supply microprocessor (Berlin et al.)

Occasional complete loss of beam for unknown reasons (power supplies?)



Deceleration Tests in AC

Slide 8

What should be done in 96?

Fix the power supply intermittent trips

Test Superheterodyne Beam Control with beam

Measure ring optics (orbits, chromaticities, dispersion etc.) at low and intermediate energies

Measure vacuum related beam behaviour (life time vs. $A_{H,V}$, heating rate $dE_{H,V}/dt$) at low and intermediate energies. Gas analysis, sublimation pumps.

If AD approved, tests of accumulation scheme (few shots) at 3.5 GeV/c



Conclusion

Very modest effort MD program, much can be done in parasite with normal operation

Modification of AC low level RF system transparent to normal operation

Deceleration of very low intensities (sensitive beam phase loop) easier than expected, pbars almost as easy as p's

The main worry is vacuum related: to bake or not to bake... => MD's at low energy needed



PS Performance Day 1996

East Hall New Look

Jean-Yves HEMERY

Abstract

The EHNL project has been triggered by the requests we received from the potential 5 new-comers to run in the EAST HALL of PS. The list of elements required for re-configuring and expanding such a facility is given. As a first step, a more detailed inventory list is being compiled. The design studies should lead to a proposal which matches the requests from the physicists and the best use of the parts presently in stock. The major milestone is fixed at July this year. By this date, it will be possible to validate the first cost estimate and the time scale of the project for completion.

At Present

Test of detectors **40 groups** for a total of
200 physicists per year

New-comers

Experiment	DIRAC	
Test of detectors	ALICE	ATLAS
	CMS	LHCB


FIRST STEP & DESIGN STUDIES

Inventory of current stock

- ⇒ Available volume
- ⇒ Iron, concrete, magnets, power supplies, monitors, stoppers, access doors, water cooling, vacuum parts, collimators, controls, survey
- ⇒ Available particles, intensities, B cycles (primaries p^+ , e^+ and secondaries)
- ⇒ "Budget"

Optimization

- ⇒ Sharing of the volume and location
(areas, counting rooms, corridors)
- ⇒ Momentum range
- ⇒ Quality of the momentum analyzers
- ⇒ Beam optics
- ⇒ Collimators, correctors and monitors
- ⇒ Scattering (air gaps, vacuum windows)
- ⇒ Beam line pulsed switching (ALICE/DIRAC)
- ⇒ Personnel protection (concrete, iron shielding, stoppers)



PS ACCELERATOR COMPLEX


AT/V/A
12.05.1992/R.ASKOVIC

PS/PA
18.02.1993/G.GRANGER

LEAR AND EXPERIMENTAL AREAS



TOP.B
AutoCAD




EHNL 03A
 20.02.1996
 G. Granger 2009
 Division PS Gr.PA/EA

Remaining amounts in % as a function of P (Gev/c) and distance (m)


distance index $\text{max}_i := 25$ $i := 0.. \text{max}_i$ $d_i := i \cdot 2$ $d_{\text{max}_i} = 50$ m
 momentum index $\text{max}_j := 30$ $j := 1.. \text{max}_j$ $P_{c_j} := j \cdot 0.5$ $P_{c_{\text{max}_j}} = 15$ GeV/c
k $m_0 := .4937$ GeV $\tau_s := 1.237 \cdot 10^{-8}$ s $c \cdot \tau_s = 3.708$ m

$$K_{i,j} := e^{\left[-d_i \cdot \left(c \cdot \tau_s \cdot \frac{P_{c_j}}{m_0} \right)^{-1} \right]}$$




distance index $\text{max}_i := 25$ $i := 0.. \text{max}_i$ $d_i := i \cdot 2$ $d_{\text{max}_i} = 50$ m
 momentum index $\text{max}_j := 9$ $j := 0.. \text{max}_j$ $P_{c_j} := j \cdot 0.2 + .2$ $P_{c_{\text{max}_j}} = 2$ GeV/c
π $m_0 := .1396$ GeV $\tau_s := 2.603 \cdot 10^{-8}$ s $c \cdot \tau_s = 7.804$ m

$$P_{i,j} := e^{\left[-d_i \cdot \left(c \cdot \tau_s \cdot \frac{P_{c_j}}{m_0} \right)^{-1} \right]}$$




Intensité des exotiques (Atlas et CMS)
23 m en aval du foyer nominal de T9.



TIME SCALE

EHNL



PS-PA-EA

PPD96

TIME SCALE

EHNL



√ **MAJOR MILESTONE**

July 96 : End of **DESIGN STUDIES** relative to **MAIN PARAMETERS** (frozen).

By this date, the list of required elements will be published. It should allow to **validate** the :

first step cost estimate
proposed time scale

PS-PA-EA

PPD96

PS Performance Day 1996

Laser ion source developments

Hartmut KUGLER

Abstract

In the HI group we experiment on Laser Ion Sources. The successful generation and acceleration of light ions has us encouraged to aim at a source of heavy ions, suitable for the LHC. The system we aim at is shown in figure 1. The realization of this source (Pb^{25+} , 10 mA, 6 μ sec, 1 Hz) can be divided in 4 phases. In this context the present (1996/97) set - up can be considered as phase 2.


This experiment consists of a free running CO_2 laser, a target (Ta, Pb), an ion extraction system (80 kV), a low energy (6.9 keV/u) transfer system (LEBT), an RFQ (acceleration of $\text{Ta}^{16+}/\text{Pb}^{18+}$ to 100 keV/u) and a measuring line (ML). We expect some mA of the desired ions at the outlet of the RFQ.

Problems to face: adaptation of extracted ion beam to LEBT, beam transfer (100 mA) and acceleration of a current (50 mA), consisting of 8-10 different charge-states, only one of interest to us. Strongly varying beam loading due to (the present) laser instabilities.

In this presentation one finds:

- an ion injection scheme with a rough estimation of the performance of a “final” source,
- target and extraction area, as in use at present,
- a Ta charge-state distribution with the highest yield at Ta^{17+} , as obtained daily,
- simulation of beam dynamics for LEBT, RFQ and ML for the present setup,
- characteristics of the RFQ,
- technical drawings of the outfit of the experiment and its housing.

HEAVY ION PRE - INJECTOR with a LASER ION SOURCE for HIGH CURRENTS



One can define 4 main phases :

- 1) *The “light ion “ experiment*
- 2) *Ta16⁺ / Pb18⁺ some mAe at 100 keV/u*
- 3) *The “Ta16⁺ / Pb18⁺” experiment with (partially) new Laser equipment*
- 4) *Assembly and running in of system with final laser, RFQ and new target chamber*

The LHC Ion Injector Chain (Laser Ion Source)

	<p>LHC</p> <p>T [TeV/u] Pb⁸²⁺ 2.76</p> <p>ℓ [cm⁻² s⁻¹] 1.9 10²⁷</p> <p>Ions/bunch 9.4 10⁷</p> <p>bunches/ring 608</p> <p>bunch spacing [ns] 125</p> <p>ϵ^* ($=(\beta\gamma)\sigma^2/\beta$) [$\mu\text{m}$] 1.5</p> <hr/> <p>Pb⁸²⁺</p> <p>Ions/bunch 1.2 10⁸</p> <p>bunches 52</p> <p>ϵ^* [μm] 1.2</p> <hr/> <p>Pb⁵⁴⁺ => Pb⁸²⁺</p> <p>Pb⁵⁴⁺</p> <p>ions/bunch 1.6 10⁸</p> <p>bunches 4</p> <p>ϵ^* [μm] 1.0</p> <hr/> <p>Pb⁵⁴⁺</p> <p>ions/bunch 2 10⁸</p> <p>ions/bunch (inj) 3 10⁸</p> <p>bunches 4</p> <p>$\epsilon_x^*, \epsilon_y^*$ [μm] 0.5, 0.5</p> <hr/> <p>Pb⁵⁴⁺ ions/pulse 1.2 10⁹</p> <p>ϵ^* [μm] 0.25</p> <p>Pb²⁵⁺ => Pb⁵⁴⁺</p> <p>Pb²⁵⁺ ions/pulse 6 10⁹</p> <hr/> <p>Pb²⁵⁺ ions/pulse 7.5 10⁹</p>	<p>one low-β experiment</p> <p>bunch spacing 125 ns</p> <p>712.8 bunch places</p> <p>filling per ring ~4 min</p> <p>$\epsilon^* = 1.0 \mu\text{m}$ useful?</p> <p>bunch compr. 2 ns</p> <p>Fixed-frequency acceleration with 200 MHz t.w. cavities</p> <p style="border: 1px solid black; padding: 2px;">Inj.kicker rise 115 ns</p> <p>Al stripper</p> <p>bunch compr. 4 ns</p> <p>125 ns bunch spacing:</p> <p style="border: 1px solid black; padding: 2px;">h=16=>17 @ 258MeV/u</p> <p>Vacuum: $\eta = 0.8$</p> <p>24.3 MeV/u: 4 bunches from h=1 to h=2 RF syst.</p> <p style="border: 1px dashed black; padding: 2px;">better vacuum ($\eta = 0.67$)</p> <p style="border: 1px solid black; padding: 2px;">Monoturn injection</p> <p>1.9 mA for 5.5 μs</p> <p>$\sim \epsilon_0 = 5 \pi \text{ mm.mrad}$</p> <p>C stripper ($\eta=0.2$)</p> <p>4.4 mA for 5.5 μs</p> <p>$\eta=0.8$ ✗</p> <p>5.5 mA for 5.5 μs</p>	
<p>LHC</p> <p>12 pulses</p> <hr/> <p>SPS</p> <p>cycle ~25 s</p> <p>13 pulses</p> <hr/> <p>PS</p> <p>cycle 1.2 s</p> <p>1 pulse</p> <hr/> <p>PSB 1 ring</p> <p>cycle 1.2 s</p> <p>1 pulse</p> <hr/> <p>LINAC3</p> <p>1 pulse</p> <hr/> <p>LIS</p>	<p>177 GeV/u</p> <p>6.15 GeV/c/u</p> <p>148.1 MeV/u</p> <p>4.2 MeV/u</p>	<p style="border: 1px solid black; padding: 2px;">modifications</p>	<p><i>K.Schindl 19/11/95</i></p>

* the η of 0.8 is based on recent Linac3 performance

Our needs (particles from the source)


ref: CERN/PS 94-34 (H1)

Source out (= 1st solenoid in), 80 kV extraction voltage:

10 mAe @ 6 microsec of Pb25+ (= $1.5 \cdot 10^{10}$ ions) at 9.6 keV/u,
4 rms emittance (about 86% of particles) normalized: $0.2 \cdot 10^{-6}$ m*rad.


With $\beta \cdot \gamma = 0.045$ for Pb25+ at 9.6 keV, this demands a
un-normalized emittance of 44 mm*mrad.

Current and emittance are scaled from 1.9 mAe of Pb54+ at 4.2 MeV/u,
expected at the entry of the PSB (see K.S. The LHC Ion Injector Chain
(Laser Ion Source)).




K. Langbein / PS

Target and extraction area for LIS



Ta-lens out of LIS, no acc.


single virtual scope (for printing) ver 0.1.vi
 10/09/95 11:47 AM



Ta_{181}^{16+} , Pb_{208}^{13+}
 $\frac{q}{m} = 0.088$, 0.087

$E_{K\alpha} (80keV) = 7.07$, $6.92 keV/u$
 $\beta =$, 3.8×10^{-3}
 -300
 $E_0 = 200 mm \times mrad \rightarrow E_h = 0.75 mm \times mrad$


12/2.96



G. Himbury

TRACE

14/2.96



```

&data
er=195158.100, q=18., w= 1.440, xi= 40.0
emiti(1)= 188.00, 188.00, dpop=25.0000,
beami(1)= 0.85, 0.0370, 0.85, 0.0370
beamf(1)= -3.128, 5.0334, -3.128, 5.0334,
mt=3, nc=2, mp=1,3,1,5
freq= 0.000, pqext= 0.00, ichrom= 0,
xm= 15.00, xpm= 100.0, ym= 60.0,
n1= 1, n2= 5, smax= 10.0, pqsmx= 2.0,
nprin= 2, ijprin(1,1)=1, 2,1, 4
nt( 1)= 1, a(1, 1)= 200.0
nt( 2)= 1, a(1, 2)= 0.5
nt( 3)= 5, a(1, 3)= 9946.5 , 480.0 ,0.0000 ,0.0000
,0.0000
nt( 4)= 1, a(1, 4)= 400.0
nt( 5)= 1, a(1, 5)= 108.502
nt( 6)= 1, a(1, 6)= 400.0
nt( 7)= 5, a(1, 7)=10233.1 , 480.0 ,0.0000 ,0.0000
,0.0000
nt( 8)= 1, a(1, 8)= 0.507
nt( 9)= 1, a(1, 9)= 100.00
&end

```


R. Scirens
A. Lombardi

Matching achieved with a minimum 200mm from extraction to the first solenoid field, with at least 100mm before the RFQ. Trace file 18_70.t01 . Extracted current is 70mA, reduced to 40mA after element 5.

LIS LEBT 70-100 mA, Ta^{16+} , 7keV/u

Soon: PATH up-graded

change input plane
LEFT SET for 18+ file 18-60.cin
change state from 11+ to 25+



A. Lombardi

100 keV/u Pb¹⁸⁺

11.12.95

1_ Operation with 18+ , tank length equal to the Legnaro one, output energy limited to 100 keV/u

RFQ Characteristics


(file: rfq18_6b.in)

Design Ion : Charge 18+, Mass 208 a.m.u
Frequency : 101.28 MHz
Vane voltage : 73 kV (1.9 Kilp)
Power losses (at 90 kOhm-m) : 75 kW (*)
Maximum electric field : 27 MV/m (rho/ro=0.75)
Vane Length : 253.18 cm
Number of cells : 307
Minimum aperture : 0.2 cm
Modulation factor (max) : 1.8
Transmission : 96 %
Current : 10 mA (I_{eff}=30mA)
Input energy : 6.9 keV/u (extrac. voltage 80 kV)
Output energy : 100 keV/u
Input emittance : 100 π mm mrad (tot,un)
Input acceptance : 200 π mm mrad (tot,un)
Transv. emittance growth : 0
Output long. emittance : 12 π deg keV/u
Maximum tool bit diameter : 4.5 cm
Transverse radius of curvature : 0.26 cm
Vane width : 0.52 cm


(*) The value of the assumed shunt impedance is theoretical, the estimate of the power losses is probably optimistic

Beam loading ~ 5 kW at 50 mA
Filling Time ~ 50 ns

101.280MHz, q= 1.0, Ws=0.095, Wg=0.750, A=0.579, amu=xxxxxxx, i= 10.0mA
phase-space projections at input of cell 1




phase-space projections at output of cell 285



A. Lombardi

RFQ 7 \rightarrow 100 keV/u Pb¹⁸⁺


101.280MHz, q= 1.0, Ws=0.095, Wg=0.750, A=0.579, amu=*****, i= 10.0mA





RFQ

$Z \rightarrow 100 \text{ keV } Pb^{18+}$

A. Lombardi





i=	0.0	
w=	20.800	
emiti	emito	
x	15.58	
y	16.00	
z	15000.00	
np	ne	value
1	3	28.360
1	5	-19.360




100 KeV/u Measuring Line

A. Lombardi, A. Ster
R. Scrivens



LASER ION SOURCE
 LAYOUT BUILDING 236 22 Jun. 1996



M. Bourgeois / PS

New Lab of LASER ION SOURCE

PS Performance Day 1996

CTF95 and CTF2

Hans BRAUN


Abstract

In 1995 experiments in the CLIC Test Facility (CTF) were performed on high charge bunch compression, high power behaviour of 30 GHz components, impedance measurements of 30 GHz RF transfer structures, beam tests of a variety of beam monitor prototypes, and photo cathodes. A considerable part of these experiments was done with respect to CTF2, an accelerator experiment presently under construction with the aim to demonstrate the two beam acceleration scheme with 30 GHz technology as foreseen for CLIC. The construction of the CTF 2 experiment is progressing well and first 30 GHz acceleration is expected for end of this year.

CTF I

Objectives:


- Act as a 30GHz high power source with $P > 60\text{MW}$ to test CLIC RF components
- Study production of high charge bunches with $\sigma_t < 2\text{ps}$ with respect to CLIC drive beam source
- Test of beam monitors and RF structures with single bunches and bunch trains



CTF II

Objectives:


- Test two beam acceleration in 30GHz technology
- Build and test prototypes of CLIC modules
- Study drive beam dynamics
- Test active alignment system
- Test CLIC beam monitoring



CTF'95 experiments

(compressed version)

experiment	result
bunch compression studies	$I_{\text{peak}} > 2 \text{ kA}$
30 GHz high power tests (60-75 MW) of CLIC/CTF2 components <ul style="list-style-type: none">• flexible waveguide• stainless steel w.g. power load• ceramic w.g. power load• phase shifter• waveguide with silver lining• waveguide with nail	no sparks
tests of CTF2 30 GHz transfer structures	Version 1 showed to strong beam position sensitivity. Version 2, built in crash program of ≈ 1 month, works satisfactory
30 GHz BPM tests with beam	resolution better than $\pm 5 \mu\text{m}$
test of new button BPM's for CTF2 drive beam and its acquisition system with beam	works, resolution better than $\pm 100 \mu\text{m}$, BW BPM $\approx 4 \text{ GHz}$, BW acquisition $\approx 500 \text{ MHz}$
high BW WCM for CTF2	works, BW $\approx 10 \text{ GHz}$, sufficient to measure charge of individual bunches
bunch length measurement with coherent transition radiation (DESY & THD)	seems to work
Test of CsI+Ge photocathodes for CTF2 probe beam (exposable to air))	QE is sufficient
Test of GaAS photocathode in RF gun. (for polarized beams in linear colliders)	kept cathode voltages of up to 85 MV/m , (DC guns typ. $1-2 \text{ MV/m}$)






Figure 4: Signal for different numbers of bunches in a train. The first value is taken with one single bunch, then bunches are added successively until the train consists of 12 bunches.






Figure 5: Detector signal for increasing single bunch charge. The number of bunches in the train is kept constant to 12.



CLIC TRANSEER STRUCTURE
4 Rocks / 30 GHz



10 CM

Integrated Spectral Intensity



Formfactor





Status of CTF2

General

- Extension of building in progress
- Layout of beamlines ready
- Magnets of 3 GHz region reused from CTF1

3 GHz RF cavities

- Probe beam RF gun reused from CTF1
- Probe beam 3 GHz accelerating structure is spare of LIL
- New drive beam RF Gun (type 4) almost ready. Type 5 already developed
- HCS construction by LAL Orsay & Philips. Delivery HCS 1 foreseen for July, HCS2 for October

3 GHz RF generation

- Timing system built, under test now
- Upgrade RF Phasing system in progress
- Modulator upgrade from 35 MW to 45 MW in progress

Laser and Photocathodes

- Upgrade Laser System in progress
- Photo Cathodes for drive beam (Cs_2Te) and probe beam ($\text{CsI}+\text{Ge}$) tested and ready for production



Beam Diagnostics

- Drive beam BPM's built, prototypes of acquisition electronic tested, components ordered
- Drive beam WCM build and tested
- Probe beam UMA's reused from CTF1
- New TCM optical beamlines in progress, streak camera upgrade ordered
- Construction of 3 GHz part (except of HCS's) will (hopefully) be finished in May


30 GHz Modules

- Installation of first and second 30 GHz module foreseen for October.

With some luck we may manage to get some 30 GHz acceleration end of this year !




Scheme of CTF2 timing system



16:59:23 FEB 14, 1996

REF .0 dBm ATTEN 10 dB




CENTER 2.99855 GHz SPAN 20.00 MHz
#RES BW 1.0 kHz VBW 1 kHz SWP 60 sec

lower sideband

17:03:19 FEB 14, 1996

REF .0 dBm ATTEN 10 dB




CENTER 2.99855 GHz SPAN 20.00 MHz
#RES BW 1.0 kHz VBW 1 kHz SWP 60 sec

carrier

16:48:28 FEB 14, 1996

REF .0 dBm ATTEN 10 dB



CENTER 2.99855 GHz SPAN 20.00 MHz
#RES BW 1.0 kHz VBW 1 kHz SWP 60 sec

upper sideband

PS Performance Day 1996

Linac 2 and Linac 3 Summaries

Maurizio VRETENAR

LINAC 2 AND 3 SUMMARIES


M. Vretenar

Abstract:

The performance of the two Hadron Linacs in terms of typical accelerated currents and emittances during the physics runs is presented. For both machines 1995 has been a positive year, with a substantial increase in beam brightness, together with a better overall stability of the machines. The improvements are mainly due to the studies done on the ion source and to the re-alignment of the IH tanks for Linac3, and to the re-alignment of the proton source and RFQ done at Linac2 during the shut-down. Nevertheless, some worries about misalignment of elements inside Linac2 tanks arose after a vacuum leak that appeared in October, pushing high on the 1996 MD priority list the study of quadrupoles alignment using the beam as a probe, in order to identify misaligned elements. Another important MD topic for Linac2 will be the reproduction of the high intensity LHC-type beam with a more stable RFQ.

LINAC 2 PERFORMANCE IN 1995

CURRENTS:



TRANSMISSIONS:

RFQ	~ 94 %
Linac Tank 1	92 %
Linac Tanks	90 %
Transfer line	94 %

EMITTANCES:

				1994
Horizontal	1.0-1.3	π mm mrad	1σ , normalised	1.7
Vertical	0.6-0.9	π mm mrad	1σ , normalised	1.2
Longitudinal	~ 6.0	deg MeV	1σ	6.1
Energy Spread	$\pm 140-160$	keV	2σ	170

STABILITY:

* no complains of instabilities in beam position at PSB input

* very low fault rate (until a bad leak...)

LINAC 3 PERFORMANCE IN 1995

Currents:

	Ion	1995	1994
Source	Pb27+	110-120 μ A	80 μ A
RFQ	Pb27+	85-90 μ A	70 μ A
Linac	Pb27+	80-85 μ A	60 μ A
after stripping	all	160-170 μ A	130 μ A
to PSB	Pb53+	25-30 μ A	22 μ A

Emittances & Energy Spread at PSB:

	1995	1994	
Horizontal emittance	0.4	0.6	mm mrad (1σ , normalised)
Vertical Emittance	0.4	0.6	mm mrad (1σ , normalised)
Energy Spread	± 2.5	± 2.5	keV/u (2σ)

LINAC2 MD PRIORITIES

(Linac3 priorities were presented by Ch.Hill during his morning talk)


HIGH INTENSITY

1. REALIGNMENT OF SOURCE AND RFQ

done at beginning of 1995, *but* the 2 weeks of beam measurements foreseen in February-March 1995 have been totally eaten up by a difficult start-up (hardware and software problems on different equipment).

⇒ the work has been done, but we have still to analyse the consequences!

2. RFQ PERFORMANCE AND STABILITY (critical issue for the high intensity beam):



⇒ NEED MD time in 1996 !

NEW & UNEXPECTED PROBLEMS

The important vacuum leak between Tank 1 and Tank 2 of October 1995 (now repaired) was due to the impact of a misfocused/misaligned beam on the beam pipe.

Question: Was the damage due to an accidental event or was it due to 18 years of operation ?

⇒ NEED MD time to study the problem and analyse the alignment of linac elements (mainly quads)

MD PRIORITIES FOR 1996

1. Assess the performance of the linac after the (heavy!) repair of the vacuum leak. *1 week at start-up*
2. Analyse the alignment of linac elements by studying their effect on the beam, in order to reduce losses (at the same time avoid other accidents and improve the high intensity beam). *1 dedicated period + some time during the year, ev. in ppm*
3. Reproduce the high intensity beam and study the effect of the RFQ and source re-alignment *1 or 2 periods of >6 hours dedicated*

Note: New measurement equipment (Bunch Shape Monitor from INR-Moscow) to be commissioned this year.

OLD AND NEW PROBLEMS (LINAC2)

	1993	1995	1996	
RFQ alignment	X			↘↘
Instabilities in the horizontal trajectory, injection into PSB	X	X		↘
Alignment and beam trajectory in the linac		X	X	↗↗
Linac mechanics			X	↗

PS Performance Day 1996

PSB summary

Karlheinz SCHINDL

PSB Summary

PSB Performances 1995

User Name	Beam Type Destination	Nr of Rings	Nr of p tot.	Nr of p/ring	(2-sigma)		Comments	Limits
					Norm. H	Emitt V		
SFTPRO	SPS Neutrino Ph.	4	2.7E+13	7.0E+12	45 pl	25 pl	even Intensity in all rings	Limit 1 capture
AA	pbar production	4	1.8E+13	4.6E+12	30 pl	15 pl	RF dipole recomb h=10 phase inv.	
ISOGPS	ISOLDE	4	3.0E+13	8.0E+12	55 pl	30 pl		LIMIT 1 (2) capture (?)
MDION	Pb 53+	4	2 E+10 (charges)					Ion Source Vacuum

LIMIT 1 : Longitudinal stability is marginal at higher intensities due to

- coupling between rf beam control loops of dual RF system (11 per ring): difficult to control, lack of understanding
- Coupled-Bunch Long. Feedback not designed for acceleration to 1 GeV (requires frequent readjusting at very high intensities)
- Instability of unknown type (GHz signals ?) in Ring 4, causing blowup and loss of a few % beam (main reason for machine activation)
- Recently octupole in-phase modes seen

LIMIT 2 : "Classical" transverse space charge limit.

At high intensity also the longitudinal space charge drastically reduces bucket area

PSB MD's 1996

Topic	Client	Remarks/Requirements/ Contribution	Prime Time	1996 hrs
h=5/h=10 Dual RF System: - study of basic properties: gap-derived or beam-derived h=10 phase; - new HW: Synchr. Detector for quadr./octup. modes; new mode analyzer	ISOLDE, SFT	relevant also for future h=1, h=2 systems maybe feedback on in-phase modes	P ¹⁾	30
h=1 / h=10 RF Systems	LHC	Controlled bunch flattening with h=10	Y	10
h=1 / h=2 Dual RF System	PSB	for intensities $> 2 \cdot 10^{12}$ p/pulse	P	20
Loss Analysis	PSB	High-energy loss ring 4, with BLM's etc	P	10
Steering and Focusing in Transfer Lines (dedicated ISOLDE line MD's needed)	LHC,SPS, ISOLDE	ABS + analysis of geometry (recomb.) ISOLDE line optics, use of SEM's, BLM Staggered extraction	Y P	10 20 8
Beam Transfer Function Measurement	PSB	Momentum distribution of injected beam measured in the ring		20
Comparison Wire Scanner / Beamscope	LHC	before ordering 8 wire scanners from TRIUMF		10
1 GeV Measurement line	LHC	Render operational, in particular for Pb		20
"Initial" Beam for LHC	LHC	$\epsilon' = 0.75 \mu\text{m}$ at 26 GeV/c; shavers?	P	10
Scintillator Screens Inj. Line, CCD cameras	Pb Ions	Test of new SW developments	Y	8
Transverse Stability with New Kicker Cables Damper Tuning	PSB, LHC	Unknowns in acceleration to 1.4 GeV		20
Ion Injection Steering, improved Focusing	Pb Ions	Correction from Screen Position (Matrix Inversion)	P	8
Multiturn Injection Study	Pb Ions, LHC	(PhD Thesis)	P	10
B-Train Generation (with new NMR markers)	Pb Ions	System tests, integration into control system		8
Ion lifetime measurements	Pb Ions	At varying energy, with AT (PhD thesis)	Y	20
Integer Stopband Compensation	PSB	Successful at ISIS - against theory! Waiting for Q-Measurement..		10
Total				260
1) P = Partially during prime time				

3 PSB PROBLEMS:

- i) Marginal stability of dual RF system: limit to highest intensities, tedious operation, losses ==> relevant also for future $h=1/h=2$ systems; longitudinal coupled-bunch instabilities for present $h=5,10$**
- ii) Loss management (mainly related to (i) and in ring 4 - to be further analysed; study of collimators and cleaning septum)**
- iii) Lack of diagnostics in ISOLDE beam line: crash programme
 - Beam transformers in GPS, HRS (*needed for Watchdog!*)**
 - 2 SEM grids and 2 PUs****

- (iv) Left with 5 BS!**

PS Performance Day 1996

LPI summary

Jean-Pierre POTIER

1995 Studies

In 95 the study time was devoted mainly to:

LPI

- e+ tuning, after the exchange of the positron trapping section and focusing solenoids (ACS25). RF conditioning OK now. operational conversion factor back to 5 E-03 at 1.8 E10 on the converter target.
- RF conditioning on ACS27 now OK up to 22 MW (11.6 MV/m average, 18.3 MV/m peak), found limited in 94 by the higher order modes sent to the cavity by a worn out klystron producing a lot of 6 and 9 GHz.
- Experiments on LILV to feed the Pre-Buncher and Buncher from MDK13 avoiding the use of MDK03 and setting up tests with the last MDK (MDK35) OFF.
- Electron beam emittance measurements in WL.WBS25 (end LILV at 200 MeV) and HIM.WBS00 (end LILW at 500 MeV) and comparison with the optical model.

LHC

Irradiation of LHC vacuum chamber samples at a critical energy of 45.3 eV (308 MeV in EPA, 7 TeV in LHC), at room temperature and in a cryostat at about 2 dg K after LEP stop. Stable 4.5 E11 / 8 bunches beam circulating during one week with a good life time.

LEA

After the running-in of the pulsed BSH00, it has been possible to share the beam between LEA (LIL Experimental Area) and LEP, enabling one to perform more easily irradiations for OPAL and ECAL/CMS collaborations on detectors.

Hall 174

Tests on strengthened pulsed solenoids have been pursued and burn-in tests have been performed on regular solenoids which will be installed with the new converter tank in 96.

LPI 96 study program

LPI studies

At 96 startup the stability of LPI with the LIL Buncher powered from LIPS13 will be checked. Then, as usual, beam machine parameters and performances will be measured, then tests on 4 bunches and 8 bunches transfer mode performed with the CPS.

Our main subjects will be:

- Optimization of the WL.SNL25 imperfections compensations using an electron beam.
- Electron and positron beam emittance and matching in LIL to the EPA transfer line.
- Beam production without MDK35
- Test of ABS in LIL and possibly at EPA injection with the PS-ABS team ?
- Training of the LPI Operation technicians in order to prepare them for the new LPI supervision scheme (LPI running without a technician during shifts 3X8h/24h).

LHC irradiation

Making profit of the long LEP stops, the cold bore experiment will continue in the synchrotron light line during 2 periods of 2 weeks and one 3 weeks period, end 96. Momentum will be 308 MeV e- beams . The main subjects will be:

- CO₂ primary photo-desorption coefficients at 77 dg K
- Observe evidence of residual gas cracking using molecules with isotopes markers.
- Recycling coefficient measurement etc....

LEA activities

Measurement for the evaluation of the explosion risks in cryogenic liquids exposed to radiation (TIS and British Institute of cryogenic/ Southampton). Irradiation's for ECAL/CMS.

Hall 174

Tests on strengthened pulsed solenoids will continue as well as the development of a conical solenoid (for positron capture improvement).

Major problems 1995 and nowadays

The **performances** of the LPI are safely above the requests of the users and apart from studies aiming at improving the availability (our major hardware effort) and the operation of LPI, there is no pressure and consequently no priority.

Controls

In 95 as in 94 and 93, the instrumentation reliability remains the weak point during studies. It should improve in 96 due to the planned upgrade of the instrumentation software.

Man Power for studies

In 93 and 94: "In the present operation scheme, MD periods of 60 to 70 h are allocated every 1 to 4 months. The use of such a long study period, with only 2 to 3 people involved in LPI studies, is completely inefficient."

In 95 the situation was still the same and is expected to continue in 96.

PS Performance Day 1996

AAC summary

Claude METZGER

AAC Summary (C.Metzger)

Performances

Comparaison des statistiques des années 1992 à 1995

	1992	1993	1994	1995	1996
Nb. heures programmées	5897 h.	5563 h.	5657 h.	5920 h.	(6168 h.)
Disponibilité du "stack" en heures	5599 h.	4963 h.	5359 h.	5774 h.	
Disponibilité du "stack" en %	94.95 %	89.22 %	94.72 %	97.53 %	
Nb. heures en mode économique	2399 h.	1438 h.	2235 h.	1860 h.	
Temps de pannes	12j.10h.05m.	25j.14h.53m.	11j.07h.57m.	18j. 00h. 08m.	
Intensité maximum	$>9 \cdot 10^{11}$	$8.61 \cdot 10^{11}$	$1.116 \cdot 10^{12}$	$1.036 \cdot 10^{12}$	
Taux de production	$1.29 \cdot 10^{10}/h.$	$1.79 \cdot 10^{10}/h.$	$1.909 \cdot 10^{10}/h.$	$1.703 \cdot 10^{10}/h.$	
Nb. heures de production	1986 h.	2305 h.	1931 h.	2673 h.	
Nb. antiprotons produits	$25610 \cdot 10^9$	$41251 \cdot 10^9$	$36879 \cdot 10^9$	$45526 \cdot 10^9$	
Nb. antiprotons extraits	$18347 \cdot 10^9$	$27320 \cdot 10^9$	$24767 \cdot 10^9$	$36134 \cdot 10^9$	

Les points marquants de l'exploitation en 95:

En général:

- Très bonne disponibilité du "stack" (97.5% du temps programmé).
- Nombre record d'antiprotons produits et extraits pour LEAR.

Production d'antiprotons:

- Lentille Lithium détruite à la fin du démarrage d'avril - remplacée par une corne - diminution du taux de production de 11% en moyenne.
- Jusqu'à fin juillet, limitation de l'intensité du faisceau de production à 1.10^{13} protons/pulse (dernière conséquence du sabotage).
- Remplacement préventif de la corne (rupture d'un boulon de fixation) pendant l'arrêt technique de septembre.
- Corne brûlée par un survoltage accidentel du pulseur.

Accumulation:

- Globalement, bonnes performances d'ensemble avec une efficacité d'accumulation de 79%.
- A signaler:
 - ⇒ Problème de refroidissement cryogénique de plusieurs terminaisons des pick-ups du "cooling AC" ayant entraîné une limitation des performances pendant quelques mois.
 - ⇒ Novembre Noir: Cinq pertes de "stack" dues à:
 - ◇ une fuite d'eau,
 - ◇ deux coupures du réseau EOS,
 - ◇ deux pannes RF.

Ejection et Transfert:

- Faible taux de pannes
- Performances fluctuantes, moyennement bonnes.
- A signaler:
 - ⇒ Instabilité de l'alimentation de BTI 8025.
 - ⇒ Modification des trajectoires due à:
 - ◇ Tests d'échauffement du tunnel du PS
 - ◇ Variation du train B (lié au test d'échauffement)
 - ⇒ Oscillations des pbars dans le PS à l'injection. Amélioration dès que le système de mesure OSC-pbar est devenu opérationnel.

Améliorations et Développements en 1966.

Accumulateur:

Avec la décision d'arrêter l'exploitation du complexe AAC actuel à la fin de 1966, aucun développement ou programme d'amélioration n'est prévu.

D'autre part, le programme de physique à LEAR est prioritaire et le temps disponible pour les Mds ne permet de faire que la maintenance et le réglage des installations.

Collecteur: (en vue de l'éventuelle conversion du AC en AD)

En sessions parasites, pendant les périodes d'exploitation en mode économique, il est prévu de poursuivre, autant qu'il se peut, les études sur:

1. la décélération de protons.
2. la décélération d'antiprotons.
3. le refroidissement stochastique d'un faisceau d'antiprotons sur le palier de 2 GeV/c.
4. le refroidissement de faisceaux bunched.

Problèmes antérieurs et leurs solutions.

1. Baisse du taux de production:

La cause de cette atténuation n'a pas encore été identifiée:

- ⇒ lentille lithium?
- ⇒ cible?
- ⇒ optique?

Après vérification de l'optique avant la cible et de celle de l'injection dans le AC, on a retrouvé le taux de production habituel. Malheureusement quelques jours après, le transformateur de la lentille lithium a grillé. Avec le remplacement de la lentille par une corne, le taux de production a baissé définitivement de 11% en moyenne.

2. Démarrage du complexe AAC:

Le personnel travaillant actuellement sur les machines de production d'antiprotons et ayant une connaissance globale de ces machines diminue d'année en année. Ceci se fait sentir en particulier lors des démarrages par des pertes de temps dues à la méconnaissance des systèmes.

Ce point perd de son importance puisque c'est la dernière année d'exploitation du complexe.

3. Organisation des mesures d'acceptance dynamique:

Dans le programme actuel nous ne disposons pas suffisamment de temps pour effectuer ces mesures lors des démarrages.

Est-il possible de les faire en parasite sans perturber l'exploitation?

Une réunion du PPC a eu lieu pour débattre ce sujet. Il n'y a pas eu de suite.

Problèmes actuels.

Dernière année d'exploitation du complexe AAC.

Arrêt définitif: le 19 décembre 1996.

?

Etude AD ⇒ Projet AD

PS Performance Day 1996

LEAR summary



Michel CHANEL

LEAR D'AVANT

1995

P MeV/c	Exp.	Flux $\times 10^3$	Ex time h	Stack 10^9	Limit.
1940	X Barrel PS 208	100 200	> 2h	5	Ex time
310	PS 201 PS 209	> 2000 (30k) 30k	W 1h → 10h	> 10	stack
200	PS 195 PS 197 PS 205	600-800 30-50 → 10 FAST	2, 2	4-5	stack stack
105	PS 201 PS 197 PS 207	100-200 10 300 1000	0,8 " 0,5	2-3	stack lifetime VACUUM!
FE 65	PS 196 PS 200T	1-2 spots .10 slots	- -	2-3	→ 10^6 m trap.
PS H 210	Jet set on Xe	-	Storage $\sim 10^{-7}$	$\sim 2 \times 10^{10}$	\bar{p} H ₀

- if $p \leq 36$ MeV/c ecool ok.




- Feedback \Rightarrow ϕ constant \rightarrow effects of 200 MW/c Ghost.



- less often
- not strong.

- H_0



for physic. (oh yes!)

LEAR SCHEDULE 1996

JAN					FEB					MAR			
Wk	1	2	3	4	5	6	7	8	9	10	11	12	13
Mo													
Tu													
We													
Th													
Fr													
Sa													
Su													

PS controls test with p+ (2nd office) (Mar 11-12)
SU TEST (Mar 13)
SU SFT (Mar 12)

APR					MAY					JUN			
Wk	14	15	16	17	18	19	20	21	22	23	24	25	26
Mo		Rest				PE MD (30h)							
Tu	SU	LEAR-MD							PE MD	Shutdown			
We	AA	prod.											
Th		200	PE 196 197 200	PE 196 197 200	PE 196 197 200	PE 196 197 200	PE 196 197 200	PE 200	PE-MD (24h)		PE 196 201	PE 196 201	PE 196 201
Fr													
Sa													
Su	Event							Wk					

PS 196 PS200 (Apr 16-20)
PS 196 PS200 (Apr 24-26)

JUL					AUG					SEP			
Wk	27	28	29	30	31	32	33	34	35	36	37	38	39
Mo		100		100				1300	PE MD (30h)		100		
Tu													PE 201 200
We	PE 196 201									PE 197			
Th		ALLOCATION PENDING		PE 201 197		PE 201 196	PE 201 196	PE 197	PE 197		PE 201 200	PE 201 200	PE-MD (24h)
Fr					PE 201 197								
Sa		PS 201											
Su													

PS 196 PS200 (Jul 27-30)
PS 196 PS200 (Aug 31-33)
PS 196 PS200 (Sep 37-39)

TOPS
→
LOW

OCT					NOV					DEC			
Wk	40	41	42	43	44	45	46	47	48	49	50	51	52
Mo		1000			1000			1000					
Tu									PE 197 196				
We													
Th		PE 197 196	PE 197 196	PE 197 196	PE 197 196	PE 197 196	PE 197 196	PE 197 196	PE-MD (24h)	PE 197 196			
Fr													
Sa													
Su													


ALLOCATION PENDING (Oct 41)
PE-MD (24h) (Nov 48)
ALLOCATION PENDING (Nov 50)

LEAR using P
 LEAR-MD
 Shutdown/Tests

Version 1.4 - 21 November 1996
M. Doer

1996

1- Motivation. malgré



to maintain high performances

2 - beg. year M.D ions

- Prepare 1997 ions M.D.

LEAR.

- finish year, p story.

by all

END STORY FEST.

Boss - budget !

PS Performance Day 1996

PS summary

Roberto CAPPI

PS summary - R.Cappi

1996 PS MD forecasts

LHC beam

26 GeV/c optics (PS & TT10)

Transverse & Long. instabilities during acceleration without...and with 40Mhz cavity

Debunching at 26 GeV/c

W.P. and resonance compensation at low energy

PSB-PS matching

HE orbit investigations

Various “calibrated” beams for common PS-SPS studies

Others

ABS: inj. and orbit optimisation

FE61 (& SE61) with calibrated intensities for

TARC

SFT beam optimisation (eventually making use of the new TT2WB pu's)

Long. & transv. “echo” phenomena

PS Beams in 1995

16.02.96

user	part.	cp [GeV]	I_b [part/p]	k_b	$\sigma^*_{x,y}$ [μ m]	$\sigma^*_{x,y}$ [μ m]	ϵ_1 [eVs]	dp/p [10 ⁻³]	β_b [m]	peculiarities	problems
SFT	p	14	$2.5 \cdot 10^{13}$	420	11	7	0.1	1	5	51 CT, very high ip, ad. deb., h=20 recapt.	coll. effects, lossy extraction
SPP/SPN	e+e-	3.5	10^{11}	4 or 8	0.05	0.01	0.01	1 (1 σ)	1.1 (1 σ)	h=8+240, J _r var. (Rob. wiggler)	trapped ions, TMC1
AA	p	26	$1.6 \cdot 10^{13}$	5	13	9	2	2.5	20	finn./merg. h=20, 10, 12, ... 20 b. compress	coll. effects, lossy inj., large ϵ_1
TST	p	3.5	$2 \cdot 10^{10}$	1	4	1.5	0.5	1.3	70	h=20, 6	
LEAR	pbars	0.6	10^{10}	1	2	2	2	2.4	160	descl. to low energy, h=10	A ₁ lim., transf. eff. 80%
PHY	p	24	$3 \cdot 10^{10}$	deb.	3	2		1.3	(0.4s)	ES in int. pos.	
PS-IONS	P653+	5.1	$1.6 \cdot 10^8$	20	1.4	1	0.03	0.23	17	b. stretching, stripped to 82-in TT2	30% vacuum losses
MD beams											
MD/ionsim	p	13	$2 \cdot 10^{10}$	20	4	1	.013	.2	3.5	bunch rotation	
MD/ionsim	p	20	10^{12}	20	4	4	0.5	0.6	25		
MD/spslw	p	26	$1.1 \cdot 10^{12}$	20	4	4	.03-3	3-2.6	2-14	w. or w/o b. rot., low ϵ_1	
MD/spslw	p	14	$1 \cdot 10^{12}$	20	4	4	.15	.66	10	w. or w/o b. rot., low ϵ_1	
MD/thcdam	p	26	10^{12}	20	4	4	0.5	0.3	35	low dp/p	
MD/FE61e+	e+	3.5	10^{11}	4 or 8	0.05	0.01	0.01	1 (1 σ)	1.1 (1 σ)	h=8-240, J _r var. (Rob. wiggler)	

NB: $\epsilon^* = \beta \gamma \sigma^2 / \beta_c$

For ion beams: cp [GeV/u] and ϵ_1 [eVs/u]

PROBLEMS IN PS PERFORMANCE (184)

Integrated performance

- ☞ no daily follow up of the main beam parameters
- ☞ one techn. supervisor is not enough

Peak performance (MD's)

- ☞ 2.5 consoles are not enough (interference)
- ☞ no archiving (yet)

Instrumentation

- ☞ meas. targets are still not in an operational status while WS software needs improvements

PROBLEMS IN PS PERFORMANCE (85)

Integrated performance

- ☞ no daily follow up of the main beam parameters
- ☞ one techn. supervisor is not enough

Peak performance (MD's)

- ☞ 2.5 consoles are not enough (interference)
- ☞ SOS in a very poor status
- ☞ no archiving (yet)

Instrumentation

- ☞ essential instruments are not in an operational status (e.g. meas. targets, WS, ..)

a last remark

With the SPS //MD cycle we are entering in a new phase of operation:

one more user
many more and “difficult” beams

this demands good

coordination,
communication,
flexibility,
collaboration

PS Performance Day 1996

Conclusions

Daniel SIMON

OPERATION : FIRST PRIORITY!

A good start-up is vital (see 1995).

"First priorities in 1996"

- Protons for SPS (neutrino experiments :
→ end 1997 - 2 years only)

CHALLENGE : run as good as 1995 !

	1993	1994	1995
Fault rate	10,6%	12%	7.5%

- Antiprotons in LEAR (last year/5500 hours)

	1993	1994	1995
Fault rate	16,7%	12.7%	13%

"High priorities"

... all other beams !

... and do not forget : tests (important) in LEAR (p^+ , Pb^{54+}) before Easter.

protons

PROTONS DELIVERED ON TARGETS from 1993 to 1995

Last value = October 11, 1995



BD-SL/division


TARGETS Y/P

Nb of days of operation

charges

Charges on Targets / 1994 vs 1995

Last value : Dec. 11, 1995



LEAD9495.XLC

Participants:

ALLARDYCE Brian	PS	HILL Charles	PS
ARDUINI Gianluigi	SL	HUBNER Kurt	AC
AUTIN Bruno	PS	JENSEN Erk	PS
AZZONI Guerino	PS	KISSLER Karl-Heinz	SL
BOILLOT Jean	PS	KOZIOL Heribert	PS
BOUCHERON Jean	PS	KUGLER Hartmut	PS
BOUTHEON Marcel	PS	LEY Rudolf	PS
BRAUN Hans-Heinrich	PS	LINDROOS Mats	PS
BRYANT Philip	PS	LINNECAR Trevor	SL
CAPPI Roberto	PS	LOMBARDI Alessandra	PS
CASPERS Friedhelm	PS	MANGLUNKI Django	PS
CHANEL Michel	PS	MARTINI Michel	PS
CHAPOCHNIKOVA Elena	SL	METRAL Gabriel	PS
CHOHAN Vinod	PS	METZGER Claude	PS
CLENDENIN James	PS	MOHL Dieter	PS
CORNELIS Karel	SL	MULDER Hendrik	PS
CORSINI Roberto	PS	O'NEIL Michael William	PS
D'AMICO Tomaso	PS	PEDERSEN Flemming	PS
DAEMS Gilbert	PS	POTIER Jean-Pierre	PS
DEKKERS Daniel	PS	RIUNAUD Jean-Pierre	PS
DELAHAYE Jean-Pierre	PS	SCHINDL Karlheinz	PS
DUCAS Vincent	PS	SCHNEIDER Gerhard	PS
DURIEU Luc	PS	SIMON Daniel Jean	PS
ERIKSSON Tommy	PS	SJOSTROM Mårten	PS
FAUGIER André	SL	STEERENBERG Rende	PS
FRAMMERY Bertrand	PS	STEINBACH Charles	PS
GAROBY Roland	PS	TANKE Eugenius	PS
GELATO Giovanni	PS	TRANQUILLE Gérard	PS
GIANNINI Roberto	PS	ULLRICH Hanns	PS
GIOVANNOZZI Massimo	PS	UMSTATTER Hans-Horst	PS
GRUBER Jacques	PS	VRETENAR Maurizio	PS
GUIGNARD Gilbert	SL	WARNER David	PS
HANCOCK Steven	PS	WILDNER Elena	PS
HASEROTH Helmut	PS	WILSON Ian	SL
HEMERY Jean-Yves	PS		