



The Compact Muon Solenoid Experiment
Conference Report

Mailing address: CMS CERN, CH-1211 GENEVA 23, Switzerland



12 October 2022

The Phase-2 Upgrade of the CMS Detector

Gabriella Pasztor for the CMS Collaboration

Abstract

The high-luminosity upgrade of the Large Hadron Collider (HL-LHC) will provide a unique opportunity to extend the physics reach of the CMS experiment by achieving unprecedented precision in the study of Standard Model (SM) processes and by increasing its discovery potential for physics beyond the SM to higher energy scales and rarer processes. The HL-LHC, however, will also bring experimental and instrumental challenges with its harsh environment high radiation levels, high number of particle collisions per bunch crossing (pileup of 140-200), and extreme final state particle multiplicities. The CMS Collaboration has embarked on an ambitious upgrade program to improve the spatial granularity and timing resolution, to extend the coverage of precision detectors to higher absolute pseudorapidities (η), to increase the data rate that can be recorded, while using more robust and more radiation hard technologies. In this paper, the main features of the CMS Phase-2 upgrade are reviewed. New high-granularity detectors will be installed a silicon pixel and strip tracker with larger coverage ($|\eta| < 4$), an η -imaging endcap calorimeter ($1.5 < |\eta| < 3$), an extended muon system in the forward region ($2.8 < |\eta| < 5$) including Gas Electron Multiplier detectors. The timing precision will also be significantly enhanced by dedicated timing detectors with 30-50 ps resolution ($|\eta| < 3$), supplemented by improved timing information from muon detectors and calorimeters with upgraded electronics. Fully reconstructed tracks with transverse momentum of $p_T > 2$ GeV and particle-flow at the level-1 hardware trigger will enable more efficient online event selection, with an increased level-1 rate (750 kHz) and latency (12.5 μ s). Trigger objects will be available at 40 MHz for monitoring and restricted data analysis through a Scouting System. The high-level trigger with a heterogeneous architecture will provide a 7.5 kHz output rate to benefit from the increased luminosity.

Presented at LHCP2022 10th Annual Large Hadron Collider Physics Conference

The Phase-2 Upgrade of the CMS Detector

Gabriella Pásztor^{a,*}

^a*Eötvös Loránd University (ELTE),*

Institute of Physics, Pázmány Péter sétány 1A, Budapest H-1117, Hungary

E-mail: Gabriella.Pasztor@cern.ch

for the CMS Collaboration

The high-luminosity upgrade of the Large Hadron Collider (HL-LHC) will provide a unique opportunity to extend the physics reach of the CMS experiment by achieving unprecedented precision in the study of Standard Model (SM) processes and by increasing its discovery potential for physics beyond the SM to higher energy scales and rarer processes. The HL-LHC, however, will also bring experimental and instrumental challenges with its harsh environment: high radiation levels, high number of particle collisions per bunch crossing (pileup of 140-200), and extreme final state particle multiplicities. The CMS Collaboration has embarked on an ambitious upgrade program to improve the spatial granularity and timing resolution, to extend the coverage of precision detectors to higher absolute pseudorapidities (η), to increase the data rate that can be recorded, while using more robust and more radiation hard technologies.

In this paper, the main features of the CMS Phase-2 upgrade are reviewed. New high-granularity detectors will be installed: a silicon pixel and strip tracker with larger coverage ($|\eta| < 4$), an imaging endcap calorimeter ($1.5 < |\eta| < 3$), an extended muon system in the forward region ($|\eta| < 2.8$) including Gas Electron Multiplier detectors. The timing precision will also be significantly enhanced by dedicated timing detectors with 30-50 ps resolution ($|\eta| < 3$), supplemented by improved timing information from muon detectors and calorimeters with upgraded electronics. Fully reconstructed tracks with transverse momentum of $p_T > 2$ GeV and particle-flow at the level-1 hardware trigger will enable more efficient online event selection, with an increased level-1 rate (750 kHz) and latency (12.5 μ s). Trigger objects will be available at 40 MHz for monitoring and restricted data analysis through a Scouting System. The high-level trigger with a heterogeneous architecture will provide a 7.5 kHz output rate to benefit from the increased luminosity.

The Tenth Annual Conference on Large Hadron Collider Physics - LHCP2022
16-20 May 2022
online

*Speaker

1. Physics motivation

The HL-LHC – expected to start operation in 2029 – will allow precision studies of electroweak symmetry breaking and new physics via quantum loops [1]. Higgs boson couplings will be measured to a few percent precision, rare challenging Higgs decays (such as $H \rightarrow c\bar{c}$), di-Higgs production and longitudinal vector boson scattering will become accessible (Fig. 1). With 14 TeV collision energy and 10-fold increase of integrated luminosity to 3000 fb^{-1} until the early 2040s, the mass reach for direct searches of exotic particles will be extended and blind spots (such as parameter regions leading to compressed supersymmetric partner mass spectra) can be uncovered. We might discover the particles responsible for the dark matter in the Universe, new resonances or long-lived particles predicted by various extensions of the SM featuring supersymmetry (SUSY), extra spatial dimensions or strong dynamics.

The next sections review the instrumentation that will allow to exploit the rich physics data delivered by the HL-LHC.

2. Silicon tracker

At the heart of CMS, Si pixel and strip detectors (Fig. 2) will measure the path of charged particles [2]. To cope with the higher particle rate, a 10 times more radiation hard, highly granular system (with 25 times as many output channels as the Phase-1 detector) is constructed. Certain subsystem (TEPX and the outermost layer of TB2S) will also serve as high-precision real-time luminometers.

Closest to the beam pipe, 2 billion hybrid micropixels of $25 \mu\text{m} \times 100 \mu\text{m}$ size form the Inner Tracker (IT) and cover 4.9 m^2 . The n-in-p type sensors of $150 \mu\text{m}$ thickness will be read out by a front-end ASIC produced in 65 nm radiation-hard CMOS technology.

The Outer Tracker (OT) consists of 43 million microstrips and 170 million macropixels covering $190 + 25 \text{ m}^2$. It will provide input at 40 MHz to the level-1 (L1) trigger [9] using a special module design. Transverse momentum discrimination is achieved by measuring hit coincidences (stubs) in sensors of double sided modules, where a flex hybrid allows to get data from both sensors to a single ASIC. For best performance, the sensor spacing is separately optimized for different detector regions, and the correlation window sizes for stub formation are tunable. Tracks are formed from




Figure 1: Expected sensitivity at HL-LHC: precision of Higgs coupling modifiers (left), significance of longitudinal WW scattering measurement (middle left), improvement for chargino exclusion (middle right) and cross-section upper limit for a SUSY scenario with compressed mass spectra (right).




Figure 2: Phase-2 CMS Tracker geometry (top left), data paths of the Outer Tracker (top right) including stub (middle right) information, enabled by a special module design (bottom right), and prototype TB2S structure (bottom left).

stubs in the OT layers, and the transverse momentum is extracted and sent as input to the L1 trigger. Displaced track reconstruction is being studied.

3. Timing layer

To limit the effects of event pileup (PU) on reconstruction performance to Run 2 levels, 4D reconstruction of tracks and vertices with 30-50 ps time resolution is needed. Overlapping vertices at the same z coordinate can be then resolved using time stamps of tracks. Precision timing improves the calculation of lepton and photon isolation, the reconstruction of hadronic jets and missing transverse momentum, b-jet tagging and (especially in heavy ion collisions) $\pi / K / p$ identification using time-of-flight measurement [4]. It can also extend the reach of long-lived particle searches.

The Barrel Timing Layer (BTL) [3] at an inner radius of 1148 mm covering $|\eta| < 1.5$ is constructed from Cerium-doped LYSO crystals read out by Silicon Photomultipliers (SiPMs) (Fig. 3). It is 40 mm thick and extends to 38 m² with a total of 332 thousand channels. Test beam




Figure 3: The design of the Barrel Timing Layer (left), the Endcap Timing Layer (middle right) and the ETL timing resolution based on testbeam data (right).

results in late 2021 showed lower than expected light yield triggering a design re-optimisation. The main concern is performance (time resolution) degradation with radiation damage.

The Endcap Timing Layer (ETL) at $|z| = 3$ m covering $1.6 < |\eta| < 3$ utilizes ultrafast large-pitch Si Low-Gain Avalanche Detectors (LGADs) and is 45 mm thick (limited by the space available between the tracker and the calorimeters). On a total surface of 14 m², it has 8.5 million channels.

4. Calorimetry

In the barrel electromagnetic (EM) calorimeter [5], the PbWO₄ crystals read out by Avalanche Photodiodes (APDs) remain. The front-end (FE) electronics will be replaced to achieve 30 ps time resolution for electrons and photon of 30 GeV at 40 MHz. A new Very Front End (VFE) board removes spikes (anomalous signals due to particles hitting the APD directly). Cooling to 9 C (from 18 C in Run 3) mitigates APD aging. To harmonize the systems, the hadron barrel calorimeter back end (BE) will use the same ATCA boards for data read out, trigger primitive generation, clock distribution to the FE, as well as control and status monitoring.

The CMS Phase-2 endcap High Granularity Calorimeter (HGCaI) will be the first imaging calorimeter at a high-PU hadron collider, designed (Fig. 4) to provide precision particle flow reconstruction improving the sensitivity for vector boson fusion and scattering and allowing more precise reconstruction of jet substructure, as well as – through its timing capability – to extend the reach for long-lived particle searches.

The system [6] uses mixed technology: 6 million Si sensor channels (120 μm x 0.5 cm² and 200/300 μm x 1.1 cm² cells) covering 620 m² in total in the region closer to the interaction point,




Figure 4: HGCaI calorimeter design (top), energy resolution in testbeam data (bottom left), response uniformity of the SiPM-on-Tile detector (bottom center), and its with a dimple in the tile (bottom right).

and 250 000 scintillator tiles read out by SiPMs ("SiPM-on-Tile") covering 370 m² in the lower fluence hadronic region. CO₂ cooling ensure a temperature of -30 C to limit radiation damage of sensors. In the EM section (CE-E) Pb, Cu, Cu-W absorbers, while in the hadronic section (CE-H) steel is used, resulting in a total weight of 215 t per endcap. The steel absorbers – now in production – achieve a flatness of 1 mm. Longitudinal sampling has been recently re-optimised to stay within space limitations while preserving calorimetric depth. CE-E features 26 layers (down from 28) with a total depth of 27.7 radiation length (X_0) and about 1.5 hadronic interaction length (λ). CE-H has 7 all-Si layers (down from 8) and 14 mixed layers, giving a total of 8.5 λ .

HGCal has 26 000 large 8 hexagonal Si modules of 12 different types, consisting of a rigid Cu/W baseplate, a gold-plated kapton foil, a Si sensor, a printed circuit board (PCB) housing the HGCROC FE read-out ASIC. 20% of the modules located at the inner and outer border regions are not fully hexagonal to minimise dead space. Modules mounted on a cooling plate with electronics and absorbers form the cassettes.

The HGCROC chip features a large dynamic range to read out MIP signals as well as those of high-energy photons. Lower energy values are digitised by a 10-bit Analog-to-Digital Converter (ADC), while higher energies are reconstructed using the time over threshold (ToT). The time of arrival (ToA) has a resolution of about 50 ps using 10-bit Time-to-Digital Converter (TDC). The data is forwarded to the ECON-D (data) and ECON-T (trigger) concentrator chips, which send the data over optical fibers to the off-detector electronics. The trigger signals (3D clusters of energy deposits) are formed in two stages of FPGAs. The per channel power consumption is about 20 mW, reaching 125 kW/endcap by the end of the HL-LHC era. Online and offline processing uses highly sophisticated pattern recognition and machine learning assisted algorithms to achieve the best particle flow reconstruction.

In the low-radiation part of the hadronic section the SiPM-on-Tile technology offers a cost-effective solution. To equalize the response across the tile, a dimple is formed around the SiPM into the scintillator. Cast and machined PVT-based material is used in the front, while in the back, where lower radiation tolerance is needed, PS-based scintillators. The areas of the tiles (4-30 cm²) and SiPMs (2, 4, 9 mm²) are optimized depending on the expected fluence. Reflective wrapping increases the light yield and cooling limits the noise of the SiPMs.

5. Muon system

In the muon system [7] (Fig. 5), the existing Drift Tube (DT), Cathode Strip Chamber (CSC), and Resistive Plate Chamber (RPC) detectors will be enhanced with upgraded electronics to cope with the 10 times higher rates and to improve their performance. The time resolution of the RPC trigger signal will decrease from 25 ns to 1.5 ns. The CSC on-detector electronics have been modernized in the long shutdown after Run 2 (LS2), as well as a slice of the barrel DTs received the new on-board electronics to test the performance in real operating conditions.

New detectors will be installed in the challenging (high rate, high background) forward region to increase redundancy and extend the geometric coverage to $|\eta| = 2.4 - 2.8$, enhance tracking performance and allow bending angle measurement at the trigger level. Three rings of Gas Electron Multiplier (GEM) chambers per endcap will be installed, instrumenting 50+100 m² by 2-layer triple-GEM, and 60 m² by 6-layer triple-GEM detectors. The first ring (GE1/1) was installed in




Figure 5: CMS Phase-2 muon system (right), first installed GE2/1 chamber (top left), structure of the GEM detectors (bottom left) and improved time resolution with the upgraded RPC electronics (bottom center).

LS2, the second (GE2/2) is scheduled for end-of-year technical stops (YETs) during Run 3, the last (ME0) for LS3. Two layers of improved RPCs (RE3/1, RE4/1) will also be placed in the outer region. One slice of the endcap is equipped by new GE2/1, RE3/1, and RE4/1 chambers.

6. Beam instrumentation and luminosity

The Beam Radiation Instrumentation and Luminosity (BRIL) project is responsible for 14 technical systems to provide beam timing, beam loss monitoring and beam abort to protect sensitive instrumentation, beam-induced background (BIB) and luminosity measurements, as well as radiation monitoring in the CMS cavern [8].

To reach the 1% precision target for luminosity determination at HL-LHC, required for example by the most precise Higgs cross-section measurements, luminometry will be both a consumer of CMS subsystem data and rely on a new dedicated bunch-by-bunch luminometer, the Fast Beam Condition Monitor (FBCM). The system design relies on maximum commonality, and introduces for some of its components the concept of luminosity triggers. At the heart of the luminosity instrumentation, the BRIL Trigger Board (BTB) will provide a special clocking scheme for independent operation of FBCM and the outermost smallest radius ring (disk 4 ring 1, D4R1) of the Tracker Endcap Pixel Detector (TEPX). At all times when beam is present in the accelerator (even during the ramping phase of the LHC cycle when the clock frequency changes), they can thus provide feedback on BIB. The BTB will also encode the beam signals to be sent from the Beam Pickup Timing Experiment (BPTX) to the Global Trigger (GT), and utilize them to generate independent triggers for D4R1 and for the rest of the TEPX to measure luminosity based on real-time pixel cluster counting, implemented on FPGA. All system (Fig. 6) will use a common histogramming firmware integrated to their backend boards.




Figure 6: CMS Phase-2 luminosity system (left), stand-alone FBCM luminometer (top right), and expected residual non-linearity of FBCM (bottom right).

FBCM, a stand-alone luminometer under full control of BRIL, will be independent of central CMS services (such as data acquisition [10], timing and control distribution system, run control, magnet status) and available outside stable beams, providing additional safety for CMS, e.g. from the Tracker high-voltage interlock. Its pragmatic design is inspired by the Run 2 BCM1F concept [11] and is based on Si-pad sensors with a fast FE ASIC. The asynchronous readout with sub-bunch-crossing time resolution will allow a better understanding of the time structure of the beams and the measurement of beam-induced background. The electronics system adapts as much as possible the Phase-2 Inner Tracker components. In the baseline design, 288 Run 2 BCM1F Si sensors of $2.89 \text{ mm}^2 \times 300 \mu\text{m}$ (utilizing already Phase-2 technology) are placed at $r = 14.5 \text{ cm}$ arranged on 4 half-disks, using a modular design. It will be located Disk 4 of the TEPX in the Tracker cold volume. Detailed simulation studies show a good statistical precision, excellent linearity, and no significant performance degradation with aging.

7. Outlook

The Phase-2 CMS detector upgrades employ novel technologies at an unprecedented scale. As the projects move from the R&D phase to the final verification before (pre-)production, the last technical challenges are being worked out. The schedules have been adjusted to the new HL-LHC time line with first beams in 2029.

For the success of the industrial size production, automatisisation is key. The integration of the complex, large scale systems require a lot of attention and vigilance, as well as extensive system tests in realistic conditions. The first phase-2 muon detector (GE1/1) and all planned muon GEM and RPC, as well as BRIL demonstrator systems have been installed and will provide valuable data for design verification.

References

- [1] ATLAS and CMS Collaborations, Snowmass White Paper Contribution: Physics with the Phase-2 ATLAS and CMS Detectors, ATL-PHYS-PUB-2022-018, CMS-PAS-FTR-22-001, <https://cds.cern.ch/record/2806962>.
- [2] CMS Collaboration, The Phase-2 Upgrade of the CMS Tracker, CERN-LHCC-2017-009, CMS-TDR-014, <https://cds.cern.ch/record/2272264/>, doi: 10.17181/CERN.QZ28.FLHW.
- [3] CMS Collaboration, A MIP Timing Detector for the CMS Phase-2 Upgrade, CERN-LHCC-2019-003, CMS-TDR-020, <https://cds.cern.ch/record/2667167>.
- [4] CMS Collaboration, New opportunities of heavy ion physics with CMS-MTD at the HL-LHC, CMS-DP-2021-037, <https://cds.cern.ch/record/2800541>.
- [5] CMS Collaboration, The Phase-2 Upgrade of the CMS Barrel Calorimeters, CERN-LHCC-2017-011, CMS-TDR-015, <https://cds.cern.ch/record/2283187>.
- [6] CMS Collaboration, The Phase-2 Upgrade of the CMS Endcap Calorimeter, CERN-LHCC-2017-023, CMS-TDR-019, <https://cds.cern.ch/record/2293646>, 10.17181/CERN.IV8M.1JY2.
- [7] CMS Collaboration, The Phase-2 Upgrade of the CMS Muon Detectors, CERN-LHCC-2017-012, CMS-TDR-016, <https://cds.cern.ch/record/2283189>.
- [8] CMS Collaboration, The Phase-2 Upgrade of the CMS Beam Radiation Instrumentation and Luminosity Detectors, CERN-LHCC-2021-008, CMS-TDR-023, <http://cds.cern.ch/record/2759074>.
- [9] CMS Collaboration, The Phase-2 Upgrade of the CMS Level-1 Trigger, CERN-LHCC-2020-004, CMS-TDR-021, <https://cds.cern.ch/record/2714892>.
- [10] CMS Collaboration, The Phase-2 Upgrade of the CMS Data Acquisition and High Level Trigger, CERN-LHCC-2021-007, CMS-TDR-022, <https://cds.cern.ch/record/2759072>.
- [11] J.M. Wanczyk, Upgraded CMS Fast Beam Condition Monitor for LHC Run 3 Online Luminosity and Beam Induced Background Measurements, CMS-CR-2022-144, presented at 11th International Beam Instrumentation Conference (IBIC 2022), Cracow, Poland, 11 - 15 Sep 2022, <https://cds.cern.ch/record/2827594>.