

Package ‘rb3’

July 14, 2024

Title Download and Parse Public Data Released by B3 Exchange

Description Download and parse public files released by B3 and convert them into useful formats and data structures common to data analysis practitioners.

Version 0.0.11

License MIT + file LICENSE

Depends R (>= 4.1.0),

Imports bizdays, stringr, proto, cli, readr, dplyr, rvest, httr, jsonlite, purrr, ascii, rlang, methods, yaml, digest, base64enc, XML, readxl, tidyr

Suggests testthat, knitr, DT, miniUI, shiny, xtable, rmarkdown, ggplot2, covr, scales, magrittr, tibble, withr, vcr (>= 0.6.0)

Collate 'rb3-package.R' 'util.R' 'transmute.R' 'fields.R' 'handlers.R' 'marketdata.R' 'download-data.R' 'file.R' 'convert_to.R' 'scraper-futures.R' 'scraper-yc.R' 'scraper-cotahist.R' 'scraper-indexes.R' 'scraper-company.R' 'addin-show-templates.R' 'addin-display-template.R' 'readers.R' 'downloaders.R' 'zzz.R'

BugReports <https://github.com/ropensci/rb3/issues>

URL <https://github.com/ropensci/rb3>, <http://ropensci.github.io/rb3/>

VignetteBuilder knitr

RoxygenNote 7.3.2

Config/testthat/edition 3

Encoding UTF-8

NeedsCompilation no

Author Wilson Freitas [aut, cre],
Marcelo Perlin [aut]

Maintainer Wilson Freitas <wilson.freitas@gmail.com>

Repository CRAN

Date/Publication 2024-07-13 23:00:02 UTC

Contents

cachedir	2
clearcache	3
code2month	3
company_cash_dividends_get	4
company_info_get	5
company_stock_dividends_get	5
company_subscriptions_get	6
convert_to	7
cotahist-extracts	8
cotahist-options-superset	10
cotahist_get	11
display_template	12
download_marketdata	12
futures_get	13
indexes_get	14
indexes_last_update	15
indexreport_get	15
index_by_segment_get	16
index_comp_get	17
index_get	18
index_weights_get	19
maturity2date	19
read_marketdata	20
show_templates	21
yc_get	22
yc_superset	24
Index	26

cachedir	<i>Returns rb3 package cache directory</i>
----------	--

Description

Returns rb3 package cache directory

Usage

```
cachedir()
```

Details

In order to set a default directory for cache, which is a good idea for those who want to increase data historically, the option `rb3.cachedir` can be set. Once it is set, the defined directory will be used as the default `cachedir`.

Value

a string with the file path of rb3 cache directory

Examples

```
cachedir()
```

clearcache	<i>Clear cache directory</i>
------------	------------------------------

Description

Clear cache directory

Usage

```
clearcache()
```

Value

Has no return

Examples

```
## Not run:  
clearcache()  
  
## End(Not run)
```

code2month	<i>Get month from maturity code</i>
------------	-------------------------------------

Description

Get the corresponding month for the string that represent maturities of futures contracts.

Usage

```
code2month(x)
```

Arguments

x a character with letters that represent the month of maturity of futures contracts.

Value

a vector of integers

Examples

```
code2month(c("F", "G", "H", "J", "K", "M", "N", "Q", "U", "V", "X", "Z"))
code2month(c("JAN", "FEV", "MAR", "NOV", "DEZ"))
```

company_cash_dividends_get

Gets company's dividends in cash

Description

Gets a list of all dividends in cash paid by the company. *A cash dividend is a payment made by a company out of its earnings to investors in the form of cash.* (<https://www.investopedia.com/>)

Usage

```
company_cash_dividends_get(code, cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

code	Represents the company, can be the stock symbol, like PETR4 or the first four characters PETR
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)

Details

The code parameter can be the stock symbol, but the returned data refers to the company, always. The returned data.frame has all company's symbols that paid dividends in cash.

Value

data.frame with company information

Examples

```
## Not run:
company_cash_dividends_get(c("PETR", "VALE", "MGLU"))

## End(Not run)
```

company_info_get	<i>Gets information about the company</i>
------------------	---

Description

Gets informations like sector, subsector, segment, total number of shares and many more.

Usage

```
company_info_get(code, cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

code	Represents the company, can be the stock symbol, like PETR4 or the first four characters PETR
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)

Details

The code parameter can be the stock symbol, but the returned data refers to the company, always.

Value

data.frame with company information

Examples

```
## Not run:  
company_info_get(c("PETR", "VALE", "MGLU"))  
  
## End(Not run)
```

company_stock_dividends_get	<i>Gets company's stocks dividends</i>
-----------------------------	--

Description

Gets a list of all stocks dividends paid by the company. *A stock dividend is a payment to shareholders that consists of additional shares rather than cash.* (<https://www.investopedia.com/>)

Usage

```
company_stock_dividends_get(code, cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

code	Represents the company, can be the stock symbol, like PETR4 or the first four characters PETR
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)

Details

The code parameter can be the stock symbol, but the returned data refers to the company, always. The returned data.frame has all company's symbols that paid dividends in stocks.

Value

data.frame with all stocks dividends

Examples

```
## Not run:
company_stock_dividends_get(c("PETR", "VALE", "MGLU"))

## End(Not run)
```

company_subscriptions_get

Gets company's subscription rights

Description

Gets a list of all company's subscription rights. *A subscription right is the right of existing shareholders in a company to retain an equal percentage ownership by subscribing to new stock issuances at or below market prices.* (<https://www.investopedia.com/>)

Usage

```
company_subscriptions_get(code, cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

code	Represents the company, can be the stock symbol, like PETR4 or the first four characters PETR
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)

Details

The code parameter can be the stock symbol, but the returned data refers to the company, always. The returned data.frame has all company's symbols that have issued subscription rights.

Value

data.frame with company information

Examples

```
## Not run:  
company_subscriptions_get(c("PDGR", "VALE", "MGLU"))  
  
## End(Not run)
```

convert_to

Converts B3 messy files to structured formats

Description

Convert B3 files to structured formats based on the template.

Usage

```
convert_to(  
  filename,  
  template = NULL,  
  parse_fields = TRUE,  
  format = "csv",  
  destdir = NULL  
)
```

Arguments

filename	a string containing a path for the file.
template	a string with the template name.
parse_fields	a logical indicating if the fields must be parsed.
format	output format
destdir	a string with destination directory to save converted file

Value

a string with the file path of generated file.

See Also

read_marketdata

Examples

```
## Not run:  
f <- system.file("extdata/Indic.txt", package = "rb3")  
res <- convert_to(f, output_format = "csv")  
res <- convert_to(f, output_format = "json")  
  
## End(Not run)
```

cotahist-extracts

Extract data from COTAHIST dataset

Description

Extracts specific data from COTAHIST dataset: stocks, funds, BDRs, ETFs, UNITs, options on stocks, options on indexes, ...

Usage

```
cotahist_equity_get(x)  
  
cotahist_bdrs_get(x)  
  
cotahist_units_get(x)  
  
cotahist_etfs_get(x)  
  
cotahist_fiis_get(x)  
  
cotahist_fidcs_get(x)  
  
cotahist_fiagros_get(x)  
  
cotahist_indexes_get(x)  
  
cotahist_equity_options_get(x)  
  
cotahist_index_options_get(x)  
  
cotahist_funds_options_get(x)  
  
cotahist_get_symbols(x, symbols)
```

Arguments

x	COTAHIST dataset returned from <code>cotahist_get</code> .
symbols	list of symbols to extract market data from cotahist

Value

a data.frame with prices, volume, traded quantities informations

Examples

```
## Not run:
df <- cotahist_equity_get(x)

## End(Not run)
## Not run:
df <- cotahist_brds_get(x)

## End(Not run)
## Not run:
df <- cotahist_units_get(x)

## End(Not run)
## Not run:
df <- cotahist_etfs_get(x)

## End(Not run)
## Not run:
df <- cotahist_fiis_get(x)

## End(Not run)
## Not run:
df <- cotahist_fidcs_get(x)

## End(Not run)
## Not run:
df <- cotahist_fiagros_get(x)

## End(Not run)
## Not run:
df <- cotahist_indexes_get(x)

## End(Not run)
## Not run:
df <- cotahist_equity_options_get(x)

## End(Not run)
## Not run:
df <- cotahist_index_options_get(x)

## End(Not run)
## Not run:
df <- cotahist_funds_options_get(x)

## End(Not run)
## Not run:
df <- cotahist_get_symbols(x, c("BBDC4", "ITSA4", "JHSF3"))
```

```
## End(Not run)
```

```
cotahist-options-superset
```

Extracts equity option superset of data

Description

Equity options superset is a dataframe that brings together all data regarding equities, equity options and interest rates. This data forms a complete set (superset) up and ready to run options models, implied volatility calculations and volatility models.

Usage

```
cotahist_equity_options_superset(ch, yc)
```

```
cotahist_options_by_symbol_superset(symbol, ch, yc)
```

Arguments

ch	cotahist data structure
yc	yield curve
symbol	character with the name of the stock

Value

A dataframe with data of equities, equity options, and interest rates.

Examples

```
## Not run:  
refdate <- Sys.Date() - 1  
ch <- cotahist_get(refdate, "daily")  
yc <- yc_get(refdate)  
ch_ss <- cotahist_equity_options_superset(ch, yc)  
petr4_ch_ss <- cotahist_options_by_symbol_superset("PETR4", ch, yc)  
  
## End(Not run)
```

cotahist_get	<i>Get COTAHIST data from B3</i>
--------------	----------------------------------

Description

Download COTAHIST file and parses it returning structured data into R objects.

Usage

```
cotahist_get(  
  refdate,  
  type = c("yearly", "monthly", "daily"),  
  cache_folder = cachedir(),  
  do_cache = TRUE  
)
```

Arguments

refdate	the reference date used to download the file. This reference date will be formatted as year/month/day according to the given type. Accepts ISO formatted date strings.
type	a string with yearly for all data of the given year, monthly for all data of the given month and daily for the given day.
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE) All valuable information is in the HistoricalPrices element of the returned list. Header and Trailer have informations regarding file generation. The HistoricalPrices element has a data.frame with data of many assets traded in the stock exchange: stocks, bdrs, funds, ETFs, equity options, forward contracts on equities and a few warrants due to some corporate events.

Value

a list with 3 data.frames: Header, HistoricalPrices, Trailer.

Examples

```
## Not run:  
# get all data to the year of 2001  
df_2001 <- cotahist_get("2001-01-01", "yearly")  
# get data of January of 2001  
df_200101 <- cotahist_get("2001-01-01", "monthly")  
# get data of 2001-01-02  
df_daily <- cotahist_get("2001-01-02", "daily")  
  
## End(Not run)
```

display_template *Display templates*

Description

display_template opens an **RStudio gadget** and **addin** that allows users to query for specific attributes of templates.

Usage

```
display_template()
```

Value

Addin has no return

Examples

```
## Not run:
display_template()

## End(Not run)
```

download_marketdata *Download datasets*

Description

Download datasets for a given template.

Usage

```
download_marketdata(template, cache_folder = cachedir(), do_cache = TRUE, ...)
```

Arguments

template	the template name
cache_folder	Location of cache folder (default = cachedir())
do_cache	a logical indicating if the existing file (previously downloaded) should be used or replaced.
...	additional arguments

Value

a string with the file path of downloaded file or NULL if download fails.

This function downloads data sets for those templates that specifies a downloader attribute. If dest is not provided, cache_folder is used and a file with template id is saved inside it.

Examples

```
## Not run:
fname <- download_marketdata("CDIIDI")

## End(Not run)
```

futures_get

Get futures prices from trading session settlements page

Description

Scrape page https://www.b3.com.br/en_us/market-data-and-indices/data-services/market-data/historical-data/derivatives/trading-session-settlements/ to get futures prices.

Usage

```
futures_mget(
  first_date = Sys.Date() - 5,
  last_date = Sys.Date(),
  by = 1,
  cache_folder = cachedir(),
  do_cache = TRUE
)

futures_get(refdate = Sys.Date(), cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

first_date	First date ("YYYY-MM-DD") to yc_mget multiple curves
last_date	Last date ("YYYY-MM-DD") to yc_mget multiple curves
by	Number of days in between fetched dates (default = 1) in yc_mget
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)
	futures_get returns the future contracts for the given date and futures_mget returns future contracts for multiple dates in a given range.
refdate	Specific date ("YYYY-MM-DD") to yc_get single curve

Value

data.frame with futures prices.

Examples

```
## Not run:
df <- futures_get("2022-04-18", "2022-04-22")

## End(Not run)
## Not run:
df_fut <- futures_get(Sys.Date())
head(df_fut)

## End(Not run)
```

indexes_get	<i>Get B3 indexes available</i>
-------------	---------------------------------

Description

Gets B3 indexes available.

Usage

```
indexes_get(cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)

Value

a character vector with symbols of indexes available

Examples

```
## Not run:
indexes_get()

## End(Not run)
```

indexes_last_update *Get the date of indexes composition last update*

Description

Gets the date where the indexes have been updated lastly.

Usage

```
indexes_last_update(cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

cache_folder Location of cache folder (default = cachedir())
do_cache Whether to use cache or not (default = TRUE)

Value

the Date when the indexes have been updated

Examples

```
## Not run:  
indexes_last_update()  
  
## End(Not run)
```

indexreport_get *Fetches indexes data from B3*

Description

Downloads index data from B3 website https://www.b3.com.br/pt_br/market-data-e-indices/servicos-de-dados/market-data/historico/boletins-diarios/pesquisa-por-pregao/pesquisa-por-pregao/.

Usage

```
indexreport_mget(  
  first_date = Sys.Date() - 5,  
  last_date = Sys.Date(),  
  by = 1,  
  cache_folder = cachedir(),  
  do_cache = TRUE  
)  
  
indexreport_get(  

```

```

    refdate = Sys.Date(),
    cache_folder = cachedir(),
    do_cache = TRUE
  )

```

Arguments

first_date	First date ("YYYY-MM-DD") to yc_mget multiple curves
last_date	Last date ("YYYY-MM-DD") to yc_mget multiple curves
by	Number of days in between fetched dates (default = 1) in yc_mget
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)
refdate	Specific date ("YYYY-MM-DD") to yc_get single curve

Details

indexreport_get returns index data for the given date and indexreport_mget returns index data for a given range of dates.

Value

A dataframe with index data (OHLC, average and daily oscillation)

Examples

```

## Not run:
df_ir <- indexreport_mget(Sys.Date() - 5, Sys.Date())
head(df_ir)

## End(Not run)
## Not run:
df_ir <- indexreport_get(Sys.Date())
head(df_ir)

## End(Not run)

```

index_by_segment_get *Get B3 indexes available*

Description

Gets B3 indexes available.

Usage

```
index_by_segment_get(index_name, cache_folder = cachedir(), do_cache = TRUE)
```


Arguments

index_name a string with the index name
 cache_folder Location of cache folder (default = cachedir())
 do_cache Whether to use cache or not (default = TRUE)

Value

A dataframe with the index stocks, their weights, segments and positions.

Examples

```
## Not run:
index_by_segment_get("IBOV")

## End(Not run)
```

index_comp_get	<i>Get composition of B3 indexes</i>
----------------	--------------------------------------

Description

Gets the composition of listed B3 indexes.

Usage

```
index_comp_get(index_name, cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

index_name a string with the index name
 cache_folder Location of cache folder (default = cachedir())
 do_cache Whether to use cache or not (default = TRUE)

Value

a character vector with symbols that belong to the given index name

Examples

```
## Not run:
index_comp_get("IBOV")

## End(Not run)
```

index_get	<i>Get index historical data</i>
-----------	----------------------------------

Description

Gets historical data from B3 indexes

Usage

```
index_get(  
  index_name,  
  first_date,  
  last_date = Sys.Date(),  
  cache_folder = cachedir(),  
  do_cache = TRUE  
)
```

Arguments

index_name	a string with the index name
first_date	First date
last_date	Last date
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)

Value

A data.frame/tibble with index data

Examples

```
## Not run:  
index_get("IBOV", as.Date("1977-01-01"), as.Date("1999-12-31"))  
  
## End(Not run)
```

index_weights_get	<i>Get the assets weights of B3 indexes</i>
-------------------	---

Description

Gets the assets weights of B3 indexes.

Usage

```
index_weights_get(index_name, cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

index_name	a string with the index name
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)

Value

data.frame with symbols that belong to the given index name with its weights and theoretical positions.

Examples

```
## Not run:  
index_weights_get("IBOV")  
  
## End(Not run)
```

maturity2date	<i>Get maturity date from maturity code</i>
---------------	---

Description

Get the corresponding maturity date for the three characters string that represent maturity of futures contracts.

Usage

```
maturity2date(x, expr = "first day", refdate = NULL)
```

Arguments

x	a character vector with three letters string that represent maturity of futures contracts.
expr	a string which indicates the day to use in maturity date. See bizdays::getdate for more details on this argument.
refdate	reference date to be passed. It is necessary to convert old maturities like JAN0, that can be Jan/2000 or Jan/2010. If refdate is greater than 2001-01-01 JAN0 is converted to Jan/2010, otherwise, Jan/2000.

Value

a Date vector with maturity dates

Examples

```
maturity2date(c("F22", "F23", "G23", "H23", "F45"), "first day")
maturity2date(c("F23", "K35"), "15th day")
maturity2date(c("AG02", "SET2"), "first day")
```

read_marketdata	<i>Read and parses files delivered by B3</i>
-----------------	--

Description

B3, and previously BMF&Bovespa, used to deliver many files with a diverse set of valuable data and informations that can be used to study of can be called of marketdata. There are files with informations about futures, option, interest rates, currency rates, bonds and many other subjects.

Usage

```
read_marketdata(
  filename,
  template = NULL,
  parse_fields = TRUE,
  do_cache = TRUE
)
```

Arguments

filename	a string containing a path for the file.
template	a string with the template name.
parse_fields	a logical indicating if the fields must be parsed.
do_cache	Whether to use cache or not (default = TRUE)

Each template has a default value for the filename, if the given file name equals one template filename attribute, the matched template is used to parse the file. Otherwise the template must be provided.

The function show_templates can be used to view the available templates and their default filenames.

Value

data.frame of a list of data.frame containing data parsed from files.

See Also

show_templates display_template

Examples

```
## Not run:  
# Eletro.txt matches the filename of Eletro template  
path <- "Eletro.txt"  
df <- read_marketdata(path)  
path <- "Indic.txt"  
df <- read_marketdata(path, template = "Indic")  
path <- "PUWEB.TXT"  
df <- read_marketdata(path, template = "PUWEB")  
  
## End(Not run)
```

show_templates	<i>Show templates.</i>
----------------	------------------------

Description

display_template opens an **RStudio gadget** and **addin** that allows users to view the available templates.

Usage

```
show_templates()
```

Value

Addin has no return

Examples

```
## Not run:  
show_templates()  
  
## End(Not run)
```

 yc_get

Fetches Yield Curve Data from B3

Description

Downloads yield curve data from B3 website <https://www2.bmf.com.br/pages/portal/bmfbovespa/lumis/lum-texas-referenciais-bmf-ptBR.asp>. Particularly, we import data for

- DI X Pre (yc_get)
- Cupom limpo (yc_usd_get)
- DI x IPCA (yc_ipca_get)

Usage

```
yc_mget(
  first_date = Sys.Date() - 5,
  last_date = Sys.Date(),
  by = 1,
  cache_folder = cachedir(),
  do_cache = TRUE
)
```

```
yc_get(refdate = Sys.Date(), cache_folder = cachedir(), do_cache = TRUE)
```

```
yc_ipca_mget(
  first_date = Sys.Date() - 5,
  last_date = Sys.Date(),
  by = 1,
  cache_folder = cachedir(),
  do_cache = TRUE
)
```

```
yc_ipca_get(refdate = Sys.Date(), cache_folder = cachedir(), do_cache = TRUE)
```

```
yc_usd_mget(
  first_date = Sys.Date() - 5,
  last_date = Sys.Date(),
  by = 1,
  cache_folder = cachedir(),
  do_cache = TRUE
)
```

```
yc_usd_get(refdate = Sys.Date(), cache_folder = cachedir(), do_cache = TRUE)
```

Arguments

`first_date` First date ("YYYY-MM-DD") to yc_mget multiple curves

last_date	Last date ("YYYY-MM-DD") to yc_mget multiple curves
by	Number of days in between fetched dates (default = 1) in yc_mget
cache_folder	Location of cache folder (default = cachedir())
do_cache	Whether to use cache or not (default = TRUE)
refdate	Specific date ("YYYY-MM-DD") to yc_get single curve

Details

See https://www.b3.com.br/data/files/8B/F5/11/68/5391F61043E561F6AC094EA8/Manual_de_Curvas.pdf for more details.

yc_get returns the yield curve for the given date and yc_mget returns multiple yield curves for a given range of dates.

yc_ipca_get returns the yield curve of real interest rates for the given date and yc_ipca_mget returns multiple yield curves of real interest rates for a given range of dates. These real interest rates consider IPCA as its inflation index.

yc_usd_get returns the yield curve of nominal interest rates for USD in Brazil for the given date and yc_usd_mget returns multiple yield curves of nominal interest rates for USD in Brazil for a given range of dates. These real interest rates consider IPCA as its inflation index.

Value

A dataframe/tibble with yield curve data

Examples

```
## Not run:
df_yc <- yc_mget(first_date = Sys.Date() - 5, last_date = Sys.Date())
head(df_yc)

## End(Not run)
## Not run:
df_yc <- yc_get(Sys.Date())
head(df_yc)

## End(Not run)
## Not run:
df_yc_ipca <- yc_ipca_mget(
  first_date = Sys.Date() - 5,
  last_date = Sys.Date()
)
head(df_yc_ipca)

## End(Not run)
## Not run:
df_yc_ipca <- yc_ipca_get(Sys.Date())
head(df_yc_ipca)

## End(Not run)
## Not run:
```

```
df_yc_usd <- yc_usd_mget(  
  first_date = Sys.Date() - 5,  
  last_date = Sys.Date()  
)  
head(df_yc_usd)  
  
## End(Not run)  
## Not run:  
df_yc_usd <- yc_usd_get(Sys.Date())  
head(df_yc_usd)  
  
## End(Not run)
```

yc_superset

Creates superset with yield curves and futures

Description

Creates superset with yield curves and future contracts indicating the terms that match with futures contracts maturities.

Usage

```
yc_superset(yc, fut)  
  
yc_usd_superset(yc, fut)  
  
yc_ipca_superset(yc, fut)
```

Arguments

yc	yield curve dataset
fut	futures dataset

Value

A dataframe with yield curve flagged with futures maturities.

Examples

```
## Not run:  
fut <- futures_get(Sys.Date() - 1)  
  
yc <- yc_get(Sys.Date() - 1)  
yc_superset(yc, fut)  
  
yc_usd <- yc_usd_get(Sys.Date() - 1)  
yc_usd_superset(yc_usd, fut)
```



```
yc_ipca <- yc_ipca_get(Sys.Date() - 1)
yc_ipca_superset(yc_ipca, fut)

## End(Not run)
```

Index

cachedir, 2
clearcache, 3
code2month, 3
company_cash_dividends_get, 4
company_info_get, 5
company_stock_dividends_get, 5
company_subscriptions_get, 6
convert_to, 7
cotahist-extracts, 8
cotahist-options-superset, 10
cotahist_bdrs_get (cotahist-extracts), 8
cotahist_equity_get
 (cotahist-extracts), 8
cotahist_equity_options_get
 (cotahist-extracts), 8
cotahist_equity_options_superset
 (cotahist-options-superset), 10
cotahist_etfs_get (cotahist-extracts), 8
cotahist_fiagros_get
 (cotahist-extracts), 8
cotahist_fidcs_get (cotahist-extracts),
 8
cotahist_fiis_get (cotahist-extracts), 8
cotahist_funds_options_get
 (cotahist-extracts), 8
cotahist_get, 11
cotahist_get_symbols
 (cotahist-extracts), 8
cotahist_index_options_get
 (cotahist-extracts), 8
cotahist_indexes_get
 (cotahist-extracts), 8
cotahist_options_by_symbol_superset
 (cotahist-options-superset), 10
cotahist_units_get (cotahist-extracts),
 8

display_template, 12
download_marketdata, 12

futures_get, 13
futures_mget (futures_get), 13

index_by_segment_get, 16
index_comp_get, 17
index_get, 18
index_weights_get, 19
indexes_get, 14
indexes_last_update, 15
indexreport_get, 15
indexreport_mget (indexreport_get), 15

maturity2date, 19

read_marketdata, 20

show_templates, 21

yc_get, 22
yc_ipca_get (yc_get), 22
yc_ipca_mget (yc_get), 22
yc_ipca_superset (yc_superset), 24
yc_mget (yc_get), 22
yc_superset, 24
yc_usd_get (yc_get), 22
yc_usd_mget (yc_get), 22
yc_usd_superset (yc_superset), 24