

Load Balancing Epic EHR

Version 1.1.0




Table of Contents

1. About this Guide	3
2. Loadbalancer.org Appliances Supported	3
3. Software Versions Supported	3
3.1. Loadbalancer.org Appliance	3
3.2. Epic EHR	3
4. Epic EHR	3
5. Load Balancing Epic EHR	3
5.1. Persistence (aka Server Affinity)	4
5.2. Virtual Service (VIP) Requirements	4
5.3. Port Requirements	4
6. Deployment Concept	4
7. Loadbalancer.org Appliance – the Basics	5
7.1. Virtual Appliance	5
7.2. Initial Network Configuration	5
7.3. Accessing the Appliance WebUI	5
7.3.1. Main Menu Options	7
7.4. Appliance Software Update	7
7.4.1. Online Update	7
7.4.2. Offline Update	8
7.5. Ports Used by the Appliance	8
7.6. HA Clustered Pair Configuration	9
8. Appliance Configuration for Epic EHR	9
8.1. Configuring VIP 1 – Hyperspace	9
8.1.1. Configuring the Virtual Service (VIP)	9
8.1.2. Defining the Real Servers (RIPs)	10
8.2. Configuring VIP 2 – Hyperspace Redirect	10
8.2.1. Configuring the Virtual Service (VIP)	11
8.3. Configuring VIP 3 – MyChart (Optional)	11
8.3.1. Configuring the Virtual Service (VIP)	11
8.3.2. Defining the Real Servers (RIPs)	12
8.4. Configuring VIP 4 – MyChart Redirect (Optional)	12
8.4.1. Configuring the Virtual Service (VIP)	13
8.5. Finalizing the Configuration	13
9. Testing & Verification	14
9.1. Using System Overview	14
10. Technical Support	14
11. Further Documentation	14
12. Appendix	15
12.1. Configuring HA - Adding a Secondary Appliance	15
12.1.1. Non-Replicated Settings	15
12.1.2. Configuring the HA Clustered Pair	16
13. Document Revision History	18

1. About this Guide

This guide details the steps required to configure a load balanced Epic EHR environment utilizing Loadbalancer.org appliances. It covers the configuration of the load balancers and also any Epic EHR configuration changes that are required to enable load balancing.

For more information about initial appliance deployment, network configuration and using the Web User Interface (WebUI), please also refer to the [Administration Manual](#).

2. Loadbalancer.org Appliances Supported

All our products can be used with Epic EHR. For full specifications of available models please refer to <https://www.loadbalancer.org/products/enterprise>.

Some features may not be available or fully supported in all cloud platforms due to platform specific limitations. For more details, please refer to the "Main Differences to our Standard (Non-Cloud) Product" section in the appropriate cloud platform Quick Start Guide or check with Loadbalancer.org support.

3. Software Versions Supported

3.1. Loadbalancer.org Appliance

- V8.9.1 and later

 **Note**

The screenshots used throughout this document aim to track the latest Loadbalancer.org software version. If you're using an older version, or the very latest, the screenshots presented here may not match your WebUI exactly.

3.2. Epic EHR

- All versions

4. Epic EHR

The Epic EHR (Electronic Health Records) software suite brings together essential tools for clinicians and patients in the healthcare space.

Epic Hyperspace is a clinician-facing platform. It's a front-end client used to access most parts of the Epic software suite, including patient charts, prescribing, and even print services.

Epic MyChart is a patient-facing web portal. It gives patients the ability to view their medical records and test results, manage their appointments and prescriptions, and more.

5. Load Balancing Epic EHR

 **Note**

It's highly recommended that you have a working Epic EHR environment first before



implementing the load balancer.

5.1. Persistence (aka Server Affinity)

The Epic EHR applications require sessions to stick to the same real server. Source IP address affinity is used to achieve this.

5.2. Virtual Service (VIP) Requirements

To provide load balancing and HA for Epic EHR, the following VIPs are required:

- Hyperspace
- Hyperspace redirect (to force inbound HTTP traffic to use HTTPS)

Optionally, additional VIPs may be required as follows:


- MyChart
- MyChart redirect (to force inbound HTTP traffic to use HTTPS)

5.3. Port Requirements

The following table shows the ports that are load balanced:

Port	Protocols	Use
80	TCP/HTTP	Redirect to HTTPS (not strictly load balanced)
443	TCP/HTTPS	Web Services

6. Deployment Concept



Note

The load balancer can be deployed as a single unit, although Loadbalancer.org recommends a

clustered pair for resilience & high availability. Please refer to the section [Configuring HA - Adding a Secondary Appliance](#) in the appendix for more details on configuring a clustered pair.

7. Loadbalancer.org Appliance – the Basics

7.1. Virtual Appliance

A fully featured, fully supported 30 day trial is available if you are conducting a PoC (Proof of Concept) deployment. The VA is currently available for VMware, Virtual Box, Hyper-V, KVM, XEN and Nutanix AHV and has been optimized for each Hypervisor. By default, the VA is allocated 2 vCPUs, 4GB of RAM and has a 20GB virtual disk. The Virtual Appliance can be downloaded [here](#).

Note The same download is used for the licensed product, the only difference is that a license key file (supplied by our sales team when the product is purchased) must be applied using the appliance's WebUI.

Note Please refer to [Virtual Appliance Installation](#) and the ReadMe.txt text file included in the VA download for additional information on deploying the VA using the various Hypervisors.

Note The VA has 4 network adapters. For VMware only the first adapter (**eth0**) is connected by default. For HyperV, KVM, XEN and Nutanix AHV all adapters are disconnected by default. Use the network configuration screen within the Hypervisor to connect the required adapters.

7.2. Initial Network Configuration

After boot up, follow the instructions on the appliance console to configure the management IP address, subnet mask, default gateway, DNS servers and other network and administrative settings.

(!) Important Be sure to set a secure password for the load balancer, when prompted during the setup routine.

7.3. Accessing the Appliance WebUI

The WebUI is accessed using a web browser. By default, users are authenticated using Apache authentication. Users can also be authenticated against LDAP, LDAPS, Active Directory or Radius - for more information, please refer to [External Authentication](#).

Note There are certain differences when accessing the WebUI for the cloud appliances. For details, please refer to the relevant [Quick Start / Configuration Guide](#).

1. Using a browser, navigate to the following URL:

<https://<IP-address-configured-during-the-network-setup-wizard>:9443/lbadmin/>

Note You'll receive a warning about the WebUI's SSL certificate. This is due to the default self signed certificate that is used. If preferred, you can upload your own certificate - for more



information, please refer to [Appliance Security Features](#).

Note

If you need to change the port, IP address or protocol that the WebUI listens on, please refer to [Service Socket Addresses](#).

2. Log in to the WebUI using the following credentials:


Username: loadbalancer

Password: <configured-during-network-setup-wizard>

Note

To change the password, use the WebUI menu option: **Maintenance > Passwords**.

Once logged in, the WebUI will be displayed as shown below:



The screenshot shows the Loadbalancer WebUI interface. The top navigation bar includes the Loadbalancer logo, a trial expiration warning, and license information. The main menu on the left includes System Overview, Local Configuration, Cluster Configuration, Maintenance, View Configuration, Reports, Logs, Support, and Live Chat. The System Overview page displays several charts: Network Bandwidth (RX: 28 Min, 2713 Avg, 27344772 Total, TX: 0 Min, 13777 Avg, 138872181 Total), System Load Average (1m, 5m, 15m averages), and Memory Usage. The interface is labeled "Enterprise VA Max".



3. You'll be asked if you want to run the Setup Wizard. Click **Dismiss** if you're following a guide or want to configure the appliance manually. Click **Accept** to start the Setup Wizard.

 **Note**

The Setup Wizard can only be used to configure Layer 7 services.

7.3.1. Main Menu Options

- System Overview** - Displays a graphical summary of all VIPs, RIPv and key appliance statistics
- Local Configuration** - Configure local host settings such as IP address, DNS, system time etc.
- Cluster Configuration** - Configure load balanced services such as VIPs & RIPv
- Maintenance** - Perform maintenance tasks such as service restarts and creating backups
- View Configuration** - Display the saved appliance configuration settings
- Reports** - View various appliance reports & graphs
- Logs** - View various appliance logs
- Support** - Create a support download, contact the support team & access useful links
- Live Chat** - Start a live chat session with one of our Support Engineers

7.4. Appliance Software Update

We recommend that the appliance is kept up to date to ensure that you benefit from the latest bug fixes, security updates and feature improvements. Both online and offline update are supported.

 **Note**

For full details, please refer to [Appliance Software Update](#) in the Administration Manual.

 **Note**

Services may need to be restarted/reloaded after the update process completes or in some cases a full appliance restart may be required. We therefore recommend performing the update during a maintenance window.

7.4.1. Online Update

The appliance periodically contacts the Loadbalancer.org update server (**update.loadbalancer.org**) and checks for updates. This is the default behavior and can be disabled if preferred. If an update is found, a notification similar to the example below will be displayed at the top of the WebUI:

Information: Update 8.13.2 is now available for this appliance.

Online Update

Click **Online Update**. A summary of all new features, improvements, bug fixes and security updates included in the update will be displayed. Click **Update** at the bottom of the page to start the update process.

 **Important**

Do not navigate away whilst the update is ongoing, this may cause the update to fail.

The update can take several minutes depending on download speed and upgrade version. Once complete, the following message will be displayed:



Information: Update completed successfully. Return to system overview.

If services need to be reloaded/restarted or the appliance needs a full restart, you'll be prompted accordingly.

7.4.2. Offline Update

If the appliance does not have access to the Internet, offline update can be used.

To check for the latest version, please refer to our product roadmap page available [here](#). To obtain the latest offline update files contact support@loadbalancer.org.

To perform an offline update:

1. Using the WebUI, navigate to: **Maintenance > Software Update**.
2. Select **Offline Update**.
3. The following screen will be displayed:

Software Update

Offline Update

The following steps will lead you through offline update.

1. Contact **Loadbalancer.org support** to obtain the offline update archive and checksum.
2. Save the archive and checksum to your local machine.
3. Select the archive and checksum files in the upload form below.
4. Click *Upload and Install* to begin the update process.

Archive: No file chosen

Checksum: No file chosen

4. Select the **Archive** and **Checksum** files.
5. Click **Upload and Install**.
6. If services need to be reloaded/restarted or the appliance needs a full restart, you'll be prompted accordingly.

7.5. Ports Used by the Appliance

By default, the appliance uses the following TCP & UDP ports:

Protocol	Port	Purpose
TCP	22 *	SSH
TCP & UDP	53 *	DNS / GSLB
TCP & UDP	123	NTP



Protocol	Port	Purpose
TCP & UDP	161 *	SNMP
UDP	6694	Heartbeat between Primary & Secondary appliances in HA mode
TCP	7778	HAProxy persistence table replication
TCP	9000 *	Gateway service (Centralized/Portal Management)
TCP	9080 *	WebUI - HTTP (disabled by default)
TCP	9081 *	Nginx fallback page
TCP	9443 *	WebUI - HTTPS
TCP	25565 *	Shuttle service (Centralized/Portal Management)

 **Note**

The ports used for SSH, GSLB, SNMP, the WebUI, the fallback page, the gateway service and the shuttle service can be changed if required. For more information, please refer to [Service Socket Addresses](#).

7.6. HA Clustered Pair Configuration

Loadbalancer.org recommend that load balancer appliances are deployed in pairs for high availability. In this guide a single unit is deployed first, adding a secondary unit is covered in the section [Configuring HA - Adding a Secondary Appliance](#) of the appendix.

8. Appliance Configuration for Epic EHR

8.1. Configuring VIP 1 – Hyperspace

8.1.1. Configuring the Virtual Service (VIP)

1. Using the web user interface, navigate to *Cluster Configuration > Layer 7 – Virtual Services* and click on **Add a new Virtual Service**.
2. Define the *Label* for the virtual service as required, e.g. **Hyperspace**.
3. Set the *Virtual Service IP Address* field to the required IP address, e.g. **192.168.85.150**.
4. Set the *Ports* field to **443**.
5. Set the *Layer 7 Protocol* to **TCP Mode**.
6. Click **Update** to create the virtual service.



Layer 7 - Add a new Virtual Service

Virtual Service		[Advanced +]
Label	Hyperspace	?
IP Address	192.168.85.150	?
Ports	443	?
Protocol		
Layer 7 Protocol	TCP Mode	?
		Cancel Update

7. Click **Modify** next to the newly created VIP.
8. In the **Persistence** section click **Advanced** to expand the menu.
9. Set **Timeout** to **60** (the default units are minutes).
10. Click **Update**.

Persistence		[Advanced]
Persistence Mode	Source IP	?
Persistence	Timeout	60

8.1.2. Defining the Real Servers (RIPs)

1. Using the web user interface, navigate to *Cluster Configuration > Layer 7 – Real Servers* and click on **Add a new Real Server** next to the newly created VIP.
2. Define the **Label** for the real server as required, e.g. **Hyperspace_Srv_1**.
3. Set the **Real Server IP Address** field to the required IP address, e.g. **192.168.85.200**.
4. Click **Update**.
5. Repeat these steps to add additional servers as required.

Layer 7 Add a new Real Server - Hyperspace

Label	Hyperspace_Srv_1	?
Real Server IP Address	192.168.85.200	?
Real Server Port		?
Re-Encrypt to Backend	<input type="checkbox"/>	?
Weight	100	?
		Cancel Update

8.2. Configuring VIP 2 – Hyperspace Redirect



8.2.1. Configuring the Virtual Service (VIP)

1. Using the web user interface, navigate to *Cluster Configuration > Layer 7 – Virtual Services* and click on **Add a new Virtual Service**.
2. Define the *Label* for the virtual service as required, e.g. **Hyperspace_redirect**.
3. Set the *Virtual Service IP Address* field to the **same** IP address used for the Hyperspace VIP, e.g. **192.168.85.150**.
4. Set the *Ports* field to **80**.
5. Set the *Layer 7 Protocol* to **HTTP Mode**.
6. Click **Update** to create the virtual service.

Layer 7 - Add a new Virtual Service

Virtual Service		[Advanced +]
Label	Hyperspace_redirect	?
IP Address	192.168.85.150	?
Ports	80	?
Protocol		
Layer 7 Protocol	HTTP Mode	?
		Cancel Update

7. Click **Modify** next to the newly created VIP.
8. In the *Other* section click **Advanced** to expand the menu.
9. Set *Force to HTTPS* to **Yes**.
10. Click **Update**.

Force to HTTPS Yes No

8.3. Configuring VIP 3 – MyChart (Optional)

8.3.1. Configuring the Virtual Service (VIP)

1. Using the web user interface, navigate to *Cluster Configuration > Layer 7 – Virtual Services* and click on **Add a new Virtual Service**.
2. Define the *Label* for the virtual service as required, e.g. **MyChart**.
3. Set the *Virtual Service IP Address* field to the required IP address, e.g. **192.168.85.151**.
4. Set the *Ports* field to **443**.
5. Set the *Layer 7 Protocol* to **TCP Mode**.
6. Click **Update** to create the virtual service.



Layer 7 - Add a new Virtual Service

Virtual Service		[Advanced +]
Label	MyChart	?
IP Address	192.168.85.151	?
Ports	443	?
Protocol		
Layer 7 Protocol	TCP Mode	?
		Cancel Update

7. Click **Modify** next to the newly created VIP.
8. In the **Persistence** section click **Advanced** to expand the menu.
9. Set **Timeout** to **60** (the default units are minutes).
10. Click **Update**.

Persistence		[Advanced]
Persistence Mode	Source IP	?
Persistence	Timeout	60

8.3.2. Defining the Real Servers (RIPs)

1. Using the web user interface, navigate to *Cluster Configuration > Layer 7 – Real Servers* and click on **Add a new Real Server** next to the newly created VIP.
2. Define the **Label** for the real server as required, e.g. **MyChart_Srv_1**.
3. Set the **Real Server IP Address** field to the required IP address, e.g. **192.168.85.210**.
4. Click **Update**.
5. Repeat these steps to add additional servers as required.

Layer 7 Add a new Real Server - MyChart

Label	MyChart_Srv_1	?
Real Server IP Address	192.168.85.210	?
Real Server Port		?
Re-Encrypt to Backend	<input type="checkbox"/>	?
Weight	100	?
		Cancel Update

8.4. Configuring VIP 4 – MyChart Redirect (Optional)



Note

If the optional *MyChart* VIP has been configured then this redirect VIP must also be configured to ensure proper operation of the load balanced *MyChart* service.

8.4.1. Configuring the Virtual Service (VIP)

1. Using the web user interface, navigate to *Cluster Configuration > Layer 7 – Virtual Services* and click on **Add a new Virtual Service**.
2. Define the *Label* for the virtual service as required, e.g. **MyChart_redirect**.
3. Set the *Virtual Service IP Address* field to the **same** IP address used for the *MyChart* VIP, e.g. **192.168.85.151**.
4. Set the *Ports* field to **80**.
5. Set the *Layer 7 Protocol* to **HTTP Mode**.
6. Click **Update** to create the virtual service.

Layer 7 - Add a new Virtual Service

Virtual Service		[Advanced +]
Label	MyChart_redirect	?
IP Address	192.168.85.151	?
Ports	80	?
Protocol		
Layer 7 Protocol	HTTP Mode	?
		Cancel Update

7. Click **Modify** next to the newly created VIP.
8. In the *Other* section click **Advanced** to expand the menu.
9. Set *Force to HTTPS* to **Yes**.
10. Click **Update**.

Force to HTTPS

Yes No

8.5. Finalizing the Configuration

To apply the new settings, HAProxy must be reloaded. This can be done using the button in the "Commit changes" box at the top of the screen or by using the **Restart Services** menu option:

1. Using the WebUI, navigate to: *Maintenance > Restart Services*.
2. Click **Reload HAProxy**.



9. Testing & Verification

Note

For additional guidance on diagnosing and resolving any issues you may have, please also refer to [Diagnostics & Troubleshooting](#).

9.1. Using System Overview

The System Overview can be viewed in the WebUI. It shows a graphical view of all VIPs & RIPS (i.e. the Hyperspace and MyChart servers) and shows the state/health of each server as well as the state of the cluster as a whole. The example below shows that all servers of both services are healthy and available to accept connections:

System Overview

2022-02-21 18:00:20 UTC

VIRTUAL SERVICE	IP	PORTS	CONNNS	PROTOCOL	METHOD	MODE	Health
Hyperspace	192.168.85.150	443	0	TCP	Layer 7	Proxy	
REAL SERVER	IP	PORTS	WEIGHT	CONNNS			
Hyperspace_Srv_1	192.168.85.200	443	100	0	Drain	Halt	
Hyperspace_Srv_2	192.168.85.201	443	100	0	Drain	Halt	
Hyperspace_Srv_3	192.168.85.202	443	100	0	Drain	Halt	
Hyperspace_redir..	192.168.85.150	80	0	HTTP	Layer 7	Proxy	
MyChart	192.168.85.151	443	0	TCP	Layer 7	Proxy	
REAL SERVER	IP	PORTS	WEIGHT	CONNNS			
MyChart_Srv_1	192.168.85.210	443	100	0	Drain	Halt	
MyChart_Srv_2	192.168.85.211	443	100	0	Drain	Halt	
MyChart_redirect..	192.168.85.151	80	0	HTTP	Layer 7	Proxy	

10. Technical Support

For more details about configuring the appliance and assistance with designing your deployment please don't hesitate to contact the support team using the following email address: support@loadbalancer.org.

11. Further Documentation

For additional information, please refer to the [Administration Manual](#).



12. Appendix

12.1. Configuring HA - Adding a Secondary Appliance

Our recommended configuration is to use a clustered HA pair of load balancers to provide a highly available and resilient load balancing solution. We recommend that the Primary appliance is fully configured first, then the Secondary appliance can be added to create an HA pair. Once the HA pair is configured, load balanced services must be configured and modified on the Primary appliance. The Secondary appliance will be automatically kept in sync.

 **Note**

For Enterprise Azure, the HA pair should be configured first. For more information, please refer to the Azure Quick Start/Configuration Guide available in the [documentation library](#)

The clustered HA pair uses Heartbeat to determine the state of the other appliance. Should the active device (normally the Primary) suffer a failure, the passive device (normally the Secondary) will take over.

12.1.1. Non-Replicated Settings

A number of settings are not replicated as part of the Primary/Secondary pairing process and therefore must be manually configured on the Secondary appliance. These are listed by WebUI menu option in the table below:

WebUI Main Menu Option	Sub Menu Option	Description
Local Configuration	Hostname & DNS	Hostname and DNS settings
Local Configuration	Network Interface Configuration	Interface IP addresses, bonding configuration and VLANs
Local Configuration	Routing	Default gateways and static routes
Local Configuration	System Date & time	Time and date related settings
Local Configuration	Physical – Advanced Configuration	Various appliance settings
Local Configuration	Portal Management	Portal management settings
Local Configuration	Security	Security settings
Local Configuration	SNMP Configuration	SNMP settings
Local Configuration	Graphing	Graphing settings
Local Configuration	License Key	Appliance licensing
Maintenance	Backup & Restore	Local XML backups
Maintenance	Software Updates	Appliance software updates
Maintenance	Firewall Script	Firewall (iptables) configuration
Maintenance	Firewall Lockdown Wizard	Appliance management lockdown settings



① Important

Make sure that where any of the above have been configured on the Primary appliance, they're also configured on the Secondary.


12.1.2. Configuring the HA Clustered Pair

ℹ Note

If you have already run the firewall lockdown wizard on either appliance, you'll need to ensure that it is temporarily disabled on both appliances whilst performing the pairing process.

1. Deploy a second appliance that will be the Secondary and configure initial network settings.
2. Using the WebUI on the Primary appliance, navigate to: *Cluster Configuration > High-Availability Configuration*.

Create a Clustered Pair



Local IP address
192.168.110.40


IP address of new peer
192.168.110.41

Password for *loadbalancer* user on peer
••••••••••••

Add new node

3. Specify the IP address and the *loadbalancer* user's password for the Secondary (peer) appliance as shown in the example above.
4. Click **Add new node**.
5. The pairing process now commences as shown below:

Create a Clustered Pair



Primary

IP: 192.168.110.40

Attempting to pair..

Secondary


IP: 192.168.110.41

configuring

6. Once complete, the following will be displayed on the Primary appliance:



High Availability Configuration - primary



7. To finalize the configuration, restart heartbeat and any other services as prompted in the "Commit changes" message box at the top of the screen.

Note

Clicking the **Restart Heartbeat** button on the Primary appliance will also automatically restart heartbeat on the Secondary appliance.

Note

For more details on configuring HA with 2 appliances, please refer to [Appliance Clustering for HA](#).

Note

For details on testing and verifying HA, please refer to [Clustered Pair Diagnostics](#).



13. Document Revision History

Version	Date	Change	Reason for Change	Changed By
1.0.0	22 February 2022	Initial version		AH
1.0.1	28 September 2022	Updated layer 7 VIP and RIP creation screenshots	Reflect changes in the web user interface	AH
1.0.2	5 January 2023	Combined software version information into one section Added one level of section numbering Added software update instructions Added table of ports used by the appliance Reworded 'Further Documentation' section Removed references to the colour of certain UI elements	Housekeeping across all documentation	AH
1.0.3	2 February 2023	Updated screenshots	Branding update	AH
1.0.4	7 March 2023	Removed conclusion section	Updates across all documentation	AH
1.1.0	24 March 2023	New document theme Modified diagram colours	Branding update	AH





Visit us: www.loadbalancer.org

Phone us: +44 (0)330 380 1064

Phone us: +1 833 274 2566

Email us: info@loadbalancer.org

Follow us: [@loadbalancer.org](https://www.loadbalancer.org)

About Loadbalancer.org

Loadbalancer.org's mission is to ensure that its clients' businesses are never interrupted. The load balancer experts ask the right questions to get to the heart of what matters, bringing a depth of understanding to each deployment. Experience enables Loadbalancer.org engineers to design less complex, unbreakable solutions - and to provide exceptional personalized support.

