



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Dell Inc.

PowerEdge 2950 (Intel Xeon processor 5120, 1.86GHz)

### SPECint®\_rate2006 = Not Run

### SPECint\_rate\_base2006 = 37.9

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Mar-2007

Hardware Availability: Jul-2006

Software Availability: Nov-2006



### Hardware

CPU Name: Intel Xeon 5120  
 CPU Characteristics: 1066 MHz Bus Speed  
 CPU MHz: 1866  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8 x 2 GB 667MHz CL5 DDR2 FB-DIMM SDRAM)  
 Disk Subsystem: 1 x 73 GB SAS 15k RPM  
 Other Hardware: None

### Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)  
 Compiler: Intel C++ Compiler 9.1 for IA32 (20061103Z) Microsoft Visual Studio 2005  
 Auto Parallel: No  
 File System: NTFS  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: Not Applicable  
 Other Software: MicroQuill SmartHeap Library 8.0



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = Not Run

PowerEdge 2950 (Intel Xeon processor 5120, 1.86GHz)

SPECint\_rate\_base2006 = 37.9

CPU2006 license: 55

Test date: Mar-2007

Test sponsor: Dell Inc.

Hardware Availability: Jul-2006

Tested by: Dell Inc.

Software Availability: Nov-2006

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	739	52.9	<b><u>738</u></b>	<b><u>52.9</u></b>	738	52.9							
401.bzip2	4	1115	34.6	1123	34.4	<b><u>1119</u></b>	<b><u>34.5</u></b>							
403.gcc	4	1579	20.4	1576	20.4	<b><u>1579</u></b>	<b><u>20.4</u></b>							
429.mcf	4	901	40.5	<b><u>902</u></b>	<b><u>40.5</u></b>	903	40.4							
445.gobmk	4	873	48.1	<b><u>873</u></b>	<b><u>48.1</u></b>	874	48.0							
456.hammer	4	1196	31.2	1196	31.2	<b><u>1196</u></b>	<b><u>31.2</u></b>							
458.sjeng	4	1076	45.0	1075	45.0	<b><u>1075</u></b>	<b><u>45.0</u></b>							
462.libquantum	4	3082	26.9	3082	26.9	<b><u>3082</u></b>	<b><u>26.9</u></b>							
464.h264ref	4	1146	77.3	1145	77.3	<b><u>1145</u></b>	<b><u>77.3</u></b>							
471.omnetpp	4	882	28.3	881	28.4	<b><u>882</u></b>	<b><u>28.3</u></b>							
473.astar	4	890	31.5	893	31.5	<b><u>891</u></b>	<b><u>31.5</u></b>							
483.xalancbmk	4	597	46.2	597	46.3	<b><u>597</u></b>	<b><u>46.3</u></b>							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Platform Notes

Snoop Filter enabled in BIOS

## General Notes

32-bit binaries were built on Windows XP Professional x64 Edition

## Base Compiler Invocation

C benchmarks:  
icl -Qc99

C++ benchmarks:  
icl

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32  
464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32  
483.xalancbmk: -Qoption, cpp, --no\_wchar\_t\_keyword



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Dell Inc.**

**SPECint\_rate2006 = Not Run**

PowerEdge 2950 (Intel Xeon processor 5120, 1.86GHz)

**SPECint\_rate\_base2006 = 37.9**

**CPU2006 license:** 55

**Test date:** Mar-2007

**Test sponsor:** Dell Inc.

**Hardware Availability:** Jul-2006

**Tested by:** Dell Inc.

**Software Availability:** Nov-2006

## Base Optimization Flags

C benchmarks:

`-fast /F512000000 shlW32M.lib -link /FORCE:MULTIPLE`

C++ benchmarks:

`-fast -Qcxx_features /F512000000 shlW32M.lib  
-link /FORCE:MULTIPLE`

## Base Other Flags

C benchmarks:

`403.gcc: -Dalloca=_alloca`

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 12:03:46 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 17 April 2007.