



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Tyan

(Test Sponsor: Advanced Micro Devices)

SPECint®\_rate2006 = 97.3

Thunder K8QW (S4881) Opteron 890

SPECint\_rate\_base2006 = 86.2

CPU2006 license: 49


Test sponsor: Advanced Micro Devices

Tested by: Advanced Micro Devices

Test date: Apr-2007

Hardware Availability: Feb-2007

Software Availability: Feb-2007



## Hardware

CPU Name: AMD Opteron 890  
 CPU Characteristics:  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip  
 CPU(s) orderable: 1,2,4 chips  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (16x1GB, DDR-400 CL3 ECC Reg Dual Rank)  
 Disk Subsystem: SATA, 250 GB  
 Other Hardware: None

## Software

Operating System: SuSE Linux Enterprise Server 10 64-bit kernel  
 Compiler: QLogic PathScale Compiler Suite, Release 3.0  
 Auto Parallel: No  
 File System: ext3  
 System State: Multi-user, run level 3  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap 8.0 32 bit Library for Linux



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Tyan

(Test Sponsor: Advanced Micro Devices)

SPECint\_rate2006 = 97.3

Thunder K8QW (S4881) Opteron 890

SPECint\_rate\_base2006 = 86.2

CPU2006 license: 49

Test sponsor: Advanced Micro Devices

Tested by: Advanced Micro Devices

Test date: Apr-2007

Hardware Availability: Feb-2007

Software Availability: Feb-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	794	98.4	<u>791</u>	<u>98.8</u>	787	99.3	8	652	120	641	122	<u>643</u>	<u>122</u>
401.bzip2	8	1272	60.7	<u>1097</u>	<u>70.4</u>	1093	70.7	8	1092	70.7	<u>1088</u>	<u>71.0</u>	1085	71.2
403.gcc	8	1156	55.7	<u>1136</u>	<u>56.7</u>	1115	57.7	8	823	78.2	820	78.6	<u>823</u>	<u>78.2</u>
429.mcf	8	1280	57.0	<u>1204</u>	<u>60.6</u>	1185	61.6	8	861	84.7	856	85.2	<u>859</u>	<u>85.0</u>
445.gobmk	8	754	111	<u>755</u>	<u>111</u>	756	111	8	<u>643</u>	<u>131</u>	644	130	642	131
456.hmmer	8	679	110	677	110	<u>677</u>	<u>110</u>	8	<u>516</u>	<u>145</u>	514	145	516	145
458.sjeng	8	942	103	937	103	<u>937</u>	<u>103</u>	8	863	112	<u>862</u>	<u>112</u>	860	113
462.libquantum	8	<u>2221</u>	<u>74.6</u>	2219	74.7	2221	74.6	8	2209	75.0	2217	74.8	<u>2213</u>	<u>74.9</u>
464.h264ref	8	1080	164	1089	163	<u>1086</u>	<u>163</u>	8	<u>1047</u>	<u>169</u>	1046	169	1047	169
471.omnetpp	8	<u>784</u>	<u>63.8</u>	782	63.9	788	63.5	8	<u>787</u>	<u>63.5</u>	785	63.7	791	63.2
473.astar	8	826	68.0	820	68.5	<u>821</u>	<u>68.4</u>	8	826	68.0	820	68.5	<u>821</u>	<u>68.4</u>
483.xalancbmk	8	522	106	<u>523</u>	<u>105</u>	525	105	8	516	107	<u>513</u>	<u>108</u>	513	108

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

taskset utility used to bind cores to processes  
 All memory slots filled on all used CPU sockets.  
 Memory bank interleave is enabled.  
 The tested system can be assembled using an SSI-MEB case and  
 a Emacs PSL-6701P 700 watt ATX 12V Power Supply.

## Base Compiler Invocation

C benchmarks:  
pathcc

C++ benchmarks:  
pathCC

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
 401.bzip2: -DSPEC\_CPU\_LP64  
 403.gcc: -DSPEC\_CPU\_LP64  
 429.mcf: -DSPEC\_CPU\_LP64  
 445.gobmk: -DSPEC\_CPU\_LP64  
 456.hmmer: -DSPEC\_CPU\_LP64  
 458.sjeng: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Tyan**

(Test Sponsor: Advanced Micro Devices)

**SPECint\_rate2006 = 97.3**

**Thunder K8QW (S4881) Opteron 890**

**SPECint\_rate\_base2006 = 86.2**

**CPU2006 license:** 49

**Test sponsor:** Advanced Micro Devices

**Tested by:** Advanced Micro Devices

**Test date:** Apr-2007

**Hardware Availability:** Feb-2007

**Software Availability:** Feb-2007

## Base Portability Flags (Continued)

462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-Ofast -OPT:malloc\_alg=1

C++ benchmarks:

-Ofast -m32 -L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap

## Peak Compiler Invocation

C benchmarks:

pathcc

C++ benchmarks:

pathCC

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
445.gobmk: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -fb\_create fbdata(pass 1) -fb\_opt fbdata(pass 2) -Ofast  
-LNO:opt=0

401.bzip2: -O3 -LNO:ou\_prod\_max=10 -OPT:Ofast -OPT:alias=disjoint

403.gcc: -fb\_create fbdata(pass 1) -fb\_opt fbdata(pass 2) -m32 -O3  
-OPT:Ofast

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Tyan**

(Test Sponsor: Advanced Micro Devices)

**SPECint\_rate2006 = 97.3**

**Thunder K8QW (S4881) Opteron 890**

**SPECint\_rate\_base2006 = 86.2**

**CPU2006 license:** 49

**Test sponsor:** Advanced Micro Devices

**Tested by:** Advanced Micro Devices

**Test date:** Apr-2007

**Hardware Availability:** Feb-2007

**Software Availability:** Feb-2007

## Peak Optimization Flags (Continued)

429.mcf: -m32 -O3 -ipa  
-L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap

445.gobmk: -fb\_create fbdata(pass 1) -fb\_opt fbdata(pass 2) -O3  
-OPT:alias=disjoint -LNO:simd=0 -LNO:minvariant=off  
-WOPT:retype\_expr=on

456.hmmer: -O2 -OPT:alias=disjoint -OPT:malloc\_alg=1 -CG:cflow=0

458.sjeng: -fb\_create fbdata(pass 1) -fb\_opt fbdata(pass 2) -O3  
-IPA:plimit=50000 -IPA:pu\_reorder=2

462.libquantum: -O3 -ipa -CG:local\_fwd\_sched=on -IPA:space=1000

464.h264ref: -fb\_create fbdata(pass 1) -fb\_opt fbdata(pass 2) -O3  
-IPA:plimit=20000 -OPT:alias=disjoint -LNO:prefetch=0

C++ benchmarks:

471.omnetpp: -Ofast -CG:gcm=off -m32  
-L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: -Ofast -m32 -OPT:unroll\_times\_max=8  
-L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/CPU2006\\_flags.20090714.html](http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/CPU2006\\_flags.20090714.xml](http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.xml)

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 11:55:28 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 16 May 2007.