



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

## SPECint®\_rate2006 = Not Run

## Acer Altos R720 (Intel Xeon X5470)

## SPECint\_rate\_base2006 = 137

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Dec-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008



### Hardware

CPU Name: Intel Xeon X5470  
 CPU Characteristics: 1333MHz system bus  
 CPU MHz: 3333  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1, 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)  
 Disk Subsystem: 1 x 73GB 10K RPM SAS HDD  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ Compiler 11.0 for Linux Build 20080930 Package ID: l\_cproc\_p\_11.0.066  
 Auto Parallel: No  
 File System: ReiserFS  
 System State: Multi-user, level 3  
 Base Pointers: 32-bit  
 Peak Pointers: Not Applicable  
 Other Software: Microquill SmartHeap V8.1 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint\_rate2006 = Not Run

Acer Altos R720 (Intel Xeon X5470)

SPECint\_rate\_base2006 = 137

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Dec-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	460	170	<b><u>455</u></b>	<b><u>172</u></b>	455	172							
401.bzip2	8	682	113	679	114	<b><u>680</u></b>	<b><u>113</u></b>							
403.gcc	8	622	103	621	104	<b><u>621</u></b>	<b><u>104</u></b>							
429.mcf	8	694	105	695	105	<b><u>695</u></b>	<b><u>105</u></b>							
445.gobmk	8	517	162	<b><u>512</u></b>	<b><u>164</u></b>	512	164							
456.hammer	8	451	165	449	166	<b><u>450</u></b>	<b><u>166</u></b>							
458.sjeng	8	<b><u>563</u></b>	<b><u>172</u></b>	563	172	562	172							
462.libquantum	8	837	198	<b><u>837</u></b>	<b><u>198</u></b>	837	198							
464.h264ref	8	604	293	<b><u>605</u></b>	<b><u>293</u></b>	605	293							
471.omnetpp	8	<b><u>716</u></b>	<b><u>69.8</u></b>	716	69.8	716	69.9							
473.astar	8	655	85.7	656	85.6	<b><u>656</u></b>	<b><u>85.6</u></b>							
483.xalancbmk	8	416	133	416	133	<b><u>416</u></b>	<b><u>133</u></b>							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Platform Notes

BIOS Settings  
Adjacent Cache Line Prefetch disabled  
Hardware Prefetch disabled

## General Notes

taskset was used to bind processes to cores except for 462.libquantum peak  
OMP\_NUM\_THREADS set to number of processors  
KMP\_AFFINITY set to "physical,0"  
KMP\_STACKSIZE set to 64M  
'ulimit -s unlimited' was set for stacksize unlimited  
This result was measured on the Acer Altos R520.  
The Altos R720 and Altos R520 are electronically equivalent.

## Base Compiler Invocation

C benchmarks:  
icc

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint\_rate2006 = Not Run

Acer Altos R720 (Intel Xeon X5470)

SPECint\_rate\_base2006 = 137

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Dec-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -inline-alloc  
-opt-malloc-options=3 -opt-prefetch

C++ benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090710.04.html>  
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090710.00.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090710.04.xml>  
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090710.00.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint\_rate2006 = Not Run

Acer Altos R720 (Intel Xeon X5470)

SPECint\_rate\_base2006 = 137

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Dec-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Tue Jul 22 21:33:41 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 24 December 2008.