



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

## SPECint®\_rate2006 = 183

## Fujitsu SPARC Enterprise T5240

## SPECint\_rate\_base2006 = 171

CPU2006 license: 19


Test date: Feb-2009

Test sponsor: Fujitsu

Hardware Availability: Jul-2009

Tested by: Sun Microsystems

Software Availability: Jun-2009



### Hardware

CPU Name: UltraSPARC T2 Plus  
 CPU Characteristics:  
 CPU MHz: 1582  
 FPU: Integrated  
 CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip, 8 threads/core  
 CPU(s) orderable: 2 chips  
 Primary Cache: 16 KB I + 8 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip  
 L3 Cache: None  
 Other Cache: None  
 Memory: 128 GB (32 x 4 GB)  
 Disk Subsystem: 748 GB RAID 0 using Solaris Volume Manager on 8x 10K RPM SUN146G SAS blocksize 384 KB  
 Other Hardware: None

### Software

Operating System: Solaris 10 10/08  
 Compiler: Sun Studio 12 Update 1 and gccfss V4.2.1 (see additional detail below)  
 Auto Parallel: No  
 File System: ufs  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other Software: None



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECint\_rate2006 = 183

Fujitsu SPARC Enterprise T5240

SPECint\_rate\_base2006 = 171

CPU2006 license: 19

Test date: Feb-2009

Test sponsor: Fujitsu

Hardware Availability: Jul-2009

Tested by: Sun Microsystems

Software Availability: Jun-2009

## Results Table

| Benchmark      | Base   |                     |                   |                     |                   |                    |                   | Peak   |                    |                   |                     |                   |                     |                   |
|----------------|--------|---------------------|-------------------|---------------------|-------------------|--------------------|-------------------|--------|--------------------|-------------------|---------------------|-------------------|---------------------|-------------------|
|                | Copies | Seconds             | Ratio             | Seconds             | Ratio             | Seconds            | Ratio             | Copies | Seconds            | Ratio             | Seconds             | Ratio             | Seconds             | Ratio             |
| 400.perlbench  | 127    | <b><u>7625</u></b>  | <b><u>163</u></b> | 7626                | 163               | 7625               | 163               | 127    | 6466               | 192               | 6457                | 192               | <b><u>6462</u></b>  | <b><u>192</u></b> |
| 401.bzip2      | 127    | 10515               | 117               | <b><u>10469</u></b> | <b><u>117</u></b> | 10439              | 117               | 127    | 10149              | 121               | <b><u>10148</u></b> | <b><u>121</u></b> | 10140               | 121               |
| 403.gcc        | 127    | <b><u>9046</u></b>  | <b><u>113</u></b> | 9051                | 113               | 9020               | 113               | 127    | 8816               | 116               | 8813                | 116               | <b><u>8816</u></b>  | <b><u>116</u></b> |
| 429.mcf        | 127    | 7335                | 158               | <b><u>7332</u></b>  | <b><u>158</u></b> | 7325               | 158               | 127    | 7335               | 158               | <b><u>7332</u></b>  | <b><u>158</u></b> | 7325                | 158               |
| 445.gobmk      | 127    | 6385                | 209               | 6397                | 208               | <b><u>6385</u></b> | <b><u>209</u></b> | 127    | 5936               | 224               | <b><u>5938</u></b>  | <b><u>224</u></b> | 5943                | 224               |
| 456.hammer     | 127    | <b><u>11063</u></b> | <b><u>107</u></b> | 11077               | 107               | 11057              | 107               | 127    | 9010               | 132               | 9041                | 131               | <b><u>9035</u></b>  | <b><u>131</u></b> |
| 458.sjeng      | 127    | <b><u>8807</u></b>  | <b><u>174</u></b> | 8792                | 175               | 8815               | 174               | 127    | 8422               | 182               | <b><u>8427</u></b>  | <b><u>182</u></b> | 8434                | 182               |
| 462.libquantum | 127    | <b><u>4583</u></b>  | <b><u>574</u></b> | 4583                | 574               | 4580               | 575               | 127    | <b><u>4533</u></b> | <b><u>581</u></b> | 4534                | 580               | 4528                | 581               |
| 464.h264ref    | 127    | 13643               | 206               | <b><u>13632</u></b> | <b><u>206</u></b> | 13629              | 206               | 127    | 13261              | 212               | 13260               | 212               | <b><u>13261</u></b> | <b><u>212</u></b> |
| 471.omnetpp    | 127    | <b><u>4668</u></b>  | <b><u>170</u></b> | 4692                | 169               | 4663               | 170               | 127    | <b><u>4668</u></b> | <b><u>170</u></b> | 4692                | 169               | 4663                | 170               |
| 473.astar      | 127    | 6722                | 133               | <b><u>6722</u></b>  | <b><u>133</u></b> | 6719               | 133               | 127    | 6193               | 144               | <b><u>6186</u></b>  | <b><u>144</u></b> | 6184                | 144               |
| 483.xalancbmk  | 127    | <b><u>4962</u></b>  | <b><u>177</u></b> | 4945                | 177               | 4983               | 176               | 127    | 4292               | 204               | <b><u>4275</u></b>  | <b><u>205</u></b> | 4264                | 206               |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

This result was measured with pre-release build 36.0 of Sun Studio 12 Update 1

Peak also uses "GCC for SPARC Systems 4.2.1", which combines gcc with the Sun Code Generator for SPARC systems. It is invoked as "gcc", and accepts source code compatible with GCC 4.2.

For more information, including support, see <http://cooltools.sunsource.net/gcc/>

## Submit Notes

A processor set was created using

```
psrset -c 1-127
```

and the runspec process was placed into the set using

```
psrset -e 1
```

The config file option 'submit' was used to select specific processors within the set, along with the pbind command.

## Operating System Notes

ulimit -s 131072 was used to allow the stack to grow up to 131072 KB (aka 128 MB). Note that saying "131072" is preferable to "unlimited", because there is a tradeoff

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECint\_rate2006 = 183

Fujitsu SPARC Enterprise T5240

SPECint\_rate\_base2006 = 171

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Sun Microsystems

Test date: Feb-2009

Hardware Availability: Jul-2009

Software Availability: Jun-2009

## Operating System Notes (Continued)

between space for the stack vs. space for the heap.

/etc/system parameters

autoup=600

Causes pages older than the listed number of seconds to be written by fsflush.

bufhwm=3000

Memory byte limit for caching I/O buffers

segmap\_percent=1

Set maximum percent memory for file system cache

tune\_t\_fsflushr=10

Controls how many seconds elapse between runs of the page flush daemon, fsflush.

tsb\_rss\_factor=128

Suggests that the the size of the TSB (Translation Storage Buffer) may be increased if it is more than 25% (128/512) full. Doing so may reduce TSB traps, at the cost of additional kernel memory.

The "webconsole" service was turned off using svcadm disable webconsole

The system had 206 GB of swap space.  
The ufs fragment size was set to 8192

## Platform Notes

This result was measured on a Sun SPARC Enterprise T5240.  
The Sun SPARC Enterprise T5240 and the Fujitsu SPARC Enterprise T5240 are electrically equivalent.

## Base Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_SOLARIS\_SPARC

403.gcc: -DSPEC\_CPU\_SOLARIS

462.libquantum: -DSPEC\_CPU\_SOLARIS

483.xalancbmk: -DSPEC\_CPU\_SOLARIS



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECint\_rate2006 = 183

Fujitsu SPARC Enterprise T5240

SPECint\_rate\_base2006 = 171

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Sun Microsystems

Test date: Feb-2009

Hardware Availability: Jul-2009

Software Availability: Jun-2009

## Base Optimization Flags

C benchmarks:

```
-g -fast -xipo=2 -xpagesize=4M -xprefetch=no%auto -xalias_level=std
-M /usr/lib/ld/map.bssalign
```

C++ benchmarks:

```
-g0 -library=stlport4 -fast -xipo=2 -xpagesize=4M -xprefetch=no%auto
-xdepend -xalias_level=compatible -M /usr/lib/ld/map.bssalign
```

## Base Other Flags

C benchmarks:

```
-xjobs=32 -V -#
```

C++ benchmarks:

```
-xjobs=32 -verbose=diags,version
```

## Peak Compiler Invocation

C benchmarks (except as noted below):

cc

403.gcc: gcc

456.hmmer: gcc

C++ benchmarks:

CC

## Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_SOLARIS_SPARC
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS
```

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xprefetch=no%auto -M /usr/lib/ld/map.bssalign
-xalias_level=std -xipo=2 -Xc -xrestrict -lfast
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECint\_rate2006 = 183

Fujitsu SPARC Enterprise T5240

SPECint\_rate\_base2006 = 171

CPU2006 license: 19

Test date: Feb-2009

Test sponsor: Fujitsu

Hardware Availability: Jul-2009

Tested by: Sun Microsystems

Software Availability: Jun-2009

## Peak Optimization Flags (Continued)

401.bzip2: -g -xprofile=collect:./feedback(pass 1)  
 -xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
 -M /usr/lib/ld/map.bssalign -xalias\_level=strong

403.gcc: -xprofile=collect:./feedback(pass 1)  
 -xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
 -xprefetch=no%auto -Wl,-M,/usr/lib/ld/map.bssalign -xipo=2  
 -xalias\_level=std

429.mcf: basepeak = yes

445.gobmk: -g -xprofile=collect:./feedback(pass 1)  
 -xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
 -xprefetch=no%auto -M /usr/lib/ld/map.bssalign  
 -xalias\_level=std -xrestrict

456.hmmer: -xprofile=collect:./feedback(pass 1)  
 -xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
 -Wl,-M,/usr/lib/ld/map.bssalign -xipo=2 -xalias\_level=std

458.sjeng: -g -xprofile=collect:./feedback(pass 1)  
 -xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
 -xprefetch=no%auto -M /usr/lib/ld/map.bssalign -xipo=2

462.libquantum: -g -fast -xpagesize=4M -xprefetch\_level=3  
 -xprefetch\_auto\_type=indirect\_array\_access  
 -M /usr/lib/ld/map.bssalign -xipo=2 -xalias\_level=std

464.h264ref: -g -xprofile=collect:./feedback(pass 1)  
 -xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
 -xprefetch=no%auto -M /usr/lib/ld/map.bssalign -xipo=2  
 -xalias\_level=std

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: -g0 -library=stlport4 -xprofile=collect:./feedback(pass 1)  
 -xprofile=use:./feedback(pass 2) -fast -xpagesize\_heap=4M  
 -xpagesize\_stack=64K -xprefetch=no%auto -xdepend  
 -xalias\_level=compatible -M /usr/lib/ld/map.bssalign  
 -xipo=2 -xarch=v8plusb -lfast -lbsdmalloc

483.xalancbmk: -g0 -library=stlport4 -fast -xpagesize=4M  
 -xprefetch=no%auto -xdepend -xalias\_level=compatible  
 -M /usr/lib/ld/map.bssalign -xipo=2 -lfast



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECint\_rate2006 = 183

Fujitsu SPARC Enterprise T5240

SPECint\_rate\_base2006 = 171

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Sun Microsystems

Test date: Feb-2009

Hardware Availability: Jul-2009

Software Availability: Jun-2009

## Peak Other Flags

C benchmarks (except as noted below):

-xjobs=32 -V -#

403.gcc: -v

456.hmmer: -v

C++ benchmarks:

-xjobs=32 -verbose=diags,version

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-12u1-and-gccfss4.2.r3.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-12u1-and-gccfss4.2.r3.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 03:18:05 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 5 August 2009.