



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp[®]_rate2006 = 3230

Compute Blade 520X (Intel Xeon E7-8890 v2)

SPECfp_rate_base2006 = 3160

CPU2006 license: 35


Test date: May-2014

Test sponsor: HITACHI

Hardware Availability: Sep-2014

Tested by: HITACHI

Software Availability: Sep-2013



Hardware

CPU Name: Intel Xeon E7-8890 v2
 CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 120 cores, 8 chips, 15 cores/chip, 2 threads/core
 CPU(s) orderable: 2,4,8 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.5 (Santiago)
 2.6.32-431.el6.x86_64
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
 Auto Parallel: No
 File System: ext4

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = 3230

Compute Blade 520X (Intel Xeon E7-8890 v2)

SPECfp_rate_base2006 = 3160

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

L3 Cache: 37.5 MB I+D on chip per chip
Other Cache: None
Memory: 2 TB (128 x 16 GB 2Rx4 PC3L-12800R-11, ECC, running at 1333 MHz)
Disk Subsystem: 2 x 300 GB SAS, 15000 RPM
Other Hardware: None

System State: Run level 3 (multi-user)
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: none

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	240	1249	2610	<u>1254</u>	<u>2600</u>	1255	2600	240	1249	2610	<u>1254</u>	<u>2600</u>	1255	2600
416.gamess	240	1210	3880	1213	3870	<u>1212</u>	<u>3880</u>	240	1204	3900	1192	3940	<u>1195</u>	<u>3930</u>
433.milc	240	872	2530	<u>872</u>	<u>2530</u>	871	2530	240	871	2530	<u>871</u>	<u>2530</u>	872	2530
434.zeusmp	240	618	3540	<u>621</u>	<u>3510</u>	628	3480	240	618	3540	<u>621</u>	<u>3510</u>	628	3480
435.gromacs	240	<u>374</u>	<u>4580</u>	374	4580	375	4560	240	371	4620	370	4630	<u>371</u>	<u>4620</u>
436.cactusADM	240	<u>752</u>	<u>3820</u>	751	3820	753	3810	240	<u>752</u>	<u>3820</u>	751	3820	753	3810
437.leslie3d	240	<u>1295</u>	<u>1740</u>	1297	1740	1295	1740	120	591	1910	589	1920	<u>591</u>	<u>1910</u>
444.namd	240	610	3150	599	3210	<u>604</u>	<u>3180</u>	240	593	3250	<u>598</u>	<u>3220</u>	601	3200
447.dealII	240	<u>430</u>	<u>6390</u>	430	6380	429	6400	240	<u>430</u>	<u>6390</u>	430	6380	429	6400
450.soplex	240	1197	1670	<u>1198</u>	<u>1670</u>	1199	1670	120	<u>567</u>	<u>1770</u>	567	1760	566	1770
453.povray	240	239	5350	243	5260	<u>240</u>	<u>5310</u>	240	210	6090	209	6120	<u>209</u>	<u>6100</u>
454.calculix	240	535	3700	540	3670	<u>538</u>	<u>3680</u>	240	535	3700	540	3670	<u>538</u>	<u>3680</u>
459.GemsFDTD	240	1585	1610	1591	1600	<u>1591</u>	<u>1600</u>	240	1585	1610	1591	1600	<u>1591</u>	<u>1600</u>
465.tonto	240	628	3760	<u>630</u>	<u>3750</u>	633	3730	240	601	3930	605	3900	<u>605</u>	<u>3910</u>
470.lbm	240	1037	3180	1038	3180	<u>1038</u>	<u>3180</u>	240	1037	3180	1038	3180	<u>1038</u>	<u>3180</u>
481.wrf	240	<u>853</u>	<u>3140</u>	852	3150	854	3140	240	<u>849</u>	<u>3160</u>	849	3160	854	3140
482.sphinx3	240	<u>1602</u>	<u>2920</u>	1599	2920	1604	2920	240	<u>1596</u>	<u>2930</u>	1594	2930	1600	2920

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = 3230

Compute Blade 520X (Intel Xeon E7-8890 v2)

SPECfp_rate_base2006 = 3160

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

Platform Notes

Sysinfo program /home/cpu2006/config/sysinfo.rev6818
\$Rev: 6818 \$ \$Date:: 2012-07-17 # \$ e86d102572650a6e4d596a3cee98f191
running on RHEL6.5x8664 Fri May 30 19:01:26 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : Intel(R) Xeon(R) CPU E7-8890 v2 @ 2.80GHz
 8 "physical id"s (chips)
240 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores : 15
siblings : 30
physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 2: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 3: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 4: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 5: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 6: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 7: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
cache size : 38400 KB
```

From /proc/meminfo

```
MemTotal: 2117225796 kB
HugePages_Total: 0
Hugepagesize: 2048 kB
```

/usr/bin/lsb_release -d

```
Red Hat Enterprise Linux Server release 6.5 (Santiago)
```

From /etc/*release* /etc/*version*

```
redhat-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

uname -a:

```
Linux RHEL6.5x8664 2.6.32-431.el6.x86_64 #1 SMP Sun Nov 10 22:19:54 EST 2013
x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 May 30 18:57

SPEC is set to: /home/cpu2006

```
Filesystem Type Size Used Avail Use% Mounted on
/dev/mapper/vg_rhel6-lv_home ext4 359G 8.8G 332G 3% /home
```

Additional information from dmidecode:

```
BIOS HITACHI 06-06 05/29/2014
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = 3230

Compute Blade 520X (Intel Xeon E7-8890 v2)

SPECfp_rate_base2006 = 3160

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

Platform Notes (Continued)

Memory:

```

64x NO DIMM Unknown
1x Samsung 393B2G7 BH0 YH9 16 GB 1333 MHz 2 rank
1x Samsung 393B2G7 BH0 YK0 16 GB 1333 MHz 2 rank
5x Samsung M393B2G7 BH0 YK0 16 GB 1333 MHz 2 rank
32x Samsung M393B2G70BH0-YK0 16 GB 1333 MHz 2 rank
89x Samsung M393B2G70QH0-YK0 16 GB 1333 MHz 2 rank

```

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

```
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
```

Filesystem page cache cleared with:

```
echo 1> /proc/sys/vm/drop_caches
```

runspec command invoked through numactl i.e.:

```
numactl --interleave=all runspec <etc>
```

BladeSymphony BS520X and Hitachi Compute Blade 520X are electronically equivalent.

The results have been measured on a Compute Blade 520X

Base Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64

416.gamess: -DSPEC_CPU_LP64

433.milc: -DSPEC_CPU_LP64

434.zeusmp: -DSPEC_CPU_LP64

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 4



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = 3230

Compute Blade 520X (Intel Xeon E7-8890 v2)

SPECfp_rate_base2006 = 3160

CPU2006 license: 35

Test date: May-2014

Test sponsor: HITACHI

Hardware Availability: Sep-2014

Tested by: HITACHI

Software Availability: Sep-2013

Base Portability Flags (Continued)

```

435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

```

-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

```

C++ benchmarks:

```

-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

```

Fortran benchmarks:

```

-xAVX -ipo -O3 -no-prec-div -opt-prefetch

```

Benchmarks using both Fortran and C:

```

-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

```

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = 3230

Compute Blade 520X (Intel Xeon E7-8890 v2)

SPECfp_rate_base2006 = 3160

CPU2006 license: 35

Test date: May-2014

Test sponsor: HITACHI

Hardware Availability: Sep-2014

Tested by: HITACHI

Software Availability: Sep-2013

Peak Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
 -prof-use(pass 2) -auto-ilp32

470.lbm: basepeak = yes

482.sphinx3: -xAVX -ipo -O3 -no-prec-div -opt-mem-layout-trans=3
 -unroll2

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
 -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
 -prof-use(pass 2) -opt-malloc-options=3

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = 3230

Compute Blade 520X (Intel Xeon E7-8890 v2)

SPECfp_rate_base2006 = 3160

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

Peak Optimization Flags (Continued)

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: -xAVX -ipo -O3 -no-prec-div -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: -xAVX -ipo -O3 -no-prec-div -auto-ilp32

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.html>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.xml>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = 3230

Compute Blade 520X (Intel Xeon E7-8890 v2)

SPECfp_rate_base2006 = 3160

CPU2006 license: 35

Test date: May-2014

Test sponsor: HITACHI

Hardware Availability: Sep-2014

Tested by: HITACHI

Software Availability: Sep-2013

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Wed Aug 6 10:09:16 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 5 August 2014.