



SPEC® CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECint®_rate2006 = 1890

SPECint_rate_base2006 = 1830

CPU2006 license: 3


Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016



Hardware

CPU Name: Intel Xeon E7-8894 v4
CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 48 cores, 2 chips, 24 cores/chip, 2 threads/core
CPU(s) orderable: 1,2 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core
L3 Cache: 60 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (32 x 16 GB 2Rx4 PC4-2400T-R, running at 1600 MHz)
Disk Subsystem: 1 x 400 GB SAS SSD, RAID 0
Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 12 (x86_64) SP2, Kernel 4.4.21-69-default
Compiler: C/C++: Version 17.0.0.098 of Intel C/C++ Compiler for Linux
Auto Parallel: No
File System: xfs
System State: Run level 3 (multi-user)
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: Microquill SmartHeap V10.2



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECint_rate2006 = 1890

SPECint_rate_base2006 = 1830

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	96	607	1540	604	1550	<u>607</u>	<u>1550</u>	96	522	1800	520	1800	<u>522</u>	<u>1800</u>
401.bzip2	96	1029	901	1036	894	<u>1033</u>	<u>897</u>	96	983	942	<u>985</u>	<u>940</u>	988	938
403.gcc	96	<u>583</u>	<u>1330</u>	587	1320	582	1330	96	<u>583</u>	<u>1330</u>	587	1320	582	1330
429.mcf	96	<u>424</u>	<u>2070</u>	423	2070	424	2070	96	<u>424</u>	<u>2070</u>	423	2070	424	2070
445.gobmk	96	<u>712</u>	<u>1420</u>	712	1410	711	1420	96	699	1440	699	1440	<u>699</u>	<u>1440</u>
456.hammer	96	327	2740	327	2740	<u>327</u>	<u>2740</u>	96	<u>309</u>	<u>2900</u>	309	2900	311	2880
458.sjeng	96	773	1500	<u>773</u>	<u>1500</u>	774	1500	96	<u>734</u>	<u>1580</u>	734	1580	734	1580
462.libquantum	96	98.1	20300	98.2	20300	<u>98.1</u>	<u>20300</u>	96	98.1	20300	98.2	20300	<u>98.1</u>	<u>20300</u>
464.h264ref	96	871	2440	860	2470	<u>862</u>	<u>2470</u>	96	834	2550	<u>834</u>	<u>2550</u>	845	2510
471.omnetpp	96	<u>827</u>	<u>726</u>	827	726	827	726	96	790	759	790	759	<u>790</u>	<u>759</u>
473.astar	96	679	992	677	995	<u>678</u>	<u>995</u>	96	679	992	677	995	<u>678</u>	<u>995</u>
483.xalancbmk	96	379	1750	<u>380</u>	<u>1740</u>	381	1740	96	379	1750	<u>380</u>	<u>1740</u>	381	1740

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"
Transparent Huge Pages enabled by default
Filesystem page cache cleared with:
echo 1 > /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>

Platform Notes

BIOS Configuration:
HP Power Profile set to Custom
HP Power Regulator to HP Static High Performance Mode
Minimum Processor Idle Power Core C-State set to C6 State
Minimum Processor Idle Power Package C-State set to No Package State
QPI Snoop Configuration set to Cluster on Die
Collaborative Power Control set to Disabled
Thermal Configuration set to Maximum Cooling
Processor Power and Utilization Monitoring set to Disabled
Memory Refresh Rate set to 1x Refresh

Sysinfo program /home/cpu2006/config/sysinfo.rev6993
Continued on next page



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9
(2.40 GHz, Intel Xeon E7-8894 v4)

SPECint_rate2006 = 1890

SPECint_rate_base2006 = 1830

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Platform Notes (Continued)

Revision 6993 of 2015-11-06 (b5e8d4b4eb51ed28d7f98696cbe290c1)
running on synergy620_manju Fri Feb 17 17:57:46 2017

This section contains SUT (System Under Test) info as seen by
some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : Intel(R) Xeon(R) CPU E7-8894 v4 @ 2.40GHz
 2 "physical id"s (chips)
 96 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 24
  siblings  : 48
  physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
 27 28 29
  physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
 27 28 29
cache size : 61440 KB
```

From /proc/meminfo

```
MemTotal:      528262092 kB
HugePages_Total:    0
Hugepagesize:    2048 kB
```

From /etc/*release* /etc/*version*

```
SuSE-release:
SUSE Linux Enterprise Server 12 (x86_64)
VERSION = 12
PATCHLEVEL = 2
# This file is deprecated and will be removed in a future service pack or
release.
# Please check /etc/os-release for details about this release.
os-release:
NAME="SLES"
VERSION="12-SP2"
VERSION_ID="12.2"
PRETTY_NAME="SUSE Linux Enterprise Server 12 SP2"
ID="sles"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:12:sp2"
```

uname -a:

```
Linux synergy620_manju 4.4.21-69-default #1 SMP Tue Oct 25 10:58:20 UTC 2016
(9464f67) x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Feb 17 17:44

SPEC is set to: /home/cpu2006

```
Filesystem      Type  Size  Used Avail Use% Mounted on
Continued on next page
```



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9
(2.40 GHz, Intel Xeon E7-8894 v4)

SPECint_rate2006 = 1890

SPECint_rate_base2006 = 1830

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Platform Notes (Continued)

/dev/sda4 xfs 331G 41G 291G 13% /home
Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS HP I40 12/08/2016

Memory:

16x UNKNOWN NOT AVAILABLE

32x UNKNOWN NOT AVAILABLE 16 GB 2 rank 2400 MHz, configured at 1600 MHz

(End of data from sysinfo program)

Regarding the sysinfo display about the memory installed, the correct amount of memory is 512 GB and the dmidecode description should have one line reading as:
32x UNKNOWN NOT AVAILABLE 16 GB 2 rank 2400 MHz, configured at 1600 MHz

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh10.2"

Binaries compiled on a system with 1x Intel Core i7-4790K CPU + 32GB RAM
memory using Redhat Enterprise Linux 7.2

Base Compiler Invocation

C benchmarks:

icc -m32 -L/opt/intel/compilers_and_libraries_2017/linux/lib/ia32

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers_and_libraries_2017/linux/lib/ia32

Base Portability Flags

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX_IA32
401.bzip2: -D_FILE_OFFSET_BITS=64
403.gcc: -D_FILE_OFFSET_BITS=64
429.mcf: -D_FILE_OFFSET_BITS=64
445.gobmk: -D_FILE_OFFSET_BITS=64
456.hmmer: -D_FILE_OFFSET_BITS=64
458.sjeng: -D_FILE_OFFSET_BITS=64
462.libquantum: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX
464.h264ref: -D_FILE_OFFSET_BITS=64
471.omnetpp: -D_FILE_OFFSET_BITS=64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECint_rate2006 = 1890

SPECint_rate_base2006 = 1830

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Base Portability Flags (Continued)

473.astar: -D_FILE_OFFSET_BITS=64
483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -no-prec-sqrt -static
-qopt-prefetch -qopt-mem-layout-trans=3 -auto-ilp32
-complex-limited-range -qopt-prefetch-issue-excl-hint -ansi-alias
-unroll-aggressive -use-intel-optimized-headers -qopt-matmul
-qopt-subscript-in-range -qopt-assume-safe-padding -qopt-calloc
-inline-calloc -qopt-malloc-options=3

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch
-qopt-mem-layout-trans=3 -use-intel-optimized-headers
-unroll-aggressive -qopt-calloc -inline-calloc -qopt-malloc-options=3
-Wl,-z,muldefs -L/home/cpu2006/sh10.2 -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32 -L/opt/intel/compilers_and_libraries_2017/linux/lib/ia32

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers_and_libraries_2017/linux/lib/ia32



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECint_rate2006 = 1890

SPECint_rate_base2006 = 1830

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Peak Portability Flags

```

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -D_FILE_OFFSET_BITS=64
429.mcf: -D_FILE_OFFSET_BITS=64
445.gobmk: -D_FILE_OFFSET_BITS=64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX
464.h264ref: -D_FILE_OFFSET_BITS=64
471.omnetpp: -D_FILE_OFFSET_BITS=64
473.astar: -D_FILE_OFFSET_BITS=64
483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX

```

Peak Optimization Flags

C benchmarks:

```

400.perlbench: -prof-gen=threadsafe(pass 1) -prof-use(pass 2)
               -xCORE-AVX2(pass 2) -par-num-threads=1(pass 1) -ipo(pass 2)
               -O3(pass 2) -no-prec-div(pass 2) -auto-ilp32

401.bzip2: -prof-gen=threadsafe(pass 1) -prof-use(pass 2)
            -xCORE-AVX2(pass 2) -par-num-threads=1(pass 1) -ipo(pass 2)
            -O3(pass 2) -no-prec-div(pass 2) -qopt-prefetch
            -auto-ilp32 -ansi-alias

403.gcc: basepeak = yes

429.mcf: basepeak = yes

445.gobmk: -xCORE-AVX2(pass 2) -prof-gen=threadsafe(pass 1)
            -prof-use(pass 2) -par-num-threads=1(pass 1) -ansi-alias
            -qopt-mem-layout-trans=3

456.hmmer: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32

458.sjeng: -prof-gen=threadsafe(pass 1) -prof-use(pass 2)
            -xCORE-AVX2(pass 2) -par-num-threads=1(pass 1) -ipo(pass 2)
            -O3(pass 2) -no-prec-div(pass 2) -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -prof-gen=threadsafe(pass 1) -prof-use(pass 2)
              -xCORE-AVX2(pass 2) -par-num-threads=1(pass 1) -ipo(pass 2)
              -O3(pass 2) -no-prec-div(pass 2) -unroll2 -ansi-alias

```

C++ benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECint_rate2006 = 1890

SPECint_rate_base2006 = 1830

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Peak Optimization Flags (Continued)

471.omnetpp: -prof-gen=threadsafe(pass 1) -prof-use(pass 2)
-xCORE-AVX2(pass 2) -par-num-threads=1(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2)
-qopt-ra-region-strategy=block -ansi-alias
-Wl,-z,muldefs -L/home/cpu2006/sh10.2 -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.html>

<http://www.spec.org/cpu2006/flags/HPE-Compiler-Flags-Intel-V1.2-HSW-revH.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.xml>

<http://www.spec.org/cpu2006/flags/HPE-Compiler-Flags-Intel-V1.2-HSW-revH.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Tue May 2 15:21:58 2017 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 2 May 2017.