



SPEC® CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation


Fujitsu Fujitsu SPARC M12-2

SPECint®_rate2006 = 1770

SPECint_rate_base2006 = 1520

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Mar-2017
Hardware Availability: Apr-2017
Software Availability: Jul-2017



Hardware

CPU Name: SPARC64 XII
 CPU Characteristics:
 CPU MHz: 3900
 FPU: Integrated
 CPU(s) enabled: 24 cores, 2 chips, 12 cores/chip, 8 threads/core
 CPU(s) orderable: 1 or 2 CPU chips; the number of orderable total cores is 2, 3, 4, .. 24
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core
 L3 Cache: 32 MB I+D on chip per chip
 Other Cache: None
 Memory: 1 TB (32 x 32 GB 2Rx4 PC4-2400T-R)
 Disk Subsystem: 1 x 600 GB 10K RPM SAS (for system disk)
 Other Hardware: None

Software

Operating System: Oracle Solaris 11.3 (with June 2017 SRU)
 Compiler: C/C++: Version 12.6 of Oracle Developer Studio
 Auto Parallel: No
 File System: tmpfs
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: None



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2

SPECint_rate2006 = 1770

SPECint_rate_base2006 = 1520

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Mar-2017
Hardware Availability: Apr-2017
Software Availability: Jul-2017

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	192	1502	1250	<u>1497</u>	<u>1250</u>	1496	1250	192	1055	1780	1070	1750	<u>1056</u>	<u>1780</u>
401.bzip2	192	2423	765	<u>2417</u>	<u>767</u>	2416	767	96	<u>1156</u>	<u>802</u>	1156	802	1155	802
403.gcc	192	<u>1303</u>	<u>1190</u>	1291	1200	1318	1170	192	1275	1210	1212	1270	<u>1237</u>	<u>1250</u>
429.mcf	192	<u>1287</u>	<u>1360</u>	1290	1360	1283	1360	96	421	2080	<u>422</u>	<u>2080</u>	422	2080
445.gobmk	192	1393	1450	<u>1392</u>	<u>1450</u>	1390	1450	192	1229	1640	<u>1228</u>	<u>1640</u>	1226	1640
456.hammer	192	987	1810	<u>987</u>	<u>1820</u>	987	1820	96	<u>452</u>	<u>1980</u>	452	1980	452	1980
458.sjeng	192	1827	1270	1829	1270	<u>1827</u>	<u>1270</u>	192	1598	1450	<u>1596</u>	<u>1460</u>	1594	1460
462.libquantum	192	314	12700	313	12700	<u>313</u>	<u>12700</u>	48	54.1	18400	<u>54.3</u>	<u>18300</u>	54.5	18300
464.h264ref	192	2266	1880	2269	1870	<u>2266</u>	<u>1870</u>	96	<u>1038</u>	<u>2050</u>	1038	2050	1036	2050
471.omnetpp	192	1504	798	1504	798	<u>1504</u>	<u>798</u>	192	<u>1439</u>	<u>834</u>	1438	834	1440	834
473.astar	192	1408	957	1408	957	<u>1408</u>	<u>957</u>	192	<u>1372</u>	<u>983</u>	1373	981	1370	984
483.xalancbmk	192	832	1590	830	1600	<u>830</u>	<u>1600</u>	192	772	1720	771	1720	<u>771</u>	<u>1720</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

Processes were assigned to specific processors using 'pbind' commands. The config file option 'submit' was used, along with a list of processors in the 'BIND' variable, to generate the pbind commands. (For details, please see the config file.)

Operating System Notes

Shell Environments:

ulimit -s 131072 was used to limit the space consumed by the stack (and therefore make more space available to the heap).

The "Logical Domains Manager" service was turned off using the command "svcadm disable ldmd".

System Tunables:

(/etc/system parameters)

autoup = 86400

Causes pages older than the listed number of seconds to be written by fsflush.
doiflush = 0

Controls whether file system metadata syncs will be executed during fsflush invocations.
dopageflush = 0

Controls whether memory is examined for modified pages during fsflush invocations.
zfs:zfs_arc_max=1073741824

Determines the maximum size of the ZFS Adaptive Replacement Cache (ARC).



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2

SPECint_rate2006 = 1770

SPECint_rate_base2006 = 1520

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Mar-2017
Hardware Availability: Apr-2017
Software Availability: Jul-2017

Platform Notes

Sysinfo program /export/cpu2006/config/sysinfo
Revision 6993 of 2015-11-06 (975e92c7086bc383773e22882bdda8dd)
running on H2S-210-D0 Fri Mar 3 16:59:12 2017

This section contains SUT (System Under Test) info as seen by
some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /usr/sbin/psrinfo
  SPARC64-XII (chipid 0, clock 3900 MHz)
  SPARC64-XII (chipid 1, clock 3900 MHz)
  2 chips
  192 threads
  3900 MHz
```

From kstat: 24 cores

From prtconf: 1046016 Megabytes

```
/etc/release:
  Oracle Solaris 11.3 SPARC
uname -a:
  SunOS H2S-210-D0 5.11 11.3 sun4v sparc sun4v
```

SPEC is set to: /export/cpu2006

```
disk: df -h /export/cpu2006
Filesystem      Size  Used  Available Capacity  Mounted on
rpool/export    547G  2.6G    401G      1%    /export
```

(End of data from sysinfo program)

General Notes

File System:
tmpfs: output_root was used to put run directories in /tmp/cpu2006
zfs: operating system

SPEC CPU2006 benchmark:
Updated with runspec --update

Base Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2

SPECint_rate2006 = 1770

SPECint_rate_base2006 = 1520

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Mar-2017
Hardware Availability: Apr-2017
Software Availability: Jul-2017

Base Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_SPARC
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS

Base Optimization Flags

C benchmarks:
-std=c99 -m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=4M
-xsegment_align=4M -xthroughput -xalias_level=std

C++ benchmarks:
-m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=4M
-xsegment_align=4M -xthroughput -xalias_level=compatible
-library=stlport4 -lfast

Base Other Flags

C benchmarks:
-xjobs=8

C++ benchmarks:
-xjobs=8

Peak Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_SPARC
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2

SPECint_rate2006 = 1770

SPECint_rate_base2006 = 1520

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Mar-2017
Hardware Availability: Apr-2017
Software Availability: Jul-2017

Peak Optimization Flags

C benchmarks:

```

400.perlbench: -std=c99 -xprofile=collect:./feedback(pass 1)
               -xprofile=use:./feedback(pass 2) -m32 -fast
               -xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
               -xthroughput -xtarget=sparc64xplus -xipo=1
               -xalias_level=std -xrestrict -xprefetch=no%auto -xO4
               -Wc,-Qiselect-funcalign=4 -xthroughput=no -lfast

401.bzip2: -std=c99 -xprofile=collect:./feedback(pass 1)
            -xprofile=use:./feedback(pass 2) -m32 -fast
            -xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
            -xthroughput -xalias_level=strong -xprefetch=no%auto
            -Wc,-Qiselect-funcalign=4 -Wc,-Qicache-chbab=1
            -xinline_param=max_inst_hard:1000,max_inst_soft:500,max_growth:60
            -lfast

403.gcc: -std=c99 -xprofile=collect:./feedback(pass 1)
          -xprofile=use:./feedback(pass 2) -m32 -fast
          -xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
          -xthroughput -xO4 -xipo=2 -xprefetch=no%auto
          -Wc,-Qiselect-funcalign=64
          -xcache=32/128/4/4:256/128/8/4:8192/128/16/24
          -xalias_level=layout

429.mcf: -std=c99 -xprofile=collect:./feedback(pass 1)
          -xprofile=use:./feedback(pass 2) -m32 -fast
          -xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
          -xthroughput -xipo=2 -xalias_level=std -xprefetch=latx:0.2
          -W2,-Asac -Wc,-Qiselect-funcalign=64

445.gobmk: -std=c99 -xprofile=collect:./feedback(pass 1)
            -xprofile=use:./feedback(pass 2) -m32 -fast
            -xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
            -xthroughput -xO4 -xalias_level=std -xrestrict
            -xprefetch=no%auto -Wc,-Qiselect-funcalign=64
            -Wc,-Qgsched-T=4

456.hmmcr: -std=c99 -xprofile=collect:./feedback(pass 1)
            -xprofile=use:./feedback(pass 2) -m32 -fast
            -xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
            -xthroughput -xipo=1 -xunroll=8 -Wc,-Qms_pipe-pref
            -Wc,-Qiselect-funcalign=4
            -xcache=32/128/4/4:256/128/8/4:8192/128/16/48

458.sjeng: -std=c99 -xprofile=collect:./feedback(pass 1)
            -xprofile=use:./feedback(pass 2) -m32 -fast
            -xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
            -xthroughput -xO4 -xipo=2 -xalias_level=std -xunroll=4
            -Wc,-Qiselect-funcalign=4 -W2,-Afully_unroll:always=on
            -xprefetch=latx:0.6 -xcheck=%none

```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2

SPECint_rate2006 = 1770

SPECint_rate_base2006 = 1520

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Mar-2017
Hardware Availability: Apr-2017
Software Availability: Jul-2017

Peak Optimization Flags (Continued)

462.libquantum: -std=c99 -m32 -fast -xtarget=sparc64xii -xpagesize=256M
-xsegment_align=256M -xthroughput -m64
-xtarget=sparc64xplus -xipo=2
-xcache=32/128/4/4:256/128/8/4:8192/128/16/24
-xinline_param=level:1 -Wc,-Qiselect-funcalign=4
-xalias_level=layout -xprefetch=latx:0.2

464.h264ref: -std=c99 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xtarget=sparc64xplus -xipo=1
-Wc,-Qiselect-funcalign=4 -xthroughput=no
-xalias_level=layout -xprefetch=latx:0.2 -xcheck=%none

C++ benchmarks:

471.omnetpp: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xipo=1 -xalias_level=compatible -xunroll=2
-xprefetch_level=3 -W2,-Asac -xthroughput=no -lfast

473.astar: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xtarget=sparc64xplus -xalias_level=compatible
-xipo=2 -xunroll=6 -xrestrict=%source
-Wc,-Qiselect-funcalign=64 -Wc,-Qgsched-T=4
-xprefetch=latx:0.3 -lfast

483.xalancbmk: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m32 -fast
-xtarget=sparc64xii -xpagesize=256M -xsegment_align=256M
-xthroughput -xipo=2 -xalias_level=compatible -xdepend
-xprefetch_level=3 -xprefetch=latx:0.4 -library=stlport4
-W2,-Asac -Wc,-Qiselect-funcalign=64 -features=no%except
-lfast

Peak Other Flags

C benchmarks:
-xjobs=8

C++ benchmarks:
-xjobs=8



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2

SPECint_rate2006 = 1770

SPECint_rate_base2006 = 1520

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Mar-2017

Hardware Availability: Apr-2017

Software Availability: Jul-2017

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Oracle-Developer-Studio12.6.html>

<http://www.spec.org/cpu2006/flags/Fujitsu-M12-2.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Oracle-Developer-Studio12.6.xml>

<http://www.spec.org/cpu2006/flags/Fujitsu-M12-2.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Apr 20 09:42:27 2017 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 April 2017.