



**ZEBRA**

# Z-Perform 1000D Receipt

## FEATURES

- Direct thermal, smooth, uncoated, paper receipt
- Excellent print quality
- 10 year archivability\*
- Available in 2.4mil (05610RM), 3.5mil (66018RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth uncoated paper tag	2.4mil / 3.5mil
TOTAL ± 10%		2.4mil / 3.5mil

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
NA	-40°F to 140°F (-40°C to 60°C)	72° F (22° C) at 50% RH

### Expected Exterior Life

Not recommended for outdoor use

## CHEMICAL RESISTANCE

	Chemical	Direct Thermal
Weak	Blood	NR
	Body Fluid	NR
	Salt Water	NR
	Water	NR
	Window Cleaner	NR
Moderate	Alcohol	NR
	Ammonia	NR
	Bleach	NR
	IPA	NR
Harsh	Gasoline	NR
	Grease	NR
	Oil	NR
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

● Recommended ● Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

- Packing lists



- Retail hang tags



- General purpose ticketing



- Work in process tagging



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | [inquiry4@zebra.com](mailto:inquiry4@zebra.com)

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.



**ZEBRA**

# Z-Perform 1000D Receipt

## Recommended Tone Settings for Zebra printers using Speed 3, Contrast 0:

	MZ220, MZ320	QL220Plus, QL320Plus, QL420Plus, QLn220, QLn320	QLn420	RW420, RW220	iMZ320, ZQ510, ZQ520	ZQ320, ZQ310
Z-Perform 1000D 2.4mil Receipt	25	20	0	10	20	10
Z-Perform 1000D 3.5mil Receipt	25	20		0		

Images will remain legible for up to 10 years provided they are formed properly and the receipts are handled and stored under the proper conditions. For archival use these receipts need to be protected from exposure to light, heat, water, solvents, cleaners, plasticizers, and oils (including vegetable oils and skin oils), and they need to be stored with compatible materials at temperatures less than 77°F, and 45-65% RH. Image durability depends on the energy used to print the receipts. To maximize image durability, receipts should be printed at the recommended tone settings.

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

**For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)**

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | [inquiry4@zebra.com](mailto:inquiry4@zebra.com)

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.