Effect of Corrugations to steady thermal explosion with power-law thermal absorptivity in microannuli

Zotin K.-H. Chu^1 and Chen Qin^2

¹ 3/F, 4, Alley 2, Road Xiushan, Leshanxinchun, Xujiahui 200030, China ² Department of Physics, Xinjiang Normal University, Urumqi 830054, China

Abstract

We obtain the approximate solutions for the steady temperature profiles of materials with a temperature-dependent thermal absorptivity inside a microannulus with wavy-rough surfaces considering a quasilinear partial differential equation by the boundary perturbation approach. Our numerical results show that the critical Frank-Kamanestkii parameter depends on the small-amplitude wavy-roughness for specific power-law of thermal absorptivity.

PACS numbers: 83.80.Jx, 66.30.Xj, 89.30.-g, 89.20.Dd, 44.05.+e

I. INTRODUCTION

Orbiting spacecraft are subjected to forces such as drag and solar pressure that have to be compensated for in order to maintain the desired orbit, and they may also have to be transferred from the initial orbit where they are placed by the launcher to their final orbit. The orientations and orbits of spacecraft are controlled by low-thrust propulsion systems. The propulsion control systems can be broadly classified as suitable for coarse and fine control. Hitherto, the major effort has been expended on the development of coarse control systems. In the 1960s, simple cold gas propulsion systems were employed and over the years more efficient systems were developed such as monopropellant hydrazine fuel, storable bipropellant mixtures providing more efficient combustion and, quite recently, new type of propulsion systems to provide higher propulsive impulse and higher performance to cope with increased spacecraft masses and longer satellite lifetimes $|1-2|$. The crucial issue which is related to the important components of many space systems is the thruster system that shall generate thrust in a well-defined direction. One means for thrust generation is solidstate micro-thrusters which requires the safety storage of fuels [3].

Meanwhile, thermal instability such as the catastrophic phenomenon of thermal runaway in which a slight change of external heating (e.g., microwave) power causes the temperature to increase rapidly to the melting point of the material (e.g., ceramic) have been studied for simple geometry cases $|4-10|$. Up to now, the basic understanding of the (microwave) heating process still remains somewhat empirical and speculative due to its highly nonlinear character. The mathematical description of this process is accordingly fraught with nonlinearities (not to mention the external heating) : The heat equation is highly temperature dependent at the temperatures required for sintering. Moreover, the thermal boundary conditions must take into account both convective and radiation heat loss. The result is a highly nonlinear initial-boundary value problem. Even for simple geometry problems, because of the highly nonlinearity characteristic, numerical approaches were often adopted to solve the corresponding equations and boundary conditions [4,9-10].

Relevant approaches have also a wide field of applications in combustion theory or for safety of storage of materials capable of exothermic chemical reaction [11]. In this short paper, we shall consider the above mentioned problems with simple geometry (say, an annulus) in microdomain. However, real surfaces are rough at the micro- or even at the meso-scale

[12-14]. We presume the roughness to be wavy-like in transverse direction along the outer and inner surfaces of the annulus which thus make the corresponding boundary conditions highly nonlinear. With this, we adopt the boundary perturbation approach [12-14] to handle the mathematically complicated boundary value problems. Our numerical results show that for certain power-law of thermal absorptivity the small amplitude wavy-roughness could influence the steady thermal behavior inside a microannulus significantly.

II. MATHEMATICAL FORMULATIONS

Considering the forced heat equation

$$
\rho c_p(T)\frac{\partial T}{\partial t} = \nabla \cdot \left(\nu(T)\nabla T\right) + \gamma(T)\phi^2
$$

where T is the temperature, ν is the thermal conductivity, γ is the thermal absorptivity, ρ is the density that is usually assumed constant, c_p is the specific heat and ϕ is the heating source. Here, the thermal absorptivity depends on the square of the external source (amplitude). Assuming constant specific heat and that the heating source (amplitude) is temperature independent, the appropriate form of above equation becomes

$$
\frac{\partial T}{\partial t} = \nabla \cdot \left(\kappa(T) \nabla T \right) + \gamma(T) \phi^2,\tag{1}
$$

where ϕ might depend on the spatial coordinates.

A. Smooth Cylinder Geometry

Without loss of the generality, we consider a class of solutions for the nonlinear reactiondiffusion equations

$$
\frac{\partial T}{\partial t} = \frac{\partial}{x \partial x} \left(x T^m \frac{\partial T}{\partial x} \right) + \delta K(x) T^n \tag{2}
$$

with the geometry of an infinite cylinder ($x \equiv r$ with r being the radius) and $m = -1$. Here, δ is the Frank-Kamanestkii parameter [15] which incorporates the chemical properties of the combustible material, the temperature of assembly as well as its geometrical dimensions. $K(x) = x^{\mu}$ and $\mu < 0$, μ is a constant. The critical value δ_{cr} defines criticality and provides, for example, a criterion for safety of storage of materials capable of exothermic chemical reaction [11,15]. Thus, δ_{cr} is important in characterizing the thermal stability properties of the material under consideration.

For the smooth geometry case, we consider the steady state thermal explosions between two infinite cylindrical material undergoing exothermic reaction by using the change of variable given by $x = \exp(y)$, $T^n = \exp(U)$ and $\Theta = U + (2 + \mu)y$ and we can obtain that closed-form solutions which are available for all real values of μ [15]. In fact, equation (2) becomes

$$
\frac{d^2\Theta}{dy^2} + \delta n e^{\Theta} = 0\tag{3}
$$

and the solutions are

$$
e^{\Theta} = \frac{C_0}{\cosh^2\left(\sqrt{\frac{n\delta C_0}{2}}y - D_0\right)} \qquad \text{or} \qquad T^n = \frac{C_0 x^{-2-\mu}}{\cosh^2\left(\sqrt{\frac{n\delta C_0}{2}}\ln x - D_0\right)} \tag{4}
$$

where C_0 , D_0 are integration constants.

Note that for the pure cylindrical case $(x \equiv r = 0)$, once $\mu \ge -1$, we must make sure the solution to be well defined considering the limit of $x \to 0$:

$$
T^{n} = \frac{(\mu + 2)^{2}}{2n\delta x^{2+\mu}\cosh^{2}\left(\frac{2+\mu}{2}\ln x - D_{0}\right)}
$$
(5)

with

$$
C_0 = \frac{(2+\mu)^2}{2n\delta}.
$$

The boundary conditions for a smooth annulus could be

$$
T^n(1) = 1 \qquad \text{and} \qquad T^n(s) = 1,\tag{6}
$$

where $s = r_1/r_2$ (cf. Fig. 1) and $x = r/r_2$. These could help us to fix C_0 and D_0 . Under this situation, we have

$$
\sqrt{\frac{n\delta}{2}}\ln s \cosh(-D_0) = D_0 + \cosh^{-1}[s^{\frac{-\mu-2}{2}}\cosh(-D_0)],\tag{7}
$$

where $\mu < -1$.

B. Wavy-Rough Annulus Geometry

We start to consider a steady state heat flow in a wavy-rough microannulus of r_2 (in mean-averaged outer radius) with the outer wall being a fixed wavy-rough surface : $r = r_2 + \epsilon \sin(k\theta)$ and r_1 (in mean-averaged inner radius) with the inner wall being a fixed wavy-rough surface : $r = r_1 + \epsilon \sin(k\theta + \beta)$, where ϵ is the amplitude of the (wavy) roughness, and the wave number : $k = 2\pi/L$ (L is the wave length), β is the phase shift. The schematic is illustrated in Fig. 1.

With the boundary perturbation approach from Refs. [12-14], we shall derive the temperature field along the wavy-rough microannuli considering dimensionless values. We firstly select $L_a \equiv r_2$ to be the characteristic length scale and set

$$
r' = r/L_a, \quad R_o = r_2/L_a, \quad R_i = r_1/L_a, \quad \epsilon' = \epsilon/L_a.
$$

After this, for simplicity, we drop all the primes. It means, now, r, R_o , R_i , and ϵ become dimensionless. The walls are prescribed as $r = R_o + \epsilon \sin(k\theta)$, $r = R_i + \epsilon \sin(k\theta + \beta)$ and the presumed steady state heat flow is along the z-direction (microannulus-axis direction). Let T be expanded in ϵ :

$$
T = T_0 + \epsilon T_1 + \epsilon^2 T_2 + \cdots,\tag{8}
$$

and on the boundary, we expand $T(r_0 + \epsilon dr, \theta (= \theta_0))$ into

$$
T(r,\theta)|_{(r_0+\epsilon dr,\theta_0)}=T(r_0,\theta)+\epsilon[dr\,T_r(r_0,\theta)]+\epsilon^2\left[\frac{dr^2}{2}T_{rr}(r_0,\theta)\right]+\cdots
$$

where the subscript means the partial differentiation (say, $T_r \equiv \partial T/\partial r$).

The corresponding equation, for simplicity (as the wavy roughness being imposed) as we select firstly $n = m + 1$, becomes

$$
\frac{\partial}{r\partial r}\left(rT^m\frac{\partial T}{\partial r}\right) + \delta r^\mu T^{m+1} = 0\tag{9}
$$

or

$$
\frac{\partial}{r\partial r}\left(r\frac{\partial\Theta}{\partial r}\right) + (m+1)\delta r^{\mu}\Theta = 0\tag{10}
$$

with $\Theta = T^{m+1}$.

Now, we can set $\eta = r^{(2+\mu)/2}$ and then obtain

$$
\frac{\partial^2 \Theta}{\partial \eta^2} + \frac{\partial \Theta}{\eta \partial \eta} + \frac{4(m+1)\delta}{(2+\mu)^2} \Theta = 0, \qquad \mu \neq -2.
$$
 (11)

Above equation has the zeroth order solution in terms of Bessel functions

$$
\Theta_0 = A_0 J_0(K\eta) + B_0 Y_0(K\eta),\tag{12}
$$

once we consider $\Theta = \Theta_0 + \epsilon \Theta_1 + \cdots$ [16]. Here, A_0 , B_0 are integration constants. $K =$ $2\sigma/(2+\mu)$ and $\sigma = [(m+1)\delta]^{1/2}$. Thus, we obtain, for $\mu \neq -2$,

$$
\Theta_0 = T_0^n = T_0^{m+1} = A_0 J_0 \left(\frac{2[(m+1)\delta]^{1/2}}{2+\mu} r^{(2+\mu)/2} \right) + B_0 Y_0 \left(\frac{2[(m+1)\delta]^{1/2}}{2+\mu} r^{(2+\mu)/2} \right) \tag{13}
$$

and for $\mu = -2$,

$$
\Theta_0 = T_0^n = T_0^{m+1} = A^* \sin\left([(m+1)\delta]^{1/2} \ln r \right) + B^* \cos\left([(m+1)\delta]^{1/2} \ln r \right). \tag{14}
$$

Here, A_0 , B_0 or A^* , B^* could be uniquely determined after imposing the boundary conditions. This leads to $T_0 = \Theta_0^{1/(m+1)}$.

As for the first order correction or solution, with the wavy-roughness effect, we can only have (considering $T^n \equiv (T_0 + \epsilon T_1 + \cdots)^n = T_0^n + \epsilon n T_1 T_0^{n-1} + \cdots$ with T_0 known), for $m = 0$,

$$
\frac{\partial^2 T_1}{\partial r^2} + \frac{\partial T_1}{r \partial r} + \frac{1}{r^2} \frac{\partial^2 T_1}{\partial \theta^2} + \delta r^\mu T_1 = 0,\tag{15}
$$

due to the complicated orientational characteristics (θ -dependent). Using the boundary conditions from the equation (6), we have

$$
T_0|_{r=s} = 1, \t T_0|_{r=1} = 1,
$$
\t(16)

$$
\frac{\partial T_0}{\partial r}|_{r=1} \sin(k\theta) + T_1|_{r=1} = 0,\tag{17}
$$

and

$$
\frac{\partial T_0}{\partial r}|_{r=s}\sin(k\theta+\beta)+T_1|_{r=s}=0,\tag{18}
$$

Equation (15) can be transformed to

$$
\frac{\partial^2 R}{\partial \xi^2} + \frac{\partial R}{\xi \partial \xi} + \left(\frac{2}{2+\mu}\right)^2 (\delta r^{\mu+2} - K^2) R = 0, \qquad T_1 = i e^{iK\theta} R(\xi), \tag{19}
$$

and solved after setting

$$
\xi^2 = r^{\mu+2}
$$
, $\nu = \frac{2}{2+\mu} \delta^{1/2}$, $\bar{K} = \frac{2}{2+\mu} K$, $\mu \neq -2$, (20)

where

$$
R(\xi) = A_1 J_{\bar{K}}(\nu \xi) + B_1 J_{-\bar{K}}(\nu \xi). \tag{21}
$$

We thus have

$$
T_1 = ie^{iK\theta} \left[A_1 J_{\frac{2}{2+\mu}K} \left(\frac{2}{2+\mu} \delta^{1/2} r^{(2+\mu)/2} \right) + B_1 J_{-\frac{2}{2+\mu}K} \left(\frac{2}{2+\mu} \delta^{1/2} r^{(2+\mu)/2} \right) \right],\tag{22}
$$

with $\mu \neq -2$ or

$$
T_1 = ie^{iK\theta} \Big[C_1 \cos\Big((\delta - K^2)^{1/2} \ln r\Big) + D_1 \sin\Big((\delta - K^2)^{1/2} \ln r\Big) \Big], \qquad \mu = -2. \tag{23}
$$

Here, A_1, B_1, C_1, D_1 could be fixed by boundary conditions or equations (16-18). In fact, from the boundary condition (17) or the wavy roughness along the annulus, we can identify $K=k. \label{eq:K}$

With the first order perturbed solution due to wavy roughness : T_1 , we can thus obtain the approximate solution for especially $m = 0$

$$
T = T_0 + \epsilon T_1 + \cdots, \tag{24}
$$

where

$$
T_0 = A_0 J_0 \left(\frac{2\delta^{1/2}}{2+\mu} r^{(2+\mu)/2}\right) + B_0 Y_0 \left(\frac{2\delta^{1/2}}{2+\mu} r^{(2+\mu)/2}\right), \qquad \mu \neq -2 \tag{25}
$$

or

$$
T_0 = A^* \sin\left(\delta^{1/2} \ln r\right) + B^* \cos\left(\delta^{1/2} \ln r\right), \qquad \mu = -2,\tag{26}
$$

with T_1 given by equations (22) and (23). To be specific, we have $(s \equiv R_i)$

$$
A_0 = \frac{Y_0(R_s s^{(2+\mu)/2}) - Y_0(R_s)}{J_0(R_s) Y_0(R_s s^{(2+\mu)/2}) - Y_0(R_s) J_0(R_s s^{(2+\mu)/2})},
$$

\n
$$
B_0 = \frac{J_0(R_s) - J_0(R_s s^{(2+\mu)/2})}{J_0(R_s) Y_0(R_s s^{(2+\mu)/2}) - Y_0(R_s) J_0(R_s s^{(2+\mu)/2})},
$$
\n(27)

where $R_s = 2\sqrt{\delta}/(2+\mu)$, and

$$
A^* = \frac{1 - \cos(\sqrt{\delta} \ln s)}{\sin(\sqrt{\delta} \ln s)}, \qquad B^* = 1.
$$
 (28)

Meanwhile, with equations (17) and (18), we can obtain

$$
A_1 = \left[F_1 J_{\frac{-2K}{2+\mu}} \left(\frac{2\sqrt{\delta}}{2+\mu} s^{(2+\mu)/2} \right) - G_1 J_{\frac{-2K}{2+\mu}} \left(\frac{2\sqrt{\delta}}{2+\mu} \right) \right] / det,\tag{29}
$$

$$
B_1 = \left[G_1 J_{\frac{2}{2+\mu}K} \left(\frac{2\sqrt{\delta}}{2+\mu} \right) - F_1 J_{\frac{2}{2+\mu}K} \left(\frac{2\sqrt{\delta}}{2+\mu} s^{(2+\mu)/2} \right) \right] / det,\tag{30}
$$

where

$$
F_1 = -\sqrt{\delta} \Big[A_0 J_1 \left(\frac{2\sqrt{\delta}}{2+\mu} \right) + B_0 Y_1 \left(\frac{2\sqrt{\delta}}{2+\mu} \right) \Big],
$$

\n
$$
G_1 = -e^{i\beta} \sqrt{\delta} s^{\mu/2} \Big[A_0 J_1 \left(\frac{2\sqrt{\delta} s^{(2+\mu)/2}}{2+\mu} \right) + B_0 Y_1 \left(\frac{2\sqrt{\delta} s^{(2+\mu)/2}}{2+\mu} \right) \Big],
$$

\n
$$
det = J_{\frac{2}{2+\mu}K} \left(\frac{2\sqrt{\delta}}{2+\mu} \right) J_{\frac{-2K}{2+\mu}} \left(\frac{2\sqrt{\delta}}{2+\mu} s^{(2+\mu)/2} \right) - J_{\frac{-2K}{2+\mu}} \left(\frac{2\sqrt{\delta}}{2+\mu} \right) J_{\frac{2}{2+\mu}K} \left(\frac{2\sqrt{\delta}}{2+\mu} s^{(2+\mu)/2} \right).
$$

III. NUMERICAL RESULTS AND DISCUSSIONS

We plot $T_0(r)$ for different μ (= -4, -1, 1) with fixed δ (= 2) in Fig. 1. The boundary conditions : $T_0(r = s = 0.4) = T_0(r = 1) = 1$ are correctly matched at both walls. Considering the contributions from the first-order perturbation $T_1(r)$, we plot the approximate temperature profiles : $T_0(r) + \epsilon T_1(r)$ with the same $\mu (= -4, -1, 1)$ in Fig. 2. Here, $\epsilon = 0.1$, $\beta = \pi/4$ and $k = 8$. We can observe that, for $\mu = -4$, the effect of first-order perturbation is quite large compared to other cases of μ .

To consider the effects of roughness, we could observe that, as evidenced from the first-order correction or approximation : T_1 , the Frank-Kamanestkii parameter (δ) depends on the wave number of wavy-roughness (cf. Eq. (23)). Thus, the critical Frank-Kamanestkii δ_{cr} depends on the square of the wave number k (or k_{cr} for certain critical ones). However, above results are only for cases of $\mu = -2$ (or $K(x) = x^{-2}$ which is defined in Eq. (2))!

IV. CONCLUSION

We adopt the boundary perturbation approach to obtain the approximate solutions for the steady temperature profiles of materials with a temperature-dependent thermal absorptivity inside a microannulus with wavy-rough surfaces considering a quasilinear partial differential equation. Our results show that the critical Frank-Kamanestkii parameter strongly depends on the wavy-roughness for specific power-law of thermal absorptivity. Acknowledgement. The first author stayed at the Chern Shiing-Shen Institute of Mathematics, Nankai University for one month. Thus the first author should thank their hospitality for their Visiting-Scholar Program.

^[1] A. Epstein and S.D. Senturia, Science 276, 1211 (1997). A.P. London, A.A. Ayon, A.H. Epstein, S.M. Spearing, T. Harrison, Y. Peles, and J.L. Kerrebrock, Sensors Actuators A 92, 351 (2001).

^[2] A. Franks, M. Luty, C.J. Robbie, M. Stedman, Nanotechnology 9, 61 (1998).

^[3] A.B. Eriksson, R. Lindegren and J. Köhler, in Proc. 13th. International Conference on Solid-State Sensors, Actuators and Microsystems (Seoul, Korea, June 5-9 ,2005). Digest of Technical Papers. TRANSDUCERS '05 (2005).

^[4] G. Roussy, A. Bennani and J. Thiebaut, J. Appl. Phys. 62, 1167 (1987).

^[5] C.J. Coleman, Appl. Math. Model. 14, 439 (1990).

^[6] C.J. Coleman, J. Aust. Math. Soc. Ser. B 33, 1 (1991).

^[7] N.F. Smyth, J. Aust. Math. Soc. B 33, 403 (1992).

- [8] G.A. Kriegsmann, J. Appl. Phys. 71, 1960 (1992).
- [9] T.R. Marchant and N.F. Smyth, SIAMJ. Appl. Math. 53, 1591 (1993).
- $[10]$ A.H. Pincombe and N.F. Smyth, IMA J. Appl. Math. 52, 141 (1994).
- [11] J. Bebernes and D. Eberly, Mathematical problems from combustion theory (Springer-Verlag, New York, 1989).
- [12] W. K.-H. Chu, Z. Angew. Math. Mech. 76, 363 (1996).
- [13] W. K.-H. Chu, Z. Angew. Math. Phys. 47, 591 (1996).
- [14] K.-H. W. Chu, Electrochimica Acta 53, 4920 (2008).
- [15] D.A. Frank-Kamenetskii, Diffusion and heat transfer in chemical kinetics (Plenum Press, New York, 1969).
- [16] Z.K.-H. Chu and C. Qin, Preprint (2008).

Fig. 1. Approximate zeroth order temperature profiles : $T_0(r)$ for different μ (= -4, -1, 1) with $\delta = 2$. The boundary conditions are satisfied at both sides $(T_0(s = 0.4) = T_0(1) = 1)$.

Fig. 2. Approximate $T_0(r) + \epsilon T_1(r)$ temperature profiles for different μ (= -4, -1, 1) with $\delta = 2$. Here, the wave number of roughness k is equal to 8, $\epsilon = 0.1$, $\beta = \pi/4$ and the inner boundary is $s = 0.4$. We can observe that the small-amplitude wavy-roughness changes the near-inner-wall temperature distribution significantly once $\mu=-4.$