# Mitigating the Learning Bias towards Repetition by Self-Contrastive Training for Open-Ended Generation

Jian Guan, Minlie Huang<sup>∗</sup>

The CoAI Group, DCST, Institute for Artificial Intelligence, State Key Lab of Intelligent Technology and Systems, Beijing National Research Center for Information Science and Technology, Tsinghua University, Beijing 100084, China j-guan19@mails.tsinghua.edu.cn, aihuang@tsinghua.edu.cn

### Abstract

Despite the huge progress in a myriad of generation tasks, pretrained language models (LMs) such as GPT2 still tend to generate repetitive texts with maximization-based decoding algorithms for open-ended generation. We attribute their overestimation of token-level repetition probabilities to the learning bias: LMs capture simple repetitive patterns faster with the MLE loss. We propose self-contrastive training to penalize the output of a premature checkpoint of the same model when it incorrectly predicts repetition, which is shown to mitigate repetition effectively while maintaining fluency on two datasets. Furthermore, we find that LMs use longer-range dependencies to predict repetitive tokens than non-repetitive ones, which may be the cause of sentence-level repetition  $\text{loops}^1$  $\text{loops}^1$ .

### 1 Introduction

Existing LMs prefer to generate repetitive texts for open-ended generation with greedy decoding or beam search [\(Welleck et al.,](#page-5-0) [2020a\)](#page-5-0). Even largescale pretrained LMs such as GPT3 [\(Brown et al.,](#page-4-0) [2020\)](#page-4-0) still generate redundant sentences [\(Dou et al.,](#page-4-1) [2022\)](#page-4-1). Despite many solutions proposed from the perspective of both training [\(Welleck et al.,](#page-5-1) [2020b\)](#page-5-1) and decoding [\(Holtzman et al.,](#page-4-2) [2020\)](#page-4-2), the cause of preference for repetition still needs to be clarified.

By analyzing the training dynamics of LMs regarding (non-)repetitive tokens, we reveal the learning bias towards repetition: LMs capture simple repetitive patterns first, which dominate the output distribution throughout the input space, and then learn more non-repetitive patterns during training. We show that the repetition problem can be mitigated by only training more steps (i.e., allowing over-fitting), although the coherence with inputs will be impacted. Conversely, when trained insufficiently, LMs will overestimate repetition probabilities even for golden prefixes. We propose selfcontrastive training (SELFCONT), which exploits the contrast with a premature checkpoint of the same model by penalizing its output when it incorrectly predicts repetition. Experiments on two datasets show that SELFCONT effectively alleviates repetition while maintaining fluency by factoring out the undesired repetition behaviors highlighted by the premature checkpoint.

Besides the above analysis about overestimating token-level repetition probabilities during training, we also find that LMs use longer-range dependencies to predict repetitive tokens than non-repetitive ones. It may explain why LMs tend to fall into repetition loops [\(Xu et al.,](#page-5-2) [2022\)](#page-5-2). The problem may be solved by improving the modeling of long-range dependencies (e.g., increasing model sizes), which are left to future work.

# 2 Related Work

Regarding the cause of the repetition problem, [Fu](#page-4-3) [et al.](#page-4-3) [\(2021\)](#page-4-3) theoretically derived bounds of repetition probabilities of the first-order Markov LM, although it is difficult to extend the bounds to general LMs. Another line of works attributed repetition to error accumulation during generation [\(Welleck](#page-5-1) [et al.,](#page-5-1) [2020b;](#page-5-1) [Arora et al.,](#page-4-4) [2022\)](#page-4-4), while LMs still prefer repetition given golden prefixes.

We divide recent works that alleviate repetition into training- and decoding-based methods: (1) Training-based Methods. [Welleck et al.](#page-5-1) [\(2020b\)](#page-5-1) proposed unlikelihood training (UL) to reduce the probabilities of repetitive generations. [Lin et al.](#page-5-3) [\(2021\)](#page-5-3) and [Xu et al.](#page-5-2) [\(2022\)](#page-5-2) further extended the framework at the token and sequence level, respectively. SELFCONT focuses on token-level modeling, which is orthogonal with sequence-level methods. [Xi et al.](#page-5-4) [\(2021\)](#page-5-4) adopted additional modules to learn repetition patterns and control repetition explicitly. (2) Decoding-based Methods.

<span id="page-0-0"></span><sup>∗</sup>Corresponding author

<sup>&</sup>lt;sup>1</sup>The code is available at [https://github.com/](https://github.com/thu-coai/SelfCont) [thu-coai/SelfCont](https://github.com/thu-coai/SelfCont)

One straightforward solution to repetition is blocking repetitive n-grams generations [\(Paulus et al.,](#page-5-5) [2018\)](#page-5-5) or penalizing probabilities of repetitive candidates [\(Keskar et al.,](#page-4-5) [2019\)](#page-4-5). [Li et al.](#page-5-6) [\(2022\)](#page-5-6) selected candidates that maximize the probability difference between different-sized models. Sampling-based decoding methods are also shown effective in avoiding repetition, such as temperature sampling [\(Ficler](#page-4-6) [and Goldberg,](#page-4-6) [2017\)](#page-4-6), Top-k sampling [\(Fan et al.,](#page-4-7) [2018\)](#page-4-7), nucleus sampling [\(Holtzman et al.,](#page-4-2) [2020\)](#page-4-2), and typical sampling [\(Meister et al.,](#page-5-7) [2022\)](#page-5-7). Although these methods reduce superficial repetition, it is unclear whether they utilize the underlying long-range dependencies to maintain coherence.

### 3 Empirical Analysis

Neural networks (NNs) are highly expressive to approximate arbitrary input-output mappings. Using Fourier analysis, [Rahaman et al.](#page-5-8) [\(2019\)](#page-5-8) showed the *spectral bias* of NNs: they learn low-frequency components faster during training, which are less complex and vary globally without local fluctuation. Our key hypothesis is that simple repetitive patterns may be such low-frequency components and learned by LMs early. In this section, we first formulate LMs  $(\S3.1)$  $(\S3.1)$ , and then investigate the training dynamics  $(\S3.2)$  $(\S3.2)$  and the ability to model long-range dependencies (§[3.3\)](#page-2-0) of LMs.

# <span id="page-1-0"></span>3.1 Language Models

LMs aim to fit the mapping  $x_t = f(x_{1:t-1})$  defined by a training corpus, where  $x_{1:t}$  is a sequence from the corpus. To this end, they are usually trained by minimizing the following cross-entropy loss:

$$
\mathcal{L} = -\mathbf{x}_t^{\mathrm{T}} \cdot \log\left[\mathrm{softmax}\left(f_\theta(x_{1:t-1})\right)\right],\quad(1)
$$

where  $\mathbf{x}_t \in \{0,1\}^{|\mathcal{V}|}$  is the one-hot representation of  $x_t$  indicating its index in the vocabulary  $\mathcal V$ , and  $f_{\theta}(x_{1:t-1}) \in \mathbb{R}^{|\mathcal{V}|}$  is the output logits of the LM parameterized by  $\theta$ . Predictably, with more training steps, argmax( $f_{\theta}$ ) is closer to the target function f. Early stopping [\(Morgan and Bourlard,](#page-5-9) [1989\)](#page-5-9) is a commonly used regularization technique to avoid over-fitting, e.g., stopping training when the validation loss reaches the minimum. Since NNs prioritize learning low-complexity components, early stopping may result in unexpected generations. We are inspired to investigate whether simple repetitive patterns in human-written texts are learned first, thus dominating the generations.

#### <span id="page-1-1"></span>3.2 Training Dynamics

We randomly sample 1k sequences containing 512 tokens from the Wikitext-103 dataset [\(Merity et al.,](#page-5-10) [2016\)](#page-5-10) and train  $GPT2_{base}$  from scratch for 100 epochs<sup>[2](#page-1-2)</sup>. Given a golden prefix  $x_{1:t-1}$ , we regard the model prediction  $\hat{x}_t = \text{argmax}(f_\theta(x_{1:t-1}))$  as correct if  $\hat{x}_t = x_t$ . We call  $x_t$  or  $\hat{x}_t$  repetitive if it is included in  $x_{1:t-1}$ , and non-repetitive otherwise.

<span id="page-1-3"></span>

Figure 1: Top: Ratios of positions where  $x_t$  or  $\hat{x}_t$  is repetitive or not, given golden prefixes of the test set. **Bottom:** Ratios of tokens that appear in previous  $l$  tokens, in model-generated texts with greedy decoding.

<span id="page-1-4"></span>Figure [1](#page-1-3) plots the training curves, revealing the learning bias of the LM: (1) The initially learned components prefer to copy input tokens throughout the input space, as indicated by predicting repetitive tokens at ∼90% of positions for both golden and generated prefixes. (2) With golden prefixes, at those positions where  $x_t$  is repetitive, the LM almost always predicts repetition during training. When  $x_t$  is non-repetitive, the LM predicts more non-repetitive tokens with more training steps. The repetition ratio also gradually decreases in modelgenerated texts. (3) The token prediction accuracy improves faster when  $x_t$  is repetitive, indicating that the LM learns repetitive patterns more easily. Moreover, we notice that the validation loss rises at the 1,500th step, where the LM predicts much more repetitive tokens than the ground truth. At the end of the training, the generation has a closer token repetition ratio to the ground truth. But manual

<span id="page-1-2"></span> $2^2$ We use only 1k samples because we expect to over-fit these samples to observe how repetition in generated texts changes with the fitting degree, considering that it will be very time-consuming to fit the whole Wikitext-103 dataset.

<span id="page-2-1"></span>

Figure 2: Perplexity scores computed on *all*, *repetitive* or *non-repetitive* tokens with different prefix lengths. The scores marked with  $\bigcirc$ ,  $\times$ ,  $\bigcirc$  and  $\bigtriangleup$  means that the p-values compared with the score when the prefix length is 250 fall in the following intervals:  $[0, 0.001), [0.001, 0.01), [0.01, 0.05)$  and  $[0.05, 1]$ , respectively.

inspection finds the coherence with inputs is poor due to over-fitting. Appendix [A.1](#page-5-11) shows several generation cases.

### <span id="page-2-0"></span>3.3 Modeling Long-Range Dependencies

Figure [1](#page-1-3) (Top) shows that LMs are still able to predict non-repetitive tokens conditioned on golden prefixes. However, it is still unclear why they get into repetition loops during generation and do not generate any non-repetitive tokens. To shed light on this behavior, we further investigate how LMs learn and utilize long-range dependencies. We finetune GPT $2<sub>base</sub>$  on the training set of Wikitext-103, and examine the effect of prefix lengths on the perplexity of tokens that have appeared in the previous 250 tokens (called *repetitive*) or not on the original test set and model-generated texts.

Figure [2](#page-2-1) indicates (1) The LM only learns dependencies within ∼100 tokens overall. When the prefix length is larger than 100, the perplexity on golden tokens no longer drops significantly  $(p \geq 0.05)$ . (2) The LM learns and utilizes longer-range dependencies to predict repetitive tokens than non-repetitive ones. The perplexity on golden repetitive/non-repetitive tokens plateaus when the prefix length is larger than 160/50, respectively. The case is similar for generated texts. (3) The LM uses short-range contexts to predict non-repetitive tokens regardless of decoding algorithms. Contexts beyond 100 tokens hardly help predict non-repetitive tokens, implying samplingbased decoding reduces repetition through randomness instead of using long-range dependencies.

Based on the above observation, we conjecture that the LMs keep repeating the same sentence with maximization-based decoding [\(Xu et al.,](#page-5-2) [2022\)](#page-5-2) because they rarely learn long-range non-repetitive patterns beyond the sentence level. When generating long texts, LMs may struggle to maintain non-repetitive within a long range. To test the idea, we train  $GPT2_{base}$  from scratch on three datasets constructed from the training set of Wikitext-103: (1)  $\mathcal{D}_{original}$ , where examples are directly sampled from the original training set; (2)  $\mathcal{D}_{\text{random}}$ , where each example contains 30 randomly sampled sentences; (3)  $\mathcal{D}_{\text{morept}}$ , where each example also contains 30 random sentences, but there is at most one token overlapping between any adjacent 5 sentences (generally the period "."). Each dataset consists of 20k examples. We then generate texts using greedy decoding conditioned on the first 50 tokens in the original test set and compute the ratio of texts which fall into loops [\(Holtzman et al.,](#page-4-2) [2020\)](#page-4-2).

<span id="page-2-2"></span>

<b>Training Sets</b> $\vert$ $\mathcal{D}_{original}$ $\mathcal{D}_{random}$ $\mathcal{D}_{morept}$		
<b>Ratios</b> $(\%) \downarrow   60.42$	96.04	1.67

Table 1: Ratios of texts which get stuck into loops generated by LMs trained on different training sets.

As shown in Table [1,](#page-2-2) compared to  $\mathcal{D}_{original}$ , the LM trained on  $\mathcal{D}_{\text{random}}$  has higher repetition ratios because it learns shorter-range non-repetitive patterns only within one sentence. Besides, although sentences in each  $\mathcal{D}_{\text{random}}$  example are unrelated, they can contain repetitive tokens<sup>[3](#page-2-3)</sup>, making the LM learn spurious long-range repetitive patterns to get into repetition loops. In contrast, the LM trained on  $D_{\text{morept}}$  rarely gets into loops since it learns both repetitive and non-repetitive patterns almost within one sentence. Specifically, any adjacent five sentences in each  $\mathcal{D}_{\text{norept}}$  example are unrelated and hardly share tokens. These findings empirically support our hypothesis. Appendix [A.2](#page-5-12) shows more details.

<span id="page-2-3"></span><sup>&</sup>lt;sup>3</sup>The ratios of tokens that have appeared in previous 128 tokens are 12.52% and 32.05% for the training sets of  $\mathcal{D}_{\text{original}}$ and  $\mathcal{D}_{\text{random}}$ , respectively.  $\mathcal{D}_{\text{random}}$  has even more repetition than Doriginal possibly because random sentences repeat highfrequency words than human-written sentences.

<span id="page-3-2"></span>

Models	<b>PPL</b>	<b>MAUVE</b> R-16	$R-128$ $R-32$	$D-3$	<b>PPL</b> $D-4$	<b>MAUVE</b> <b>R-16</b>	$R-32$	$R-128$ $D-3$	$D-4$
Greedy			Dataset: Wikitext-103				Dataset: WritingPrompts		
<b>MLE</b> UL <b>ScaleGrad</b>	2.55 3.20 4.61	3.29 41.23 33.91 7.16 7.66 29.82	70.18 83.28 76.89 61.90 66.14 50.69	19.27 25.13 36.96	23.95 1.76 31.90 2.01 47.34 2.87	71.08 0.61 1.63 59.43 11.17 52.29	87.20 81.63 69.53	89.43 9.61 85.89 11.66 76.16 18.16	11.40 14.30 24.40
<b>SELFCONT</b>	6.47	17.34 23.29	39.41 62.46	46.71	3.30 57.66	20.05 35.13	53.69	74.09 23.30	31.52
<b>Nucleus</b>			Dataset: Wikitext-103				Dataset: WritingPrompts		
<b>MLE</b> UL <b>ScaleGrad</b>	20.66 15.54 12.41	21.09 19.40 21.78 18.45 18.59 25.69	48.11 30.22 29.57 46.69 29.24 45.19	71.92 69.63 66.35	84.75 18.68 82.87 19.39 14.14 80.23	88.54 20.95 81.49 18.36 77.82 18.62	32.53 27.98 27.80	48.87 60.38 42.65 63.92 41.22 56.74	81.55 82.93 77.27
<b>SELFCONT</b>	19.02	34.37 16.45	26.47 45.10	72.02	84.78 19.86	89.84 17.56	26.98	43.39 63.33	83.51
<b>Ground Truth</b>	18.31	100 17.38	27.92 46.29	72.34	84.20 24.01	100 16.36	26.47	42.30 74.49	90.01

Table 2: Automatic evaluation results with greedy and nucleus decoding on Wikitext-103 and WritingPrompts.

# 4 Self-Contrastive Training

We denote the premature checkpoint as  $f_{\theta_0}$ , which frequently predicts repetitive tokens. Formally, the SELFCONT algorithm is formulated as follows:

$$
f_{\theta} = f_{\theta_1} + \mathrm{sg}(wf_{\theta_0}),\tag{2}
$$

$$
w = \lambda \mathbb{1}(x_t \notin x_{1:t-1}) \mathbb{1}(\hat{x}_t \in x_{1:t-1}) \tag{3}
$$

$$
\hat{x}_t = \operatorname{argmax}\left(f_{\theta_0}(x_{1:t-1})\right),\tag{4}
$$

where  $sg(\cdot)$  means stopping back-propagation of gradients,  $\lambda$  is a tunable hyper-parameter to control the extent of repetition penalty, and  $\mathbbm{1}$  is the indicator function.  $f_{\theta_1}$  is the target LM initialized from  $f_{\theta_0}$ , and we optimize  $f_{\theta}$  using Eq. [1](#page-1-4) until the validation loss converges to the minimum. The gradient for each token  $u \in V$  has changed to:

$$
\nabla_u \mathcal{L} = \frac{\exp(f_{\theta_1}|_u)}{\sum_{v \in \mathcal{V}} w_{v,u} \exp(f_{\theta_1}|_v)} - \mathbb{1}(u = x_t), \tag{5}
$$

$$
w_{v,u} = \exp\big(w(f_{\theta_0}|_v - f_{\theta_0}|_u)\big),\tag{6}
$$

where  $f_{\theta_1}|_u$  is the output of  $f_{\theta_1}$  at the *u*-th dimension. If w is 0,  $w_{v,u}$  is always 1 and  $\nabla_u \mathcal{L}$  degenerates to the same as the vanilla LM. If  $w$  is not 0 and u is not  $x_t$ , tokens with high logits under  $f_{\theta_0}$ will receive larger gradients than the vanilla LM since  $w_{v,u}$  is mostly smaller than 1 with different v. As for  $u = x_t$  ( $w \neq 0$ ), it may also be penalized with a positive gradient if  $f_{\theta_0}|_u$  is large enough, which usually means a dull token. By penalizing components that excessively prefer repetitive or dull tokens highlighted by  $f_{\theta_0}$ ,  $f_{\theta_1}$  can utilize more complex patterns learned later to generate texts.

### 5 Experiments

Datasets We conduct experiments on Wikitext-103 [\(Merity et al.,](#page-5-10) [2016\)](#page-5-10) and WritingPrompts [\(Fan](#page-4-7)

[et al.,](#page-4-7) [2018\)](#page-4-7). The prompt and story in each Writing-Prompts example are concatenated as a sequence. We set the maximum sequence length to 512 and take the first 50 tokens as input to generate the rest. Table [3](#page-3-0) presents the detailed statistics.

<span id="page-3-1"></span><span id="page-3-0"></span>

<b>Datasets</b>	Train	<b>Validation</b>	<b>Testl</b>	Avg. Len
<b>Wikitext-103</b>	201,632	448	480	512
<b>WritingPrompts</b>	272,600	15.620	15.138	439

Table 3: Statistics of the datasets.

**Baselines** We compare SELFCONT to three baselines: MLE, token-level UL [\(Welleck et al.,](#page-5-1) [2020b\)](#page-5-1) and ScaleGrad [\(Lin et al.,](#page-5-3) [2021\)](#page-5-3). Since SELFCONT focuses on token-level modeling, we do not compare it to sentence-level methods that directly penalize repetition loops, e.g., DITTO [\(Xu et al.,](#page-5-2) [2022\)](#page-5-2).

Implementation All baselines are implemented based on  $GPT2_{base}$ . We set the batch size to 16, the learning rate to 1e-4, and  $\lambda$  in Eq. [3](#page-3-1) to 4.0. For SELFCONT, we fine-tune  $GPT2_{base}$  for one epoch using MLE and take the checkpoint as  $f_{\theta_0}$ for both datasets. We use different  $p$  for different models based on the performance on the validation set. Appendix [B](#page-6-0) shows more details.

**Metrics** We use perplexity (PPL) under  $GPT2_{x}$ to evaluate fluency, MAUVE [\(Pillutla et al.,](#page-5-13) [2021\)](#page-5-13) to measure the similarity between golden and generated distributions, the token repetition ratios (R-l) to measure the ratio of tokens that appear in previous l tokens [\(Welleck et al.,](#page-5-1) [2020b\)](#page-5-1), and distinct (D $n)$  [\(Li et al.,](#page-5-14) [2016\)](#page-5-14) to evaluate the *n*-gram diversity. The closer scores to the ground truth mean better quality for all metrics.

Results As shown in Table [2,](#page-3-2) SELFCONT outperforms baselines in all metrics using greedy decoding. However, the high R-128 score shows it can still generate repetition loops due to the disability of small-scale LMs to model long-range dependencies. Using nucleus decoding, we see that different baselines can achieve similar repetition ratios and diversity to the truth by tuning  $p$ , while SELFCONT has better fluency and higher MAUVE scores.

# 6 Conclusion

We present empirical studies on LMs' preference for repetition by analyzing the training dynamics, which highlights their learning bias towards simple repetitive patterns. We propose penalizing outputs of a premature checkpoint during training, which effectively mitigates repetition while maintaining fluency. We also provide insight into why LMs easily fall into repetition loops by showing their disability to model long-range dependencies. Sampling-based decoding reduces repetition through randomness but not utilizing long-range dependencies. We believe that maximization-based decoding can also generate coherent texts without repetition by improving the modeling of long-range dependencies, which is left to future work.

# Acknowledgments

This work was supported by the National Science Foundation for Distinguished Young Scholars (with No. 62125604) and the NSFC projects (Key project with No. 61936010). This work was also supported by the Guoqiang Institute of Tsinghua University, with Grant No. 2020GQG0005.

# 7 Limitations

The limitations of this paper mainly lie in the following folds: (1) We do not provide any theoretical analysis for the correlation between long-range dependencies and repetition loops, as well as solutions to avoid repetition loops with maximizationbased decoding. (2) We do not discuss the source of LMs' learning bias, which may be caused by multiple factors, such as the Transformer architecture [\(Vaswani et al.,](#page-5-15) [2017\)](#page-5-15), the MLE loss, or the auto-regressive generation manner. (3) We conduct experiments based on GPT2 due to resource limitations. The conclusions may differ for extra-large LMs (such as GPT3). (4) We do not experiment with RNN-based models, which are also shown to prefer repetition [\(Elman,](#page-4-8) [1990\)](#page-4-8). (5) We do not perform the manual evaluation to compare SELFCONT with baselines since we focus on repetition in this

paper, which can be automatically evaluated reliably. Perplexity and mauve scores are also shown to correlate highly with manual evaluation for evaluating fluency and overall quality, respectively.

# References

- <span id="page-4-4"></span>Kushal Arora, Layla El Asri, Hareesh Bahuleyan, and Jackie Chi Kit Cheung. 2022. Why exposure bias matters: An imitation learning perspective of error accumulation in language generation. In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 700–710.
- <span id="page-4-0"></span>Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. [Language models are few-shot learners.](http://arxiv.org/abs/2005.14165)
- <span id="page-4-1"></span>Yao Dou, Maxwell Forbes, Rik Koncel-Kedziorski, Noah A Smith, and Yejin Choi. 2022. Is gpt-3 text indistinguishable from human text? scarecrow: A framework for scrutinizing machine text. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7250–7274.
- <span id="page-4-8"></span>Jeffrey L Elman. 1990. Finding structure in time. *Cognitive science*, 14(2):179–211.
- <span id="page-4-7"></span>Angela Fan, Mike Lewis, and Yann Dauphin. 2018. Hierarchical neural story generation. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 889–898.
- <span id="page-4-6"></span>Jessica Ficler and Yoav Goldberg. 2017. Controlling linguistic style aspects in neural language generation. In *Proceedings of the Workshop on Stylistic Variation*, pages 94–104.
- <span id="page-4-3"></span>Zihao Fu, Wai Lam, Anthony Man-Cho So, and Bei Shi. 2021. A theoretical analysis of the repetition problem in text generation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 12848–12856.
- <span id="page-4-2"></span>Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2020. [The curious case of neural text de](https://openreview.net/forum?id=rygGQyrFvH)[generation.](https://openreview.net/forum?id=rygGQyrFvH) In *International Conference on Learning Representations*.
- <span id="page-4-5"></span>Nitish Shirish Keskar, Bryan McCann, Lav R Varshney, Caiming Xiong, and Richard Socher. 2019. Ctrl: A conditional transformer language model for controllable generation. *arXiv preprint arXiv:1909.05858*.
- <span id="page-5-14"></span>Jiwei Li, Michel Galley, Chris Brockett, Jianfeng Gao, and Bill Dolan. 2016. [A diversity-promoting ob](https://doi.org/10.18653/v1/n16-1014)[jective function for neural conversation models.](https://doi.org/10.18653/v1/n16-1014) In *NAACL HLT 2016, The 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, San Diego California, USA, June 12-17, 2016*, pages 110–119. The Association for Computational Linguistics.
- <span id="page-5-6"></span>Xiang Lisa Li, Ari Holtzman, Daniel Fried, Percy Liang, Jason Eisner, Tatsunori Hashimoto, Luke Zettlemoyer, and Mike Lewis. 2022. Contrastive decoding: Open-ended text generation as optimization. *arXiv preprint arXiv:2210.15097*.
- <span id="page-5-3"></span>Xiang Lin, Simeng Han, and Shafiq Joty. 2021. [Straight](https://proceedings.mlr.press/v139/lin21b.html) [to the gradient: Learning to use novel tokens for neu](https://proceedings.mlr.press/v139/lin21b.html)[ral text generation.](https://proceedings.mlr.press/v139/lin21b.html) In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 6642–6653. PMLR.
- <span id="page-5-7"></span>Clara Meister, Tiago Pimentel, Gian Wiher, and Ryan Cotterell. 2022. Typical decoding for natural language generation. *arXiv preprint arXiv:2202.00666*.
- <span id="page-5-10"></span>Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. 2016. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*.
- <span id="page-5-9"></span>Nelson Morgan and Hervé Bourlard. 1989. Generalization and parameter estimation in feedforward nets: Some experiments. *Advances in neural information processing systems*, 2.
- <span id="page-5-5"></span>Romain Paulus, Caiming Xiong, and Richard Socher. 2018. A deep reinforced model for abstractive summarization. In *International Conference on Learning Representations*.
- <span id="page-5-13"></span>Krishna Pillutla, Swabha Swayamdipta, Rowan Zellers, John Thickstun, Sean Welleck, Yejin Choi, and Zaid Harchaoui. 2021. [Mauve: Measuring the gap be](https://proceedings.neurips.cc/paper/2021/file/260c2432a0eecc28ce03c10dadc078a4-Paper.pdf)[tween neural text and human text using divergence](https://proceedings.neurips.cc/paper/2021/file/260c2432a0eecc28ce03c10dadc078a4-Paper.pdf) [frontiers.](https://proceedings.neurips.cc/paper/2021/file/260c2432a0eecc28ce03c10dadc078a4-Paper.pdf) In *Advances in Neural Information Processing Systems*, volume 34, pages 4816–4828. Curran Associates, Inc.
- <span id="page-5-8"></span>Nasim Rahaman, Aristide Baratin, Devansh Arpit, Felix Draxler, Min Lin, Fred Hamprecht, Yoshua Bengio, and Aaron Courville. 2019. On the spectral bias of neural networks. In *International Conference on Machine Learning*, pages 5301–5310. PMLR.
- <span id="page-5-15"></span>Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008.
- <span id="page-5-0"></span>Sean Welleck, Ilia Kulikov, Jaedeok Kim, Richard Yuanzhe Pang, and Kyunghyun Cho. 2020a. [Consistency of a recurrent language model](https://doi.org/10.18653/v1/2020.emnlp-main.448) [with respect to incomplete decoding.](https://doi.org/10.18653/v1/2020.emnlp-main.448) In *Proceedings of the 2020 Conference on Empirical Methods in*

*Natural Language Processing (EMNLP)*, pages 5553–5568, Online. Association for Computational Linguistics.

- <span id="page-5-1"></span>Sean Welleck, Ilia Kulikov, Stephen Roller, Emily Dinan, Kyunghyun Cho, and Jason Weston. 2020b. [Neural text generation with unlikelihood training.](https://openreview.net/forum?id=SJeYe0NtvH) In *International Conference on Learning Representations*.
- <span id="page-5-4"></span>Yadong Xi, Jiashu Pu, and Xiaoxi Mao. 2021. [Tam](http://arxiv.org/abs/2112.08657)[ing repetition in dialogue generation.](http://arxiv.org/abs/2112.08657) *CoRR*, abs/2112.08657.
- <span id="page-5-2"></span>Jin Xu, Xiaojiang Liu, Jianhao Yan, Deng Cai, Huayang Li, and Jian Li. 2022. [Learning to break the loop:](https://openreview.net/forum?id=sexfswCc7B) [Analyzing and mitigating repetitions for neural text](https://openreview.net/forum?id=sexfswCc7B) [generation.](https://openreview.net/forum?id=sexfswCc7B) In *Advances in Neural Information Processing Systems*.

# A Details for Empirical Analysis

### <span id="page-5-11"></span>A.1 Training Dynamics

Table [4](#page-6-1) shows several cases generated by the LM with greedy decoding at different training steps. We summarize the findings as follows: (1) In the beginning, the LM keeps repeating the high-frequency word "<eos>," indicating that it does not capture phrase-level dependencies yet. (2) At the 1500th step, the LM first generates a few fluent sentences and then gets stuck into the repetition of "the building," showing that it learns long-range dependencies conditioned on the golden prefix while the repetitive patterns dominate the probability distributions conditioned on the generated prefix. This case suggests the global tendency towards repetition for out-of-distribution inputs. (3) At the 6000th step, the LM can generate long, fluent texts without repetition. However, it is difficult for the LM to maintain coherence with inputs due to over-fitting. For example, in the generated first sentence, "she had begun in 1962," "she" conflicts with "he" in the input.

### <span id="page-5-12"></span>A.2 Long-Range Dependencies

**Observation** For the experiment in Figure [2,](#page-2-1) we generate texts with three decoding algorithms conditioned on the first 50 tokens on the test set. Ancestral decoding means directly sampling tokens from the original probability distribution. For nucleus decoding, we set  $p$  to 0.9. Figure [3](#page-6-2) shows the performance of GPT2large, which shows similar results with GPT2<sub>base</sub> in Figure [2.](#page-2-1)

<span id="page-6-1"></span>

Table 4: Generation cases with greedy decoding at different training steps to investigate the training dynamics. The inputs are highlighted in bold.

<span id="page-6-2"></span>

Figure 3: Perplexity scores computed on *all*, *repetitive* or *non-repetitive* tokens with different prefix lengths based on GPT2<sub>large</sub>. The scores marked with  $\bigcirc$ ,  $\times$ ,  $\bigcirc$  and  $\bigtriangleup$  means that the *p*-values compared with the score when the prefix length is 250 fall in the following intervals:  $[0, 0.001), [0.001, 0.01), [0.01, 0.05)$  and  $[0.05, 1]$ , respectively.

Verification For the experiment in Table [1,](#page-2-2) we use the same approach to construct the corresponding validation sets of 480 examples for  $\mathcal{D}_{original}$ ,  $\mathcal{D}_{\text{random}}$  and  $\mathcal{D}_{\text{norent}}$ , and train three LMs until the best validation performance. Table [5](#page-7-0) shows several generation cases with greedy decoding. The LMs trained on  $\mathcal{D}_{original}$  and  $\mathcal{D}_{random}$  fall into repetition loops. Although the LM trained on  $\mathcal{D}_{\text{norent}}$ also generates sentences that have previously appeared, it does not get stuck into loops. We further investigate whether the three LMs show the selfreinforcement effect: the more times a sentence is repeated in the context, the higher the probability of continuing to generate that sentence [\(Holtzman](#page-4-2) [et al.,](#page-4-2) [2020;](#page-4-2) [Xu et al.,](#page-5-2) [2022\)](#page-5-2). Figure [4](#page-7-1) indicates that the LMs trained on  $\mathcal{D}_{original}$  and  $\mathcal{D}_{random}$  show the above effect, while the LM trained on  $\mathcal{D}_{\text{norent}}$ 

does not. The results suggest that longer-range repetitive patterns biased LMs to fall into repetition loops through the self-reinforcement effect whether such patterns are true or spurious. The LM trained on  $\mathcal{D}_{\text{norent}}$  always generate sentences in a limited set due to greedy decoding which aims to find the global maxima of probability distributions, instead of the preference for repetition loops.

### <span id="page-6-0"></span>B Hyper-Parameters

We decide the hyper-parameters  $\lambda$  in Eq. [3](#page-3-1) and p for nucleus sampling by searching for the value that makes the R-64 score of generated texts closest to the ground truth on the validation set. We search  $\lambda$ in the range  $\{1.0, 2.0, 3.0, 4.0, 5.0, 6.0\}$ , and p in the range {0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9}. Table [6](#page-7-2) shows the settings of p for different models.

<span id="page-7-0"></span>

<b>Training Set</b>	<b>Cases</b>
$\mathcal{D}_{original}$	$\epsilon$ eos = Robert Boulter = $\epsilon$ eos $\epsilon$ eos Robert Boulter is an English film, television and theatre actor. He had a guest @-@ starring role on the television series The Bill in 2000. He has appeared in several films, including the television series The Bill, The Bill Goes to Washington, and The Bill Goes to Washington. He has also appeared in several films, including The Bill Goes to Washington, The Bill Goes to Washington, and The Bill Goes to Washington. He has also appeared in several films, including The Bill Goes to Washington, The Bill Goes to Washington, and The Bill Goes to Washington, <eos> Boulter was born in London, England, on 23 May 1986. He is the third child of actor and actress Robert Boulter and his wife, Susan. He is the third of five children born to his wife Susan and their three children, Robert, Roberta, and Roberta. Robert Boulter's father, Robert Boulter, was a film director and producer. He was the first actor to be cast in a film role, and the first to be cast in a television series. He was also the first actor to be cast in a television series. <eos> Boulter's father, Robert Boulter , was a film director and producer. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series. He was the first actor to be cast in a television series</eos></eos>
$\mathcal{D}_{\text{random}}$	<eos> = Robert Boulter = <eos> <eos> Robert Boulter is an English film, television and theatre actor. He had a guest @-@ starring role on the television series The Bill in 2000. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <math>\langle</math>unk&gt;, a small, rectangular structure that was built in the late 19th century. The first of these was the <math>\langle</math>unk&gt;, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk> a small, rectangular structure that was built in the late 19th century. The first of these was the <math>\langle</math>unk&gt;, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small, rectangular structure that was built in the late 19th century. The first of these was the <unk>, a small</unk></unk></unk></unk></unk></unk></unk></unk></unk></unk></unk></unk></unk></unk></unk></unk></eos></eos></eos>
$\mathcal{D}_{\text{morept}}$	<eos> = Robert Boulter = <eos> <eos> Robert Boulter is an English film, television and theatre actor. He had a guest @-@ starring role on the television series The Bill in 2000. The first two were built by the British Royal Navy. It was also released on the iTunes Store on September 28, 2010. It is also possible that he was a member of the royal family. He also said that he would not be returning to the team. @ 5 m) wide and 2 feet (0 @. The song was written by producer and songwriter David Gilmour . It was also released on the iTunes Store on September 28, 2010. It was also released on the iTunes Store on September 28, 2010. It was also released on the iTunes Store on September 28, 2010. @ 5 million (US \$ 2 @, @ 000). The song was written by producer and songwriter David Gilmour. He also said that he would not be returning to the team. It was also released on the iTunes Store on September 28, 2010. It is also possible that he was a member of the royal family . @ 5 m) wide and 2 feet (0 @. The two ships were to be joined by two smaller ships . It was also released on the iTunes Store on September 28, 2010. He also said that he would not be returning to the team. It was also released on the iTunes Store on September 28, 2010. @ 5 million (US \$ 2 @, @ 000) worldwide . The song was written by David Gilmour and directed by David Gilmour . It was also released on the iTunes Store on September 28, 2010. It is also possible that he was a member of the royal family. He also said that he would not be returning to the team. <math>@</math> 5 m) wide and 2 feet (0<math>@</math>. The two ships were protected by armour plates of 100 millimeters (3 @. It was also released on the iTunes Store on September 28, 2010. It was also released on the iTunes Store on September 28, 2010.</eos></eos></eos>

Table 5: Cases generated by three LMs trained on different training sets with greedy decoding. The inputs are highlighted in bold.

<span id="page-7-1"></span>

Figure 4: Average per-token perplexity scores of texts generated by LMs trained on  $\mathcal{D}_{original}$ ,  $\mathcal{D}_{random}$  and  $\mathcal{D}_{\text{norent}}$  with greedy decoding. We compute their respective perplexity scores using the corresponding LMs.

<span id="page-7-2"></span>

Table 6: Settings of  $p$  for nucleus sampling.

As for baselines, we follow the original papers to set  $\alpha$  to 1.0 for UL and  $\gamma$  to 0.2 for ScaleGrad.

As for the choice of  $f_{\theta_0}$ , we empirically choose

the checkpoint after training for one epoch, which allows enough training steps for self-contrastive training. We use the premature checkpoint of the same model instead of other models since different models may have different biases. It costs about 24 hours to train SELFCONT on Wikitext-103 (∼10 epochs) or CNN News (∼6 epochs). The results are based on one NVIDIA Tesla V100 (32GB memory) with a random single run.

# C Modeling Token-Level Repetition

We compare SELFCONT with baselines in terms of the performance for modeling token-level repetition. As shown in Table [7,](#page-8-0) SELFCONT achieves higher overall accuracy, higher F1 score on nonrepetitive tokens, and comparable F1 score on repetitive tokens.

# D Case Study

Table [8](#page-9-0) and Table [9](#page-10-0) show the cases generated by different models on Wikitext-103 with greedy decoding and nucleus decoding, respectively. We see that SELFCONT can still get stuck into loops with greedy decoding since it hardly learns longer-range dependencies than standard LMs. Although sam-

<span id="page-8-0"></span>

Models	Acc	<b>Repetitive</b>			<b>Non-Repetitive</b>		
		P	R	F1	Р	R	F1
MLE	78.9	67.4	87.0	75.9	90.2	73.9	81.2
UL	80.5	70.9	83.0	76.5	88.2	78.9	83.3
<b>ScaleGrad</b>	81.6	75.9	76.1	76.0	85.2	85.0	85.1
<b>SELFCONT</b>	82.3	78.5	73.9	76.1	84.4	87.4	85.9

Table 7: Repetition prediction performance on the test set of Wikitext-103. Acc is the overall accuracy of predicting whether the next token is repetitive. We regard the model-predicted token (with the maximum probability) as repetitive if it has appeared in the previous 64 tokens (non-repetitive otherwise). P, R and F1 means the precision, recall and F1 on the class of (non-)repetitive tokens.

pling helps reduce superficial repetition, it does not utilize underlying long-range dependencies to maintain long-range coherence. Therefore, it is important to improve the modeling of long-range dependencies to essentially solve the repetition problem in future work.

<span id="page-9-0"></span>

Table 8: Cases generated by different models with greedy decoding on Wikitext-103. The inputs are highlighted in bold.

<span id="page-10-0"></span>

Table 9: Cases generated by different models with nucleus decoding on Wikitext-103. The inputs are highlighted in bold, while the incoherent sentences are underlined.