ConfusionPrompt: Practical Private Inference for Online Large Language Models

Peihua Mai^{a,b}, Youjia Yang^b, Ran Yan^a, Rui Ye^c, Yan Pang^{a,b,*}

 a National University of Singapore, 15 Kent Ridge Drive 119245, Singapore

 b NUS (Chongqing) Research Institute, Building 4, Internet Industrial Park Phase 2, Chongqing Liang Jiang New Area, Chongqing, China

^cMediaBrain Lab, Shanghai Jiaotong University, 303A, SEIEE building 5, Shanghai Jiao Tong University, 800 Dongchuan Road, Shanghai, China

Abstract

State-of-the-art large language models (LLMs) are typically deployed as online services, requiring users to transmit detailed prompts to cloud servers. This raises significant privacy concerns. In response, we introduce ConfusionPrompt, a novel framework for private LLM inference that protects user privacy by: (i) decomposing the original prompt into smaller sub-prompts, and (ii) generating pseudo-prompts alongside the genuine sub-prompts, which are then sent to the LLM. The server responses are later recomposed by the user to reconstruct the final output. This approach offers key advantages over previous LLM privacy protection methods: (i) it integrates seamlessly with existing black-box LLMs, and (ii) it delivers a significantly improved privacyutility trade-off compared to existing text perturbation methods. We also develop a (λ, μ, ρ) -privacy model to formulate the requirements for a privacy-preserving group of prompts and provide a complexity analysis to justify the role of prompt decomposition. Our empirical evaluation shows that ConfusionPrompt achieves significantly higher utility than local inference methods using open-source models and perturbation-based techniques, while also reducing memory consumption compared to open-source LLMs.

Keywords: Large language model, privacy-preserving computation, private inference, confusion strategy

[∗]Corresponding author: Yan Pang (jamespang@nus.edu.sg), Department of Analytics and Operations, National University of Singapore, 15 Kent Ridge Drive 119245

1. Introduction

Large language models (LLMs) have demonstrated remarkable capabilities across a wide range of tasks [\[1,](#page-19-0) [2,](#page-19-1) [3\]](#page-19-2), leading to their growing integration into real-world applications such as medical consultations [\[4\]](#page-19-3) and financial services [\[5\]](#page-19-4). State-ofthe-art LLMs, such as OpenAI's ChatGPT [\[6\]](#page-19-5), are predominantly offered as online services. This is mainly due to intellectual property considerations, as model owners are reluctant to disclose their proprietary parameters to users [\[7\]](#page-19-6). However, direct usage of such LLM online services could raise significant privacy concerns, as users often transmit prompts containing sensitive information that should ideally remain confidential from the server.

Existing solutions to privacy-preserving model inference, such as encryption [\[8,](#page-19-7) [9\]](#page-20-0) and perturbation [\[10\]](#page-20-1) techniques, are often impractical for private LLM inference. In encryption-based methods, the server leverages homomorphic encryption (HE) [\[11\]](#page-20-2) and Secure Multiparty Computation (MPC) [\[12\]](#page-20-3) to conduct private inference on the users' encrypted query. The practicality of this method is limited by its high computation overheads, especially on LLMs (e.g., GPT-3 has 175B parameters [\[1\]](#page-19-0)). On the other hand, the basic idea of perturbation-based methods is to inject a specific level of noise into the user's input before releasing it to the server, which is challenging to strike a satisfied privacy-utility balance [\[13\]](#page-20-4).

Another limitation of the aforementioned solutions is their dependence on the service provider to modify their infrastructure or disclose specific model parameters, which can be prohibitively costly. Encryption-based techniques require significant investment from platform in hardware and algorithmic acceleration to support efficient computation. Perturbation-based methods often rely on local differential privacy (LDP) [\[14\]](#page-20-5) to ensure privacy with formal guarantees. For improved LDP performance, recent studies have proposed deploying certain modules on the user side, necessitating the sharing of specific model parameters by the server [\[15,](#page-20-6) [16,](#page-20-7) [17\]](#page-20-8). These requirements impose additional burdens and proprietary concerns on the service provider, hindering the deployment of these solutions.

To alleviate the above concerns, this paper proposes ConfusionPrompt, a novel private LLM inference framework that can be seamlessly integrated with existing online black-box LLMs. The core idea of ConfusionPrompt is to construct a set of prompts, containing real and fake prompts, designed to confuse the server, making the curious server fail to infer the real user prompt. However, a significant challenge arises when a prompt contains multiple sensitive attributes. In such cases, the user needs to consider all combinations of true and fake attributes to effectively confuse an attacker with prior knowledge of certain attributes, rendering the query complexity growing exponentially with the number of attributes. To address this issue, we

propose a decomposition approach in which the query is divided into sub-questions. This ensures that the private information is distributed across different sub-queries, thereby reducing the complexity to approximately linear in the nunber of attributes (see Figure [2\)](#page-12-0).

Building on the aforementioned concepts, our proposed ConfusionPrompt consists of four critical steps: (1) The user decomposes the original prompt into several sub-prompts; (2) For each genuine sub-prompt, the user generates a set of pseudo prompts that obfuscate sensitive attributes in the genuine sub-prompt, continuing this process until the desired level of privacy is achieved. (3) The user sends a group of both genuine and pseudo-prompts to the online service, retrieves the responses, and isolates the sub-responses corresponding to the genuine sub-prompts. (4) Finally, user recomposes the sub-responses to obtain the final result. This framework empowers the user with independent deployment, eliminating the need for additional privacypreserving actions from the service provider.

Accordingly, we develop a (λ, μ, ρ) -privacy model for ConfusionPrompt to formulate the requirements for a privacy-preserving group of prompts. Through complexity analysis, we show that for a prompt p with $U(p)$ private attributes and a privacy budget μ , the basic confusion strategy without decomposition requires generating $\mathcal{O}\left((1/\mu)^{U(\mathbf{p})}\right)$ fake prompts, while our decomposition strategy in ConfusionPrompt can reduce the complexity to $\mathcal{O}((1/\mu)U(\mathbf{p}))$ in the ideal decomposition scenario. Based on the privacy model and complexity analysis, we derive the criteria for an ideal decomposer and generator, and accordingly design a two-stage training strategy.

Our key contributions are as follows:

- We are the first to propose a private LLM inference framework using confusionbased strategy. Our ConfusionPrompt framework can be seamlessly implemented by clients with existing online black-box LLMs, such as ChatGPT and Claude, providing an improved privacy-utility trade-off. In addition, Our framework can be integrated with Trusted Execution Environment (TEE) [\[18\]](#page-20-9) solutions. Even in the event of a TEE compromise, user privacy remains safeguarded through the confusion strategy.
- To ensure user privacy, we define a privacy model to formulate the requirements of a group of prompts, including both real and pseudo prompts. Furthermore, we introduce a local decomposition module to reduce the complexity of the prompt group under the same privacy parameters.
- Experiments show that ConfusionPrompt can achieve a consistently and significantly better utility than the local inference method using open-source models

and LDP-based methods. Moreover, ConfusionPrompt significantly reduces memory overhead compared to open-source LLMs.

2. Related Works

In this section, we review three types of methods for privacy-preserving LLM inference: anonymization-based method, encryption-based method, and perturbationbased method.

Anonymization-based method. Traditional anonymization techniques rely on Named Entity Recognition (NER) to redact Personally Identifiable Information (PII) such as individuals' names, social security number, and email addresses [\[19,](#page-21-0) [20\]](#page-21-1). Recent research on LLM inference involves sanitizing sensitive items in the input and subsequently de-anonymize the LLM's returned responses [\[21,](#page-21-2) [22\]](#page-21-3). The downside of this method is that anonymization fall short in concealing other sensitive information, including verbs and non-named entities [\[23\]](#page-21-4).

Encryption-based method. Cryptonets [\[24\]](#page-21-5) proposed the first neural network inference on encrypted data using homomorphic encryption (HE). They approximated the non-linear function such as Sigmoid and MaxPooling by polynomials. Iron [\[25\]](#page-21-6) designed specialized and efficient protocols for two types of computationally heavy operations in Transformer-based inference: (i) matrix multiplications, and (ii) complex functions including Softmax, GELU activations, and LayerNorm. To achieve further speedup, [\[8\]](#page-19-7) transformed the high-overhead functions into cryptography-friendly approximations, and finetuned the model to maintain accuracy.

Perturbation-based method. Perturbation-based methods provide privacy guarantee by inject calibrated noise into the input. Existing studies utilizing this method predominantly focus on privacy protection in fine-tuning [\[26,](#page-21-7) [27\]](#page-21-8) and prompt-tuning phases [\[28,](#page-21-9) [29\]](#page-22-0), while few studies investigate the privacy-preserving inference paradigm. A major challenge in perturbation-based private inference is to balance the utility and privacy tradeoff. Recent studies have proposed Text2Text [\[30\]](#page-22-1) and paraphraser-based approaches [\[31,](#page-22-2) [32\]](#page-22-3) to privatize text with LDP. Split-N-Denoise (SnD) [\[16\]](#page-20-7) deployed the token embedding layer at the client side, and introduced a user-side denoising model to correct the purturbed embedding output for downstream tasks.

3. ConfusionPrompt: Design and Formulation

In this section, we first illustrate the overview of our proposed ConfusionPrompt, which consists of three critical components: decomposer, generator, and recomposer. Then, we develop a privacy model to formulate the requirements for achieving privacypreserving inference.

3.1. Overall Design

Denote $G_s: \mathcal{V}^* \to \mathcal{V}^*$ as the LLM deployed as cloud service such as ChatGPT [\[6,](#page-19-5) [7\]](#page-19-6), where \mathcal{V}^* is the vocabulary space. Instead of sending raw user prompt to the cloud, our ConfusionPrompt introduces a new privacy-preserving inference paradigm, which makes it significantly hard for any third party to infer the real original user prompt even if it happens to access the information sent from the user. Basically, ConfusionPrompt involves the following six steps:

Step 1: decomposition of the original prompt. We first introduce a decomposer $G_d: \mathcal{V}^* \to \mathcal{V}^*$ that aims to decompose the user's original prompt p to a sequence of genuine sub-prompts $p = [p_1, p_2, ..., p_{|\mathbf{p}|}]$, resulting in fewer private attributes (i.e., private information) in each sub-prompt.

Step 2: generation of pseudo prompts. A pseudo prompt generator $G_f: \mathcal{V}^* \to \mathcal{V}^*$ is introduced to generate a pseudo prompt given a genuine sub-prompt by replacing specified critical information. By generating multiple pseudo prompts for each genuine sub-prompt and mixing them together as a prompt group, we are able to hide the genuine sub-prompts, thus increasing the difficulty of being inferred. For the simplicity of privacy analysis, we design to enforce the pseudo prompt to be consistent with the genuine prompt in terms of syntactic structure.

Step 3: evaluation of privacy level. To ensure that the genuine prompt is safely hidden in the prompt group, we also need to design some criteria (e.g., semantic irrelevance) to evaluate the usability of generated pseudo prompts. Based on these criteria, we iteratively sample and filter the pseudo prompts until the prompt group meets the privacy requirement, which will be introduced in details in Section [3.2.](#page-4-0)

Step 4: communication with cloud server. Here, the user sends the prompt group to the server for the usage of LLM on the cloud, while the server subsequently sends back the response group to the user. During this process, we expect that it will be hard for the server to infer the original user prompt according to the prompt group, therefore safeguarding user's privacy.

Step 5: retrieval of interested response. Since the user itself is aware of which sub-prompts are genuine, it can seamlessly retrieve the corresponding sub-responses and discard the responses of pseudo prompts.

Step 6: recomposition of sub-responses. Here, we introduce a recomposer G_r : $\mathcal{V}^* \to \mathcal{V}^*$ that maps a sequence of sub-prompt-response pairs to a final response.

3.2. Privacy Model

3.2.1. Rationale of Privacy Model

Here, we define a (λ, μ, ρ) -privacy model to formulate the requirements that the group of pseudo prompts should satisfy for privacy protection, which offers guidance

Figure 1: Overview of ConfusionPrompt.

for the evaluation of privacy level and training of models (i.e., decomposer, generator, and recomposer). To explain the rationale of our privacy model, we follow [\[33\]](#page-22-4) to quantify the privacy risk of the queries exposed to the server.

Consider a set of prompts denoted as $P = \{p_1, p_2, ..., p_n\}$. For any $p \in P$, let $\pi(\mathbf{p})$ be the adversary's prior probability that \mathbf{p} is the genuine prompt provided by the user. Then the adversary's posterior probability $\pi(\mathbf{p}|\mathbf{P})$ of the same event is:

$$
\pi(\mathbf{p}|\mathbf{P}) = \frac{\pi(\mathbf{p})}{\sum_{\mathbf{p}' \in \mathbf{P}} \pi(\mathbf{p}')}.
$$
\n(1)

Let p^0 denote the genuine prompt provided by the user. Then the privacy risk associated with the set of prompts P revealed to the server can be formulated as:

$$
Risk(\boldsymbol{P}) = \sum_{\boldsymbol{p}' \in \boldsymbol{P}} \pi(\boldsymbol{p}'|\boldsymbol{P}) \cdot \text{Sim}(\boldsymbol{p}', \boldsymbol{p}^0),
$$
\n(2)

where Sim is some measure of similarity between two prompts.

Equation [2](#page-5-0) suggests three possible methods to minimize the privacy risk. First, reducing $\text{Sim}(\pmb{p}', \pmb{p}^0)$ for any $\pmb{p}' \neq \pmb{p}^0$ leads to a decrease in Risk (\pmb{P}) . Therefore, generating deceptive prompts that are semantically distinct from the genuine prompt can effectively lower the privacy risk. Second, $Risk(P)$ is reduced when $\pi(p'|P)$ is high for prompts p' that do not resemble p^0 . This implies that fabricated prompts

should be crafted to appear as realistic as possible. Finally, $Risk(P)$ decreases if we increase the number of prompts p' with low $\text{Sim}(p', p^0)$. This can be achieved by increasing the number of fake prompts with different semantic meaning.

Based on the observations, we develop the following criteria for the fabricated prompts: (i) The fabricated attributes in the pseudo prompt should be semantically irrelevant to the original attributes in genuine prompt, so that the genuine user information can be effectively obfuscated [\[34\]](#page-22-5). (ii) The genuine prompt should be obfuscated by sufficient number of pseudo prompts, and the attacker can not easily identify the real prompt from the combination pattern even with background knowledge. (iii) The pseudo prompt should appear genuine rather than obviously fabricated. Thus it's crucial to maintain the fluency and reasonability of the pseudo prompts.

3.2.2. Construction of Privacy Model

In the following, we first give the definitions of private attributes and their semantic relevance.

Definition 1 (Private Attributes). Denote \mathcal{U} as the attribute space, and \mathcal{P} as the prompt space. Given a sub-prompt list $p \in \mathcal{P}$, its private attributes are denoted as $U(\mathbf{p}) = \{u_1, u_2, ..., u_m\}$ for m attributes.

Remark 2. For conciseness, the prompt in Definition [1](#page-6-0) could be a full prompt p , or a sequence of decomposed prompts with the same intention $p = [p_1, p_2, ..., p_{|\mathbf{p}|}].$

The private attributes encompass a range of elements, including verbs, adjectives, and nouns, which extend beyond personally identifiable information (PIIs). Next, we define the semantic similarity between two private attributes.

Definition 3 (Attribute-attribute Similarity). Given two attributes $u_1, u_2 \in \mathcal{U}$, an attribute similarity function measures the semantic similarity between u_1 and u_2 : $\text{Sim}(u_1, u_2) : \mathcal{U} \times \mathcal{U} \to \mathbb{R}.$

For a pair of genuine and pseudo prompts, we define the correspondent attributes as followed:

Definition 4 (Correspondent Attributes). Given two prompts $p_1, p_2 \in \mathcal{P}$, the correspondent attribute of $u_i \in U(\mathbf{p}_1)$ in \mathbf{p}_2 , is defined as the attribute at the same syntactic position of p_2 , denoted by Corr (u_i, p_1, p_2) .

Remark 5. The definition assumes that: (1) p_1 and p_2 have the same syntactic structure; (2) if u_i occurs in p_1 multiple times, the correspondent locations in p_2 return the same attribute.

For example, given the original question "What are the responsibilities of software engineers?" and private attribute "software engineer", the correspondent attribute in the fake question "What are the responsibilities of school teachers?" would be "school teacher". Based on the correspondent attributes and attribute-attribute similarity, we can define the semantic similarity between two prompts below:

Definition 6 (Prompt-prompt Similarity). Given two prompts $p_1, p_2 \in \mathcal{P}$, their similarity can be defined by the similarity between each pair of correspondence attributes:

$$
\text{Sim}(\boldsymbol{p}_1, \boldsymbol{p}_2) = \max_{u_i \in U(\boldsymbol{p}_1)} \text{Sim} (u_i, \text{Corr}(u_i, \boldsymbol{p}_1, \boldsymbol{p}_2))
$$
\n(3)

We proceed to the definition of significance of an attribute, which is tied to the likelihood of a curious server being able to identify the genuine attribute from a group of genuine and pseudo-prompts.

Definition 7 (Significance of Single Attribute). Denote $P = \{p_1, p_2, ..., p_n\}$ as a group of prompts. The significance of an attribute $u \in U(\mathbf{p}_i)$ related to a group of prompts P is defined as:

$$
Sig(u, \boldsymbol{P}) = \frac{\sum_{j=1}^{n} H(u, \boldsymbol{p}_i, \boldsymbol{p}_j)}{n},
$$
\n(4)

where:

$$
H(u, \boldsymbol{p}_i, \boldsymbol{p}_j) = \begin{cases} 1 & \text{Corr } (u, \boldsymbol{p}_i, \boldsymbol{p}_j) = u \\ 0 & \text{otherwise} \end{cases}
$$
 (5)

In our setting, the group of prompts consists of one genuine prompt along with a collection of pseudo prompts. The significance of a true attribute can be considered as the proportion of its occurrence within the group of prompts. In the following, we provide the definition of significance for multiple attributes.

Definition 8 (Significance of Attribute Set). Suppose p_0 denotes the genuine prompt. The significance of attribute set $U(\mathbf{p}_i)$ related to a group of prompts ${\bm P} = \{{\bm p}_0, {\bm p}_1, ..., {\bm p}_n\}$ is defined as:

$$
Sig(U(\boldsymbol{p}_0), \boldsymbol{P})
$$

=
$$
\max_{u_k} \max_{h} \max_{\mathcal{V}} \frac{\sum_{j=1}^{n} \bar{H}(\mathcal{V}, p_{0h}, p_{jh})}{\sum_{j=1}^{n} \bar{H}(\mathcal{V} \setminus u_k, p_{0h}, p_{jh})}
$$

s.t. $u_k \in \mathcal{V} \subseteq U(p_{0h}),$ (6)

where:

$$
\bar{H}(\mathcal{V}, p_{0h}, p_{jh}) = \begin{cases}\n1 & \text{Corr } (u, p_{0h}, p_{jh}) = u \,\forall u \in \mathcal{V} \\
\text{or } \mathcal{V} = \emptyset \\
0 & \text{otherwise}\n\end{cases}
$$
\n(7)

 p_{ih} is the h-th decomposed sub-prompt in the *i*-th prompt. In case that the attacker have prior knowledge of some private attributes, we introduce a notation V as a subset of private attributes in p_{0h} . Then we consider the proportion of a given attribute conditioning on any possible set of private attributes to bound the possibility of correctly identify the target attribute with some background knowledge. Now, we provide the definition of genuineness for the third criterion:

Definition 9 (Genuineness). Denote $D : \mathcal{P} \to \mathbb{R}$ as a function to discriminate between fabricated and genuine prompts. A larger value returned by D indicates a higher likelihood of a prompt being genuine. The genuineness of a prompt $p \in \mathcal{P}$ can be defined as $Genu(p) = D(p)$.

Based on Definition [6,](#page-7-0) [8,](#page-7-1) and [9,](#page-8-0) we can formulate our proposed (λ, μ, ρ) -privacy model as:

Definition 10 (User Privacy). Let $\boldsymbol{P} = \{p_0, p_1, ..., p_n\}$ be a group of prompts, where p_0 is the genuine user prompt and the remaining ones are pseudo prompts. If P satisfies the following requirements, then it is deemed that it can ensure (λ, μ, ρ) privacy of user prompt p_0 with respect to discriminator D:

- Each pseudo prompt should be semantically irrelavant to user prompt p_0 , i.e., $\forall i \in [1, n], \, \text{Sim}(\boldsymbol{p}_0, \boldsymbol{p}_i) \leq \lambda.$
- The users' sensitive attributes should be obfuscated by sufficient pseudo prompts, i.e., $\text{Sig}(\text{U}(p_0), P) \leq \mu$.
- Each pseudo prompt should not be classified as fabricated prompt by discriminator D, i.e., $\forall i \in [1, n]$, $Genu(p_i) = D(p_i) > \rho$.

In Appendix [Appendix B,](#page-26-0) we provide the relationship between our privacy model and the upper bound on the success rate of inference attacks, which states that an curious server can do no better than random guessing if the combination of attributes are uniformly distributed.

4. ConfusionPrompt: User-Side Models

Following the overall design and the requirements in privacy model, this section introduces how to enable ConfusionPrompt through the design of user-side models, including decomposer, generator, and recomposer.

4.1. Decomposer

A decomposer is designed to decompose an original user prompt into several subprompts, such that the required number of pseudo prompts to ensure the same level of privacy preservation can be significantly reduced. In the following, we theoretically demonstrate the benefit of a local decompose module in terms of complexity measured by the number of required pseudo prompts.

4.1.1. Complexity Analysis

We first show the complexity for single-paragraph prompt, that is, the prompt is not decomposed.

Theorem 11 (Complexity for Single Paragraph). Let $P = \{p_0, p_1, ..., p_n\}$ be a group of prompts, where p_0 is the genuine user prompt and the remaining ones are dummy prompts. Suppose each prompt in the group represents a single paragraph $|\mathbf{p}_i|=1$, $\forall i \in [1, n]$. To achieve (λ, μ, ρ) -privacy, it requires that

$$
n \ge \left(\frac{1}{\mu}\right)^{|U(\mathbf{p}_0)|}.\tag{8}
$$

Accordingly, we provide the following complexity analysis for decomposed prompts, which are a key component in our ConfusionPrompt.

Theorem 12 (Complexity for Decomposed Prompt). Let $P = \{p_0, p_1, ..., p_n\}$ be a group of prompts, where p_0 is the user prompt and the remaining ones are dummy prompts. Suppose each prompt in the group represents a sequence of decomposed prompt with the same intention $p_i = [p_{i1}, p_{i2}, ..., p_{il}], \forall i \in [1, n]$. To achieve (λ, μ, ρ) privacy, it requires that

$$
n \ge \sum_{j=1}^{l} \left(\frac{1}{\mu}\right)^{|U(p_{0j})|} \tag{9}
$$

 $Specifically, if $|U(\mathbf{p}_0)| = l$ and $|U(p_{0j})| = 1, \forall j \in [1, l]$, then$

$$
n \geq \frac{|U(\mathbf{p}_0)|}{\mu} \tag{10}
$$

Theorem [11](#page-9-0) and [12](#page-9-1) compare the complexities between single prompt and decomposed sub-prompt, where the proof is defered to Appendix [Appendix A.](#page-25-0) In the ideal scenario, the complexity can be reduced to $\mathcal{O}(|U(\mathbf{p}_0)|/\mu)$ after decomposition. An intuitive explanation is given in Figure [2.](#page-12-0)

4.1.2. Requirements of Ideal Decomposer

Now, we can articulate the criteria for an ideal decomposer:

- A fundamental requirement for the decomposition process is to follow the collectively exhaustive principle [\[35\]](#page-22-6). In other words, the collection of responses to decomposed sub-prompts should recover the whole response.
- An ideal decomposer would optimize the complexity, i.e., the required number of pseudo prompts, in two aspects: (i) each sub-prompt contains as few attributes as possible; (ii) each attribute appears in as few prompts as possible.

4.1.3. Model Training

We design a two-stage training approach to optimize the above objectives. In the first stage, we finetune a pretrained language model (LM) on demonstration data for decomposition task, where the LM is trained to generate decomposition given a full prompt. In the second stage, the LM is prompted to output multiple decompositions for each input. From the generations, a subset of preferred decompositions is selected to further fine-tune the model. The procedure to select preferred examples are as follows:

- Evaluate whether each decomposition adheres to the MECE principle, discarding any that do not meet this standard.
- Among the MECE-compliant decompositions, assess the complexity of each using a predefined parameter μ , and select the top k examples for each prompt with the lowest complexity.

4.2. Generator

Generator takes an genuine prompt p and its private attributes $U(p)$ as input and produces a pseudo prompt p' with replaced attributes. The generator will be run for multiple times to obtain a series of pseudo prompts for each genuine prompt.

4.2.1. Requirements

The requirements for a pseudo prompt suggest the following criteria for an ideal generator:

- The generator should produce pseudo prompt with fake information that is semantically irrelevant to the correspondent attributes in genuine prompt.
- The pseudo prompt should not be classified as fabricated prompt by a strong discriminator D.

4.2.2. Model training.

The generator is trained using a similar procedure described in Section [4.1.3.](#page-10-0) In the first stage, we fine-tune a pretrained LM using demonstration data for replacement task, where the LM is trained to generate new prompt with replaced attributes. In the second stage, we collect the preferred generations considering both semantic relevance and genuineness, with criteria given as follows:

- Compute s, the similarity between the pseudo and original prompt.
- Compute f , the genuineness score for the pseudo prompt.
- Calculate the overall score $\beta f s$, where β is the hyperparameter controlling the weight of the genuiness score.
- Select the top k examples for each prompt with the highest overall score.

4.3. Recomposer

The local re-composition LM combines the retrieved sub-prompts and subresponses to produce the final whole response. We train a local recomposer on a collection of demonstration data with supervise learning. Specifically, given a complete prompt p and a set of sub-prompt-response pairs $((p_1, r_1), \ldots (p_k, r_k))$, the recomposer G_r is trained to maximize $\log p_{G_r}(r|p,(p_1,r_1),...(p_k,r_k))$ where r is the final response.

4.4. Algorithm

Algorithm [1](#page-12-1) outlines the procedure for our private inference framework ConfusionPrompt. The client starts with decomposing the full prompt into sub-prompts and then generates a collection of qualified fake prompts that meet the privacy requirement. It can be derived immediately from the algorithm that our protocol meets (λ, μ, ρ) -privacy.

5. Experiment

5.1. Experiment Setup

We evaluate our framework on two multi-hop reasoning datasets: StrategyQA [\[36\]](#page-22-7) and MuSiQue [\[37\]](#page-22-8). We integrate ConfusionPrompt with different online LLMs including GPT-4, GPT-4-Turbo, and GPT-4o [\[7\]](#page-19-6). We consider the privacy parameters $\lambda \in [0.5, 0.8], 1/\mu \in [5, 50],$ and $\rho \in [1, 4]$ unless specified. Refer to Appendix [Appendix C.2](#page-29-0) for the training of decomposer, generator, and recomposer.

We extract the private attributes of StrategyQA and MuSiQue through the steps below (see Appendix [Appendix C.1](#page-27-0) for details):

Figure 2: Example of decomposition savings in query complexity. Decomposition module reduces the query complexity from 9 to 6 under privacy requirement $\mu = 3$. This reduction becomes more pronounced with larger values of μ . For instance, the complexity decreases from 100 to 20 under privacy requirement $\mu = 10$.

Algorithm 1 ConfusionPrompt

Input: Original prompt p, privacy parameters λ , μ , and ρ . **Output:** Final response r .

- 1: User decomposes the original prompt into sub-tasks $p_0 = G_d(p)$.
- 2: for $p_{0h} \in \boldsymbol{p}_0$ do
- 3: User keeps sampling from the generator until there are n distinct pseudo prompts with *n* given by [9,](#page-9-2) where each one $1 \leq i \leq n$ has prompt similarity $\text{Sim}(p_{0h}, p_{ih}) \leq \lambda$ and genuineness score $\text{Genu}(p_{ih}) \geq \rho$.
- 4: end for
- 5: User sends the group of genuine and pseudo prompts $\boldsymbol{P} = \{\boldsymbol{p}_0, \boldsymbol{p}_1, ..., \boldsymbol{p}_n\}$ to the server.
- 6: Server returns a collection of responses $(r_0, ..., r_n)$.
- 7: User retrieves the response corresponding to the genuine prompt r_0 .
- 8: User obtains the final response r using the local recomposition model.
- Step 1: sample construction. We adopt a semi-automated method to extract private attributes from each sample. First, we extract the entities using a combination of two NER methods: Spacy [\[38\]](#page-22-9) and Flair [\[39\]](#page-23-0). Then we manually correct and supplement the private attributes for each query.
- Step 2: model finetuning. An LLM is finetuned using the private attribute samples to guide the LLM output private attributes given a query.
- Step 3: attribute extraction. The remaining queries are fed into the finetuned LLM to generate private attributes.

5.2. Empirical Privacy Evaluation

We simulate two types of inference attacks to investigate the privacy protection level under various combinations of privacy parameters.

Prompt Identification Attack: an attack that identifies the true query from a group of fake and true prompts. Denote $\mathbf{q} = [q_1||q_2||...||q_n]$ as the concatenated group of queries, and k as the index for the true query. We finetune a BART-large classification model G_{PIA} to predict the index of the true query $k = G_{\text{PIA}}(\mathbf{q})$.

Attribute Inference Attack: an attack that infers the sensitive features of records from either a group of prompts, or differentially privatized inputs. We rely on the twitter text dataset [\[40\]](#page-23-1) to predict the gender based on the user's review.

Noted that prompt identification attack is specifically designed for our framework, and attribute inference attack can be applied to both ConfusionPrompt and DP-based methods.

5.3. Experiment Results

5.3.1. Privacy Experiments

Figure [3](#page-14-0) visualizes the attack accuracy for prompt identification attack under various combinations of significance μ , genuineness ρ , similarity λ . It can be observed that: (a) decreasing significance μ consistently reduces the attack accuracy. (b) As the genuineness threshold ρ increases from 1 to 4, the attack accuracy approaches that of random guessing. The result reveals that it becomes harder for the attacker to distinguish the true query as the fake prompts become more realistic. (c) There's no clear relationship between the attack accuracy and similarity threshold λ . Such privacy parameter could be more related to the attribute inference attack discussed later.

Figure [4](#page-14-1) presents the attack accuracies of attribute inference attack for both ConfusionPrompt and LDP-based methods, from which we can make the following observations: (1) Paraphrase generally leads to higher attack accuracies compared to

Figure 3: Prompt identification attack accuracy under various combinations of privacy parameters.

Text2text. This can be attributed to the fact that the semantic meanings of certain key words remain unchanged during the paraphrasing process. (2) The attack accuracies decrease to a plateau when $1/\mu \geq 15$ or $\epsilon \leq 1$. This suggests that beyond these thresholds, further increasing the privacy protection metrics does not significantly reduce the attack accuracy. (3) The attack accuracy for ConfusionPrompt with $1/\mu > 15$ is similar to that of Text2Text with $\epsilon \leq 1$, indicating certain alignment for the privacy protection between LDP-based methods and our framework. (4) Decreasing the similarity threhold λ helps to reduce the attribute inference attack accuracies.

Figure 4: Attribute inference attack accuracy for ConfusionPrompt and LDP-based methods.

5.3.2. Utility Evaluation

For StrategyQA, we report the accuracy scores (ACC) and area under the roc curve (AUC) to assess the the classification task. For MuSiQue, we report the F1 score, ROUGE-L, and exact matching (EM) to evaluate the question answering task [\[41\]](#page-23-2). We benchmark our framework with $\mu = 15$, $\rho = 4$, and $\lambda = 0.5$ against five baseline methods: (1) a local Llama2 [\[42\]](#page-23-3) model with 7B parameters; (2) a local Vicuna [\[43\]](#page-23-4) model with 13B parameters; (3) Text-to-text privatization (Text2Text) [\[30\]](#page-22-1), where the query is privatized with LDP by replacing each word with the perturbed token embeddings; (4) Paraphraser [\[31,](#page-22-2) [32\]](#page-22-3) that paraphrases the prompt with LDP mechanism using a language model; (5) querying online GPTs with no privacy protection. In the former two methods, the user downloads the open-source models and directly extract the final response from the model. In methods (3) and (4), the queries are privatized with LDP privacy budget $\epsilon = 10$ before transmission to the server. For the final approach, the complete prompt is transmitted to the service provider without any confusion strategy

METHOD	PRIVACY		STRATEGYQA		MUSIQUE		
	PROTECTION	ACC	AUC	F1	ROUGHL	ΕM	
$LLAMA2-7B$	YES	0.602	0.581	0.484	0.485	0.321	
$VICUNA-13B$	$_{\rm Yes}$	0.646	0.628	0.417	0.416	0.225	
TEXT2TEXT (GPT-3.5-TURBO)	YES	0.528	0.496	0.019	0.019	0.010	
TEXT2TEXT (GPT-4-TURBO)	$_{\rm Yes}$	0.537	0.506	0.028	0.027	0.014	
TEXT2TEXT (GPT-40)	$_{\rm Yes}$	0.533	0.500	0.021	0.020	0.012	
PARAPHRASER (GPT-3.5-TURBO)	YES	0.489	0.478	0.076	0.076	0.028	
PARAPHRASER (GPT-4-TURBO)	YES	0.546	0.523	0.060	0.061	0.026	
PARAPHRASER (GPT-40)	$_{\rm Yes}$	0.537	0.515	0.072	0.072	0.038	
GPT-3.5-TURBO	No	0.751	0.737	0.604	0.605	0.439	
GPT-4-TURBO	No	0.803	0.798	0.663	0.664	0.503	
$GPT-40$	No	0.791	0.784	0.721	0.721	0.557	
ConfusionPrompt (GPT-3.5-Turbo)	YES	0.723	0.726	0.606	0.605	0.445	
ConfusionPrompt (GPT-4-Turbo)	$_{\rm Yes}$	0.741	0.743	0.633	0.634	0.495	
ConfusionPrompt (GPT-40)	$_{\rm Yes}$	0.733	0.739	0.685	0.684	0.535	

Table 1: Utility comparisons between our proposed ConfusionPrompt and baselines.

The privacy parameters for ConfusionPrompt are fixed at $\mu = 15$, $\rho = 4$, and $\lambda = 0.5$. The privacy budgets for LDP-based methods are set to $\epsilon = 10$ and $\delta = 10^{-4}$.

The results are reported in Table [1.](#page-15-0) From the results, we can see that (1) online proprietary models outperform open-source models by over 11% and 24%, repectively, for StrategyQA and MuSiQue, indicating the strong motivation for users to use online service while preserving privacy. (2) ConfusionPrompt based on various online models consistently and significantly outperforms LDP-based methods, showing the effectiveness of our proposed method. Notably, our framework possesses a distinct advantage over perturbation-based methods: increasing the privacy protection level

does not adversely affect performance since the true queries are always provided to the server.

5.3.3. Decomposition Benefits

Theorem [11](#page-9-0) and [12](#page-9-1) show that the decomposition module could reduce the number of pseudo prompts required to be sent to the server. In this section, we empirically demonstrate practical benefits by analyzing the monetary cost of our ConfusionPrompt framework. In particular, we compute the monetary ratio, the ratio of the monetary cost for using ConfusionPrompt compared to the direct query method, both before and after the application of the decomposition module.

Figure [5](#page-16-0) presents the query cost benefits achieved through our decomposition module. It can be observed that the complexity gains become increasingly pronounced as the level of privacy protection increases. This can be attributed to the fact that the complexity experiences polynomial growth before decomposition, whereas it exhibits approximate linearity after decomposition. Our protocol offers substantial savings ranging from an average reduction of $1.9\times$ at $\mu = 1/10$ to an average reduction of 18.3 \times at $\mu = 1/50$.

Figure 5: Monetary ratio of strategyQA and MuSiQue dataset before (*decomp*) and after $(w/o$ $decomp)$ decompositon under various significance μ . Decomposition in ConfusionPrompt substantially reduces the monetary cost, indicating its efficiency.

5.3.4. Computation Overhead Analysis

To validate the practicality of our method, we investigate the user-side computation overhead in terms of memory cost and sampling cost.

In Table [2,](#page-17-0) we present the memory cost required for the three local models, as well as that for local open-source LLMs. From the results, we can see that our proposed ConfusionPrompt is significantly efficient compared to inferring large open-source language models on the user side. Specifically, it requires only 61.2% and 79.7% memory cost compared to running LLaMa2-7B and Vicuna 13B, respectively, on the user side.

Table 2: Memory cost for local inference with 10 samples.							
					LOCAL MODEL LLAMA2-7B VICUNA-13B DECOMPOSER GENERATOR RECOMPOSER TOTAL (CONFUSIONPROMPT)		
MEMORY COST $25885MB$ 49653MB		$3867\mathrm{MB}$	-3865MB	- 2306MB	10038MB		

 $T = \begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}$ (1 samples) cost for local inference with 10 samples.

Algorithm [1](#page-12-1) suggests that the generator keeps generating fake prompts until the (λ, μ, ρ) -privacy is satisfied. Therefore, it is crucial to consider the number of sampling times it takes for a generator to produce sufficient qualified pseudo prompts. Table [3](#page-17-1) presents the number of generations to perform and the time cost for each generation under different levels of significance μ . It requires to conduct sampling for an average of 3.23 times the $1/\mu$. Note that $1/\mu$ can be treated as the minimal number of sampling times to achieve the privacy budget when the prompt contains only one private attribute. The average time per sampling is 1.73 seconds, and thus the overall time consumption for each sample ranges from 30 seconds at $\mu = 1/5$ to 161 seconds at $\mu = 1/30$.

Table 3: Cost of generation in terms of number of samplings and time cost per sampling (seconds).

$1/\mu$	10.	-20-	-30
NUMBER OF SAMPLINGS 17.7 30.1 65.3 93.5			
TIME PER SAMPLING		1.73 SECONDS	

5.3.5. Local Model Selection

In this section we justify the selection of decomposor and recomposor. For decomposor, we obtain the BLEU between the generated decomposition and reference provided by the dataset. For recomposor, the models are evaluated in terms of the accuracy metrics described in Section [5.3.2,](#page-14-2) using the golden decomposition and sub-answer as training and testing inputs.

Table [4](#page-18-0) presents the experiment results on MuSiQue using models from three different classes of varying sizes. While Flan-T5-large exhibits the best performance for both tasks, we select BART-large as the decomposition and recomposition model due to its balanced trade-off between model size and performance.

6. Discussion

In this section, we provide further clarifications and discussions on practical issues of our framework.

	PARAMETER	DECOMPOSER	RECOMPOSER		
	SIZE	BLEU	F1	ROUGEL	ЕM
BART-BASE	139M	0.314	0.563	0.564	0.446
BART-LARGE	406M	0.402	0.640	0.641	0.525
T5-BASE	223M	0.343	0.581	0.580	0.484
T5-LARGE	737M	0.408	0.646	0.645	0.554
FLAN-T5-BASE	248M	0.367	0.608	0.609	0.518
FLAN-T5-LARGE	783M	0.458	0.671	0.671	0.577

Table 4: Parameter size and performance on both decomposition and recomposition tasks across various models for MuSiQue.

Protection capability of privacy model. Our (λ, μ, ρ) -privacy model establishes requirements for fabricated prompts to mitigate privacy risks. Rather than offering a worst-case privacy guarantee such as LDP, the model quantifies the criteria that a group of prompts should satisfy. Our empirical experiments associate the privacy parameters with attack success rate. It is important to note that the privacy model should be regarded as an enhancement over the insecure status quo, rather than a substitute for formal privacy guarantees.

Tradeoff between privacy and query cost. Whereas traditional perturbation-based methods trade privacy for utility, our ConfusionPrompt trades privacy for query complexity while providing accurate responses. This approach is particularly suitable for clients with high privacy demands who can accommodate these costs, such as finance and healthcare organizations. Additionally, although query costs rise linearly with the number of tokens in API services, users of chatbot services can submit unlimited requests under a fixed subscription fee, allowing for enhanced privacy protection at a manageable cost.

7. Conclusion

This paper proposes a private inference framework on online LLMs, termed ConfusionPrompt. We deploy three local models on the user side: (i) decomposer that maps an original prompt to a sequence of sub-prompts, (ii) generator that produces pseudo prompts by replacing private attributes in the genuine sub-prompts, (iii) recomposer that maps the decomposed prompt-response pairs from the cloud service to the final response. Such design endows our framework with advantages over previous protocols that: (i) it can be seamlessly integrated with existing black-box LLMs

where the service providers have no need to modify their already-built framework, and (ii) it achieves better privacy-utility trade-off than existing LDP-based privatization methods. We develop a (λ, μ, ρ) -privacy model to formulate the requirement for a privacy-preserving group of prompts, and accordingly provide a complexity analysis to demonstrate the benefits of the decomposition module. Experiments show that our ConfusionPrompt significantly outperforms the inference with local open-sourced LLMs in terms of utility and computation cost.

References

- [1] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. Advances in neural information processing systems, 33:1877–1901, 2020.
- [2] Baptiste Roziere, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Tal Remez, Jérémy Rapin, et al. Code llama: Open foundation models for code. arXiv preprint arXiv:2308.12950, 2023.
- [3] Siyuan Huang, Zhengkai Jiang, Hao Dong, Yu Qiao, Peng Gao, and Hongsheng Li. Instruct2act: Mapping multi-modality instructions to robotic actions with large language model. arXiv preprint arXiv:2305.11176, 2023.
- [4] Arun James Thirunavukarasu, Darren Shu Jeng Ting, Kabilan Elangovan, Laura Gutierrez, Ting Fang Tan, and Daniel Shu Wei Ting. Large language models in medicine. Nature medicine, 29(8):1930–1940, 2023.
- [5] Shijie Wu, Ozan Irsoy, Steven Lu, Vadim Dabravolski, Mark Dredze, Sebastian Gehrmann, Prabhanjan Kambadur, David Rosenberg, and Gideon Mann. Bloomberggpt: A large language model for finance. arXiv preprint arXiv:2303.17564, 2023.
- [6] Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. Advances in Neural Information Processing Systems, 35:27730–27744, 2022.
- [7] OpenAI. Gpt-4 technical report. arXiv preprint arXiv:2303.08774, 2023.
- [8] Xuanqi Liu and Zhuotao Liu. Llms can understand encrypted prompt: Towards privacy-computing friendly transformers. arXiv preprint arXiv:2305.18396, 2023.
- [9] Tianyu Chen, Hangbo Bao, Shaohan Huang, Li Dong, Binxing Jiao, Daxin Jiang, Haoyi Zhou, Jianxin Li, and Furu Wei. The-x: Privacy-preserving transformer inference with homomorphic encryption. arXiv preprint arXiv:2206.00216, 2022.
- [10] Minxin Du, Xiang Yue, Sherman SM Chow, Tianhao Wang, Chenyu Huang, and Huan Sun. Dp-forward: Fine-tuning and inference on language models with differential privacy in forward pass. arXiv preprint arXiv:2309.06746, 2023.
- [11] Abbas Acar, Hidayet Aksu, A Selcuk Uluagac, and Mauro Conti. A survey on homomorphic encryption schemes: Theory and implementation. ACM Computing Surveys (Csur), 51(4):1–35, 2018.
- [12] Ronald Cramer, Ivan Bjerre Damgård, et al. Secure multiparty computation. Cambridge University Press, 2015.
- [13] Lingjuan Lyu, Xuanli He, and Yitong Li. Differentially private representation for nlp: Formal guarantee and an empirical study on privacy and fairness. In Findings of the Association for Computational Linguistics: EMNLP 2020, pages 2355–2365, 2020.
- [14] Cynthia Dwork. Differential privacy. In International colloquium on automata, languages, and programming, pages 1–12. Springer, 2006.
- [15] Chen Qu, Weize Kong, Liu Yang, Mingyang Zhang, Michael Bendersky, and Marc Najork. Natural language understanding with privacy-preserving bert. In Proceedings of the 30th ACM International Conference on Information \mathcal{B} Knowledge Management, pages 1488–1497, 2021.
- [16] Peihua Mai, Ran Yan, Zhe Huang, Youjia Yang, and Yan Pang. Split-anddenoise: Protect large language model inference with local differential privacy. In Forty-first International Conference on Machine Learning.
- [17] Mohammad Malekzadeh and Fahim Kawsar. Salted inference: Enhancing privacy while maintaining efficiency of split inference in mobile computing. In Proceedings of the 25th International Workshop on Mobile Computing Systems and Applications, pages 14–20, 2024.
- [18] Mohamed Sabt, Mohammed Achemlal, and Abdelmadjid Bouabdallah. Trusted execution environment: What it is, and what it is not. In 2015 IEEE Trust $com/BigDataSE/Ispa$, volume 1, pages 57–64. IEEE, 2015.
- [19] Maud Ehrmann, Ahmed Hamdi, Elvys Linhares Pontes, Matteo Romanello, and Antoine Doucet. Named entity recognition and classification in historical documents: A survey. ACM Computing Surveys, 56(2):1–47, 2023.
- [20] Guillaume Lample, Miguel Ballesteros, Sandeep Subramanian, Kazuya Kawakami, and Chris Dyer. Neural architectures for named entity recognition. arXiv preprint arXiv:1603.01360, 2016.
- [21] Zhigang Kan, Linbo Qiao, Hao Yu, Liwen Peng, Yifu Gao, and Dongsheng Li. Protecting user privacy in remote conversational systems: A privacy-preserving framework based on text sanitization. arXiv preprint arXiv:2306.08223, 2023.
- [22] Yu Chen, Tingxin Li, Huiming Liu, and Yang Yu. Hide and seek (has): A lightweight framework for prompt privacy protection. arXiv preprint arXiv:2309.03057, 2023.
- [23] Balamurugan Anandan, Chris Clifton, Wei Jiang, Mummoorthy Murugesan, Pedro Pastrana-Camacho, and Luo Si. t-plausibility: Generalizing words to desensitize text. Trans. Data Priv., $5(3):505-534$, 2012.
- [24] Ran Gilad-Bachrach, Nathan Dowlin, Kim Laine, Kristin Lauter, Michael Naehrig, and John Wernsing. Cryptonets: Applying neural networks to encrypted data with high throughput and accuracy. In International conference on machine learning, pages 201–210. PMLR, 2016.
- [25] Meng Hao, Hongwei Li, Hanxiao Chen, Pengzhi Xing, Guowen Xu, and Tianwei Zhang. Iron: Private inference on transformers. Advances in Neural Information Processing Systems, 35:15718–15731, 2022.
- [26] Gavin Kerrigan, Dylan Slack, and Jens Tuyls. Differentially private language models benefit from public pre-training. arXiv preprint arXiv:2009.05886, 2020.
- [27] Da Yu, Saurabh Naik, Arturs Backurs, Sivakanth Gopi, Huseyin A Inan, Gautam Kamath, Janardhan Kulkarni, Yin Tat Lee, Andre Manoel, Lukas Wutschitz, et al. Differentially private fine-tuning of language models. arXiv preprint arXiv:2110.06500, 2021.
- [28] Haonan Duan, Adam Dziedzic, Nicolas Papernot, and Franziska Boenisch. Flocks of stochastic parrots: Differentially private prompt learning for large language models, 2023.
- [29] Yansong Li, Zhixing Tan, and Yang Liu. Privacy-preserving prompt tuning for large language model services, 2023.
- [30] Oluwaseyi Feyisetan, Borja Balle, Thomas Drake, and Tom Diethe. Privacy-and utility-preserving textual analysis via calibrated multivariate perturbations. In Proceedings of the 13th international conference on web search and data mining, pages 178–186, 2020.
- [31] Saiteja Utpala, Sara Hooker, and Pin Yu Chen. Locally differentially private document generation using zero shot prompting. arXiv preprint arXiv:2310.16111, 2023.
- [32] Justus Mattern, Benjamin Weggenmann, and Florian Kerschbaum. The limits of word level differential privacy. In Findings of the Association for Computational Linguistics: NAACL 2022, pages 867–881, 2022.
- [33] Hwee Hwa PANG, Xuhua DING, and Xiaokui XIAO. Embellishing text search queries to protect user privacy. (2010). In Proceedings of the VLDB Endowment: 36th International Conference on Very Large Data Bases: Singapore, pages 13–17, 2010.
- [34] Zongda Wu, Jie Shi, Chenglang Lu, Enhong Chen, Guandong Xu, Guiling Li, Sihong Xie, and S Yu Philip. Constructing plausible innocuous pseudo queries to protect user query intention. Information Sciences, 325:215–226, 2015.
- [35] Ethan M Rasiel. *The McKinsey Way*. McGraw-Hill New York, 1999.
- [36] Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies. Transactions of the Association for Computational Linguistics, 9:346–361, 2021.
- [37] Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. Musique: Multihop questions via single-hop question composition. Transactions of the Association for Computational Linguistics, 10:539–554, 2022.
- [38] Bhargav Srinivasa-Desikan. Natural Language Processing and Computational Linguistics: A practical guide to text analysis with Python, Gensim, spaCy, and Keras. Packt Publishing Ltd, 2018.
- [39] Alan Akbik, Tanja Bergmann, Duncan Blythe, Kashif Rasul, Stefan Schweter, and Roland Vollgraf. Flair: An easy-to-use framework for state-of-the-art nlp. In Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics (demonstrations), pages 54–59, 2019.
- [40] Pradeep Vashisth and Kevin Meehan. Gender classification using twitter text data. In 2020 31st Irish Signals and Systems Conference (ISSC), pages 1–6. IEEE, 2020.
- [41] Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W Cohen, Ruslan Salakhutdinov, and Christopher D Manning. Hotpotqa: A dataset for diverse, explainable multi-hop question answering. $arXiv$ preprint $arXiv:1809.09600$, 2018.
- [42] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. arXiv preprint arXiv:2307.09288, 2023.
- [43] Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, et al. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality. See https://vicuna. lmsys. org (accessed 14 April 2023), 2023.
- [44] Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. Bart: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pages 7871–7880, 2020.
- [45] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. Journal of machine learning research, 21(140):1–67, 2020.
- [46] Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, et al. Scaling instruction-finetuned language models. Journal of Machine Learning Research, 25(70):1–53, 2024.
- [47] Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. arXiv preprint arXiv:1908.10084, 2019.
- [48] Gopichand Kanumolu, Lokesh Madasu, Pavan Baswani, Ananya Mukherjee, and Manish Shrivastava. Unsupervised approach to evaluate sentence-level fluency: Do we really need reference? *arXiv preprint arXiv:2312.01500*, 2023.
- [49] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:1907.11692, 2019.
- [50] Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: $100,000+$ questions for machine comprehension of text. In *Proceedings of the* 2016 Conference on Empirical Methods in Natural Language Processing, pages 2383–2392, 2016.
- [51] Dheeru Dua, Yizhong Wang, Pradeep Dasigi, Gabriel Stanovsky, Sameer Singh, and Matt Gardner. Drop: A reading comprehension benchmark requiring discrete reasoning over paragraphs. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 2368–2378, 2019.
- [52] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In Proceedings of the $40th$ annual meeting of the Association for Computational Linguistics, pages 311–318, 2002.

Appendix A. Proof of Theorem [11](#page-9-0) and [12](#page-9-1)

We begin with the proof for Theorem [11](#page-9-0) as followed:

Proof. For the prompt with single paragraph, the significance can by represented as:

$$
Sig(U(p_0), P) = \max_{u_k} \max_{\mathcal{V}} \frac{\sum_{i=1}^n \bar{H}(\mathcal{V}, p_0, p_i)}{\sum_{i=1}^n \bar{H}(\mathcal{V}\backslash u_k, p_0, p_i)}
$$
(A.1)
s.t. $u_k \in \mathcal{V} \subseteq U(p_0)$

, where p_0 is the genuine prompt, and p_i is the i^{th} prompt in the prompt group, and:

$$
\bar{H}(\mathcal{V}, p_0, p_i) = \begin{cases}\n1 & \text{Corr } (u, p_0, p_i) = u \,\forall u \in \mathcal{V} \\
\text{or } \mathcal{V} = \emptyset \\
0 & \text{otherwise}\n\end{cases} (A.2)
$$

For $\text{Sig}(U(p_0), P) = \mu$, it's obvious that there should be at least $1/\mu$ distinct values, including genuine and fake values, assigned to each attributes. Otherwise suppose u_k have less than $1/\mu$ distinct values, we would have:

$$
\frac{\sum_{j=1}^{|P|} H(u_k, p_0, p_j)}{|P|} > \mu,
$$
\n(A.3)

which violates the expression [A.1.](#page-25-1)

Next, we claim that each possible combination of attribute set values must appear at least once within the prompt group. To proof by contradiction, let's suppose that there is one combination missing in the group while the others appear once. Then we can consider two cases:

(a) The missing combination doesn't contain any true values. Then the significance of other single attribute must be larger than μ . This is because for a set containing all combinations, the proportion of the occurrence for each attribute is exactly μ . Therefore, such removal would make their significance smaller.

(b) The missing combination contains a subset of true values $\mathcal{V} \subseteq U(p_0)$. Then conditioning on the subset V , the proportion of any other single attribute would be over μ , as their original proportion is μ . Therefore, for any $u_k \notin V$, it holds that:

$$
\frac{\sum_{i=1}^{n} \bar{H}(\mathcal{V} \cup u_k, p_0, p_i)}{\sum_{i=1}^{n} \bar{H}(\mathcal{V}, p_0, p_i)} > \mu,
$$
\n(A.4)

which violates the expression [A.1.](#page-25-1)

To make each combination occur at least once, we should have at least $(1/\mu)^{|U(p_0)|}$ prompts in the group. \Box Following that, we can proceed to the proof for Theorem [12:](#page-9-1)

Proof. Let $\mu = \text{Sig}(U(p_0), P)$ denotes the significance. According to Theorem [11,](#page-9-0) for each sub-query $p_{0h} \in \mathbf{p}_0$, we should have at least $(1/\mu)^{||U(p_{0h})||}$ prompts to satisfy:

$$
\max_{u_k} \max_{\mathcal{V}} \frac{\sum_{i=1}^n \bar{H}(\mathcal{V}, p_{0h}, p_{ih})}{\sum_{i=1}^n \bar{H}(\mathcal{V} \setminus u_k, p_{0h}, p_{ih})} \le \mu
$$
\n
$$
\text{s.t.} u_k \in \mathcal{V} \subseteq U(p_{0h})
$$
\n
$$
(A.5)
$$

Then the proof completes by summing up the number of prompts over all sub- \Box queries.

Appendix B. Bound on Inference Attack

In this section, we consider the scenario where an attacker attempts to identify the target attribute by prior knowledge of other attributes and the combination pattern of attribute values. The following theorem states that an curious server can do no better than random guessing if the combination of values are uniformly distributed:

Lemma 1. Suppose the attacker is guessing the attributes from attribute combination pattern in \bf{P} . The attacker can do no more better than random guessing if the following condition is satisfied:

• Each combination of attribute set has the same occurrence times in the prompt groups P , i.e., the combinations are uniformly distributed.

From the proof of Theorem [11](#page-9-0) and [12,](#page-9-1) we can construct a uniformly distributed prompt group under the optimal number of prompts. Therefore, we can turn to the success rate under an random guessing attack, which is bounded by Lemma [2.](#page-26-1)

Lemma 2. Given a group of prompts $P = \{p_0, p_1, ..., p_n\}$ with (λ, μ, ρ) -privacy, suppose that the attacker have prior knowledge about the attribute subset $\mathcal{V} \subseteq U(\mathbf{p}_0)$. By random guessing, the probability of correctly identifying any target attribute $u \in U(\boldsymbol{p}_0) \wedge u \notin V$ is upper bounded by μ .

Proof. According to Definition [8,](#page-7-1) it holds that:

$$
\frac{\sum_{j=1}^{n} \bar{H}(\mathcal{V}, p_{0h}, p_{jh})}{\sum_{j=1}^{n} \bar{H}(\mathcal{V} \setminus u, p_{0h}, p_{jh})} \le \mu
$$
\n(B.1)

for any h and u . In other words, the proportion of any attribute u conditioning on the prior knowledge attribute set V is upper bounded by μ . Therefore, by random guessing, the probability of correctly identifying any target attribute u is upper bounded by μ . \Box

An interpretation of the above lemmas is that under (λ, μ, ρ) -privacy, we can always construct a group of prompts with optimal complexity, where the probability of correctly identifying any target attribute is upper bounded by μ , if the attacker utilizes the combination pattern of attributes (ignoring the semantic meaning).

Appendix C. Experiment

Appendix C.1. Construction of Private Attributes

During step 1, we label the private attributes according to the following guidelines:

- Identify the key components for a query, including but not limited to proper nouns, phrases, verbs, and adjectives.
- Ensure that there is no overlapping information between different private attributes within the same query.
- Each private attribute should be as succinct as possible. For example, instead of labeling "spouse of the Green performer" as a single attribute, it is preferable to split it into "spouse" and "Green performer" as separate attributes.

The third point is to ensure privacy protection even when an attacker possesses prior knowledge of certain attributes. Table [C.5](#page-27-1) provides several examples of private attributes.

Table C.5: Examples of private attributes in Strategy QA and MuSiQue.			
QUERY	PRIVATE ATTRIBUTES		
Are blue lips normal?	blue lips, normal		
Could ten gallons of seawater crush a six seawater crush, ten gallons, six year old year old?			
Who is the spouse of the Green per- spouse, Green performer former?			
What instrument is played by the person play instrument, The Blackout All-Stars from The Blackout All-Stars?			
What is the capital of the county that capital of the county, Pine Springs Pine Springs is located in?			

Table C.5: Examples of private attributes in StrategyQA and MuSiQue.

In step 2, we evaluate the generative quality of various LLMs on five models: i) GPT-4-Turbo with few-shot examples, ii) GPT-3.5-Turbo finetuned with 100 samples,

Type	N	Example Question	Potential Risks
Business	20	'As a VP of marketing at MovieMagic, I am considering	Reveal the strategic considera- tions of the company
		a shift in our advertising spend	
		from TV to digital platforms.	
		What are the key factors to con- sider?'	
Legal	20	I have a meeting with a client at	Reveal the sensitive case details
		Clark Legal Services in Boston	of a client
		who wants to create a trust.	
		What are the different types of	
		trusts available?'	
Health	20	'My 3-year-old daughter, Emily,	Reveal the medical and personal
		has just been diagnosed with a	info of family members
		peanut allergy. How can I en-	
		sure she avoids peanuts at her	
		daycare?'	
Career	20	'I have worked as a civil engi-	Reveal the personal career expe-
		neer at AECOM for five years	rience and work location
		in Los Angeles. What certifica-	
		tions should I pursue for career	
		advancement?'	
Education	20	I am a parent evaluating private	Reveal the personal info and
		schools in Chicago for my 6-year-	
		old son, Matthew. What are the	
		key factors to consider in choos-	
		ing a school with special needs	
		support?'	
Social	20	'My company is hosting a corpo-	Reveal the location and purpose
		rate event at the Hilton in Las	of the private business event
		Vegas. How can I network effec-	
		tively with potential clients?	
Personal	20	If am moving to a penthouse in	Reveal the residential location,
		Manhattan in July. How can I	moving schedule and personal
		best use natural light in my home	preference for decor
		decor?	

Table C.6: Sample Questions and Associated Risks for Each Category of PrivCP.

iii) BART-large [\[44\]](#page-23-5), iv) T5-large [\[45\]](#page-23-6), and v) Flan-T5-Xlarge [\[46\]](#page-23-7). The latter three open-source models are finetuned with 1000 samples.

Table [C.7](#page-29-1) presents the performance on a human-labeled test dataset. It can be observed that the finetuned version of GPT-3.5-turbo gives the best result, and thus it's used as the attribute extraction model throughout our experiment.

METHOD	STRATEGYQA			MUSIQUE		
	F1.	ROUGHL	ЕM	$_{\rm F1}$	ROUGHL	ЕM
GPT-4-TURBO	0.689	0.748	0.080	0.811	0.762	0.234
GPT-3.5-TURBO	0.803	0.881	0.421	0.846	0.789	0.333
BART-LARGE	0.713	0.690	0.227	0.664	0.634	0.118
T5-LARGE	0.603	0.595	0.102	0.381	0.383	0.010
$FLAN-T5-LARGE$	0.669	0.683	0.243	0.380	0.383	0.026

Table C.7: Comparison of various attribute extraction models.

Appendix C.2. Training of local models

In this section, we describe the training of decomposer, generator, and recomposer, respectively.

Training of decomposer: The decomposition model is finetuned on a pretrained BART model [\[44\]](#page-23-5) with 406M parameters. In the first stage, we utilize the decomposition samples from StrategyQA and MuSiQue as demonstration data. In the second stage, we evaluate the response through the following steps: (i) extract the sub-answers using gpt-4-turbo and obtain the final answers using a recomposition model to judge whether the decomposition returns a correct answer; (ii) compute the complexity measured by the number of required pseudo prompts under $\mu = 10$.

During step (i), to address the recomposer's limitations in determining the correctness of the final answer, we train a robust recomposition model by fine-tuning LLaMa2-7B. Note that during inference, we adopt a much smaller recomposition model for efficiency.

Training of generator: The generator is finetuned on the BART-large model. To collect demonstration data for the first stage, we prompt GPT-4-turbo to generate multiple pseudo prompts given the raw prompt and its private attributes using the following template.

Please replace the phrases {attributes} in the each of the following sentences, such that each sentence is fluent and reasonable, and the alterntive phrases have irrelevant meaning as {attributes}.

Please return $\{\# \text{ of replaces}\}$ replacements for each sentence.

Strictly respond in the form of JSON with the following format: {"S1": ["replacement 1", "replacement 2",...], "S2": ["replacement 1", "replacement 2",...]}.

Sentences: {dictionary of sentences}

In the second, we employ two models to evaluate the semantic similarity and genuineness, including a local similarity evaluation model and discriminator. For similarity evaluation model, we adopt a fine-tuned version of MiniLM-6L model [\[47\]](#page-24-0) to extract the embedding of each private attribute. The semantic relevance between a pair of attributes is given by the cosine similarity between their embeddings. For discriminator, We leverage GPT-4o to construct the training dataset for training a local discriminator. As the genuineness is closely related to the sentence's fluency, we instruct GPT-4o to evaluate the fluency for each sentence [\[48\]](#page-24-1) (see detailed instruction in [Appendix C.3\)](#page-30-0).

Training of recomposer: The recomposition model is finetuned on a pretrained RoBERTa [\[49\]](#page-24-2) and BART-large [\[44\]](#page-23-5) model, respectively, for strategyQA and MuSiQue. We utilize the sub-prompts & sub-responses given in StrategyQA and MuSiQue dataset as well as the final response to train a recomposition model. To improve the performance of recomposor, we pretrain the model on two addition datasets, SQuAD [\[50\]](#page-24-3) and DROP [\[51\]](#page-24-4).

Appendix C.3. Semantic Similarity Model and Discriminator

The comparison data collection for the generator involves a local similarity evaluation model and discriminator.

Similarity evaluation model: We adopt a finetuned version of MiniLM-6L model [\[47\]](#page-24-0) to extract the embedding of each private attribute. The semantic relevance between a pair of attributes is given by the cosine similarity between their embeddings.

Discriminator: We leverage GPT-4 to construct the training dataset for training a local discriminator. As the genuineness is closely related to the sentence's fluency, we prompt GPT-4 to evaluate the fluency for each sentence with the following template [\[48\]](#page-24-1):

Given multiple sentences, use the scoring rules below to score each sentence's fluency on a scale of 1 to 4:

1. Score 1: Incomprehensible. Inarticulate/ non-fluent sentence.

2. Score 2: Low Quality. Partially fluent sentence: (a) only half of the sentence

is fluent or (b) more than 1 missing words or (c) more than 1 misspelt words or d) contains individual fluent word-groups with missing coherence between them.

3. Score 3: Moderate. Sentence is predominantly fluent but contains either (a) misspelt word or (b) missing word or (c) multiple occurrence of a word.

4. Score 4: Perfect. Perfectly fluent sentence without any syntactic or grammatical error.

Strictly respond in the form of JSON with the following format: {"S1": the score, "S2": the score}.

Sentences: {dictionary of sentences}

On obtaining 4000 training and 700 validation samples, we finetune a Bert-base (110M parameters) to train a local discriminator.

Appendix C.4. Generator for Longer Attributes

In this section, we explore the generator's capability to replace longer attributes. Dataset Construction: To explore the generator's ability on generating longer attributes, we craft a privacy dataset for ConfusionPrompt (PrivCP) with sensitive information from 7 categories. For each category, we utilize GPT-4 to generate 50 simulated user queries. Then we manually inspect and select 20 queries for necessary grammatical and semantic adjustments. Table [C.6](#page-28-0) presents an example from each category and its associated risks.

In Table [C.8,](#page-31-0) we summarize the statistic of private attribute for strategyQA, MuSiQue, and PrivCP in terms of three metrics: i) average number of private attributes per query, ii) average length of each attribute (measured by the number of words), and iii) average attribute-to-query ratio (measured by the percentage of attribute words in a query). It can be observed that PrivCP has much longer attributes than the two standard benchmarks.

		ATTRIBUTES OF ATTRIBUTES	AVG. $\#$ OF AVG. LENGTH AVG. ATTRIBUTE- TO-QUERY RATIO
STRATEGYQA MUSIQUE PrivCP	2.18 2.82 2.52	1.74 2.72 6.75	40.88% 43.20% 73.80%

Table C.8: Statistics of private attributes on three datasets.

Avg. stands for average.

Generation Performance: The generation quality is evaluated with the following measures: i) BLEU [\[52\]](#page-24-5) between the generated psuedo sentence and a set of referenced replacements, ii) fluency score on a scale from 1 to 4, and iii) semantic similarity scores ranging from 0 to 1. Details on the computation of fluency and similarity scores are provided in Appendix [Appendix C.3.](#page-30-0)

We evaluate the generation performance on three language models in Table [C.9.](#page-32-0) It can be observed that while there is no significant variation of similarity score among models, Flan-T5-large has the best performance in terms of BLEU and fluency score.

	BLEU	SCORE	FLUENCY SIMILARITYY PARATEMETR SCORE	SIZE
BART-LARGE	0.345	2.9	0.53	406M
T5-LARGE	0.406	3.66	0.557	737M
FLAN-T5-LARGE	0.428	3.7	0.555	783M

Table C.9: Generation performance and parameter size of various language models.

Appendix C.5. Accuracy of Discriminator

We assess the reliability of the local discriminator with two metric: accuracy (ACC) and mean squared error (MSE). The discriminator is trained on 4000 samples and tested on 700 samples. To validate the capability of a GPT-4 scorer, we constructe 100 samples with manual labeling and obtain the performance of GPT-4 judger on this dataset. According to Table [C.10,](#page-32-1) the ACC of local discriminator is above 0.7 for a 4-label classification problem, with MSE approximately 16% of the total scale (0-3). The scores given by GPT-4 judger are also close to the human labels.

Table C.10: Accuracy and MSE for local discriminator and GPT-4 judger.

	Local discriminator		GPT-4 judger	
	ACC	${MSE}$	\vert ACC	MSE
Metrics 0.710		0.488	0.800	0.200

The local discriminator is tested on the validation data scored by GPT-4. GPT-4 Judger is evaluated against ground-truth data with manual label.