Sparse Recovery for Overcomplete Frames: Sensing Matrices and Recovery Guarantees

Xuemei Chen*, Christian Kümmerle[†], and Rongrong Wang[‡]

Abstract. Signal models formed as linear combinations of few atoms from an over-complete dictionary or few frame vectors from a redundant frame have become central to many applications in high dimensional signal processing and data analysis. A core question is, by exploiting the intrinsic low dimensional structure of the signal, how to design the sensing process and decoder in a way that the number of measurements is essentially close to the complexity of the signal set. This chapter provides a survey of important results in answering this question, with an emphasis on a basis pursuit like convex optimization decoder that admits a wide range of random sensing matrices. The results are quite established in the case signals are sparse in an orthonormal basis, while the case with frame sparse signals is much less explored. In addition to presenting the latest results on recovery guarantee and how few random heavier-tailed measurements fulfill these recovery guarantees, this chapter also aims to provide some insights in proof techniques. We also take the opportunity of this book chapter to publish an interesting result (Theorem 3.10) about a restricted isometry like property related to a frame.

I. Introduction. In the last two decades, the problem of recovering structured signals from significantly under-sampled linear measurements, often referred to as *compressed sensing* or *compressive sensing*, has been extensively studied by applied mathematicians, signal processing researchers, information theorists and statisticians since building on and extending the seminal works of Donoho, Candès, Romberg and Tao [26, 23, 42], which showed that a generic variant of the problem can be solved efficiently from a number of random linear measurements that is essentially linear in the dimension of the set of structured signals. The ensued line of research has led to the popularization of related data-efficient, optimization-based decoders in seismology and geophysics [82, 80, 102, 45, 66, 10], magnetic resonance tomography and medical imaging [83, 78, 69, 50, 43, 97, 3], and machine learning [108, 47, 84, 64, 93].

Formally, in this problem, we wish to recover $z_0 \in \mathbb{R}^d$ from its under-sampled and possibly corrupted linear measurement $y = Az_0 + w \in \mathbb{R}^m$ where *m* is typically much less than *d* and *w* represents the measurement corruption. Given that $A \in \mathbb{R}^{m \times d}$ is underdetermined, such recovery is only possible if we have more information about z_0 . Additionally, due to the unavoidable presence of noise *w*, we are interested in a recovery procedure which is able to identify z_0 up to an error that is proportional to a norm ||w|| of *w*.

While this problem is ill-posed without further assumption, in the general setting of compressed sensing, the problem is made well-posed by assuming that z_0 is an element of a set with an underlying low dimensional structure. Specifically, z_0 could be sparse in the standard basis (which means that the majority of its coordinates are zero), in an application-tailored orthogonal basis such as a suitable wavelet [83, 85] or shearlet basis [79], or be written as a linear combination of only a few atoms in a redundant dictionary [48, 96, 24, 86]. Similarly, z_0 can be a matrix of low rank, in which case the *A* corresponds to a linear operator acting on matrices. In this case, the problem is known under the name *low-rank matrix recovery* [39, 19, 32, 34], and has applications in recommender systems [75, 98], image processing [71, 103], computational physics [104, 25] and control theory [49, 46].

^{*}Department of Mathematics and Statistics, University of North Carolina Wilmington, 601 S. College Rd., Wilmington, NC 28403 (chenxuemei@uncw.edu).

[†]Department of Computer Science, The University of North Carolina at Charlotte, 9201 University City Blvd, Charlotte, NC 28223 (kuemmerle@charlotte.edu).

[‡]Department of Computational Mathematics, Science and Engineering and Department of Mathematics, Michigan State University, 426 Auditorium Rd., East Lansing, MI 48824 (wangron6@msu.edu).

The theoretical understanding of the compressed sensing problem and of the properties of suitable, efficient reconstruction algorithms has reached some maturity in the literature. We point to the monographs [55, 99, 120, 3] and references therein for an overview of known results. Conditions for low-rank matrix recovery using tractable algorithms have similarly been established in the last few years; for that problem, there are fewer comprehensive works covering the general theory, but [62, 31, 39, 19, 34] contain the majority of the most relevant results.

However, the vast majority of results for these problems study recovery guarantees if the signal z_0 is sparse or low-rank with respect to the standard basis or an orthogonal basis set. In many application domains, this assumption is too rigid to be satisfied, or better reconstruction can be achieved by considering sparsity of the signal with respect with to a transform domain, which is typically chosen using a certain degree of redundancy [47, 64, 84, 17]. Specifically, in this chapter, we present and review results on theoretical guarantees for parsimonious recovery problems under this more realistic modeling.

In particular, we will focus on the case where z_0 is sparse or approximately sparse in a dictionary or frame $F = \{f_1, f_2, \dots, f_n\}$.¹ In the finite dimensional setting we are considering, we can think of F as a spanning set of \mathbb{R}^d . Moreover, when appropriate, we will also use F for the matrix $F = [f_1, f_2, \dots, f_n] \in \mathbb{R}^{d \times n}$ collecting the frame elements of the frame. With this preparation, we can define, for a positive integer k representing a sparsity level, the set of F-k-sparse vectors $z \in \mathbb{R}^d$ as

(1.1)
$$\Sigma_{F,k} := \left\{ z \in \mathbb{R}^d : z = \sum_{i=1}^n x_i f_i = Fx, \|x\|_0 \le k \right\}$$

with $||x||_0$ denoting the number of non-zero entries of *x*.

For the compressed sensing problem of recovering vectors sparse with respect to a frame, the key questions have been focused on:

- Q1. Which tractable algorithm or decoder can be used to recover $z_0 \in \Sigma_{F,k}$, given access to *A* and $y = Az_0$?
- Q2. Given *F*, how to design the sensing matrix *A* so that the decoder found in Q1 is successful?
- Q3. For the design in Q2, what is the minimum number of measurements *m*?
- Q4. With the appropriately designed *A*, is the decoder found in Q1 stable and robust with respect to model misfit and additive noise?

In this chapter, we provide a short survey about relevant results addressing these questions. To quantify the model misfit with regards to the signal space (1.1), we define

(1.2)
$$\sigma_{F,k}(z) := \min_{v \in \Sigma_{F,k}} \|z - v\|_F,$$

the distance of z to the set of *F*-*k*-sparse vectors. Here the *F*-norm is defined using the ℓ_1 -norm

(1.3)
$$||z||_F := \min\{||x||_1 : Fx = z\},\$$

based on coefficients relative to the frame F.

To be more specific about Q4, we would like the decoder $\Delta : \mathbb{R}^m \to \mathbb{R}^d$ to perform relatively well even when the signals are not exactly *F*-*k*-sparse (meaning that $\sigma_{F,k}(z) > 0$; such a property is known as *stability* [55, Section 4.2]), and also under the presence of measurement noise *w* (this is known as *robustness* [55, Section 4.3]). Quantifying the latter

¹A set of vector $F = \{f_i\}_{i \in I}$ is a *frame* for a Hilbert space H if there exists $0 < A \le B < \infty$ such that $A||x||^2 \le \sum_{i \in I} |\langle x, f_i \rangle|^2 \le B||x||^2$ for all $x \in H$.

using a suitable norm ||w|| on w, it is desirable to obtain a stable and robust recovery guarantee such that there exist constants C_1 , C_2 depending on A and possibly the dimensions which allow the inequality

(1.4)
$$||z - \Delta(Az + w)|| \le C_1 \sigma_{F,k}(z) + C_2 ||w||,$$

to hold for all $z \in \mathbb{R}^d$.

Regarding QI, as common in the compressed sensing literature, we distinguish two types of efficient decoders: iterative solvers such as greedy methods [59, 110] or thresholding based methods [94] (among which compressive sampling matching pursuit [38, 58] and iterative hard thresholding [52] are some of the most well-known examples) and decoders based on the solution of an optimization problem.

Due to their popularity in imaging problems [3] and the maturity of their theory, we will focus on optimization-based decoders defined as the solution of optimization problems of the form

(1.5)
$$\Delta_{f,A,\eta}(y) := \operatorname*{argmin}_{z \in \mathbb{R}^d} f(z) \quad \text{subject to} \quad ||Az - y||_2 \le \eta,$$

where $f : \mathbb{R}^d \to \mathbb{R}$ is a suitable objective function [22, 37, 55, 4, 86]. It is understood that the objective function f needs to be selected in a way that is simultaneously sparsity-promoting, can be evaluated efficiently, and also such that the respective optimization problem of (1.5) is easy or at least tractable to solve. While non-convex choices of f [53, 101, 116, 4, 121], [120, Chapter 7] often lead to improved performance compared to convex sparsity-promoting functions, choosing f as a convex function has the advantage that properties of the solution of (1.5) can be decoupled from the particular solver to be used and that they can be analyzed using mature tools from convex optimization [55, 3].

For the frame-based recovery problem (1.1), the convex *F*-norm $f(z) = ||z||_F$ of (1.3) happens to be a suitable objective function, in which case the decoder (1.5) is denoted as

(1.6)
$$\Delta_{F,A,\eta}(y) = \operatorname*{argmin}_{z \in \mathbb{R}^d} \|z\|_F \quad \text{subject to} \quad \|Az - y\|_2 \le \eta.$$

Notations and Organization. For an integer *N*, we let [*N*] be the index set $\{1, 2, \dots, N\}$. For a vector *x*, $||x||_p = (\sum |x_i|^p)^{1/p}$ is its *p*-norm. If *T* is an index set, then x_T is the vector that has the same value as *x* on *T* and 0 elsewhere. For a matrix *A*, ker(*A*) is the kernel (null space) of *A*, and $||A||_2$ is its spectral norm. I_N is the $N \times N$ identity matrix.

The rest of the chapter is organized as follows. Section 2 provides recovery guarantees of the ℓ_1 minimization problem for recovering vectors sparse in an orthonormal basis under various conditions, as listed in Definition 2.1, on the sensing matrix *A*. We make a comparison among these conditions towards the end. Section 3 explores recovery guarantees of (1.6), i.e., the ℓ_1 synthesis method with the general frame *F*. Our attention focuses on the null space property like conditions for the sensing matrix *A*. The ℓ_1 analysis method is also touched upon as a related model. Section 4 focuses on how random sensing matrices fulfill the conditions laid out in Definition 2.1 or Definition 3.1. Sub-Gaussian matrices have been typical in this regard while we also provide a wider range of random measurements with heavier-tail behavior than sub-Gaussian.

2. Recovery Guarantees for Signals with Sparsity in Orthonormal Basis. We first present relevant results for the case that the frame matrix F is the identity matrix, which corresponds to the setup of the initial works of compressed sensing theory [26, 23, 42, 37, 55]. In this case, (1.6) becomes

(2.1)
$$\Delta_{1,A,\eta}(y) \coloneqq \Delta_{I_d,A,\eta}(y) = \operatorname*{argmin}_{z \in \mathbb{R}^d : ||Az-y||_2 \le \eta} ||z||_1,$$

which is also known by the name of *quadratically constrained basis pursuit* [26, 14, 3], and for $\eta = 0$, it can be simplified to the equality-constrained *basis pursuit* [28, 55] decoder

(2.2)
$$\Delta_{1,A,0}(y) = \operatorname{argmin}_{z} ||z||_{1} \text{ subject to } Az = y.$$

Equality-constrained *basis pursuit* is a suitable decoder in the case of a non-existent or small noise level, or in the case of unknown noise level [117, 51, 14].

Suitable recovery guarantees for (2.1) and (2.2) can in most cases easily be extended to $\Delta_{F,A,\eta}(y)$ or $\Delta_{F,A,0}(y)$ and a signal model in which *F* is not the identity, but an orthonormal basis, by incorporating *F* into the measurement matrix *A* as $\Delta_{I_d,AF,\eta}(y)$. We shorten the notation to $\Sigma_k = \Sigma_{I_d,k}$ and $\sigma_k(z) = \sigma_{I_d,k}(z)$ for this section.

To answer Q₂, a series of properties on the sensing matrix have been proposed over the years, the most relevant of which we list below. These properties can be used to characterize the performance of the decoders $\Delta_{1,A,\eta}$ for problems involving such sensing matrices.

Definition 2.1. Let $A \in \mathbb{R}^{m \times d}$.

1. *A* is said to have the *null space property* of order k [44, 61, 37] if

(NSP-k)
$$||z_T||_1 < ||z_{T^c}||_1, \quad \forall z \in \ker(A) \setminus \{0\}, \forall T \text{ with } |T| \le k.$$

2. *A* is said to satisfy the *restricted isometry property* [23] of order *k* with constant $0 \le \delta < 1$ if

(RIP-(k,
$$\delta$$
)) $(1-\delta)||z||_2^2 \le ||Az||_2^2 \le (1+\delta)||z||_2^2, \quad \forall z \in \Sigma_k.$

3. If *A* has ℓ_2 -normalized columns a_1, a_2, \dots, a_d , then the *coherence* of *A* [111] is defined as

(2.3)
$$\mu(A) := \max_{i \neq j} |\langle a_i, a_j \rangle|.$$

4. *A* is said to have the ℓ_q -robust null space property of order *k* with $\rho > 0, \tau > 0$ [51] if

$$(\text{RNSP-}(q,k,\rho,\tau)) ||z_T||_q \le \frac{\rho}{k^{1-1/q}} ||z_{T^c}||_1 + \tau ||Az||_2, \forall z \in \mathbb{R}^d, \forall T \text{ with } |T| \le k.$$

5. *A* is said to have the *quotient property* [117, 51] with constant $\alpha > 0$ if

$$(\text{QP-}\alpha) \qquad \qquad \|y\|_A \le \alpha \sqrt{k_*} \|y\|_2, \forall y \in \mathbb{R}^m,$$

where $k^* = m/\log(ed/m)$.

6. *A* is said to satisfy the *robust width property* of order *k* with constants c_0, c_1 [16] if

(RWP-
$$(k, c_0, c_1)$$
) $||z||_2 \le \frac{c_0}{\sqrt{k}} ||z||_1, \forall z \in \mathbb{R}^d \text{ such that } ||Az||_2 < c_1 ||z||_2.$

Given the definition (1.3), the quotient property with constant α (QP- α) holds if and only if for any $y \in \mathbb{R}^m$, there exists $z \in \mathbb{R}^d$ such that Az = y and $||z||_1 \le \alpha \sqrt{k_*} ||y||_2$. (QP- α) can be also interpreted as a geometric property [60, 63] stating that the ℓ_2 -ball B_2^d is contained in an appropriately scaled centrally symmetric polytope spanend by the columns of A = $[a_1, a_2, \ldots, a_d]$, which can be written as $B_2^d \subseteq \alpha \sqrt{k_*}A(B_1^m)$ if $A(B_1^m)$ is the image of the ℓ_1 -ball B_1^m with respect to A. The *width property*, proposed in [72], is a weaker version of (RWP- (k, c_0, c_1)) and closely related to the null space property (NSP-k).

We sample some important results affirmatively answering Q4 for suitable parameter choices.

Theorem 2.2 ([20]). If A satisfies the RIP- $(2k, \delta)$ with $\delta < 1/\sqrt{2}$, then there exists constants $D_1, D_2 > 0$ such that

(2.4)
$$||z - \Delta_{1,A,\eta} (Az + w)||_2 \le D_1 \frac{\sigma_k(z)}{\sqrt{k}} + D_2 \eta$$

for all $z \in \mathbb{R}^d$ and $w \in \mathbb{R}^m$ with $||w||_2 \leq \eta$. Both D_1, D_2 only depend on δ .

Inequality (2.4) provided by Theorem 2.2 provides a stable and robust recovery guarantee for the decoder $\Delta_{1,A,\eta}$ as outlined in (1.4) in the case that *A* satisfies an RIP of order 2*k* and if the noise ℓ_2 -norm satisfies $||w||_2 \le \eta$.

Theorem 2.3 ([44, 61]). $\Delta_{1,A,0}(Az) = z$ for any $z \in \Sigma_k$ if and only if A satisfies (NSP-k).

Theorem 2.3 provides a sharp characterization of the success of the basis pursuit decoder $\Delta_{1,A,0}$ in absence of additive noise *w* for exactly *k*-sparse coefficient vectors *z*.

Theorem 2.4 ([61]). If A has ℓ_2 -normalized columns and its coherence $\mu(A)$ (see (2.3)) satisfies $\mu(A) < \frac{1}{2k-1}$, then $\Delta_{1,A,0}(Az) = z$ for any $z \in \Sigma_k$.

While the coherence assumption of Theorem 2.4 is strictly stronger than the NSP assumption (NSP-*k*), the latter is NP-hard to certify computationally given a matrix *A* [109], whereas $\mu(A)$ can be computed easily.

With the generalizations (RNSP- (q, k, ρ, τ)) of the null space property (NSP-k), it is possible to obtain robust recovery guarantees of the type (1.4) as well:

Theorem 2.5 ([51, Theorem 5]). Given $q \ge 1$, if $A \in \mathbb{R}^{m \times d}$ satisfies (RNSP- (q, k, ρ, τ)) with $0 < \rho < 1$, then for all $z \in \mathbb{R}^d$ and $w \in \mathbb{R}^m$ with $||w||_2 \le \eta$,

(2.5)
$$\|z - \Delta_{1,A,\eta} (Az + w)\|_1 \le \frac{2(1+\rho)}{1-\rho} \sigma_k(z) + \frac{2\tau}{1-\rho} k^{1-\frac{1}{q}} \eta,$$

and

(2.6)
$$\|z - \Delta_{1,A,\eta} (Az + w)\|_{p} \leq \frac{2(1+\rho)^{2}}{1-\rho} \frac{\sigma_{k}(z)}{k^{1-1/p}} + \frac{3+\rho}{1-\rho} \tau k^{\frac{1}{p}-\frac{1}{q}} \eta$$

for 1 .

Similar results can be obtained via robust width properties (RWP- (k, c_0, c_1)) of A.

Theorem 2.6 ([16, Theorem 3]). If A satisfies (RWP- (k, c_0, c_1)), then

(2.7)
$$||z - \Delta_{1,A,\eta} (Az + w)||_2 \le 4c_0 \frac{\sigma_k(z)}{\sqrt{k}} + \frac{2}{c_1} \eta.$$

for all $z \in \mathbb{R}^d$ and $w \in \mathbb{R}^m$ with $||w||_2 \leq \eta$.

Unlike the other properties defined in Definition 2.1, the quotient property (QP- α) alone does not provide any recovery guarantees for compressed sensing decoders. However, if the sensing matrix satisfies (QP- α) in addition to another property which guarantees recovery under noiseless measurements, it can be shown that equality-constrained basis pursuit $\Delta_{1,A,0}$ of (2.2) is likewise a noise-robust decoder, see [117], [51, Section 11.2].

More specifically, $y = Az_0 + w$ can be seen as a perturbed version of the true measurement. We note that the programs $\Delta_{1,A,\eta}$ or $\Delta_{f,A,\eta}$ from (2.1) and (1.5) need the noise strength level η as an input parameter, which may not be accessible in many applications. The advantage of $\Delta_{1,A,0}$ or $\Delta_{f,A,0}$ is that they amount to a noise-blind method, where robust reconstruction can still be obtained with reasonable sensing matrices. We will cite a result from [51]. Theorem 2.7 ([51, Theorem 11]). If $A \in \mathbb{R}^{m \times d}$ satisfies $RNSP(q, k, \rho, \tau k_*^{1/q-1/2})$ with $k \leq ck_*$ and (QP- α), then for any $1 \leq p \leq q$,

(2.8)
$$\|z - \Delta_{1,A,0}(Az + w)\|_{p} \le C \frac{\sigma_{k}(z)}{k^{1-1/p}} + Dk_{*}^{\frac{1}{p} - \frac{1}{2}} \|w\|_{2}$$

for all $z \in \mathbb{R}^d$ and $w \in \mathbb{R}^m$. The constants C, D > 0 depend only on ρ, τ, α, c .

The restricted isometry property (RIP- (k,δ)) is considered as the strongest one among the sparse recovery inducing properties of Definition 2.1. They are related to each other as follows.

- RIP implies RNSP. It is stated in [55, Theorem 6.13] that if A satisfies RIP- $(2k, \delta)$, then A satisfies the RNSP- $(2, k, \rho, \tau)$ with $\rho = \frac{\delta}{\sqrt{1-\delta^2}-\delta/4}$ and $\tau = \frac{\sqrt{1+\delta}}{\sqrt{1-\delta^2}-\delta/4}$. If $\delta < \frac{4}{\sqrt{41}} \approx 0.6246$, then it holds that $\rho < 1$, which is necessary for making the robust guarantees (2.6) work.²
- RNSP implies RWP. Theorem 2.6 also goes the other direction. That is, if for all $z \in \mathbb{R}^d$ and $w \in \mathbb{R}^m$ with $||w||_2 \le \eta$, it holds $||z - \Delta_{1,A,\eta}(Az + w)||_2 \le C_1 \frac{\sigma_k(z)}{\sqrt{k}} + C_2\eta$, then *A* must satisfy RWP- $(k, 2C_0, \frac{1}{2C_1})$. Therefore with Theorem 2.5, we see RNSP- $(2, k, \rho, \tau)$ implies RWP of order *k* with constants derived from (2.6).
- (NSP-*k*) is the weakest of all due to Theorem 2.3. Moreover, only the NSP is a property which solely depends on the kernel of *A*. In order to have a fair comparison between the reconstruction performance of, say RIP, and NSP, we need to consider sensing matrices that have the same null space as some RIP matrix. See [15] for more details.
- QP does not imply RIP, nor vice versa [117].

NSP is sensitive to column scaling, as shown below.

Lemma 2.8. If *B* satisfies (NSP-k), then there exists a diagonal matrix *D* such that *BD* does not satisfy (NSP-k).

Proof. Fix $v \in \ker(B) \setminus \{0\}$ and choose |T| = k, such that $0 < ||v_T||_1 < ||v_{T^c}||_1$. Let $(\operatorname{diag}(D))_T = \frac{||v_T||_1}{||v_{T^c}||_{1+1}}$ and $(\operatorname{diag}(D))_{T^c} = 1$.

Define w such that $w_T = \frac{\|v_{T^c}\| + 1}{\|v_T\|_1} v_T$ and $w_{T^c} = v_{T^c}$. Clearly $w \in \ker(BD) \setminus \{0\}$, but $\|w_T\|_1 = \|v_{T^c}\|_1 + 1 > \|v_{T^c}\|_1 = \|w_{T^c}\|_1$. This concludes that BD does not satisfy (NSP-k).

3. Recovery Guarantees for Sparse Signal With Respect to a Frame. It can be proven [81, 30] that (1.6) is equivalent to the so called ℓ_1 -synthesis method:

(3.1)
$$\Delta_{F,A,\eta}(y) := F(\Delta_{1,AF,\eta}(y)) = F(\operatorname{argmin}_{x} ||x||_{1}, \text{ subject to } ||AFx - y||_{2} \le \eta).$$

The idea is that given $y \approx Az_0$, we first use $\Delta_{1,AF,\eta}(y)$ to recover a (hopefully sparse) coefficient of z_0 . We then recover the original signal by applying the synthesis operator *F* to the coefficient.

Recalling (1.2), let

and therefore $\sigma_{F,k}(z) = ||z - z_k||_F$.

Definition 3.1. Fix a frame $F \in \mathbb{R}^{d \times n}$. Let $A \in \mathbb{R}^{m \times d}$.

1. *A* is said to have the *F* null space property of order *k* [30, 29] if

$$(F-\text{NSP-}k) \qquad \qquad \|v\|_F < \|z - v\|_F, \ \forall z \in \ker(A) \setminus \{0\}, \ \forall v \in \Sigma_{F,k}$$

²We note that the stable and robust guarantee (2.6) with p = 2 for $\Delta_{1,A,\eta}$ is implied by the RIP-(2 k, δ) even for the weaker (and optimal) assumption $\delta < \sqrt{2}/2 \approx 0.7071$ on δ , as shown in [21, Theorem 2.1].

2. *A* is said to have the *robust F null space property* of order *k* [29] if there exist constants $\tau > 0$ and $0 < \rho < 1$ such that

$$(F-\text{RNSP-}(k,\rho,\tau)) \qquad \qquad \|z_k\|_F \le \rho \|z-z_k\|_F + \tau \|Az\|_2, \ \forall z \in \mathbb{R}^d.$$

3. *A* is said to have the *strong F null space property* of order *k* with constant c > 0 [30, 29] if

$$(F-\text{SNSP-}(k,c)) \qquad \qquad \|z-v\|_F - \|v\|_F \ge c\|z\|_2, \ \forall z \in \ker(A), \forall v \in \Sigma_{F,k}.$$

4. *A* is said to have the *F* restricted isometry property of order *k* with constant $0 \le \delta < 1$ [24] if

~

$$(F-\text{RIP-}(k,\delta)) \qquad (1-\delta)\|z\|_2^2 \le \|Az\|_2^2 \le (1+\delta)\|z\|_2^2, \ \forall x \in \Sigma_{F,k}.$$

Remark 3.2. An equivalent, but less intuitive version of (F-NSP-k) can be found in [30, Definition 4.1]. Similarly, an equivalent definition of (F-SNSP-(k, c)) can be found in [30, Definition 5.1].

Remark 3.3. By definition, *F*-SNSP-(k, c) implies *F*-NSP-k. A remarkable result [30, Theorem 5.5] states that *F*-NSP-k implies *F*-SNSP-(k, c) for some c > 0.

Remark 3.4. [30, Theorem 7.2] states that the following three conditions are equivalent if *F* is *full spark* (every *d* columns of *F* are linearly independent) [6]:

(i) *A* has *F*-NSP-*k*.
(ii) *A* has *F*-SNSP-(*k*, *c*) for some *c* > 0.
(iii) *AF* has NSP-*k*.

Theorem 3.5 ([30, 29]). $\Delta_{F,A,0}(Az) = z$ for any $z \in \Sigma_{F,k}$ if and only if A satisfies F-NSP-k.

Theorem 3.5 is analogous to Theorem 2.3. For a result such as Theorem 2.5, we need the frame F to be somewhat regular in the following way:

Definition 3.6 ([29, Definition 2.5]). We call *F s*-splittable with constant $\beta > 0$ if for any $x, y \in \mathbb{R}^d$,

$$(3.3) ||x+y||_F \ge ||x_s||_F - ||y_s||_F + \beta(||y-y_s||_F - ||x-x_s||_F).$$

Requiring *F* to be regular in the above way is not surprising as the unit ball of *F*-norm (1.3) is the convex hull of columns in *F* (together with its negatives). In the case where *F* is the canonical basis, we have $\beta = 1$, which is the optimal value. We conjecture that all full-spark frames are splittable with small enough β , and it would be interesting work to estimate β based on certain frame properties of *F*.

Theorem 3.7 ([29, Corollary 5.3]). Let *F* be *s*-splittable with constant β and *A* has *F*-RNSP- (k, ρ, τ) with $\rho < \beta$, then for any $z \in \mathbb{R}^d$ and $||w||_2 \le \eta$, we have

$$\|z - \Delta_{F,A,\eta} (Az + w)\|_F \le \frac{(1+\beta)(1+\rho)}{\beta(\beta-\rho)} \sigma_{F,s}(z) + \frac{2\tau(1+\beta)}{\beta-\rho} \eta.$$

The above theorem is a generalization of (2.5) in Theorem 2.5 (with q = 1). It remains to be future work to establish a performance guarantee like (2.6), which should involve a modified version of *F*-RNSP-(k, ρ, τ).

Theorem 3.8 ([29, Corollary 5.4]). If A has F-SNSP-(k, c), then for any $z \in \mathbb{R}^d$ and $||w||_2 \leq \eta$, we have

(3.4)
$$||z - \Delta_{F,A,\eta} (Az + w)||_2 \le \frac{2}{\nu_A} \left(\frac{\sqrt{n}}{c} + 1\right) \eta + \frac{2}{c} \sigma_{F,k}(z),$$

where v_A is the smallest nonzero singular value of A.

By Remark 3.3, *F*-SNSP-(*k*, *c*) is a minimal condition, which partially explains the weaker performance guarantee than that of Theorem 3.7 due to the growth term \sqrt{n} in (3.4).

It is yet to be researched how the equality-constrained decoder $\Delta_{F,A,0}$ behaves under reasonable conditions on *A*. As mentioned previously, a result similar to Theorem 2.7 is beneficial when noise-level η is unknown.

Analysis Sparsity Models. Another popular optimization method in the form of (1.5) is the ℓ_1 -analysis method:

(3.5)
$$\operatorname{argmin}_{z} \|Gz\|_{1}, \text{ subject to } \|Az - y\|_{2} \le \eta,$$

where *G* is sparsifying transformation such that Gz is sparse. Note that this is not necessarily in the general framework (1.1), but is a relevant model with wide applications, such as finite difference and wavelet transform for imaging problems [78]. In particular, if *F* is a Parseval frame, then $G = F^T$ is a popular choice [24, 5], and we denote it by

(3.6)
$$\Lambda_{F,A,\eta}(y) := \operatorname{argmin}_{z} \|F^{T}z\|_{1}, \quad \text{subject to } \|Az - y\|_{2} \le \eta.$$

Theorem 3.9 ([24, Theorem 1.4]). Let F be Parseval³. If A satisfies F-RIP- $(2k, \delta)$ with $\delta < 0.08$, then

(3.7)
$$||z - \Lambda_{F,A,\eta}(Az + w)||_2 \le D_1 \frac{\sigma_k(F^T z)}{\sqrt{k}} + D_2 \eta$$

for all $z \in \mathbb{R}^d$ and $w \in \mathbb{R}^m$ with $||w||_2 \leq \eta$. Both D_1, D_2 only depend on δ .

An interesting phenomenon with Theorem 3.9 is that there is a mismatch between signal model and sensing matrix requirement. The condition F-RIP- (k, δ) requires A to act as a near isometry on $\Sigma_{F,s}$, so one hopes that with appropriately chosen s and δ , F-RIP- (k, δ) is able to provide a performance guarantee in the form of (1.4). However, (3.7) only guarantees the stable recovery of analysis sparse signals. It has been a long standing question whether F-RIP- (k, δ) is able to guarantee the performance of the ℓ_1 -synthesis method (3.1). We answer this question negatively in this book chapter, and it is essentially due to the lack of involvement of some F-related-norm in the inequality F-RIP- (k, δ) .

Let us make things simpler for a moment and let F = D be an $d \times d$ invertible diagonal matrix. In this case, $\Sigma_{D,k} = \Sigma_k$, which means RIP-(k, δ) is equivalent to D-RIP-(k, δ). However, the ℓ_1 -synthesis method is highly sensitive to D, even when reduced to a diagonal matrix. To be precise, we have $\Delta_{D,A,\eta}(y) = \Delta_{1,AD,\eta}(y)$, whose success of recovering all signals in Σ_k requires AD to satisfy NSP-k by Theorem 2.3, but this cannot be true for all D by Lemma 2.8.

The above argument can be generalized to full spark frame F as shown below.

Theorem 3.10. Assume F is of full spark, then A satisfying F-RIP- $(2k, \delta)$ does not guarantee the exact recovery of all F-sparse signals through the ℓ_1 -synthesis method $\Delta_{F,A,0}$, regardless of how small δ is.

Proof. Fix a non-singular diagonal matrix *D*. If *A* satisfying *F*-RIP- $(2k, \delta)$ does guarantee $\Delta_{F,A,0}(Az_0) = z_0$ for all $z_0 \in \Sigma_{F,k}$, then *A* satisfying *FD*-RIP- $(2k, \delta)$ also guarantees $\Delta_{FD,A,0}(Az_0) = z_0$ for all $z_0 \in \Sigma_{FD,k} = \Sigma_{F,k}$, which is equivalent to *A* satisfying *FD*-NSP-*k* by Theorem 3.5, and further equivalent to *AFD* satisfying NSP-*k* by Remark 3.4.

However, by Lemma 2.8, we can pick *D* such that *AFD* does not satisfy NSP-*k*, which is a contradiction.

 $^{{}^{3}}FF^{T} = I$

4. Sensing Matrix Design. After having characterized abstract conditions for which ℓ_1 synthesis decoders are able to robustly identify *F*-*k*-sparse vectors from undersampled measurements in Section 3, we address now the question which particular sensing matrices *A* are
suitable and satisfy conditions as laid out in Definition 2.1 or Definition 3.1. Apart from the
choice of the sensing matrix (question Q2), we are also shedding light on the minimum number *m* of rows of *A* (number of measurements) that is sufficient to enable successful recovery.
In particular, we seek to find desirable *A* with *m* being as small as possible, while fixing *n*,
the number of frame vectors, *d*, the ambient signal dimension, and *k*, the sparsity level.

4.1. Sensing Matrices for Identity Matrix *F*. A core theme in the theory of compressed sensing problems has been the fact that in order to obtain recovery guarantees that hold uniformly across all signals in the desired sparse signal set such as $\Sigma_{F,k}$ while at the same time keeping the number of measurements *m* close to the complexity of the signal set, random matrix ensembles are more suitable than deterministic designs for *A*. In this section, we present some key results that apply in the standard compressed sensing setting where the frame matrix is the identity matrix such that $F = I_d$.

While deterministically designed sensing matrices can achieve empirical performance on par with the one of ideal random designs based on Gaussian sensing matrices [92], it has been notoriously hard to obtain deterministic sensing matrices with *m* rows that are able to reconstruct *k*-sparse signals in a setting where *m* depends almost linearly on *k*. The best known results for deterministically constructed sensing matrices requires *A* to have $m = O(k^2)$ rows using coherence-based analysis [13] or $m = (k^{2-\epsilon})$ rows for some $\epsilon > 0$ using a RIP-based analysis [12]. In the latter case, however, we also require the sensing matrix to be almost square such that $d^{1-\epsilon} \leq m$. We refer to [8, 36, 7], [115, Chapter 5] for an overview for proof techniques and open questions.

On the other hand, allowing for random designs of *A*, we can achieve much better results such that already $m = O(k \log(d/k))$ measurements are sufficient for robust and stable recovery, if entries, rows, or columns of *A* are drawn independently from some suitable distributions. Key results for different distributional assumptions have been obtained in [42, 23, 26, 9, 90, 73, 51, 88, 89, 1], the implications of which we report below. The order $\Omega(k \log(d/k))$ is known to be necessary, as shown by [54], [55, Chapter 10], cf. Theorem 4.3 below.

Sub-Gaussian Measurements. The most well-studied class of random matrices suitable for compressed sensing, which also includes matrices with Gaussian i.i.d. entries, are sub-Gaussian sensing matrices [90] with rows or columns that are independent sub-Gaussian random vectors, which can be defined as follows.

Definition 4.1 ([112, 114]). A random vector ϕ is called a *sub-Gaussian vector* with parameter σ if there exists a constant $\sigma > 0$ such that

$$\Pr\left(|\langle \phi, z \rangle| \ge t\right) \le 2\exp(-t^2/(2\sigma^2))$$

for each $t \ge 0$ and for every ℓ_2 -unit norm vector z.

Furthermore, we call a random vector *centered* if $\mathbb{E}[\phi] = 0$, and we call it *isotropic* if $\mathbb{E}[\phi\phi^{\top}] = I$ where *I* is the identity matrix [114, Definition 3.2.1].

Theorem 4.2 ([113, Theorem 5.65],[55, Theorem 9.2]). Let A be an $(m \times d)$ matrix with independent sub-Gaussian rows or sub-Gaussian columns ϕ (in the latter case, we further assume that $\|\phi\|_2 = \sqrt{m}$ almost surely) of parameter σ . Then there exist constants C, c > 0, depending only on σ from Definition 4.1, such that $\frac{1}{\sqrt{m}}A$ satisfies RIP- (k,δ) with probability at least $1 - 2\exp(-cm\delta^2)$ provided that

$$m \ge C\delta^{-2}k\log(ed/k)$$

Combined with Theorem 2.2, Theorem 4.2 implies that a sub-Gaussian matrix, with *m* at least on the order of $k \log(d/k)$, with large probability, allows ℓ_1 -minimization $\Delta_{1,A,\eta}$ to recover nearly sparse signals stably and robustly. Conversely, $m = O(k \log(d/k))$ is also needed for any decoder to recover nearly sparse signals, as seen in Theorem 4.3, which can be shown using results about Gelfand widths of ℓ_1 -balls [57, 54].

Theorem 4.3 ([55, Proposition 10.7]). Let $1 . Suppose that there exist a matrix <math>A \in \mathbb{R}^{m \times d}$ and a decoder Δ such that for any $z \in \mathbb{R}^d$,

$$\|z - \Delta(Az)\|_p \le \frac{C}{k^{1-1/p}} \sigma_k(z),$$

then $m \ge c_1 k \log(ed/k)$ for some $c_1, c_2 > 0$ only depending on C.

The methodology for proving Theorem 4.2 for independent rows has been developed in [90] using a concentration inequality for sub-Gaussian vectors. For the case of independent sub-Gaussian columns, it is convenient to use extremal singular value estimates [113, Theorem 5.65] and for the special case when *A* is Gaussian, results with sharper bounds can be obtained in this manner [23].

Apart from Gaussians, the class of sub-Gaussian distributions of Definition 4.1 includes also random vectors defined via independent Bernoulli entries, bounded entries or random vectors uniformly distributed on a unit sphere.

Given Theorem 2.5, the optimal number of measurements can also be achieved by proving that sub-Gaussian matrices satisfy a robust null space property such as RNSP- (q, k, ρ, τ) . In fact, this can be considered as a superior route because the robust NSP is weaker than the RIP for the same sparsity level k, and hence possibly admits a broader class of random matrices.

Heavy-Tailed Measurements. For designing sensing matrices based on random designs, it is a natural question to ask what the weakest possible assumption on the distribution of the random vector ϕ contained in its rows are. Using properties such as NSP-k and RNSP- (q, k, ρ, τ) , it has been possible to show that heavier-tailed matrices with just sub-exponential, but not sub-Gaussian tail decay exhibit similar guarantees as sub-Gaussian sensing matrices, despite the fact that they cannot satisfy a RIP- (k, δ) unless their number of rows scales as $m = \Omega(k \log^2(ed/k))$ [2]. A noticeable example for such is matrices with i.i.d. entries that follow a Weibull distribution with scale parameters between $1 \le r \le 2$ (which include the Laplace distribution as a special case) and which is sub-exponential [51]. It has been shown that for such matrices, the RNSP of order k holds with large probability with $m = O(k \log(ed/k))$ [51], making such matrices candidates for optimal performance of the decoder $\Delta_{1,A,\eta}$. For exact recovery, i.e., the NSP-k of A is satisfied, it was shown in [73, Theorem 7.3] that $m = O(k \log(ed/k))$ measurements of a random ensemble defined from vectors distributed as other sub-exponential distributions (including log-concave distributions) are sufficient.

Optimal compressed sensing recovery guarantees for heavy-tailed distributions were subsequently developed and generalized [89, 40, 1] using the small-ball method (due to Shahar Mendelson and Vladimir Koltchinskii [87, 74, 88]) based on the observation [89, Theorem B] that while the lower inequality in the property RIP-(k, δ) is easily fulfilled for heavy-tailed distribution satisfying a non-degeneracy assumption stating that not the entire distributional mass is located around the origin, it is sufficient to satisfy the upper RIP-inequality for 1-sparse vectors.

Instead of sub-Gaussianity, we state below two weaker assumptions that still enable respective sensing matrices to achieve stable and robust recovery from a minimal amount of measurements via $\Delta_{1,A,\eta}$.

Definition 4.4 (Distributions satisfying small-ball assumption, [89, Definition 1.4], [40, Inequality (9)], [1]). We say the distribution of a random vector $\phi \in \mathbb{R}^d$ satisfies a small-ball assumption on the set $S \subset \mathbb{R}^d$ with constants u, c > 0 if

$$\inf_{x \in S} \Pr(|\langle \phi, x \rangle| \ge u) \ge c.$$

Definition 4.5 (Distributions with *K* well-behaved entrywise moments, [89, Theorem A(1)], [40, Inequality (12)], [1, Assumption 3]). We say the distribution of a random vector $\phi = (\phi_1, \ldots, \phi_d) \in \mathbb{R}^d$ has *K* well-behaved entrywise moments with constants $\alpha \ge 1/2$ and $\lambda > 0$ if for each $i = 1, \ldots, d$ and for all $2 \le p \le K$,

$$\|\phi_i\|_{L^p} \le \lambda p^{\alpha}.$$

For a random variable *X*, we define $||X||_{L^p} := \mathbb{E}(|X|^p)^{1/p}$. For sensing matrices *A* with independent rows that are centered and satisfy Definition 4.4 and Definition 4.5, we state below the result with the weakest known distributional assumptions that still lead to robust recovery via $\Delta_{1,A,\eta}$ in the optimal measurement regime. We refer to [55, Section 7.2] for results quantifying the distributional tail decay based on moment bounds such as (4.1).

Theorem 4.6 ([1, Variation on Theorem 4.1]). Let a_i/\sqrt{m} , $i \in [m]$ be independent rows of the measurement matrix A drawn from centered distributions satisfying Definition 4.4 on the set

$$S_{k,\rho}^{2} := \left\{ v \in \mathbb{R}^{d} : \exists T \subset [d] \text{ with } |T| = k \text{ such that } \|v_{T}\|_{2} \ge \frac{\rho}{\sqrt{k}} \|v_{T^{c}}\|_{1} \right\} \cap \mathbb{S}_{\ell_{2}}^{d-1}$$

with constants u, c > 0 and Definition 4.5 with constants $K = \log(ed/k)$, c > 0 and $\alpha \ge 1/2$ and $\lambda > 0$, respectively. Then as long as the number of measurements *m* satisfies

(4.2)
$$m \gtrsim \max\left\{k \log(ed/k), \log^{\max\{2\alpha-1,1\}}(ed/k)\right\},$$

it holds that with probability of at least $1 - e^{-\Omega(m)}$, the decoder $\Delta_{1,A,\eta}$ provides stable and robust recovery of all $z \in \mathbb{R}^d$ from y = Az + w with $||w||_2 \le \eta$ such that

(4.3)
$$\|z - \Delta_{1,A,\eta} (Az + w)\|_p \le C \frac{\sigma_s(z)}{k^{1-1/p}} + Dk^{\frac{1}{p} - \frac{1}{2}} \eta,$$

for each $1 \le p \le 2$, where the constants C, D > 0 only depend on u, c, α and λ .

The recovery guarantee (4.3) matches the RIP-based ones and the best known one of (2.6), and its proof can be written by establishing a RNSP-(2, k, ρ , τ) with high probability, combined with Theorem 2.5. We refer to Subsection 4.3 for a proof sketch.

The assumption on a bound of only $\log(ed/k)$ leading moments in Theorem 4.6 is weaker than the ones of the similar results [40, Corollary 8] and [89, Theorem A] (in the latter case, with a little caveat): Corollary 8 of [40] required *independence* of the coordinates ϕ_1, \ldots, ϕ_d of the random vector ϕ constituting the rows of the sensing matrix, and furthermore, requires $K = \log(d)$ moments with the growth condition (4.1) instead of $\log(ed/k)$, as well as the small-ball condition of Definition 4.4 on the entire ℓ_2 -sphere $\mathbb{S}_{\ell_2}^{d-1}$ instead of only on $S_{k,\rho}^2$ ⁴. Furthermore, Theorem 4.6 has the smaller exponent of $2\alpha - 1$ instead of $4\beta - 1$ in [89, Theorem A] in the measurement bound (4.2), and also requires $O(\log(d))$ well-behaved moments; the small-ball condition of [89, Theorem A] is, on the other hand, weaker than the

⁴On the other hand, a close inspection of their proof technique shows that a restriction to $S_{k,\rho}^2$ would also work.

one of Theorem 4.6 as Definition 4.4 is only required on the set $\{z \in \mathbb{R}^d : ||z||_0 \le k\} \cap \mathbb{S}_{\ell_2}^{d-1}$, which is a subset of $S_{k,\rho}^2$.

We note that a small-ball assumption as in Definition 4.4 is rarely restrictive: It essentially means that not too much probability mass is assigned to 0 in the distributional marginals defined by the set *S*, and can be derived from weak moment bounds in marginal direction such as $\|\langle \phi, t \rangle\|_{L^{2+\epsilon}} \leq \kappa \|\langle \phi, t \rangle\|_{L^2}$ or $\|\langle \phi, t \rangle\|_{L^2} \leq \kappa \|\langle \phi, t \rangle\|_{L^1}$ for all $t \in S$, or directly from Definition 4.5 if the entries of ϕ are independent (cf. proof of [1, Theorem 3.2], in the case of ϕ is isotropic, via the Paley-Zygmund inequality [55, Lemma 7.16].

Definition 4.5 for $\alpha = 1/2$ can be interpreted as requiring the first *K* moments to grow like the moments of sub-Gaussian random variables, however, moments beyond the *K*-th moment do not even need to exist. Examples for design matrices covered by Theorem 4.6 include Student-*t* random variables of degree $K = \lceil \log(ed/k) \rceil$, which do not have finite moments beyond degree *K*.

Structured Random Matrices. In engineering applications of compressed sensing, the usage of fully randomized measurement matrices–Gaussian, sub-Gaussian or heavy-tailed ones– is in most prohibitive due to physical and hardware constraints [77, 3]. Depending on the application, a specifically structured sensing process is required. For example, *A* could correspond to partial Fourier measurements for magnetic resonance imaging [83], to a partial circular convolution for radar imaging [95, 65] and deblurring [91], or binary measurements [107].

The work by Rudelson and Vershynin [100] states that a random selection of an order of $O(k \log^3(k) \log(d))$ Fourier measurements are enough to recover signals in Σ_k . This number is improved in [35], but not likely to reach the optimal number $k \log(d/k)$. Another remarkable result by Krahmer and Ward [78] uses the analysis sparsity model (3.5) with *G* being the finite difference operator. They show that $O(k \log^3(k) \log^5(d))$ random partial Fourier measurements are sufficient.

For subsampled convolution, the sensing matrix A can be expressed as $Az = (z * c)_{\Omega}$, where c is the generator and Ω indicates the index for subsampling. It is shown in [91] that if c is sub-Gaussian, then $O(k \log(d/k))$ subsampled random convolution measurements (if $k \leq \sqrt{d/\log(d)}$) are enough to satisfy the RNSP, hence ensure the success of $\Delta_{1,A,\eta}$. However, it is worth noting that the signals must be sparse in the canonical basis and it remains an open problem to obtain the optimal number of measurements for signals sparse in any orthonormal basis. The proof technique utilizes the small-ball property and moment estimates of sub-Gaussian vectors. It would be very interesting to generalize their results for heavier-tailed generators.

4.2. Sensing Matrices for General Frames *F*. Compared to the setup studied in Subsection 4.1, sensing matrix design in the presence of general rectangular frame matrices $F \in \mathbb{R}^{d \times n}$ has been less explored. In this section, we will restrict ourselves to the case that *F* is full spark, motivated by Remark 3.4. Full spark matrices include many common dictionaries (Wavelet, Curvelet, Discrete Cosine Transform, etc.) and will be obtained with probability 1 if *F* is randomly drawn from some continuous distribution family.

Given a full spark dictionary F, the goal is to find sensing matrices A that have as few rows as possible while still ensuring exact recovery of signals in $\Sigma_{F,k}$ via the ℓ_1 -synthesis decoder $\Delta_{F,A,\eta}$. Due to Remark 3.4, a premise for such A to exist is F satisfying NSP-k. In other words, if a full spark F does not have NSP-k, then the exact recovery of signals in $\Sigma_{F,k}$ is impossible with ℓ_1 -synthesis. This is because Remark 3.4 states that when F is full spark, AF must satisfy the NSP-k for uniform recovery of signals in $\Sigma_{F,k}$ due to Theorem 3.5, which in turn means Fitself must satisfy the NSP-k. To be able to obtain robust and stable recovery guarantees, we work with a slightly stronger version of the ℓ_2 -robust null space property RNSP- $(2, k, \rho, \tau)$ of Definition 2.1 defined in Definition 4.7, which is convenient to work with for deriving robust recovery results of the ℓ_1 -synthesis decoder $\Delta_{F,A,\eta}$.

Definition 4.7. (Robust-NSP* [40, 1]) Given $1 \le q \le 2$, *F* is said to fulfill the ℓ_q -robust null space property* of order *k* with constant $0 < \rho < 1$ and $\tau > 0$, also called RNSP*- (q, k, ρ, τ) , if

(4.4)
$$\inf_{v \in S^q_{k,\rho}} \|Fv\|_2 \ge \tau^{-1}$$

where

$$S_{k,\rho}^q := \left\{ v \in \mathbb{R}^n : \exists T \subset [n] \text{ with } |T| = k \text{ such that } \|v_T\|_q \ge \frac{\rho}{k^{1-1/q}} \|v_{T^c}\|_1 \right\} \cap \mathbb{S}_{\ell_q}^{n-1}.$$

By a compactness argument, it follows that there exists a $\tau > 0$ such that F satisfies RNSP*- $(2, k, \rho, \tau)$ provided that F satisfies a *stable* null space property, i.e., there exists a $0 < \rho < 1$ such that $||v_T||_2 \leq \frac{\rho}{\sqrt{k}} ||v_{T^c}||_1$ for all $v \in \text{Ker}(F) \setminus \{0\}$ and all k-sparse support sets $T \subset [n]$. This condition can in turn be used to derive optimal recovery guarantees for equality-constrained basis pursuit (by considering F as the sensing matrix) from exact measurements and is applicable to both sparse and approximately sparse vectors [55, Chapter 4]. The RNSP*- $(2, k, \rho, \tau)$ with a fixed constant τ for random frames F can be established with high probability if the rows of F are i.i.d. and drawn from well-behaved distributions and $d \geq k \log(n/k)$ [40, Corollary 8], [1, Theorem 4.1].

In fact, it is easy to verify that the RNSP*- (q, k, ρ, τ) implies the RNSP- (q, k, ρ, τ) for each set of parameters.

Proposition 4.8. If a matrix $F \in \mathbb{R}^{d \times n}$ fulfills RNSP*- (q, k, ρ, τ) , i.e., the ℓ_q -robust null space property* of order k with constant $0 < \rho < 1$ and $\tau > 0$ from Definition 4.7, then it also fulfills the RNSP- (q, k, ρ, τ) of Definition 2.1.

We recall the simple argument from the proof of [40, Theorem 3].

Proof of Proposition 4.8. Assume that $F \in \mathbb{R}^{d \times n}$ fulfills RNSP*- (q, k, ρ, τ) . Let us first assume $v \in \mathbb{R}^n$ be such that $||Fv||_2 < ||v||_q/\tau$. In this case, we see that

$$\left\|F\frac{v}{\|v\|_q}\right\|_2 < \frac{1}{\tau},$$

which means that $v/||v||_q \in \mathbb{S}_{\ell_q}^{n-1}$ cannot be contained in the set $S_{k,\rho}$, which implies that for any subset $T \subset [n]$ with |T| = k, it holds that

$$\|v_T\|_q < \frac{\rho}{k^{1-1/q}} \|v_{T^c}\|_1 \le \frac{\rho}{k^{1-1/q}} \|v_{T^c}\|_1 + \tau \|Fv\|_2.$$

On the other hand, if $v \in \mathbb{R}^n$ is such that $||Fv||_2 \ge ||v||_q/\tau$, then it holds that

$$\|v_T\|_q \le \|v\|_q \le \tau \|Fv\|_2 \le \frac{\rho}{k^{1-1/q}} \|v_{T^c}\|_1 + \tau \|Fv\|_2.$$

Thus, the defining inequality of RNSP- (q, k, ρ, τ) holds for each $v \in \mathbb{R}^n$.

For any frame *F* satisfying the RNSP- $(2, k, \rho, \tau)$, it can be shown that robust and stable recovery guarantees of the ℓ_1 -synthesis decoder $\Delta_{F,A,\eta}$ hold for a minimal number of rows of *A* if *A* is a sub-Gaussian sensing matrix [27].

Theorem 4.9 (see [27, Corollary 3.6], [1]). Suppose that rows of A are i.i.d., sub-Gaussian vectors with parameters σ and that F is of full spark satisfying RNSP*-(2, k, ρ , τ) and its columns satisfy max{ $\|f_i\|_2^2 : i \in [n]$ } $\leq \theta = O(1)$. Then as long as the number of measurements m satisfies

$$m \gtrsim k \log(n/k),$$

the ℓ_1 -synthesis decoder $\Delta_{F,A,\eta}$ provides stable and robust recovery of both the coefficient vector $x \in \mathbb{R}^n$ and the signal $z \in \mathbb{R}^d$ from y = Az + w = AFx + w with $||w||_2 \le \eta$ such that

(4.5)
$$\|x - \Delta_{1,AF,\eta}(AFx + w)\|_2 \lesssim \frac{\sigma_k(x)}{\sqrt{k}} + \frac{\tau}{\sigma}\eta$$

and

(4.6)
$$||z - \Delta_{F,A,\eta} (Az + w)||_2 \lesssim ||F||_2 \left(\frac{\sigma_k(x)}{\sqrt{k}} + \frac{\tau}{\sigma}\eta\right)$$

with probability at least $1 - e^{-\Omega(m)}$.

Theorem 4.9 differs from [27, Corollary 3.6] in that the latter uses a RNSP*- $(1, k, \rho, \tau)$ assumption on *F* (under the name *stable NSP*) instead of RNSP*- $(2, k, \rho, \tau)$. Following [1], we use here the RNSP*- $(2, k, \rho, \tau)$, together with Theorem 2.5 and Proposition 4.8, to obtain the optimal order dependence of the summand measuring the sparsity order misfit through $\sigma_k(x)$, for which the RNSP*- $(1, k, \rho, \tau)$ is not sufficient.

Akin to the case of a signal model $\Sigma_{I_d,k}$ of *k*-sparse vectors in the standard basis, it has turned out that heavy-tailed sensing matrices *A* beyond the sub-Gaussian can also lead to similar guarantees. In [1], the conclusions of Theorem 4.9 have been generalized to include sensing matrices with independent rows whose distribution is only required to have $O(\log(en/s))$ well-behaved moments. In particular, we use the following definition, which is a generalization of Definition 4.5.

Definition 4.10 (Distributions with *K* well-behaved spherical moments). We say the distribution of a random vector $\phi \in \mathbb{R}^d$ has *K* well-behaved spherical moments with constants $\alpha \ge 1/2$ and $\lambda > 0$ in direction of a ℓ_2 -unit norm vector $a \in \mathbb{S}^{d-1}$ if for all $2 \le p \le K$,

$$\|\langle \phi, a \rangle\|_{L^p} \le \lambda p^{\alpha}$$

For measurement matrices whose rows are drawn from distributions satisfying Definition 4.10, the resulting recovery guarantee applicable at the minimal number of rows is stated in the following theorem.

Theorem 4.11 ([1, Variant of Theorem 3.1]). Let a_i/\sqrt{m} , $i \in [m]$ be the rows of the measurement matrix A and the full spark frame $F \in \mathbb{R}^{d \times n}$ be given. Suppose the a_i are independent realizations from some centered distributions satisfying Definition 4.4 for $\mathbb{S}_{\ell_2}^{n-1}$ with constants u, c > 0, and that Definition 4.10 holds in the direction of all frame columns $f_j/||f_j||_2$, $j = 1, \ldots n$, up to $K = \Omega(\log(\frac{en}{k}))$ moments with moment growth parameter $\alpha \ge 1/2$ and constant $\lambda > 0$. Suppose F satisfies the RNSP*- $(2, k, \rho, \tau)$ and its columns satisfy $\max\{||f_i||_i^2 : i \in [n]\} \le \theta$. Then as long as the number of measurements m satisfies

$$m \gtrsim \max\left\{k \log(en/k), \log^{\max\{2\alpha-1,1\}}(en/k)\right\},\$$

we have with probability at least $1 - e^{-\Omega(m)}$, the ℓ_1 -synthesis decoder $\Delta_{F,A,\eta}$ provides stable and robust recovery of both the coefficient vector and the signal from y = Az + w = AFx + w with $||w||_2 \le \eta$ such that

$$\|x - \Delta_{1,AF,\eta} (AFx + w)\|_2 \lesssim \frac{\sigma_s(x)}{\sqrt{k}} + \tau \eta$$

and

$$\|z - \Delta_{F,A,\eta} (Az + w)\|_2 \lesssim \|F\|_2 \left(\frac{\sigma_s(x)}{\sqrt{k}} + \tau\eta\right).$$

The first three properties in Definition 3.1 are set up to recover the signal only, without necessarily recovering the sparse coefficient. Supported by numerical experiments and a geometric non-uniform phase transition analysis, it has been argued in [86] that a recovery of $z \in \Sigma_{F,k}$ is possible robustly in setups where the sparse coefficient vector cannot be identified, which in some sense extends the scope of applicability of ℓ_1 -synthesis techniques.

The results presented in this section, Theorem 4.9 and Theorem 4.11, although achieving the optimal number of measurements in a sense, both require the null space property on F, and thus recover the signal and coefficient simultaneously. This is essentially due to the challenge of analyzing the null space type properties in Definition 3.1 directly, and the existing work has resorted to applying properties in Definition 2.1 to AF. To show certain class of random sensing matrices satisfy F-RNSP- (k, ρ, τ) or a variation of it is still an open problem.

Following a different viewpoint, supported by numerical experiments and a geometric non-uniform phase transition analysis, it has been argued in [86] that a robust recovery of $z \in \Sigma_{F,k}$ is possible in setups where the sparse coefficient vector cannot be identified, which in some sense extends the scope of applicability of ℓ_1 -synthesis techniques. A current limitation of the analysis in [86] is that compared to the above theorems it only applies to sub-Gaussian sensing matrices *A*. It remains an open problem to extend such a signal-centric non-uniform analysis to a broader class of random and structured sensing matrices.

4.3. A Proof Sketch For ℓ_1 -Synthesis Recovery Guarantees. We now briefly sketch some of the key steps that can be taken to prove recovery guarantees for ℓ_1 -synthesis decoders of the type $\Delta_{F,A,n}$ as presented in Theorem 4.9, Theorem 4.11 and Theorem 4.6.

The starting point is based on the idea that once we consider Definition 4.7 of the RNSP*- (q, k, ρ, τ) of the measurement-frame matrix product AF, we can use a technique for lower bounding non-negative empirical processes developed in the series of papers [87, 74, 88] to obtain non-trivial lower bound of $\inf_{v \in S_{k,\rho}^2} ||AFv||_2$. This gives rise to (4.4) with a bounding constant that holds with high probability over the draws of A, which would correspond to an RNSP*- $(2, k, \rho, \tau)$ for AF and enables robust recovery guarantees for ℓ_1 -synthesis through Proposition 4.8.

Proposition 4.12 ([74, Theorem 1.5], [112, Proposition 5.1]). Fix a set $S \subset \mathbb{R}^d$. Let $\phi \in \mathbb{R}^d$ be a random vector and let $\Phi \in \mathbb{R}^{m \times d}$ be a random matrix whose rows are i.i.d copies of ϕ . Then, for any t > 0 and u > 0,

(4.8)
$$\inf_{x \in S} \|\Phi x\|_2 \ge u\sqrt{m}Q_{2u}(S;\phi) - 2W_m(S;\phi) - ut,$$

with probability at least $1 - e^{-t^2/2}$, where $W_m(S, \phi) := \mathbb{E} \sup_{x \in S} \left\langle x, \frac{1}{\sqrt{m}} \sum_{i=1}^m \varepsilon_i \phi_i \right\rangle$ is the *mean empirical width* of *S* with respect to ϕ if $\varepsilon_1, \ldots, \varepsilon_m$ are independent Rademacher random variables (attaining values ± 1 with probability 1/2), and $Q_u(S; \phi) := \inf_{x \in S} \Pr(|\langle \phi, x \rangle| \ge u)$ a small-ball probability bound of ϕ with respect to the set *S* (cf. also Definition 4.4).

Proposition 4.12 can be shown by estimating, for fixed $x \in S$, that $\|\Phi x\|_2 \ge \frac{1}{\sqrt{m}} \|\Phi x\|_1 = \frac{1}{\sqrt{m}} \sum_{i=1}^m |\langle \phi_i, x \rangle| \ge \frac{u}{\sqrt{m}} \sum_{i=1}^m \mathbb{1}_{\{|\langle \phi_i, x \rangle| \ge u\}}$ where ϕ_1, \ldots, ϕ_m are independent copies of ϕ and $\mathbb{1}_B$ a 1-0 random variable indicating whether the *B* takes places or not, comparing the resulting bound with $u\sqrt{m}Q_{2u}(S;\phi)$ and using the bounded differences inequality [11, Section 6.1]; a transparent proof can be found in [112, Section 5.5].

With Proposition 4.12 applied to $\Phi = A$ and $S = FS_{k,\rho}^2$, it remains to lower bound $Q_{2u}(FS_{k,\rho}^2;\phi)$ for appropriately chosen constant *u* and upper bound the empirical mean width $W_m(FS_{k,\rho}^2,\phi)$.

For the former, we can calculate that

$$\begin{aligned} Q_{2u}(FS_{k,\rho}^{2};\phi) &= \inf_{x \in FS_{k,\rho}^{2}} \Pr(|\langle \phi, x \rangle| \ge u) = \inf_{v \in S_{k,\rho}^{2}} \Pr(|\langle \phi, Fv \rangle| \ge u) \\ &= \inf_{v \in S_{k,\rho}^{2}} \Pr\left(\left|\left\langle \phi, \frac{Fv}{\|Fv\|_{2}}\right\rangle\right| \ge \frac{u}{\|Fv\|_{2}}\right) \ge \inf_{v \in S_{k,\rho}^{2}} \Pr\left(\left|\left\langle \phi, \frac{Fv}{\|Fv\|_{2}}\right\rangle\right| \ge \tau u\right) \end{aligned}$$

using the assumption that *F* satisfies RNSP*- $(2, k, \rho, \tau)$ (the last inequality is not needed for the case $F = I_d$). The latter term can be further lower bounded by the constant *c* from Definition 4.4 since $\frac{Fv}{\|Fv\|_2} \in \mathbb{S}_{\ell_2}^{n-1}$ in the case of Theorem 4.11, and lower bounded by an absolute constant through the Paley-Zygmund inequality [55, Lemma 7.16] in the sub-Gaussian case of Theorem 4.9.

For the empirical mean width of the set $FS_{k,\rho}^2$, we can use the result [40, Lemma 2] that implies the geometric inclusion $S_{k,\rho}^2 \subset (2 + \rho^{-1}) \operatorname{conv}(Z_k)$ with $Z_k := \{z \in \mathbb{R}^n : ||z||_0 \le k, ||z||_2 = 1\}$, where $\operatorname{conv}(\cdot)$ denote the convex hull of the respective set. With the notation $V := m^{-1/2} \sum_{i=1}^m \varepsilon_i \phi_i$, this leads to estimate that

$$W_m(FS_{k,\rho}^2, \phi) = \mathbb{E} \sup_{x \in FS_{k,\rho}^2} \langle x, V \rangle = \mathbb{E} \sup_{x \in S_{k,\rho}^2} \langle x, F^\top V \rangle$$

$$\leq (2 + \rho^{-1}) \mathbb{E} \sup_{x \in \text{conv}(Z_k)} \langle x, F^\top V \rangle$$

$$= (2 + \rho^{-1}) \mathbb{E} \sup_{x \in Z_k} \langle x, F^\top V \rangle = (2 + \rho^{-1}) \left(\sum_{i=1}^k ((F^\top V)_i^*)^2 \right)^{1/2}$$

using the fact that the supremum of the linear form over a set and over its convex hull coincide; for a vector $z = (z_i, ..., z_n)$, we denoted the *i*-th largest coordinate in absolute value as z_i^* . In the case of sub-Gaussian vectors, it is possible to invoke the majorizing measure theorem [105, Theorem 2.7.2 and Theorem 2.10.1] to bound $\mathbb{E} \sup_{x \in Z_k} \langle x, F^\top V \rangle$ by a constant times the Gaussian width of the set FZ_k , as used in [27], which can be bounded explicitly by properties of the Gaussian distribution.

For heavy-tailed distributions, however, one can use the weak moment assumption on inner products of the ϕ_i with the columns f_j for the frame matrix F (Definition 4.10) in conjunction with the following elementary lemma applied to $z = (\langle f_1, V \rangle, \dots, \langle f_n, V \rangle)$, which was shown in [1] and which relaxes the assumptions of [88, Lemma 6.5].

Lemma 4.13 (Bound on Order Statistics Norm, [1, Lemma 5.1]). There exists an absolute constant C > 0 for which the following holds. Let $k \in \mathbb{N}$. Assume that z_1, \ldots, z_n are centered random variables with variance 1 that fulfill for each $i \in [n]$ that for every $p \le 2\log(n/k)$, $||z_i||_{L_p} \le \lambda \sqrt{p}$. Then

$$\mathbb{E}\left[\sum_{i=1}^{k} \left(z_{i}^{*}\right)^{2}\right]^{1/2} \leq C\lambda \sqrt{k\log\left(\frac{n}{k}\right)},$$

where z_i^* denotes the *i*-th coordinate of the non-increasing rearrangement of the vector $z = (|z_1|, ..., |z_n|)$.

Putting these proof ingredients together is suitable to establish Theorems 4.6, 4.9 and 4.11.

Open Questions. To the best of our knowledge, results on recovery guarantees for dictionary or frame sparse signals for structured design matrices for minimum measurement numbers are rare and hardly existent, especially for ℓ_1 -synthesis decoders. It would be interesting to investigate if some of the presented techniques can be adapted to analyze designs based on partial bounded orthogonal systems or partial circulant matrices in the frame-sparse setup. A generalization of the analysis of subsampled convolutions of [91] to this setup, potentially even with heavy-tailed generator vector, might be in reach due to the similarity of their techniques, but remains open at this point.

While not a focus of this chapter, we note that also for ℓ_1 -analysis decoders such as $\Lambda_{F,A,\eta}$ from (3.6), there are only few strong results about structured random measurements available, which are based on the (*F*-RIP-(k, δ)) of Definition 3.1, such as those of [76]. It would be interesting to explore whether NSP-based proof strategies such as presented in this chapter leads to guarantees applicable for fewer measurements than *F*-RIP based ones for ℓ_1 -analysis decoders.

5. Outlook. In this chapter, we presented results about the interplay of decoder, sensing matrix properties enabling robust recovery and discussed the question of sensing matrix design in this context, for the problem of identifying signals that are linear combinations of few dictionary atoms or frame vectors. We also presented several open research directions. By focusing on convex decoders, our survey cannot do justice to the analysis of practically very relevant non-convex and iterative decoders; however, the comparatively mature theory of convex decoders can be seen as a starting point for further developing the analysis of such decoders as well.

Related to the sparse recovery problems we studied are also low-rank matrix recovery problems [39, 19, 32, 34, 56], non-linear variants of which have gained renewed interest in the machine learning community [67, 119, 68]. While robust recovery guarantees based on (robust) null space properties are also available for such problems [118], existing ones are not applicable in a uniform manner for many important special cases such as entrywise sampling (matrix completion). However, we note that relevant problem variants can be considered as *Schatten-1-synthesis* or *Schatten-1-analysis* problems in analogy to the concepts presented here. Examples are the Euclidean distance geometry problems, whose low-rank optimization perspective can be considered as a nuclear (or Schatten-1) norm minimization problem with respect to a synthesis operator that maps Gram matrices to pairwise distance matrices [41, 106], and low-rank (block-)Hankel/Toeplitz recovery problems [33, 70, 18], which can be framed as low-rank recovery problems with respect to a Hankel or Toeplitz-type analysis operator. Exploring the benefits of this perspective remains for future investigations.

Acknowledgements. XC is partially funded by NSF grant 2307827.

REFERENCES

- [1] Pedro Abdalla and Christian Kümmerle, *Dictionary-sparse recovery from heavy-tailed measurements*, Information and Inference: A Journal of the IMA 11 (2022), no. 4, 1501–1526.
- [2] Radoslaw Adamczak, Alexander E. Litvak, Alain Pajor, and Nicole Tomczak-Jaegermann, Restricted isometry property of matrices with independent columns and neighborly polytopes by random sampling, Constructive Approximation 34 (2011), 61–88.
- [3] Ben Adcock and Anders C. Hansen, *Compressive imaging: Structure, sampling, learning*, Cambridge University Press, 2021.
- [4] Akram Aldroubi, Xuemei Chen, and Alex Powell, *Stability and robustness of* ℓ_q *minimization using null space property*, Proceedings of the 9th International Conference on Sampling Theory and Applications (SampTA), Singapore, 2011.
- [5] Akram Aldroubi, Xuemei Chen, and Alexander M. Powell, Perturbations of measurement matrices and

dictionaries in compressed sensing, Appl. Comput. Harmon. Anal. 33 (2012), no. 2, 282-291.

- [6] Boris Alexeev, Jameson Cahill, and Dustin G. Mixon, Full Spark Frames, J. Fourier Anal. Appl. 18 (2012), no. 6, 1167–1194. MR 3000979
- [7] Youness Arjoune, Naima Kaabouch, Hassan El Ghazi, and Ahmed Tamtaoui, A performance comparison of measurement matrices in compressive sensing, International Journal of Communication Systems 31 (2018), no. 10, e3576.
- [8] Afonso S. Bandeira, Matthew Fickus, Dustin G. Mixon, and Percy Wong, The road to deterministic matrices with the restricted isometry property, Journal of Fourier Analysis and Applications 19 (2013), no. 6, 1123–1149.
- [9] Richard Baraniuk, Mark Davenport, Ronald DeVore, and Michael Wakin, *A simple proof of the restricted isometry property for random matrices*, Constructive approximation **28** (2008), 253–263.
- [10] Richard Baraniuk and Philippe Steeghs, Compressive sensing: A new approach to seismic data acquisition, The Leading Edge 36 (2017), no. 8, 642–645.
- [11] Stéphane Boucheron, Gábor Lugosi, and Pascal Massart, *Concentration inequalities: A nonasymptotic theory of independence*, Oxford university press, 2013.
- [12] Jean Bourgain, Stephen Dilworth, Kevin Ford, Sergei Konyagin, and Denka Kutzarova, Explicit constructions of RIP matrices and related problems, Duke Mathematical Journal 159 (2011), no. 1, 145 – 185.
- [13] Jean Bourgain and M. Z. Garaev, On a variant of sum-product estimates and explicit exponential sum bounds in prime fields, Mathematical Proceedings of the Cambridge Philosophical Society, vol. 146, Cambridge University Press, 2009, pp. 1–21.
- [14] Simone Brugiapaglia and Ben Adcock, Robustness to unknown error in sparse regularization, IEEE Transactions on Information Theory 64 (2018), no. 10, 6638–6661.
- [15] Jameson Cahill, Xuemei Chen, and Rongrong Wang, The gap between the null space property and the restricted isometry property, Linear Algebra and its Applications 501 (2016), 363–375.
- [16] Jameson Cahill and Dustin G. Mixon, Robust width: A characterization of uniformly stable and robust compressed sensing, Excursions in Harmonic Analysis, Volume 6: In Honor of John Benedetto's 80th Birthday (2021), 343–371.
- [17] Jian-Feng Cai, Raymond H Chan, and Zuowei Shen, *A framelet-based image inpainting algorithm*, Applied and Computational Harmonic Analysis **24** (2008), no. 2, 131–149.
- [18] Jian-Feng Cai, Tianming Wang, and Ke Wei, Fast and provable algorithms for spectrally sparse signal reconstruction via low-rank Hankel matrix completion, Applied and Computational Harmonic Analysis 46 (2019), no. 1, 94–121.
- [19] Jian-Feng Cai and Ke Wei, *Exploiting the structure effectively and efficiently in low-rank matrix recovery*, Processing, Analyzing and Learning of Images, Shapes, and Forms **19** (2018), 21 pp.
- [20] T. Tony Cai and Anru Zhang, Sparse representation of a polytope and recovery of sparse signals and low-rank matrices, IEEE transactions on information theory **60** (2013), no. 1, 122–132.
- [21] _____, Sparse representation of a polytope and recovery of sparse signals and low-rank matrices, IEEE transactions on information theory **60** (2013), no. 1, 122–132.
- [22] Emmanuel Candès and Terence Tao, *Decoding by linear programming*, IEEE Transactions on Information Theory **51** (2005), no. 12, 4203–4215.
- [23] _____, Near optimal signal recovery from random projections and universal encoding strategies, IEEE Transactions on Information Theory **52** (2006), 5406–5425.
- [24] Emmanuel J. Candès, Yonina C. Eldar, Deanna Needell, and Paige Randall, Compressed sensing with coherent and redundant dictionaries, Applied and Computational Harmonic Analysis 31 (2011), no. 1, 59–73.
- [25] Emmanuel J. Candès, Yonina C. Eldar, Thomas Strohmer, and Vladislav Voroninski, *Phase retrieval via matrix completion*, SIAM Review 57 (2015), no. 2, 225–251.
- [26] Emmanuel J. Candès, Justin K. Romberg, and Terence Tao, Stable signal recovery from incomplete and inaccurate measurements, Communications on Pure and Applied Mathematics 59 (2006), no. 8, 1207– 1223.
- [27] Peter G. Casazza, Xuemei Chen, and Richard G. Lynch, Preserving injectivity under subgaussian mappings and its application to compressed sensing, Applied and Computational Harmonic Analysis 49 (2020), no. 2, 451–470.
- [28] Scott Shaobing Chen, David L. Donoho, and Michael A. Saunders, *Atomic decomposition by basis pursuit*, SIAM review **43** (2001), no. 1, 129–159.
- [29] Xuemei Chen, A unified recovery of structured signals using atomic norm, Information and Inference: A Journal of the IMA 13 (2024), no. 1, iaado50.
- [30] Xuemei Chen, Haichao Wang, and Rongrong Wang, A null space analysis of the l₁-synthesis method in dictionary-based compressed sensing, Applied and Computational Harmonic Analysis 37 (2014), no. 3, 492–515.
- [31] Yudong Chen, Incoherence-optimal matrix completion, IEEE Transactions on Information Theory 61 (2015),

no. 5, 2909–2923.

- [32] Yudong Chen and Yuejie Chi, Harnessing Structures in Big Data via Guaranteed Low-Rank Matrix Estimation: Recent Theory and Fast Algorithms via Convex and Nonconvex Optimization, IEEE Signal Process. Mag. 35 (2018), no. 4, 14–31.
- [33] Yuxin Chen and Yuejie Chi, Robust Spectral Compressed Sensing via Structured Matrix Completion, IEEE Trans. Inf. Theory 60 (2014), no. 10, 6576–6601.
- [34] Yue M. Lu Chi, Yuejie and Yuxin Chen, Nonconvex Optimization Meets Low-Rank Matrix Factorization: An Overview, IEEE Trans. Signal Process. 67 (2019), no. 20, 5239–5269.
- [35] Abdellah Chkifa, Nick Dexter, Hoang Tran, and Clayton Webster, Polynomial approximation via compressed sensing of high-dimensional functions on lower sets, Mathematics of Computation 87 (2018), no. 311, 1415–1450.
- [36] Charles Clum and Dustin G. Mixon, Derandomized compressed sensing with nonuniform guarantees for l₁ recovery, Journal of Fourier Analysis and Applications 28 (2022), no. 2, 35.
- [37] Albert Cohen, Wolfgang Dahmen, and Ronald DeVore, *Compressed sensing and best k-term approximation*, Journal of the American Mathematical Society **22** (2009), 211–231.
- [38] Mark A. Davenport, Deanna Needell, and Michael B. Wakin, *Signal space cosamp for sparse recovery with redundant dictionaries*, IEEE Transactions on Information Theory **59** (2012), no. 10, 6820–6829.
- [39] Mark A. Davenport and Justin Romberg, *An overview of low-rank matrix recovery from incomplete observations*, IEEE J. Sel. Topics Signal Process. **10** (2016), 608–622.
- [40] S. Dirksen, G. Lecué, and H. Rauhut, On the gap between restricted isometry properties and sparse recovery conditions, IEEE Trans. Inf. Theory 64 (2018), no. 8, 5478–5487.
- [41] Ivan Dokmanić, Reza Parhizkar, Juri Ranieri, and Martin Vetterli, *Euclidean Distance Matrices: Essential theory, Algorithms, and Applications*, IEEE Signal Processing Magazine **32** (2015), no. 6, 12–30.
- [42] David Donoho, *Compressed Sensing*, IEEE Transactions on Information Theory **52** (2006), no. 4, 1289–1306.
- [43] David Donoho, Blackboard to bedside: How high-dimensional geometry is transforming the mri industry, Notices of the AMS **65** (2018), no. 1, 40–44.
- [44] David Donoho and Michael Elad, *Optimally sparse representation in general (nonorthogonal) dictionaries via l*₁ *minimization*, Proceedings of the National Academy of Science **100** (2003), no. 5, 2197–202.
- [45] David L. Donoho and Benjamin F. Logan, Signal recovery and the large sieve, SIAM Journal on Applied Mathematics 52 (1992), no. 2, 577–591.
- [46] Florian Dörfler, Jeremy Coulson, and Ivan Markovsky, Bridging direct and indirect data-driven control formulations via regularizations and relaxations, IEEE Transactions on Automatic Control 68 (2022), no. 2, 883–897.
- [47] Michael Elad and Michal Aharon, *Image denoising via sparse and redundant representations over learned dictionaries*, IEEE Transactions on Image Processing **15** (2006), no. 12, 3736–3745.
- [48] Michael Elad, Peyman Milanfar, and Ron Rubinstein, *Analysis versus synthesis in signal priors*, Inverse Problems **23** (2007), no. 3, 947–968.
- [49] Maryam Fazel, Haitham A. Hindi, and Stephen P. Boyd, *Rank minimization and applications in system theory*, Proceedings of the 2004 American Control Conference, no. 4, 2004, pp. 3273–3278.
- [50] Christoph Forman, Jens Wetzl, Carmel Hayes, and Michaela Schmidt, *Compressed sensing: a paradigm shift in mri*, MAGNETOM Flash (2016), 19.
- [51] Simon Foucart, Stability and robustness of ℓ₁-minimizations with weibull matrices and redundant dictionaries, Linear Algebra and its Applications 441 (2014), 4–21.
- [52] _____, Dictionary-sparse recovery via thresholding-based algorithms, Journal of Fourier Analysis and Applications 22 (2016), 6–19.
- [53] Simon Foucart and Ming-Jun Lai, *Sparsest solutions of underdetermined linear systems via* ℓ_q -minimization for $0 < q \le 1$, Applied and Computational Harmonic Analysis **26** (2009), no. 3, 395–407.
- [54] Simon Foucart, Alain Pajor, Holger Rauhut, and Tino Ullrich, *The gelfand widths of* ℓ_p *-balls for* 0 , Journal of Complexity**26**(2010), no. 6, 629–640.
- [55] Simon Foucart and Holger Rauhut, *A mathematical introduction to compressive sensing*, Birkhäuser/Springer, New York, 2013.
- [56] Tim Fuchs, David Gross, Peter Jung, Felix Krahmer, Richard Kueng, and Dominik Stöger, Proof methods for robust low-rank matrix recovery, Compressed Sensing in Information Processing, Springer, 2022, pp. 37–75.
- [57] Andrey Y. Garnaev and Efim Davydovich Gluskin, On widths of the euclidean ball, Journal of Soviet Mathematics 30 (1984), 200–204.
- [58] Raja Giryes, Sangnam Nam, Michael Elad, Rémi Gribonval, and Mike E Davies, *Greedy-like algorithms for the cosparse analysis model*, Linear Algebra and its Applications **441** (2014), 22–60.
- [59] Raja Giryes and Deanna Needell, *Greedy signal space methods for incoherence and beyond*, Applied and Computational Harmonic Analysis **39** (2015), no. 1, 1–20.
- [60] Efim Davydovich Gluskin, Extremal properties of orthogonal parallelepipeds and their applications to the

geometry of banach spaces, Mathematics of the USSR-Sbornik 64 (1989), no. 1, 85.

- [61] Rémi Gribonval and Morten Nielsen, *Sparse representations in unions of bases*, IEEE Transactions on Information Theory **49** (2003), no. 12, 3320–3325.
- [62] David Gross, *Recovering low-rank matrices from few coefficients in any basis*, IEEE Transactions on Information Theory **57** (2011), no. 3, 1548–1566.
- [63] Olivier Guédon, Felix Krahmer, Christian Kümmerle, Shahar Mendelson, and Holger Rauhut, On the geometry of polytopes generated by heavy-tailed random vectors, Communications in Contemporary Mathematics 24 (2022), no. 03, 2150056.
- [64] Trevor Hastie, Robert Tibshirani, and Martin Wainwright, *Statistical learning with sparsity*, Monographs on Statistics and Applied Probability **143** (2015), no. 143, 8.
- [65] Jarvis Haupt, Waheed U Bajwa, Gil Raz, and Robert Nowak, Toeplitz compressed sensing matrices with applications to sparse channel estimation, IEEE transactions on information theory 56 (2010), no. 11, 5862–5875.
- [66] Felix J. Herrmann, Randomized sampling and sparsity: Getting more information from fewer samples, Geophysics 75 (2010), no. 6, WB173–WB187.
- [67] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen, LoRA: Low-rank adaptation of large language models, International Conference on Learning Representations (ICLR), 2022.
- [68] Uijeong Jang, Jason D. Lee, and Ernest K. Ryu, LoRA training in the NTK regime has no spurious local minima, Forty-first International Conference on Machine Learning (ICML), 2024.
- [69] Oren N Jaspan, Roman Fleysher, and Michael L Lipton, Compressed sensing mri: a review of the clinical literature, The British journal of radiology 88 (2015), no. 1056, 20150487.
- [70] Kyong Hwan Jin, Dongwook Lee, and Jong Chul Ye, A general framework for compressed sensing and parallel MRI using annihilating filter based low-rank Hankel matrix, IEEE Transactions on Computational Imaging 2 (2016), no. 4, 480–495.
- [71] Kyong Hwan Jin and Jong Chul Ye, *Annihilating filter-based low-rank Hankel matrix approach for image inpainting*, IEEE Transactions on Image Processing 24 (2015), no. 11, 3498–3511.
- [72] Boris S Kashin and Vladimir N Temlyakov, *A remark on compressed sensing*, Mathematical notes **82** (2007), 748–755.
- [73] Vladimir Koltchinskii, Oracle Inequalities in Empirical Risk Minimization and Sparse Recovery Problems: Ecole d'Eté de Probabilités de Saint-Flour XXXVIII-2008, vol. 2033, Springer, Heidelberg, 2011.
- [74] Vladimir Koltchinskii and Shahar Mendelson, *Bounding the smallest singular value of a random matrix without concentration*, Int. Math. Res. Not. IRMN **2015** (2015), no. 23, 12991–13008.
- [75] Yehuda Koren, Robert Bell, and Chris Volinsky, *Matrix factorization techniques for recommender systems*, Computer **42** (2009), no. 8, 30–37.
- [76] Felix Krahmer, Deanna Needell, and Rachel Ward, *Compressive sensing with redundant dictionaries and structured measurements*, SIAM Journal on Mathematical Analysis 47 (2015), no. 6, 4606–4629.
- [77] Felix Krahmer and Holger Rauhut, *Structured random measurements in signal processing*, GAMM-Mitteilungen **37** (2014), no. 2, 217–238.
- [78] Felix Krahmer and Rachel Ward, *Stable and robust sampling strategies for compressive imaging*, IEEE Transactions on Image Processing **23** (2014), no. 2, 612–622.
- [79] Gitta Kutyniok, Jakob Lemvig, and Wang-Q. Lim, Compactly supported shearlets, Approximation Theory XIII: San Antonio 2010 (New York, NY) (Marian Neamtu and Larry Schumaker, eds.), Springer, New York, 2012, pp. 163–186.
- [80] Shlomo Levy and Peter K Fullagar, *Reconstruction of a sparse spike train from a portion of its spectrum and application to high-resolution deconvolution*, Geophysics **46** (1981), no. 9, 1235–1243.
- [81] Yulong Liu, Shidong Li, Tiebin Mi, Hong Lei, and Weidong Yu, Performance analysis of l₁-synthesis with coherent frames, 2012 IEEE International Symposium on Information Theory Proceedings, IEEE, 2012, pp. 2042–2046.
- [82] Benjamin Franklin Logan, *Properties of high-pass signals*, Ph.D. thesis, Columbia University, 1965.
- [83] Michael Lustig, David Donoho, and John M. Pauly, Sparse MRI: The application of compressed sensing for rapid MR imaging, Magnetic Resonance in Medicine 58 (2007), no. 6, 1182–1195.
- [84] Julien Mairal, Jean Ponce, Guillermo Sapiro, Andrew Zisserman, and Francis Bach, *Supervised dictionary learning*, Advances in Neural Information Processing Systems (NIPS) **21** (2008), 1033–1040.
- [85] Stéphane Mallat, A wavelet tour of signal processing, Elsevier, 1999.
- [86] Maximilian März, Claire Boyer, Jonas Kahn, and Pierre Weiss, Sampling rates for l₁-synthesis, Foundations of Computational Mathematics 23 (2023), no. 6, 2089–2150.
- [87] Shahar Mendelson, A remark on the diameter of random sections of convex bodies, Geometric Aspects of Functional Analysis: Israel Seminar (GAFA) 2011-2013, Springer, 2014, pp. 395–404.
- [88] _____, Learning without concentration, J. ACM 62 (2015), no. 3, 21:1–21:25.
- [89] Shahar Mendelson and Guillaume Lecué, Sparse recovery under weak moment assumptions, J. Eur. Math.

Soc. 19 (2017), no. 3, 881–904.

- [90] Shahar Mendelson, Alain Pajor, and Nicole Tomczak-Jaegermann, Uniform uncertainty principle for bernoulli and subgaussian ensembles, Constructive Approximation **28** (2008), 277–289.
- [91] Shahar Mendelson, Holger Rauhut, and Rachel Ward, *Improved bounds for sparse recovery from subsampled random convolutions*, Ann. Appl. Probab. **28** (2018), no. 6, 3491–3527.
- [92] Hatef Monajemi, Sina Jafarpour, Matan Gavish, Stat 330/CME 362 Collaboration, David L. Donoho, Sivaram Ambikasaran, Sergio Bacallado, Dinesh Bharadia, Yuxin Chen, Young Choi, et al., *Deterministic matrices matching the compressed sensing phase transitions of gaussian random matrices*, Proceedings of the National Academy of Sciences 110 (2013), no. 4, 1181–1186.
- [93] Vardan Papyan, Yaniv Romano, Jeremias Sulam, and Michael Elad, Theoretical foundations of deep learning via sparse representations: A multilayer sparse model and its connection to convolutional neural networks, IEEE Signal Processing Magazine 35 (2018), no. 4, 72–89.
- [94] Tomer Peleg and Michael Elad, *Performance guarantees of the thresholding algorithm for the cosparse analysis model*, IEEE Transactions on Information Theory **59** (2013), no. 3, 1832–1845.
- [95] Holger Rauhut, Justin Romberg, and Joel A Tropp, *Restricted isometries for partial random circulant matrices*, Applied and Computational Harmonic Analysis **32** (2012), no. 2, 242–254.
- [96] Holger Rauhut, Karin Schnass, and Pierre Vandergheynst, *Compressed sensing and redundant dictionaries*, IEEE Transactions on Information Theory **54** (2008), no. 5, 2210–2219.
- [97] Saiprasad Ravishankar, Jong Chul Ye, and Jeffrey A Fessler, *Image reconstruction: From sparsity to dataadaptive methods and machine learning*, Proceedings of the IEEE **108** (2019), no. 1, 86–109.
- [98] Benjamin Recht and Christopher Ré, *Parallel stochastic gradient algorithms for large-scale matrix completion*, Mathematical Programming Computation **5** (2013), no. 2, 201–226.
- [99] Irina Rish and Genady Grabarnik, Sparse modeling: Theory, algorithms, and applications, CRC Press, 2014.
- [100] Mark Rudelson and Roman Vershynin, *On sparse reconstruction from Fourier and Gaussian measurements*, Communications on Pure and Applied Mathematics **61** (2008), 1025–1045.
- [101] Rayan Saab and Özgür Yılmaz, *Sparse recovery by non-convex optimization–instance optimality*, Applied and Computational Harmonic Analysis **29** (2010), no. 1, 30–48.
- [102] Fadil Santosa and William W. Symes, Linear inversion of band-limited reflection seismograms, SIAM Journal on Scientific and Statistical Computing 7 (1986), no. 4, 1307–1330.
- [103] Soumyadip Sengupta, Tal Amir, Meirav Galun, Tom Goldstein, David W Jacobs, Amit Singer, and Ronen Basri, A new rank constraint on multi-view fundamental matrices, and its application to camera location recovery, Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2017, pp. 4798–4806.
- [104] Yoav Shechtman, Yonina C Eldar, Oren Cohen, Henry Nicholas Chapman, Jianwei Miao, and Mordechai Segev, Phase retrieval with application to optical imaging: A contemporary overview, IEEE Signal Processing Magazine 32 (2015), no. 3, 87–109.
- [105] Michel Talagrand, Upper and lower bounds for stochastic processes: Decomposition theorems, Ergebnisse der Mathematik und ihrer Grenzgebiete. 3. Folge / A Series of Modern Surveys in Mathematics, vol. 60, Springer Science & Business Media, 2021.
- [106] Abiy Tasissa and Rongjie Lai, Exact reconstruction of euclidean distance geometry problem using low-rank matrix completion, IEEE Transactions on Information Theory 65 (2018), no. 5, 3124–3144.
- [107] Laura Thesing and Anders Christian Hansen, Non-uniform recovery guarantees for binary measurements and infinite-dimensional compressed sensing, Journal of Fourier Analysis and Applications 27 (2021), no. 2, 14.
- [108] Robert Tibshirani, *Regression shrinkage and selection via the lasso*, Journal of the Royal Statistical Society: Series B (Methodological) 58 (2018), no. 1, 267–288.
- [109] Andreas M. Tillmann and Marc E. Pfetsch, The computational complexity of the restricted isometry property, the nullspace property, and related concepts in compressed sensing, IEEE Transactions on Information Theory 60 (2013), no. 2, 1248–1259.
- [110] Tom Tirer and Raja Giryes, *Generalizing cosamp to signals from a union of low dimensional linear subspaces*, Applied and Computational Harmonic Analysis **49** (2020), no. 1, 99–122.
- [111] Joel A. Tropp, *Greed is good: Algorithmic results for sparse approximation*, IEEE Transactions on Information theory **50** (2004), no. 10, 2231–2242.
- [112] _____, Convex recovery of a structured signal from independent random linear measurements, Sampling Theory, a Renaissance: Compressive Sensing and Other Developments (2015), 67–101.
- [113] Roman Vershynin, Introduction to the non-asymptotic analysis of random matrices, Compressed Sensing, Theory and Applications (Y. Eldar and G. Kutyniok, eds.), Cambridge University Press, Cambridge, 2012, pp. 210–268.
- [114] Roman Vershynin, High-dimensional probability: An introduction with applications in data science, Cambridge Series in Statistical and Probabilistic Mathematics, vol. 47, Cambridge University Press, Cambridge, 2018.

- [115] Mathukumalli Vidyasagar, *An introduction to compressed sensing*, Society for Industrial and Applied Mathematics, Philadelphia, PA, 2019.
- [116] David Wipf and Srikantan Nagarajan, Iterative reweighted ℓ_1 and ℓ_2 methods for finding sparse solutions, IEEE Journal of Selected Topics in Signal Processing 4 (2010), no. 2, 317–329.
- [117] Przemyslaw Wojtaszczyk, Stability and instance optimality for gaussian measurements in compressed sensing, Foundations of Computational Mathematics 10 (2010), 1–13.
- [118] Jirong Yi and Weiyu Xu, Necessary and sufficient null space condition for nuclear norm minimization in low-rank matrix recovery, IEEE Transactions on Information Theory **66** (2020), no. 10, 6597–6604.
- [119] Yuchen Zeng and Kangwook Lee, *The expressive power of low-rank adaptation*, The Twelfth International Conference on Learning Representations (ICLR), 2024.
- [120] Yun-Bin Zhao, Sparse optimization theory and methods, 1st ed., CRC Press, 2018.
- [121] Le Zheng, Arian Maleki, Haolei Weng, Xiaodong Wang, and Teng Long, *Does* ℓ_p *-minimization outperform* ℓ_1 *-minimization?*, IEEE Transactions on Information Theory **63** (2017), no. 11, 6896–6935.