



Google Pay™ integration

Version 1.0

Changes to the document

| Date | Changing | Version |
|------------|-----------------|---------|
| 2024-05-21 | Initial version | 1.0 |

| | |
|---|----------|
| Changes to the document | 2 |
| Introduction | 4 |
| Google Pay & Corvus Pay | 4 |
| Using the CorvusPay payment method (standard <i>redirect</i> integration) | 4 |
| Using the CorvusPay API..... | 5 |
| Google Pay API Web Integration | 5 |
| Google Pay API Android Integration..... | 5 |
| Google Pay API configuration | 5 |
| Payment processing | 6 |
| Secure Customer Authentication (SCA/3DS) and PSD2..... | 7 |

Introduction

Google Pay™ is a digital wallet for online payments offered by Google.

It is an advanced and secure solution that customers can use to add credit/debit cards to their wallet and use them to pay at webshops or mobile applications that use the CorvusPay service.

By combining the Google API with the CorvusPay API, the payment process is fast, easy and secure.

Increase your conversion rate with these features:

- Your customers simply select a card from their Google Pay wallet.
- Google Pay and CorvusPay manage all sensitive user data for you.
- A secure encryption/decryption method raises your customers' trust in the entire payment process and significantly reduces online fraud.

To make all this possible, Google Pay tokenizes your customers' cards as follows:

- Tokenized cards outside of card schemes: standard physical credit cards that require 3D-Secure verification for additional fraud protection. This is only applicable for payments through your point of sale, and this method of authorization is called PAN_ONLY.
- Cards tokenized within card schemes: A virtual card with a device-specific account number (DPAN). These types of cards are used in place of a real plastic card. Since the digital signature of the mobile device used for payment protects these cards from fraud, 3D-Secure is unnecessary. This only applies to users who use Google Digital Wallet on their mobile device, and the authorization method is called CRYPTOGRAM_3DS.

To pay with Google Pay, your customers can use cards of the following brands: Visa, MasterCard, American Express, Discover, JCB.

Google Pay & CorvusPay

To use the Google Pay service, it is necessary to integrate with the CorvusPay system in one of two ways:

- Standard *redirect* integration using CorvusPay payment form
- Integration via CorvusPay API

To activate the Google Pay payment method through the CorvusPay system, you need to do the following:

- Submit a request to our customer service support@CorvusPay.com
- Follow the Google Pay API Terms of Use
<https://payments.developers.google.com/terms/aup>

Using the CorvusPay payment method (standard *redirect* integration)

Before activating the Google Pay payment method on the CorvusPay payment form, the merchant must complete the integration with the CorvusPay system.

After activating the Google Pay payment method, a Google Pay tab will be added to the CorvusPay payment form, which will enable Google Pay payment.

Using the CorvusPay API

CorvusPay supports Google Pay transactions directly through its API. CorvusPay provides CRYPTOGRAM_3DS authorization method for Google Pay.

The integration itself includes the following steps:

1. Merchants integrate with the Google Pay API.
2. The customer selects the Google Pay button on the webshop or the merchant's mobile app.
3. The customer confirms the payment and Google Pay returns the payment token to the merchant.
4. The merchant encodes the received token using Base64 and sends it to the Corvus Pay API as part of the POST request at /api/1.6/auth.

Before you start with integration to Google Pay API you must accept the Google Pay API Terms of Service <https://payments.developers.google.com/terms/sellertos>

Google Pay API Web Integration

To integrate your webshop with the Google Pay API, follow the instructions provided in the [Google Pay API documentation for web applications](#). Familiarize yourself with the [Google Pay web application brand guidelines](#) and see the Google Pay integration guidelines to [Google Pay web application integration checklist](#).

Google Pay API Android Integration

To integrate your Android app with the Google Pay API, follow the instructions provided in the [Google Pay documentation for Android developers](#). Familiarize yourself with the [Google Pay Android App Brand Guidelines](#) and see the [Google Pay Android Integration Checklist guidelines](#).

Google Pay API configuration

To initiate a transaction, your web or mobile app must send a request to the Google Pay API, specifying the payment method within the [PaymentMethod](#) object.

Configuration parameters

Set the following properties under "parameters":

```
"allowedAuthMethods": [ "CRYPTOGRAM_3DS" ]  
"allowedCardNetworks": [ "AMEX", "DISCOVER", "JCB", "MASTERCARD", "VISA" ]
```

Set the following properties under "tokenizationSpecification.parameters":

- "gateway": "corvuspays"
- "gatewayMerchantId": Use your storeID.

Example of a PaymentMethod object:

```
{  
    "type": "CARD",  
    "parameters": {  
        "allowedAuthMethods": [ "CRYPTOGRAM_3DS" ],  
        "allowedCardNetworks": [ "AMEX", "DISCOVER", "JCB", "MASTERCARD", "VISA" ]  
    },
```

```

"tokenizationSpecification": {
    "type": "PAYMENT_GATEWAY",
    "parameters": {
        "gateway": "corvuspay",
        "gatewayMerchantId": "602"
    }
}
}

```

Payment processing

After successfully initiating a transaction via the Google Pay API on your web or mobile application, you will receive a `PaymentData` object in the response. To complete the payment, it is necessary to pass the `"token"` parameter (`paymentData.paymentMethodData.tokenizationData.token`) to the CorvusPay API. The parameter needs to be encoded using the Base64 algorithm before being sent. This encoded value should be sent as the value of the `"thirdPartyTokenData"` parameter, along with `"thirdPartyTokenType"` set to `"GOOGLE_PAY"`, and all other necessary parameters according to the integration documentation on the `"/api/1.6/auth"` endpoint.

Example:

```

POST /api/1.6/auth
Headers:
Content-Type: application/json
Accept: application/json

Body:
{
    "storeID": "602",
    "orderNumber": "e5b913",
    "language": "hr",
    "amount": "100.23",
    "currency": "EUR",
    "cart": "Shoes",
    "cardholderName": "Pero",
    "cardholderSurname": "Peric",
    "cardholderEmail": "peroperic@gmail.com",
    "cardholderIp": "234.234.234.432",
    "cardholderCountryCode": "HR",
    "userAgent": "Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 Safari/537.36",
    "thirdPartyTokenType": "GOOGLE_PAY",
    "thirdPartyTokenData": "eyJzaWduYXR1cmUiOjJNRV1DSVFEZi85QXc4NE41VXBPFbVMTuTStRUIptUDRGbTRMYSticE9udmlaZXgyd0loQUtBM1Q3UUxKNDRuNHNqbk5Yb3ZKdCtvZ2VXTUZIR2N0TWFQOGtpcS93czUiLCJpbnRlcmlZGlhdGVTaWduaW5nS2V5Ijp7InNpZ25lZEtleSI6IntcImtleVZhBHV1XCI6XCJNRmt3RXdZSEtvWk16ajBDQVFZSUtvWk16ajBEQVFjRFFnQUVpWGY2bkR5eXYxL2lQcThZa1prMGJ50HhwM1ZteGpGVNTnt0VhZ0WhxL3N5cG1VYjRaYVhBNTN1dnNNVEJns09aNVJSL1hURHzQ0N1ld1FmRE1ORWFzR1xcdTAwM2RcXHUwMDNkXCIsXCJrZX1FeHBpcmF0aW9uXCI6XCIxNzE1NjU0NDA1NzM2XCJ9IiwiC2lnbmF0dXJ1cyI6WyJNRVFDSDUNSV3ZnT1ZY0JuVGt1M1Iv0U9Fd3BMNHZmSjh3Rzd1NkZMV E93L3c4My9BaUJIQmd1Y09oVTZ0K2p4S016Tm9IRWEySGdXOVNiM1h1S1Zhd19oeW52b2VRXHUwMDNkXHUwMDNkI119LCJwcm90b2NvbFZlcnNpb24iOjFQ3YyIiwiC2lnbmVktWVzc2FnZSI6IntcImVuY3J5cHR1ZE11c3NhZ2VcIjp cIjdBTWxuY2NBb3AvSSszU3FqOUJ6d0ZNvnB6dXZEen1YZktKbUVwaXzsNUpGYmh2eW5QRWx0Q21obEuVsm80MVnn T1JRQ250N2xPdFY4bjZBaW840U1yU21SejB1RFRqZTZHaWx3aFNYSGdhcm12cmNDd2RBNGp3SDRsV1pHWDJkWFJql ytITWp1WmxhQkYxZDhLVGxTYTY2TURibmJISHG3YVRZOGx6Y1BXUTN5b2JUVHplRzJCWjAyRzRXNXhWbWVScW1GL0 Y1dGJxeXhpMUFGvkMvMjFRL1pCckN1MH14V09hcTRsWTJzRj1zNnFr0DFqZ312b09WSkQ0UGpQRHdRd3pMbGdxV25 ONE1ValM1ZjQxcXdqSjZr0WZSWDB0L0FvYko2YnhNRkNtL05qREY1Yy9vRzNhQ1ZRDJEuk9hdypT01Nc2xnQkNW bFNoMk91RW82RzcrQ0ZzSDRWSV1tWE9xRW8wYXhDdkdVU3YrcXZ0SFV1TGRoMvh0WZvcnVWdkludVY2Nm1HWThNe jZaSVdGW11pNklzV1JWT3Yxa01DODVhSHE1QThHVmEzTnoxOEpCQk8wZ1B5WUtxdzdYZmwzdmduL0Rvb0RmMndQtisvOEphL3VONkJJVVMyQ0x3QjFZV1RXTmIwV31Ebmh3ZmNqMzRFV2ZvNjVuem1pcDRNTHJnMnF4eVR5dW5tYWxTZUdaUW1UL3dNbkdYt0t6ckZkbDhnXFx1MDAzzFwiLFwiZXBw11cmFsUHVibG1js2V5XC16XCJCSkpXTkRnZi9TSzBJ NzYzdj12dFdRdTfYv3htVloyY3VWODRzMC9PdHyVTwT1eUtyOXNPbxZqdFRBTGvOM1NvdGFzNmNKbVJIdW51N1JaM"

```

```
TRNU2pKw1FcXHUwMDNkXCIsXCJ0YWdcIjpcIitwTCtjUUMyL1h1cDYvWU9vQURBbk4ybW52SUNRV3ZiUEJueWNsaUFseVlcXHUwMDNkXCJ9In0=",
  "requireComplete": false,
  "signature": "070168fe121daa434a98ec33a29904d6f3a1cfac561232ed1414869f72529b2a"
}
```

Note: In this case, the parameters "cardNumber", "ccMonth" and "ccYear" should be omitted.

[Secure Customer Authentication \(SCA/3DS\) and PSD2](#)

Google Pay supports CRYPTOGRAM_3DS authentication method that is SCA (Strong Customer Authentication) compliant, thus avoiding the need for additional 3DS verification.