



1

Document Identifier: DSP0239

2

Date: 2024-07-22

3

Version: 1.11.1

4

Management Component Transport Protocol (MCTP) IDs and Codes

5

Supersedes: 1.11.0

6

Document Class: Normative

7

Document Status: Published

8

Document Language: en-US

Copyright Notice

Copyright © 2009, 2012, 2015, 2017, 2019–2022, 2024 DMTF. All rights reserved.

- 9 DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability. Members and non-members may reproduce DMTF specifications and documents, provided that correct attribution is given. As DMTF specifications may be revised from time to time, the particular version and release date should always be noted.
- 10 Implementation of certain elements of this standard or proposed standard may be subject to third-party patent rights, including provisional patent rights (herein “patent rights”). DMTF makes no representations to users of the standard as to the existence of such rights, and is not responsible to recognize, disclose, or identify any or all such third-party patent right owners or claimants, nor for any incomplete or inaccurate identification or disclosure of such rights, owners, or claimants. DMTF shall have no liability to any party, in any manner or circumstance, under any legal theory whatsoever, for failure to recognize, disclose, or identify any such third-party patent rights, or for such party’s reliance on the standard or incorporation thereof in its product, protocols, or testing procedures. DMTF shall have no liability to any party implementing such standard, whether such implementation is foreseeable or not, nor to any patent owner or claimant, and shall have no liability or responsibility for costs or losses incurred if a standard is withdrawn or modified after publication, and shall be indemnified and held harmless by any party implementing the standard from any and all claims of infringement by a patent owner for such implementations.
- 11 For information about patents held by third parties which have notified DMTF that, in their opinion, such patents may relate to or impact implementations of DMTF standards, visit <https://www.dmtf.org/about/policies/disclosures>.
- 12 This document’s normative language is English. Translation into other languages is permitted.

CONTENTS

1 Foreword	4
1.1 Acknowledgments	4
2 Introduction	5
2.1 Document conventions	5
2.1.1 Typographical conventions	5
2.1.2 ABNF usage conventions	5
2.1.3 Reserved and unassigned values	5
2.1.4 Byte ordering	6
2.1.5 Notation	6
3 Scope	7
4 Normative references	8
5 Terms and definitions	11
6 Symbols and abbreviated terms	12
7 MCTP Message Type codes	13
8 MCTP physical medium identifiers	15
9 MCTP physical transport binding identifiers	17
10 MCTP host interface type identifiers	18
11 Host interface protocol identifiers	19
12 ANNEX A (informative) Notation	20
13 ANNEX B (informative) Change Log	21
14 Bibliography	22

14 **1 Foreword**

15 The *Management Component Transport Protocol (MCTP) IDs and Codes* (DSP0239) was prepared by the PMCI Working Group.

16 DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability.

17 **1.1 Acknowledgments**

18 DMTF acknowledges the following individuals for their contributions to this document:

19 **Editors:**

- Hemal Shah — Broadcom Inc.
- Tom Slaight — Intel Corporation
- Philip Chidester — Dell Inc.
- Edward Newman — Hewlett Packard Enterprise

20 **Contributors:**

- Alan Berenbaum — SMSC
- Patrick Caporale — Lenovo
- Kelly Couch — Intel Corporation
- Samer El-Haj-Mahmoud — ARM, Inc.
- Yuval Itkin — NVIDIA Corporation
- Janusz Jurski — Intel Corporation
- Ed Klodnicki — IBM
- Patrick Kutch — Intel Corporation
- Eliel Louzoun — Intel Corporation
- Jose Marinho — Arm Limited
- Balaji Natrajan — Microchip Technology Inc.
- Chandra Nelogal — Dell Technologies
- Zvika Perry — Cavium
- Bob Stevens — Dell Technologies
- Supreeth Venkatesh — Advanced Micro Devices

21 **2 Introduction**

22 This document presents a collection of IDs and codes that are used across the Management Component Transport Protocol (MCTP) and transport binding specifications.

23 The MCTP defines a communication model intended to facilitate communication between:

- Management controllers and other management controllers
- Management controllers and management devices

24 The communication model includes a message format, transport description, message exchange patterns, and configuration and initialization messages.

25 The *MCTP Base Protocol Specification* ([DSP0236](#)) describes the protocol and commands used for communication within and initialization of an MCTP network. Associated with the *Base Protocol Specification* are transport binding specifications that define how the MCTP base protocol and MCTP control commands are implemented on a particular physical transport type and medium.

26 **2.1 Document conventions**

27 **2.1.1 Typographical conventions**

28 The following typographical conventions are used in this document:

- Document titles are marked in *italics*.
- ABNF rules are in monospaced font.

29 **2.1.2 ABNF usage conventions**

30 Format definitions in this document are specified using ABNF (see [RFC5234](#)), with the following deviations:

- Literal strings are to be interpreted as case-sensitive Unicode characters, as opposed to the definition in [RFC5234](#) that interprets literal strings as case-insensitive US-ASCII characters.

31 **2.1.3 Reserved and unassigned values**

32 Unless otherwise specified, any reserved, unspecified, or unassigned values in enumerations or other numeric ranges are reserved for future definition by DMTF.

33 Unless otherwise specified, numeric or bit fields that are designated as reserved shall be written as 0 (zero) and ignored when read.

34 2.1.4 Byte ordering

35 Unless otherwise specified, byte ordering of multi-byte numeric fields or bit fields is “Big Endian” (that is, the lower byte offset holds the most significant byte, and higher offsets hold lesser significant bytes).

36 2.1.5 Notation

37 See [Annex A](#) for notation.

38 **3 Scope**

39 The *Management Component Transport Protocol (MCTP) IDs and Codes* document provides a consolidated list of major IDs and codes used across the MCTP protocol and transport binding specifications. Only IDs and codes that are required by a particular specification are to be included in that specification. IDs and code values for other specifications are not to be repeated for reference. Instead, provide a reference to this specification.

40 The following is an overview of the different sets of codes and identifiers (enumeration values) that are specified in this document:

- **MCTP message type codes**

41 Collection of the message type codes used for MCTP messages

- **MCTP physical medium identifiers**

42 Collection of identifiers for the different types of physical media that have been defined

- **MCTP physical transport binding identifiers**

43 Collection of identifiers for the specifications that define the operation, formatting, addressing, and encapsulation of MCTP packets over different physical media

- **MCTP host interface type identifiers**

44 Collection of identifiers for the different physical interfaces used to transfer MCTP packets between the host and the management controller

45 **4 Normative references**

46 The following referenced documents are indispensable for the application of this document. For dated or versioned references, only the edition cited (including any corrigenda or DMTF update versions) applies. For references without a date or version, the latest published edition of the referenced document (including any corrigenda or DMTF update versions) applies.

47 DMTF specifications are available at https://www.dmtf.org/standards/published_documents.

48 DMTF DSP0004, *Common Information Model (CIM) Metamodel 3.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0004_3.0.pdf

49 DMTF DSP0134, *SMBIOS Reference Specification 3.7* https://www.dmtf.org/sites/default/files/standards/documents/DSP0134_3.7.pdf

50 DMTF DSP0222, *Network Controller Sideband Interface (NC-SI) Specification 1.2* https://www.dmtf.org/sites/default/files/standards/documents/DSP0222_1.2.pdf

51 DMTF DSP0223, *Generic Operations Specification 2.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0223_2.0.pdf

52 DMTF DSP0233, *Management Component Transport Protocol (MCTP) I3C Transport Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0233_1.0.pdf

53 DMTF DSP0234, *CXL™ Fabric Manager API over MCTP Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0234_1.0.pdf

54 DMTF DSP0235, *NVMe (NVM Express) Management Messages over MCTP Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0235_1.0.pdf

55 DMTF DSP0236, *Management Component Transport Protocol (MCTP) Base Specification 1.3* https://www.dmtf.org/sites/default/files/standards/documents/DSP0236_1.3.pdf

56 DMTF DSP0237, *Management Component Transport Protocol (MCTP) SMBus/I²C Transporting Binding Specification 1.2* https://www.dmtf.org/sites/default/files/standards/documents/DSP0237_1.2.pdf

57 DMTF DSP0238, *Management Component Transport Protocol (MCTP) PCIe VDM Transport Binding Specification 1.3* https://www.dmtf.org/sites/default/files/standards/documents/DSP0238_1.3.pdf

58 DMTF DSP0241, *PLDM Over MCTP Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0241_1.0.pdf

59 DMTF DSP0253, *MCTP Serial Transport Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0253_1.0.pdf

60 DMTF DSP0254, *MCTP KCS Transport Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0254_1.0.pdf

61 DMTF DSP0261, *NC-SI Over MCTP Binding Specification 1.3* https://www.dmtf.org/sites/default/files/standards/documents/DSP0261_1.3.pdf

- 62 DMTF DSP0275, *Security Protocol and Data Model (SPDM) over MCTP Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0275_1.0.pdf
- 63 DMTF DSP0276, *Secured Messages using SPDM over MCTP Binding Specification 1.1* https://www.dmtf.org/sites/default/files/standards/documents/DSP0276_1.1.pdf
- 64 DMTF DSP0281, *CXL™ Type 3 Device Component Command Interface over MCTP Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0281_1.0.pdf
- 65 DMTF DSP0283, *Management Component Transport Protocol (MCTP) over Universal Serial Bus (USB) Transport Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0283_1.0.pdf
- 66 DMTF DSP0284, *Management Component Transport Protocol (MCTP) Memory-Mapped BMC Interface (MMBI) Transport Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0284_1.0.pdf
- 67 DMTF DSP0290, *Management Component Transport Protocol (MCTP) UCle™ Transport Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0290_1.0.pdf
- 68 DMTF DSP0291, *PCIe Management Interface (PCIe-MI) over MCTP Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0291_1.0.pdf
- 69 DMTF DSP0292, *Management Component Transport Protocol (MCTP) PCC Transport Binding Specification 1.0* https://www.dmtf.org/sites/default/files/standards/documents/DSP0292_1.0.pdf
- 70 DMTF DSP1001, *Management Profile Usage Guide 1.2* https://www.dmtf.org/sites/default/files/standards/documents/DSP1001_1.2.pdf
- 71 IETF RFC5234, *ABNF: Augmented BNF for Syntax Specifications*, January 2008 <https://tools.ietf.org/html/rfc5234>
- 72 ISO/IEC Directives, Part 2, *Rules for the structure and drafting of ISO and IEC documents*, <https://www.iso.org/sites/directives/current/part2/index.xhtml>
- 73 PCI-SIG, *PCI Express Base Specification 1.1*, PCIe V1.1, March 28, 2005 <https://pcisig.com/specifications>
- 74 PCI-SIG, *PCI Express Base Specification 2.1*, PCIe V2.1, March 4, 2009 <https://pcisig.com/specifications>
- 75 PCI-SIG, *PCI Express Base Specification 3.1a*, PCIe V3.1a, December 7, 2015 <https://pcisig.com/specifications>
- 76 PCI-SIG, *PCI Express Base Specification 4.0*, PCIe V4.0, October 5, 2017 <https://pcisig.com/specifications>
- 77 PCI-SIG, *PCI Express Base Specification 5.0*, PCIe V5.0, May 28, 2019 <https://pcisig.com/specifications>
- 78 PCI-SIG, *PCI Express Base Specification 6.2*, PCIe V6.2, February 12, 2024 <https://pcisig.com/specifications>
- 79 NXP Semiconductors UM10204, *I²C-bus specification and user manual*, Rev. 6, 4 April 2014 <https://web.archive.org/web/20210813122132/https://www.nxp.com/docs/en/user-guide/UM10204.pdf>
- 80 SMBus, *System Management Bus (SMBus) Specification v2.0*, SMBus, 2000 <http://smbus.org/specs/smbus20.pdf>
- 81 SMBus, *System Management Bus (SMBus) Specification v3.0*, SMBus, December 20, 2014 http://smbus.org/specs/SMBus_3_0_20141220.pdf
- 82 SMBus, *System Management Bus (SMBus) Specification v3.1*, SMBus, March 19, 2018 http://smbus.org/specs/SMBus_3_1_20180319.pdf

- 83 *MIPI Alliance Specification for I3C® (Improved Inter Integrated Circuit)*, version 1.0, MIPI Alliance, Inc., 23 December 2016 (Adopted 31 December 2016) <https://www.mipi.org/specifications/i3c-sensor-specification>
- 84 *MIPI Alliance Specification for I3C BasicSM (Improved Inter Integrated Circuit – Basic)*, version 1.0, MIPI Alliance, Inc., 19 July 2018 (Adopted 8 October 2018) <https://resources.mipi.org/mipi-i3c-basic-v1-download>
- 85 *CXL™ 3.1 Specification* <https://www.computeexpresslink.org/download-the-specification>
- 86 *Intelligent Platform Management Interface Specification Second Generation*, v2.0, April 21, 2015
<https://www.intel.com/content/dam/www/public/us/en/documents/specification-updates/ipmi-intelligent-platform-mgt-interface-spec-2nd-gen-v2-0-spec-update.pdf>
- 87 *Private Enterprise Numbers*, Internet Assigned Numbers Authority (IANA) <https://www.iana.org/assignments/enterprise-numbers/enterprise-numbers>

88 **5 Terms and definitions**

- 89 In this document, some terms have a specific meaning beyond the normal English meaning. Those terms are defined in this clause.
- 90 The terms “shall” (“required”), “shall not”, “should” (“recommended”), “should not” (“not recommended”), “may”, “need not” (“not required”), “can” and “cannot” in this document are to be interpreted as described in [ISO/IEC Directives, Part 2](#), Clause 7. The terms in parentheses are alternatives for the preceding term, for use in exceptional cases when the preceding term cannot be used for linguistic reasons. Note that [ISO/IEC Directives, Part 2](#), Clause 7 specifies additional alternatives. Occurrences of such additional alternatives shall be interpreted in their normal English meaning.
- 91 The terms “clause”, “subclause”, “paragraph”, and “annex” in this document are to be interpreted as described in [ISO/IEC Directives, Part 2](#), Clause 6.
- 92 The terms “normative” and “informative” in this document are to be interpreted as described in [ISO/IEC Directives, Part 2](#), Clause 3. In this document, clauses, subclauses, or annexes labeled “(informative)” do not contain normative content. Notes and examples are always informative elements.
- 93 The terms defined in [DSP0004](#), [DSP0223](#), and [DSP1001](#) apply to this document.
- 94 Refer to [DSP0236](#) for terms and definitions that are used in the MCTP specifications.

95 **6 Symbols and abbreviated terms**

96 Refer to [DSP0236](#) for symbols and abbreviated terms that are used in the MCTP specifications.

97 7 MCTP Message Type codes

98 [Table 1](#) defines the values for the Message Type field for different message types transported through MCTP.

99 NOTE A device that supports a given message type might not support that message type equally across all busses that connect to the device.

100

Table 1 — MCTP Message Types

Message Type	Message Type Code	Description
MCTP Control	0x00	Messages used to support initialization and configuration of MCTP communication within an MCTP network, as specified in DSP0236
Platform Level Data Model (PLDM)	0x01	Messages used to convey Platform Level Data Model (PLDM) traffic over MCTP, as specified in DSP0241 .
NC-SI over MCTP	0x02	Messages used to convey NC-SI Control traffic over MCTP, as specified in DSP0261 .
Ethernet over MCTP	0x03	Messages used to convey Ethernet traffic over MCTP as specified in DSP0261 .
NVM Express Management Messages over MCTP	0x04	Messages used to convey NVM Express (NVMe) Management Messages over MCTP, as specified in DSP0235 .
SPDM over MCTP	0x05	Messages used to convey Security Protocol and Data Model Specification (SPDM) traffic over MCTP, as specified in DSP0275 .
Secured Messages	0x06	Messages used to convey <i>Secured Messages using SPDM over MCTP Binding Specification</i> traffic, as specified in DSP0276 .
CXL FM API over MCTP	0x07	Messages used to convey <i>CXL™ Fabric Manager API over MCTP Binding Specification</i> traffic as specified in DSP0234 .
CXL CCI over MCTP	0x08	Messages used to convey <i>CXL™ Type 3 Device Component Command Interface over MCTP Binding Specification</i> traffic as specified in DSP0281 .
PCIe-MI over MCTP	0x09	Messages used to convey <i>PCIe Management Interface (PCIe-MI) over MCTP Binding Specification</i> traffic as specified in DSP0291 .
Vendor Defined – PCI	0x7E	Message type used to support VDMs where the vendor is identified using a PCI-based vendor ID. The specification of the format of this message is given in DSP0236 . Otherwise, the message body content is specified by the vendor, company, or organization identified by the given vendor ID.

Message Type	Message Type Code	Description
Vendor Defined – IANA	0x7F	Message type used to support VDMs where the vendor is identified using an IANA-based vendor ID. This format uses a number from the <i>Private Enterprise Numbers</i> table that is assigned and maintained by the Internet Assigned Numbers Authority (IANA) as the means of identifying a particular vendor, company, or organization. The specification of the format of this message is given in DSP0236 . Otherwise, the message body content is specified by the vendor, company, or organization identified by the given vendor ID.
Reserved	all other	Reserved

101 8 MCTP physical medium identifiers

102 [Table 2](#) defines a set of numbers that correspond to different media types that can be used with MCTP. The identifier is primarily used to identify which physical addressing format is used for MCTP packets on the bus.

103 NOTE PCIe revision numbers are intended to indicate specification compatibility, not bit transfer rate or throughput.

104 **Table 2 — MCTP Physical Medium Identifiers**

Physical Media Identifier	Description
0x00	Unspecified
0x01	SMBus 2.0 100 kHz compatible
0x02	SMBus 2.0 or I ² C 100 kHz compatible
0x03	I ² C 100 kHz compatible (Standard-mode)
0x04	SMBus 3.0 or I ² C 400 kHz compatible (Fast-mode)
0x05	SMBus 3.0 or I ² C 1 MHz compatible (Fast-mode Plus)
0x06	I ² C 3.4 MHz compatible (High-speed mode)
0x07	Reserved
0x08	PCIe revision 1.1 compatible
0x09	PCIe revision 2.0 compatible
0x0A	PCIe revision 2.1 compatible
0x0B	PCIe revision 3.x compatible
0x0C	PCIe revision 4.x compatible
0x0D	PCIe revision 5.x compatible or CXL 1.x / 2.x compatible
0x0E	PCIe revision 6.x Non-Flit Mode compatible
0x0F	PCI compatible (PCI 1.0, 2.0, 2.1, 2.2, 2.3, 3.0, PCI-X 1.0, PCI-X 2.0)
0x10	USB 1.1 compatible
0x11	USB 2.0 compatible
0x12	USB 3.0 compatible
0x13:0x17	Reserved
0x18	NC-SI over RBT (A physical interface based on RMII as defined in DSP0222)

Physical Media Identifier	Description
0x19	Management Component Transport Protocol (MCTP) UCle™ Transport Binding Specification DSP0290
0x1A	Management Component Transport Protocol (MCTP) PCC Transport Binding Specification DSP0292
0x1B:0x1F	Reserved
0x20	KCS ¹ Legacy (Fixed Address Decoding)
0x21	KCS ¹ over PCI (Base Class 0xC0 Subclass 0x01)
0x22	Serial Host ² Legacy (Fixed Address Decoding)
0x23	Serial Host ² over PCI (Base Class 0x07 Subclass 0x00)
0x24	Asynchronous Serial ³ (Between MCs and IMDs)
0x25:0x2F	Reserved
0x30	I3C Basic compatible
0x31:0x3F	Reserved
0x40	PCIe revision 6.x Flit Mode Compatible or CXL 3.X compatible
0x41:0xFF	Reserved

1. Keyboard Controller Style Interface – refer to [DSP0254](#).
2. Serial Host refers to a register based UART interface.
3. Asynchronous Serial refers to an 8-bit asynchronous bi-directional serial transmission media where characters are transmitted independently (i.e., each frame carries 8-bits of data).

105 9 MCTP physical transport binding identifiers

106 [Table 3](#) defines a set of numbers that correspond to different media types that can be used with MCTP. The identifier indicates which physical addressing format is used for MCTP packets on the bus.

107 **Table 3 — MCTP Physical Transport Binding Identifiers**

MCTP Physical Transport Binding Identifier	Description
0x00	Reserved
0x01	MCTP over SMBus (DSP0237)
0x02	MCTP over PCIe VDM (DSP0238)
0x03	MCTP over USB (DSP0283)
0x04	MCTP over KCS (DSP0254)
0x05	MCTP over Serial (DSP0253)
0x06	MCTP over I3C (DSP0233)
0x07	MCTP over MMBI (DSP0284)
0x08	MCTP over PCC (DSP0292)
0x09	MCTP over UCle (DSP0290)
0xFF	Vendor defined NOTE: A vendor-defined transport binding must meet the requirements in DSP0236 (in particular, when being bridged to or from standard MCTP transport binding and media combinations).
All other	Reserved

108 10 MCTP host interface type identifiers

109 The SMBIOS specification [DSP0134](#) reserves a range of host interface type identifiers 0x00 through 0x3F for use by this specification. [Table 4](#) defines a set of numbers that correspond to different MCTP host interface types that can be used with MCTP. The identifier indicates which physical interface to transfer MCTP packets between the host and the management controller.

110 **Table 4 — MCTP Host Interface Type Identifiers**

MCTP Host Interface Type Identifier	Description
0x00	Reserved
0x01	Reserved
0x02	KCS: Keyboard Controller Style – refer to the section titled “Keyboard Controller Style (KCS) Interface” of IPMI
0x03	8250 UART Register Compatible
0x04	16450 UART Register Compatible
0x05	16550/16550A UART Register Compatible
0x06	16650/16650A UART Register Compatible
0x07	16750/16750A UART Register Compatible
0x08	16850/16850A UART Register Compatible
0x09	I2C / SMBUS
0x0A	I3C
0x0B	PCIe VDM
0x0C	MMBI
0x0D	PCC
0x0E	UCIe
0x0F	USB
0x10:0x3F	Reserved
all other	Assigned by the SMBIOS specification (DSP0134)

111 **11 Host interface protocol identifiers**

112 In earlier versions of this specification, this section contained a table of host interface protocol identifiers. That table has been moved to the description of the Type 42 record in the SMBIOS specification ([DSP0134](#)) version 3.1.1 or later.

113 12 ANNEX A (informative) Notation

114 Examples of notations used in this document are as follows:

2:N	In field descriptions, this will typically be used to represent a range of byte offsets starting from byte two and continuing to and including byte N. The lowest offset is on the left, the highest is on the right.
(6)	Parentheses around a single number can be used in message field descriptions to indicate a byte field that may be present or absent.
(3:6)	Parentheses around a field consisting of a range of bytes indicates the entire range may be present or absent. The lowest offset is on the left, the highest is on the right.
<u>PCIe</u>	Underlined, blue text is typically used to indicate a reference to a document or specification called out in the “Normative References” section or to items hyperlinked within the document.
rsvd	Abbreviation for “reserved.” Case insensitive.
[4]	Square brackets around a number are typically used to indicate a bit offset. Bit offsets are given as zero-based values (that is, the least significant bit (LSb) offset = 0).
[7:5]	A range of bit offsets. The most significant bit is on the left, the least significant bit is on the right.
1b	The lower case “b” following a number consisting of 0s and 1s is used to indicate the number is being given in binary format.
0x12	A leading “0x” is used to indicate a number given in hexadecimal format.

13 ANNEX B (informative) Change Log

Version	Date	Description
1.0.0	2009-07-28	
1.1.0	2009-11-03	Added Host Interface Type Identifiers. Added Host Interface Protocol Identifiers. Added reference to NC-SI and added clarification on physical medium identifiers.
1.2.0	2012-06-04	Added Ethernet over MCTP message type. Clarified the description of NC-SI over MCTP and PLDM over MCTP. Added I2C fast plus and high-speed physical medium identifiers. Clarified RMII/NC-SI physical medium identifier description. Fixed references.
1.3.0	2015-03-06	Added message type NVMe (NVM Express) Management Messages over MCTP. Updated references.
1.4.0	2017-01-11	Limited host interface type identifiers to the range 0x00:0x3F. Moved the host interface protocol identifier table to the SMBIOS specification. Updated references.
1.5.0	2017-11-16	Updated contributors and references. Added support for SMBus 3.0 and PCIe Gen 4.
1.6.0	2019-06-04	Added an MCTP Message Type for SPDM. Added an MCTP physical medium identifiers for PCIe revision 5.0, and I3C.
1.7.0	2020-05-26	Added an MCTP Message Type for MCTP Security using SPDM. Added an MCTP physical medium identifiers for CXL.
1.7.1	2020-12-07	Update the contributor list. Correct the I3C entries in the MCTP physical medium identifiers table.
1.7.2	2021-04-05	Removed separate entry for CXL from physical medium identifiers table since CXL uses PCIe as the physical medium. Added CXL compatible reference to physical medium identifier table PCIe 5.x row. Updated to comply with ISO guidelines.
1.8.0	2021-01-12	Added CXL FM API over MCTP to Message Type table. Add MCTP over I3C to MCTP physical transport binding identifiers table.
1.9.0	2021-11-09	Added I2C/SMBUS, I3C, and PCIe VDM to the MCTP host interface type identifiers table. Added CXL CCI over MCTP to the Message Type table. Updated references.
1.10.0	2022-10-28	Added MMBI identifiers for physical transport binding, and host interface type.
1.11.0	2024-02-05	Added 0xE as PCIe 6.X Flit Mode Compatible identifier. Added ID for MMBI. Fixed broken links. Added UCle physical medium. Added message type for PCIe-MI over MCTP. Added media type identifier for MCTP over PCC. Added physical transport IDs for MCTP over PCC and MCTP over UCle. Added host interface types PCC, UCle, and USB.
1.11.1	2024-07-22	Updated the PCIe 6.X opcodes. 0xE is Non-Flit mode, 0x40 is a new value for Flit Mode.

116

14 Bibliography

117

RMII Consortium, *Reduced Media Independent Interface (RMII) Specification v1.2*, RMII, March 20, 1988,
http://ebook.pldworld.com/_eBook/-Telecommunications,Networks-/TCPIP/RMII/rmii_rev12.pdf