

One Talk CP925 IP Conference Phone

Specifications



**4" Multi-touch
Screen**



**Bluetooth
Wireless
Microphone
(optional accessory)**



**Pairing via
Bluetooth**



The One Talk CP925 IP conference phone is an advanced, high-definition conference phone. It is specifically designed for small to medium conference rooms. The CP925 is built with acoustic fabric, which is impervious to any accidental liquid spills. The fingerprint-proof touch LCD screen makes it easy for everyone to control the many features of the phone. There are 7 built-in microphones to provide a clear and natural conference call experience. You can also connect CP925 to your mobile device via Bluetooth or USB.

- 4" 240 x 320 TFT color screen with intuitive user interface
- Up to 20-hours of talk time
- Up to 160-hour standby time
- Quick charge feature (10-minute charge time for 2-hour talk time)
- HD audio and noise cancellation
- Headset connection via Bluetooth or 3.5 mm jack
- Vibration alarm

Key features and benefits

Efficient design, easy-to-use user interface

The One Talk CP925 IP Conference Phone has a 4-inch touch screen, an ultra-thin body for a low-profile table or desktop fit and an ingenious hidden wiring slot – perfect for any small to medium business conference rooms.

HD audio, smooth communication

The CP925 Y-shaped design comes with 6 microphones for sound reception and 1 microphone for noise cancellation. Its 20-foot and 360° omni-direction voice detection provides users with clear and natural voice conference experience.

Rich features and high expansibility

The CP925 enables multiple participants from different locations to communicate smoothly and reduce costs for your company. You can also connect CP925 to your mobile devices through Bluetooth or USB port. The CPW25 Bluetooth wireless expansion microphone provides 10-foot sound pickup range so everyone's voice can be heard.

Audio features

- Optimal HD audio
- Yealink Noise Proof Technology
- Smart Noise Filtering
- 20-foot microphone pickup range
- Apply to small to medium conference room
- Built-in 6-microphone array, 360-degree voice pickup
- Built-in 1-microphone array, decrease noise
- Loudspeaker
- Frequency: 100-20,000 Hz
- Volume: 94dB at 0.5-m peak volume
- 56mm diameter and 5w speaker
- Full-duplex speakerphone with AEC
- Echo cancellation tail length is up to 320ms
- Background noise suppression
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO

Phone features

- 1 SIP account
- Call hold, mute, DND, call recording
- 5-way conference call
- Redial, call waiting, 911 emergency call
- Call forward, call transfer
- Ring tone selection/import/delete
- Set date time manually or automatically
- Volume adjustment
- Pairing via Bluetooth
- Create meeting directly
- Active speaker

Directory

- Local phonebook up to 1,000 entries
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded
- Block list

Features

- Intercom
- Anonymous call
- Anonymous call rejection
- Voice mail
- Distinctive ringtone
- Call pickup

Display

- 4" 480x800 capacitive touch screen
- Volume key
- Home button

Interface

- 1 x RJ45 10/100M ethernet port
- Built-in Wi-Fi (2.4GHz/5GHz, 802.11a/b/g/n)
- Built-in Bluetooth 4.2
- Power over Ethernet (IEEE 802.3af), class 3
- 1 x USB 2.0 Type-C device port
- 1 x Security slot

Network and security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server redundancy supported
- IPv4/IPv6
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice encryption
- Transport Layer Security (TLS1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Adb encryption authenticated

- Digest authentication using MD5/SHA1/SHA224/SHA256/SHA384/SHA512
- WPA2/WPA3
- Secure boot
- GARP (Generic Attribute Registration Protocol)

Other physical features

- Color: Black
- External Yealink PoE adapter (optional)
- Power consumption (PSU): 3.5W-11W
- Power consumption (PoE): 4W-12W
- Dimension (W*D*H): 11.2 inch. x 11.39 inch. x 2.32 inch.
- Operating humidity: 10-90%
- Storage temperature: 14-104°F

Package features

- Package contents:
 - IP conference phone
 - Ethernet Cable (7.5m CAT5E UTP cable)
 - Power adapter
 - Quick start guide

Compliance



For additional support information, please visit [verizon.com/support/one-talk](https://www.verizon.com/support/one-talk)