One Talk T53W IP Desk Phone

Prime business phone for better productivity









Adjustable HD Audio Screen

Built-in Bluetooth

USB 2.0

Built-in

Wi-Fi

The T53W is an easy-to-use business phone that delivers optimum desktop efficiency and productivity. Advanced features include: 3.7-inch graphical LCD screen; Bluetooth 4.2; dual band 2.4G/5G Wi-Fi; USB 2.0 port for call recording, wired/wireless USB headset or up to three EXP50 expansion modules.

Key features and benefits

User friendly

The T53W IP Phone features an adjustable 3.7-inch graphical LCD that you can readily adjust to a comfortable viewing angle. The T53W is coupled with the latest version of Yealink Optimal HD Voice technologies, including Yealink Acoustic Shield technology that effectively eliminates background noises, and delivers crystal-clear voice. Meanwhile, complying with the latest Hearing Aid Compatibility (HAC) regulations. Its Hearing Aid Compatibility (HAC)-compliant handset allows people with hearing loss to hear more clearly.

High expandability

A built-in USB 2.0 port allows you to enjoy USB call recording via a USB flash drive. Via this USB port, you also can connect wired/wireless USB headset, and connect up to 3 expansion modules EXP50 which can be programmed with up to 180 paperless DSS keys.

Efficient installation and provisioning


The T53W supports Zero Touch Provisioning without any complex manual settings.

What you get with the One Talk T53W Desk Phone

- 3.7" 360x160-pixel graphical LCD with backlight
- Adjustable LCD screen
- Built-in Bluetooth 4.2
- Built-in dual band 2.4G/5G Wi-Fi (802.11a/b/g/n/ac)
- USB 2.0 port for USB recording, wired/wireless USB headsets and EXP50
- Dual-port gigabit Ethernet
- PoE-compliant support
- HAC handset
- · Wall-mountable

Specifications





Specifications

Audio features

- · HD voice: HD handset, HD speaker
- · Hearing aid compatible (HAC) handset
- Acoustic shield
- Smart Noise Filtering
- · Audio codec: AMR-WB and AMR-NB
- DTMF: In-band, out-of-band (RFC 2833) and SIP INFO
- · Full-duplex hands-free speakerphone

Phone features

- · Call hold, mute, DND, redial, auto answer
- · One-touch speed dial, call forward, call waiting, call transfer
- 6-way conferencing
- Ring tone selection
- · Set date time manually or automatically
- · Built-in dual band Wi-Fi:
 - Network standard: IEEE802.11a/b/g/n/ac
 - Transmission rate: Up to 433Mbps (dynamic)
 - Frequency range: 2.4 GHz/5.0 GHz
- Built-in Bluetooth 4.2 for:
 - Bluetooth headsets
 - Bluetooth call
- USB port (2.0 compliant) for:
 - Wired/wireless USB headset
 - USB call recording through USB flash drive
 - Expansion module EXP50 (up to 3)
 - Wireless Headset Adapter EHS40
- Enhanced DSS key

Directory

- · Local phonebook with up to 1000 entries
- Black list
- Remote phonebook
- · Smart dialing
- Phonebook search/import/export

USB 2.0

Call history: dialed/received/missed/forwarded

Advanced features

• Busy Lamp Field (BLF), Bridged Line Appearance (BLA)

USB Flash Drive

- · Anonymous call, anonymous call rejection
- Voice mail
- · Call park, call pickup

Display and indicator

- 3.7" 360x160-pixel graphical LCD with backlight
- · LED for call and message waiting indication
- · Dual-color (red or green) illuminated LEDs for line status
- · Intuitive user interface with icons and soft keys
- · Caller ID with name and number
- · Power saving

Feature keys

- · 8 line keys with LED
- 8 line keys can be programmed up to 21 various features (3-page view)
- 5 features keys:
 - mute, headset, message, redial, hands-free speakerphone



- · 4 context-sensitive "soft" keys
- 6 navigation keys
- Volume control keys
- Illuminated mute/headset/hands-free speakerphone key

Interface

- Dual-port gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 2
- 1 x USB port (2.0 compliant)
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

Management

- Phone lock for personal privacy protection
- Reset to factory, reboot

Network and security

- SIP v1 (RFC2543), v2 (RFC3261)
- · NAT traversal: STUN mode
- · Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP/PPPoE
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- · SRTP for voice
- Transport Layer Security (TLS1.2)
- HTTPS certificate manager
- · AES encryption for configuration file
- · Digest authentication
- IPv6
- LLDP/CDP/DHCP VLAN
- ICE

Other physical features

- · Color: Classic Grey
- Wall-mountable (optional)
- · AC adapter:
 - AC 100~240 V input and DC 5 V/1.2 A output
- USB output currency: 5 V 500 mA
- Power consumption (PSU): 1.3 W-2.3 W

- Power consumption (PoE): 1.8 W-3.1 W
- Operating humidity: 10~95%
- Operating temperature: +14~122°F

Package content

- T53W IP phone
- · Handset with handset cord
- · Ethernet cable
- Stand
- · Quick start guide
- · Power adapter

Compliance





For additional support information, please visit verizon.com/support/one-talk

